

## **APPENDIX C - TRAFFIC ANALYSIS**





**Appendix D**

**Technical Appendix**

**Intersection Level of Service**

**Diagrams and Worksheets**

**City of Rocklin**

**General Plan Update EIR**

*prepared for*  
City of Rocklin

*prepared by*  
DKS Associates

May 3, 2011



**INTERSECTION LOS DIAGRAMS  
ALL SCENARIOS**

---

**Figure D1**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Conditions**

<p>EXPM</p> <table border="1"> <tr> <td>Ov</td> <td>230</td> <td>Ig</td> <td>497</td> </tr> <tr> <td></td> <td>19</td> <td></td> <td>688</td> </tr> <tr> <td></td> <td>555</td> <td></td> <td>32</td> </tr> <tr> <td></td> <td></td> <td>Rocklin</td> <td></td> </tr> <tr> <td></td> <td>207</td> <td></td> <td></td> </tr> <tr> <td></td> <td>619</td> <td></td> <td>15 In</td> </tr> <tr> <td></td> <td>10</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.633</td> <td></td> </tr> </table>	Ov	230	Ig	497		19		688		555		32			Rocklin			207				619		15 In		10					In		N/S	Split Phase	LOS: B		E/W	Protected	V/C: 0.633		<table border="1"> <tr> <td>In</td> <td>69</td> <td>In</td> <td>26</td> </tr> <tr> <td></td> <td>426</td> <td></td> <td>22</td> </tr> <tr> <td></td> <td>55</td> <td></td> <td>100</td> </tr> <tr> <td></td> <td></td> <td>Sierra College</td> <td></td> </tr> <tr> <td></td> <td>160</td> <td></td> <td></td> </tr> <tr> <td></td> <td>25</td> <td></td> <td>39 In</td> </tr> <tr> <td></td> <td>126</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.560</td> <td></td> </tr> </table>	In	69	In	26		426		22		55		100			Sierra College			160				25		39 In		126					In		N/S	Protected	LOS: A		E/W	Protected	V/C: 0.560		<table border="1"> <tr> <td>In</td> <td>209</td> <td>In</td> <td>57</td> </tr> <tr> <td></td> <td>55</td> <td></td> <td>364</td> </tr> <tr> <td></td> <td>57</td> <td></td> <td>61</td> </tr> <tr> <td></td> <td></td> <td>Sierra Meadows</td> <td></td> </tr> <tr> <td></td> <td>175</td> <td></td> <td></td> </tr> <tr> <td></td> <td>244</td> <td></td> <td>45 In</td> </tr> <tr> <td></td> <td>53</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.552</td> <td></td> </tr> </table>	In	209	In	57		55		364		57		61			Sierra Meadows			175				244		45 In		53					In		N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.552		<table border="1"> <tr> <td>In</td> <td>17</td> <td>In</td> <td>63</td> </tr> <tr> <td></td> <td>492</td> <td></td> <td>24</td> </tr> <tr> <td></td> <td>31</td> <td></td> <td>28</td> </tr> <tr> <td></td> <td></td> <td>Del Mar/ Dominguez</td> <td></td> </tr> <tr> <td></td> <td>50</td> <td></td> <td></td> </tr> <tr> <td></td> <td>34</td> <td></td> <td>29 In</td> </tr> <tr> <td></td> <td>133</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.569</td> <td></td> </tr> </table>	In	17	In	63		492		24		31		28			Del Mar/ Dominguez			50				34		29 In		133					In		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.569	
Ov	230	Ig	497																																																																																																																																																																
	19		688																																																																																																																																																																
	555		32																																																																																																																																																																
		Rocklin																																																																																																																																																																	
	207																																																																																																																																																																		
	619		15 In																																																																																																																																																																
	10																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Split Phase	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.633																																																																																																																																																																	
In	69	In	26																																																																																																																																																																
	426		22																																																																																																																																																																
	55		100																																																																																																																																																																
		Sierra College																																																																																																																																																																	
	160																																																																																																																																																																		
	25		39 In																																																																																																																																																																
	126																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.560																																																																																																																																																																	
In	209	In	57																																																																																																																																																																
	55		364																																																																																																																																																																
	57		61																																																																																																																																																																
		Sierra Meadows																																																																																																																																																																	
	175																																																																																																																																																																		
	244		45 In																																																																																																																																																																
	53																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Split Phase	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.552																																																																																																																																																																	
In	17	In	63																																																																																																																																																																
	492		24																																																																																																																																																																
	31		28																																																																																																																																																																
		Del Mar/ Dominguez																																																																																																																																																																	
	50																																																																																																																																																																		
	34		29 In																																																																																																																																																																
	133																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.569																																																																																																																																																																	
<b>1 Granite Dr &amp; Rocklin Rd</b>	<b>2 Granite Dr &amp; Sierra College Bl</b>	<b>3 Granite Dr &amp; Sierra Meadows</b>	<b>4 Pacific St &amp; Del Mar/ Dominguez</b>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>44</td> <td>In</td> <td>47</td> </tr> <tr> <td></td> <td>925</td> <td></td> <td>6</td> </tr> <tr> <td></td> <td>104</td> <td></td> <td>70</td> </tr> <tr> <td></td> <td></td> <td>Pacific</td> <td></td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> </tr> <tr> <td></td> <td>12</td> <td></td> <td>30 In</td> </tr> <tr> <td></td> <td>61</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.515</td> <td></td> </tr> </table>	In	44	In	47		925		6		104		70			Pacific			27				12		30 In		61					In		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.515		<table border="1"> <tr> <td>In</td> <td>227</td> <td>In</td> <td>4</td> </tr> <tr> <td></td> <td>580</td> <td></td> <td>32</td> </tr> <tr> <td></td> <td>6</td> <td></td> <td>8</td> </tr> <tr> <td></td> <td></td> <td>Midas</td> <td></td> </tr> <tr> <td></td> <td>134</td> <td></td> <td></td> </tr> <tr> <td></td> <td>30</td> <td></td> <td>16 In</td> </tr> <tr> <td></td> <td>142</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.500</td> <td></td> </tr> </table>	In	227	In	4		580		32		6		8			Midas			134				30		16 In		142					In		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.500		<table border="1"> <tr> <td>In</td> <td>28</td> <td>In</td> <td>204</td> </tr> <tr> <td></td> <td>505</td> <td></td> <td>120</td> </tr> <tr> <td></td> <td>140</td> <td></td> <td>468</td> </tr> <tr> <td></td> <td></td> <td>Pacific</td> <td></td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> </tr> <tr> <td></td> <td>91</td> <td></td> <td>459 In</td> </tr> <tr> <td></td> <td>16</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.688</td> <td></td> </tr> </table>	In	28	In	204		505		120		140		468			Pacific			27				91		459 In		16					In		N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.688		<table border="1"> <tr> <td>In</td> <td>10</td> <td>In</td> <td>81</td> </tr> <tr> <td></td> <td>578</td> <td></td> <td>44</td> </tr> <tr> <td></td> <td>85</td> <td></td> <td>122</td> </tr> <tr> <td></td> <td></td> <td>Sierra Meadows</td> <td></td> </tr> <tr> <td></td> <td>6</td> <td></td> <td></td> </tr> <tr> <td></td> <td>19</td> <td></td> <td>102 In</td> </tr> <tr> <td></td> <td>26</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Ov</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.411</td> <td></td> </tr> </table>	In	10	In	81		578		44		85		122			Sierra Meadows			6				19		102 In		26					Ov		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.411	
In	44	In	47																																																																																																																																																																
	925		6																																																																																																																																																																
	104		70																																																																																																																																																																
		Pacific																																																																																																																																																																	
	27																																																																																																																																																																		
	12		30 In																																																																																																																																																																
	61																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.515																																																																																																																																																																	
In	227	In	4																																																																																																																																																																
	580		32																																																																																																																																																																
	6		8																																																																																																																																																																
		Midas																																																																																																																																																																	
	134																																																																																																																																																																		
	30		16 In																																																																																																																																																																
	142																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.500																																																																																																																																																																	
In	28	In	204																																																																																																																																																																
	505		120																																																																																																																																																																
	140		468																																																																																																																																																																
		Pacific																																																																																																																																																																	
	27																																																																																																																																																																		
	91		459 In																																																																																																																																																																
	16																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Split Phase	V/C: 0.688																																																																																																																																																																	
In	10	In	81																																																																																																																																																																
	578		44																																																																																																																																																																
	85		122																																																																																																																																																																
		Sierra Meadows																																																																																																																																																																	
	6																																																																																																																																																																		
	19		102 In																																																																																																																																																																
	26																																																																																																																																																																		
		Ov																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.411																																																																																																																																																																	
<b>5 Pacific St &amp; Farron St</b>	<b>6 Pacific St &amp; Midas Ave</b>	<b>7 Pacific St &amp; Rocklin Rd</b>	<b>8 Pacific St &amp; Sierra Meadows</b>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>43</td> </tr> <tr> <td></td> <td>779</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>50</td> <td></td> <td>84</td> </tr> <tr> <td></td> <td></td> <td>Woodside</td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>136 In</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.505</td> <td></td> </tr> </table>	In	0	In	43		779		0		50		84			Woodside			0				0		136 In		0					In		N/S	Protected	LOS: A		E/W	Protected	V/C: 0.505		<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>1,153</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>21</td> </tr> <tr> <td></td> <td></td> <td>Rocklin</td> <td></td> </tr> <tr> <td></td> <td>70</td> <td></td> <td></td> </tr> <tr> <td></td> <td>1,098</td> <td></td> <td>17 In</td> </tr> <tr> <td></td> <td>111</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.520</td> <td></td> </tr> </table>	In	0	In	0		0		1,153		0		21			Rocklin			70				1,098		17 In		111					In		N/S	Protected	LOS: A		E/W	Protected	V/C: 0.520		<table border="1"> <tr> <td>Ov</td> <td>407</td> <td>In</td> <td>32</td> </tr> <tr> <td></td> <td>8</td> <td></td> <td>647</td> </tr> <tr> <td></td> <td>74</td> <td></td> <td>13</td> </tr> <tr> <td></td> <td></td> <td>Pacific</td> <td></td> </tr> <tr> <td></td> <td>252</td> <td></td> <td></td> </tr> <tr> <td></td> <td>743</td> <td></td> <td>10 In</td> </tr> <tr> <td></td> <td>170</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.636</td> <td></td> </tr> </table>	Ov	407	In	32		8		647		74		13			Pacific			252				743		10 In		170					In		N/S	Split Phase	LOS: B		E/W	Protected	V/C: 0.636		<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>728</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td>Rocklin</td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> </tr> <tr> <td></td> <td>730</td> <td></td> <td>0 In</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.243</td> <td></td> </tr> </table>	In	0	In	0		0		728		0		0			Rocklin			0				730		0 In		0					In		N/S	Protected	LOS: A		E/W	Protected	V/C: 0.243	
In	0	In	43																																																																																																																																																																
	779		0																																																																																																																																																																
	50		84																																																																																																																																																																
		Woodside																																																																																																																																																																	
	0																																																																																																																																																																		
	0		136 In																																																																																																																																																																
	0																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.505																																																																																																																																																																	
In	0	In	0																																																																																																																																																																
	0		1,153																																																																																																																																																																
	0		21																																																																																																																																																																
		Rocklin																																																																																																																																																																	
	70																																																																																																																																																																		
	1,098		17 In																																																																																																																																																																
	111																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.520																																																																																																																																																																	
Ov	407	In	32																																																																																																																																																																
	8		647																																																																																																																																																																
	74		13																																																																																																																																																																
		Pacific																																																																																																																																																																	
	252																																																																																																																																																																		
	743		10 In																																																																																																																																																																
	170																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Split Phase	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.636																																																																																																																																																																	
In	0	In	0																																																																																																																																																																
	0		728																																																																																																																																																																
	0		0																																																																																																																																																																
		Rocklin																																																																																																																																																																	
	0																																																																																																																																																																		
	730		0 In																																																																																																																																																																
	0																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.243																																																																																																																																																																	
<b>9 Pacific St &amp; Woodside Dr</b>	<b>10 Rocklin Rd &amp; Aguilar Rd</b>	<b>11 Rocklin Rd &amp; El Don Dr</b>	<b>12 Rocklin Rd &amp; Fire Station No 1</b>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>126</td> <td>In</td> <td>126</td> </tr> <tr> <td></td> <td>1</td> <td></td> <td>543</td> </tr> <tr> <td></td> <td>195</td> <td></td> <td>9</td> </tr> <tr> <td></td> <td></td> <td>SC Driveway</td> <td></td> </tr> <tr> <td></td> <td>113</td> <td></td> <td></td> </tr> <tr> <td></td> <td>709</td> <td></td> <td>4 In</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.482</td> <td></td> </tr> </table>	In	126	In	126		1		543		195		9			SC Driveway			113				709		4 In		27					In		N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.482		<table border="1"> <tr> <td>In</td> <td>101</td> <td>In</td> <td>25</td> </tr> <tr> <td></td> <td>250</td> <td></td> <td>166</td> </tr> <tr> <td></td> <td>55</td> <td></td> <td>63</td> </tr> <tr> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> </tr> <tr> <td></td> <td>106</td> <td></td> <td></td> </tr> <tr> <td></td> <td>231</td> <td></td> <td>56 In</td> </tr> <tr> <td></td> <td>500</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Ov</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.614</td> <td></td> </tr> </table>	In	101	In	25		250		166		55		63			Sierra College Bl			106				231		56 In		500					Ov		N/S	Protected	LOS: B		E/W	Protected	V/C: 0.614		<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>751</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>66</td> </tr> <tr> <td></td> <td></td> <td>Rocklin</td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> </tr> <tr> <td></td> <td>654</td> <td></td> <td>42 In</td> </tr> <tr> <td></td> <td>34</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.317</td> <td></td> </tr> </table>	In	0	In	0		0		751		0		66			Rocklin			0				654		42 In		34					In		N/S	Protected	LOS: A		E/W	Protected	V/C: 0.317		<table border="1"> <tr> <td>In</td> <td>48</td> <td>In</td> <td>22</td> </tr> <tr> <td></td> <td>778</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>48</td> <td></td> <td>6</td> </tr> <tr> <td></td> <td></td> <td>El Don</td> <td></td> </tr> <tr> <td></td> <td>23</td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>10 In</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.387</td> <td></td> </tr> </table>	In	48	In	22		778		0		48		6			El Don			23				0		10 In		27					In		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.387	
In	126	In	126																																																																																																																																																																
	1		543																																																																																																																																																																
	195		9																																																																																																																																																																
		SC Driveway																																																																																																																																																																	
	113																																																																																																																																																																		
	709		4 In																																																																																																																																																																
	27																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Split Phase	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.482																																																																																																																																																																	
In	101	In	25																																																																																																																																																																
	250		166																																																																																																																																																																
	55		63																																																																																																																																																																
		Sierra College Bl																																																																																																																																																																	
	106																																																																																																																																																																		
	231		56 In																																																																																																																																																																
	500																																																																																																																																																																		
		Ov																																																																																																																																																																	
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.614																																																																																																																																																																	
In	0	In	0																																																																																																																																																																
	0		751																																																																																																																																																																
	0		66																																																																																																																																																																
		Rocklin																																																																																																																																																																	
	0																																																																																																																																																																		
	654		42 In																																																																																																																																																																
	34																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.317																																																																																																																																																																	
In	48	In	22																																																																																																																																																																
	778		0																																																																																																																																																																
	48		6																																																																																																																																																																
		El Don																																																																																																																																																																	
	23																																																																																																																																																																		
	0		10 In																																																																																																																																																																
	27																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.387																																																																																																																																																																	
<b>13 Rocklin Rd &amp; Havenhurst Cir</b>	<b>14 Rocklin Rd &amp; Sierra College Bl</b>	<b>15 Rocklin Rd &amp; South Grove St</b>	<b>16 Sierra College Bl &amp; El Don Dr</b>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>54</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>740</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> </tr> <tr> <td></td> <td>48</td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>32 In</td> </tr> <tr> <td></td> <td>96</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.651</td> <td></td> </tr> </table>	In	54	In	0		740		0		0		0			Sierra College Bl			48				0		32 In		96					In		N/S	Protected	LOS: B		E/W	Protected	V/C: 0.651		<table border="1"> <tr> <td>In</td> <td>44</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>818</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td>4</td> </tr> <tr> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> </tr> <tr> <td></td> <td>26</td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>1 In</td> </tr> <tr> <td></td> <td>18</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.357</td> <td></td> </tr> </table>	In	44	In	0		818		0		4		4			Sierra College Bl			26				0		1 In		18					In		N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.357		<table border="1"> <tr> <td>In</td> <td>30</td> <td>In</td> <td>3</td> </tr> <tr> <td></td> <td>717</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td>1</td> </tr> <tr> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> </tr> <tr> <td></td> <td>23</td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>1 In</td> </tr> <tr> <td></td> <td>26</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.650</td> <td></td> </tr> </table>	In	30	In	3		717		0		4		1			Sierra College Bl			23				0		1 In		26					In		N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.650		<table border="1"> <tr> <td>Ig</td> <td>647</td> <td>In</td> <td>54</td> </tr> <tr> <td></td> <td>504</td> <td></td> <td>107</td> </tr> <tr> <td></td> <td>78</td> <td></td> <td>38</td> </tr> <tr> <td></td> <td></td> <td>Pacific</td> <td></td> </tr> <tr> <td></td> <td>435</td> <td></td> <td></td> </tr> <tr> <td></td> <td>106</td> <td></td> <td>22 In</td> </tr> <tr> <td></td> <td>316</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>In</td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.635</td> <td></td> </tr> </table>	Ig	647	In	54		504		107		78		38			Pacific			435				106		22 In		316					In		N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.635	
In	54	In	0																																																																																																																																																																
	740		0																																																																																																																																																																
	0		0																																																																																																																																																																
		Sierra College Bl																																																																																																																																																																	
	48																																																																																																																																																																		
	0		32 In																																																																																																																																																																
	96																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.651																																																																																																																																																																	
In	44	In	0																																																																																																																																																																
	818		0																																																																																																																																																																
	4		4																																																																																																																																																																
		Sierra College Bl																																																																																																																																																																	
	26																																																																																																																																																																		
	0		1 In																																																																																																																																																																
	18																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.357																																																																																																																																																																	
In	30	In	3																																																																																																																																																																
	717		0																																																																																																																																																																
	4		1																																																																																																																																																																
		Sierra College Bl																																																																																																																																																																	
	23																																																																																																																																																																		
	0		1 In																																																																																																																																																																
	26																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Split Phase	V/C: 0.650																																																																																																																																																																	
Ig	647	In	54																																																																																																																																																																
	504		107																																																																																																																																																																
	78		38																																																																																																																																																																
		Pacific																																																																																																																																																																	
	435																																																																																																																																																																		
	106		22 In																																																																																																																																																																
	316																																																																																																																																																																		
		In																																																																																																																																																																	
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Split Phase	V/C: 0.635																																																																																																																																																																	
<b>17 Sierra College Bl &amp; Nightwatch</b>	<b>18 Sierra College Bl &amp; Scarborough</b>	<b>19 Sierra College Bl &amp; Southside Ranch</b>	<b>20 Sunset Bl &amp; Pacific St</b>																																																																																																																																																																

**Figure D1**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Conditions**

<table border="1"> <tr> <td>In</td> <td>325</td> <td>In</td> <td>56</td> </tr> <tr> <td>←</td> <td>32</td> <td>↑</td> <td>1,240</td> </tr> <tr> <td>→</td> <td>57</td> <td>↓</td> <td>220</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">LOS: D</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.824</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>306</td> <td>↑</td> <td>62</td> </tr> <tr> <td>→</td> <td>751</td> <td>↓</td> <td>28</td> </tr> <tr> <td>←</td> <td>96</td> <td>↓</td> <td>90</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	325	In	56	←	32	↑	1,240	→	57	↓	220	Split Phase		LOS: D		Protected		V/C: 0.824		In		Sunset		←	306	↑	62	→	751	↓	28	←	96	↓	90	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>69</td> <td>In</td> <td>67</td> </tr> <tr> <td>←</td> <td>13</td> <td>↑</td> <td>1,120</td> </tr> <tr> <td>→</td> <td>12</td> <td>↓</td> <td>68</td> </tr> <tr> <td colspan="2">Permitted</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.560</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>85</td> <td>↑</td> <td>25</td> </tr> <tr> <td>→</td> <td>862</td> <td>↓</td> <td>15</td> </tr> <tr> <td>←</td> <td>23</td> <td>↓</td> <td>26</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	69	In	67	←	13	↑	1,120	→	12	↓	68	Permitted		LOS: A		Protected		V/C: 0.560		In		Sunset		←	85	↑	25	→	862	↓	15	←	23	↓	26	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>24</td> <td>In</td> <td>279</td> </tr> <tr> <td>←</td> <td>50</td> <td>↑</td> <td>1,134</td> </tr> <tr> <td>→</td> <td>163</td> <td>↓</td> <td>170</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: D</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.805</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>58</td> <td>↑</td> <td>41</td> </tr> <tr> <td>→</td> <td>833</td> <td>↓</td> <td>62</td> </tr> <tr> <td>←</td> <td>23</td> <td>↓</td> <td>118</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	24	In	279	←	50	↑	1,134	→	163	↓	170	Protected		LOS: D		Protected		V/C: 0.805		In		Sunset		←	58	↑	41	→	833	↓	62	←	23	↓	118	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>607</td> <td>In</td> <td>67</td> </tr> <tr> <td>←</td> <td>233</td> <td>↑</td> <td>247</td> </tr> <tr> <td>→</td> <td>60</td> <td>↓</td> <td>108</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.478</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>612</td> <td>↑</td> <td>223</td> </tr> <tr> <td>→</td> <td>430</td> <td>↓</td> <td>290</td> </tr> <tr> <td>←</td> <td>264</td> <td>↓</td> <td>61</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	607	In	67	←	233	↑	247	→	60	↓	108	Protected		LOS: A		Protected		V/C: 0.478		In		Blue Oaks		←	612	↑	223	→	430	↓	290	←	264	↓	61	In		In		N/S		N/S		E/W		E/W	
In	325	In	56																																																																																																																																																																																																
←	32	↑	1,240																																																																																																																																																																																																
→	57	↓	220																																																																																																																																																																																																
Split Phase		LOS: D																																																																																																																																																																																																	
Protected		V/C: 0.824																																																																																																																																																																																																	
In		Sunset																																																																																																																																																																																																	
←	306	↑	62																																																																																																																																																																																																
→	751	↓	28																																																																																																																																																																																																
←	96	↓	90																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	69	In	67																																																																																																																																																																																																
←	13	↑	1,120																																																																																																																																																																																																
→	12	↓	68																																																																																																																																																																																																
Permitted		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.560																																																																																																																																																																																																	
In		Sunset																																																																																																																																																																																																	
←	85	↑	25																																																																																																																																																																																																
→	862	↓	15																																																																																																																																																																																																
←	23	↓	26																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	24	In	279																																																																																																																																																																																																
←	50	↑	1,134																																																																																																																																																																																																
→	163	↓	170																																																																																																																																																																																																
Protected		LOS: D																																																																																																																																																																																																	
Protected		V/C: 0.805																																																																																																																																																																																																	
In		Sunset																																																																																																																																																																																																	
←	58	↑	41																																																																																																																																																																																																
→	833	↓	62																																																																																																																																																																																																
←	23	↓	118																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	607	In	67																																																																																																																																																																																																
←	233	↑	247																																																																																																																																																																																																
→	60	↓	108																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.478																																																																																																																																																																																																	
In		Blue Oaks																																																																																																																																																																																																	
←	612	↑	223																																																																																																																																																																																																
→	430	↓	290																																																																																																																																																																																																
←	264	↓	61																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
<p><b>21</b>    <b>Sunset Bl &amp; Springview Dr</b></p>	<p><b>22</b>    <b>Sunset Bl &amp; Topaz Ave</b></p>	<p><b>23</b>    <b>Sunset Bl &amp; Whitney Bl</b></p>	<p><b>101</b>    <b>Blue Oaks Bl &amp; Lonetree</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>7</td> <td>In</td> <td>8</td> </tr> <tr> <td>←</td> <td>1</td> <td>↑</td> <td>360</td> </tr> <tr> <td>→</td> <td>17</td> <td>↓</td> <td>2</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.244</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>18</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>629</td> <td>↓</td> <td>0</td> </tr> <tr> <td>←</td> <td>0</td> <td>↓</td> <td>1</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	7	In	8	←	1	↑	360	→	17	↓	2	Split Phase		LOS: A		Protected		V/C: 0.244		In		Blue Oaks		←	18	↑	0	→	629	↓	0	←	0	↓	1	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>18</td> <td>In</td> <td>24</td> </tr> <tr> <td>←</td> <td>298</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>27</td> <td>↓</td> <td>35</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.287</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>9</td> <td>↑</td> <td>38</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>496</td> </tr> <tr> <td>←</td> <td>23</td> <td>↓</td> <td>58</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	18	In	24	←	298	↑	0	→	27	↓	35	Protected		LOS: A		Split Phase		V/C: 0.287		In		Blue Oaks		←	9	↑	38	→	0	↓	496	←	23	↓	58	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>13</td> <td>In</td> <td>131</td> </tr> <tr> <td>←</td> <td>124</td> <td>↑</td> <td>1</td> </tr> <tr> <td>→</td> <td>72</td> <td>↓</td> <td>2</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.194</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Destiny</td> </tr> <tr> <td>←</td> <td>13</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>93</td> </tr> <tr> <td>←</td> <td>3</td> <td>↓</td> <td>2</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	13	In	131	←	124	↑	1	→	72	↓	2	Protected		LOS: A		Split Phase		V/C: 0.194		In		Destiny		←	13	↑	0	→	0	↓	93	←	3	↓	2	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>10</td> <td>In</td> <td>15</td> </tr> <tr> <td>←</td> <td>599</td> <td>↑</td> <td>1</td> </tr> <tr> <td>→</td> <td>17</td> <td>↓</td> <td>16</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.308</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Adams</td> </tr> <tr> <td>←</td> <td>15</td> <td>↑</td> <td>41</td> </tr> <tr> <td>→</td> <td>1</td> <td>↓</td> <td>523</td> </tr> <tr> <td>←</td> <td>46</td> <td>↓</td> <td>20</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	10	In	15	←	599	↑	1	→	17	↓	16	Protected		LOS: A		Split Phase		V/C: 0.308		In		Adams		←	15	↑	41	→	1	↓	523	←	46	↓	20	In		In		N/S		N/S		E/W		E/W	
In	7	In	8																																																																																																																																																																																																
←	1	↑	360																																																																																																																																																																																																
→	17	↓	2																																																																																																																																																																																																
Split Phase		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.244																																																																																																																																																																																																	
In		Blue Oaks																																																																																																																																																																																																	
←	18	↑	0																																																																																																																																																																																																
→	629	↓	0																																																																																																																																																																																																
←	0	↓	1																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	18	In	24																																																																																																																																																																																																
←	298	↑	0																																																																																																																																																																																																
→	27	↓	35																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.287																																																																																																																																																																																																	
In		Blue Oaks																																																																																																																																																																																																	
←	9	↑	38																																																																																																																																																																																																
→	0	↓	496																																																																																																																																																																																																
←	23	↓	58																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	13	In	131																																																																																																																																																																																																
←	124	↑	1																																																																																																																																																																																																
→	72	↓	2																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.194																																																																																																																																																																																																	
In		Destiny																																																																																																																																																																																																	
←	13	↑	0																																																																																																																																																																																																
→	0	↓	93																																																																																																																																																																																																
←	3	↓	2																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	10	In	15																																																																																																																																																																																																
←	599	↑	1																																																																																																																																																																																																
→	17	↓	16																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.308																																																																																																																																																																																																	
In		Adams																																																																																																																																																																																																	
←	15	↑	41																																																																																																																																																																																																
→	1	↓	523																																																																																																																																																																																																
←	46	↓	20																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
<p><b>102</b>    <b>Blue Oaks Bl &amp; Market Place</b></p>	<p><b>103</b>    <b>Blue Oaks Bl &amp; Van Buren Way</b></p>	<p><b>104</b>    <b>Five Star &amp; Destiny Dr</b></p>	<p><b>105</b>    <b>Lonetree Bl &amp; Adams Dr</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>4</td> <td>In</td> <td>0</td> </tr> <tr> <td>←</td> <td>217</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.272</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Atherton</td> </tr> <tr> <td>←</td> <td>35</td> <td>↑</td> <td>20</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>406</td> </tr> <tr> <td>←</td> <td>185</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	4	In	0	←	217	↑	0	→	0	↓	0	Protected		LOS: A		Protected		V/C: 0.272		In		Atherton		←	35	↑	20	→	0	↓	406	←	185	↓	0	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>8</td> <td>In</td> <td>4</td> </tr> <tr> <td>←</td> <td>788</td> <td>↑</td> <td>2</td> </tr> <tr> <td>→</td> <td>5</td> <td>↓</td> <td>14</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.469</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Grand Canyon</td> </tr> <tr> <td>←</td> <td>20</td> <td>↑</td> <td>161</td> </tr> <tr> <td>→</td> <td>1</td> <td>↓</td> <td>668</td> </tr> <tr> <td>←</td> <td>66</td> <td>↓</td> <td>42</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	8	In	4	←	788	↑	2	→	5	↓	14	Protected		LOS: A		Split Phase		V/C: 0.469		In		Grand Canyon		←	20	↑	161	→	1	↓	668	←	66	↓	42	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>39</td> <td>In</td> <td>9</td> </tr> <tr> <td>←</td> <td>625</td> <td>↑</td> <td>6</td> </tr> <tr> <td>→</td> <td>15</td> <td>↓</td> <td>29</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.442</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Redwood</td> </tr> <tr> <td>←</td> <td>49</td> <td>↑</td> <td>133</td> </tr> <tr> <td>→</td> <td>4</td> <td>↓</td> <td>538</td> </tr> <tr> <td>←</td> <td>99</td> <td>↓</td> <td>30</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	39	In	9	←	625	↑	6	→	15	↓	29	Protected		LOS: A		Split Phase		V/C: 0.442		In		Redwood		←	49	↑	133	→	4	↓	538	←	99	↓	30	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>1</td> <td>In</td> <td>6</td> </tr> <tr> <td>←</td> <td>396</td> <td>↑</td> <td>1</td> </tr> <tr> <td>→</td> <td>9</td> <td>↓</td> <td>212</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.514</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">West Oaks</td> </tr> <tr> <td>←</td> <td>1</td> <td>↑</td> <td>7</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>367</td> </tr> <tr> <td>←</td> <td>4</td> <td>↓</td> <td>115</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	1	In	6	←	396	↑	1	→	9	↓	212	Protected		LOS: A		Protected		V/C: 0.514		In		West Oaks		←	1	↑	7	→	0	↓	367	←	4	↓	115	In		In		N/S		N/S		E/W		E/W	
In	4	In	0																																																																																																																																																																																																
←	217	↑	0																																																																																																																																																																																																
→	0	↓	0																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.272																																																																																																																																																																																																	
In		Atherton																																																																																																																																																																																																	
←	35	↑	20																																																																																																																																																																																																
→	0	↓	406																																																																																																																																																																																																
←	185	↓	0																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	8	In	4																																																																																																																																																																																																
←	788	↑	2																																																																																																																																																																																																
→	5	↓	14																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.469																																																																																																																																																																																																	
In		Grand Canyon																																																																																																																																																																																																	
←	20	↑	161																																																																																																																																																																																																
→	1	↓	668																																																																																																																																																																																																
←	66	↓	42																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	39	In	9																																																																																																																																																																																																
←	625	↑	6																																																																																																																																																																																																
→	15	↓	29																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.442																																																																																																																																																																																																	
In		Redwood																																																																																																																																																																																																	
←	49	↑	133																																																																																																																																																																																																
→	4	↓	538																																																																																																																																																																																																
←	99	↓	30																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	1	In	6																																																																																																																																																																																																
←	396	↑	1																																																																																																																																																																																																
→	9	↓	212																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.514																																																																																																																																																																																																	
In		West Oaks																																																																																																																																																																																																	
←	1	↑	7																																																																																																																																																																																																
→	0	↓	367																																																																																																																																																																																																
←	4	↓	115																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
<p><b>106</b>    <b>Lonetree Bl &amp; Atherton Rd</b></p>	<p><b>107</b>    <b>Lonetree Bl &amp; Grand Canyon Dr</b></p>	<p><b>108</b>    <b>Lonetree Bl &amp; Redwood Dr</b></p>	<p><b>109</b>    <b>Lonetree Bl &amp; West Oaks Bl</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>42</td> <td>In</td> <td>10</td> </tr> <tr> <td>←</td> <td>0</td> <td>↑</td> <td>265</td> </tr> <tr> <td>→</td> <td>12</td> <td>↓</td> <td>3</td> </tr> <tr> <td colspan="2">Permitted</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.197</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Park</td> </tr> <tr> <td>←</td> <td>87</td> <td>↑</td> <td>2</td> </tr> <tr> <td>→</td> <td>361</td> <td>↓</td> <td>1</td> </tr> <tr> <td>←</td> <td>11</td> <td>↓</td> <td>1</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	42	In	10	←	0	↑	265	→	12	↓	3	Permitted		LOS: A		Protected		V/C: 0.197		In		Park		←	87	↑	2	→	361	↓	1	←	11	↓	1	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>34</td> <td>In</td> <td>5</td> </tr> <tr> <td>←</td> <td>689</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>7</td> <td>↓</td> <td>14</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.391</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Quarry</td> </tr> <tr> <td>←</td> <td>41</td> <td>↑</td> <td>90</td> </tr> <tr> <td>→</td> <td>4</td> <td>↓</td> <td>926</td> </tr> <tr> <td>←</td> <td>33</td> <td>↓</td> <td>7</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	34	In	5	←	689	↑	0	→	7	↓	14	Protected		LOS: A		Split Phase		V/C: 0.391		In		Quarry		←	41	↑	90	→	4	↓	926	←	33	↓	7	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>61</td> <td>In</td> <td>0</td> </tr> <tr> <td>←</td> <td>552</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.520</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Farrier</td> </tr> <tr> <td>←</td> <td>37</td> <td>↑</td> <td>269</td> </tr> <tr> <td>→</td> <td>0</td> <td>↓</td> <td>624</td> </tr> <tr> <td>←</td> <td>165</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	61	In	0	←	552	↑	0	→	0	↓	0	Protected		LOS: A		Protected		V/C: 0.520		In		Farrier		←	37	↑	269	→	0	↓	624	←	165	↓	0	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>7</td> <td>In</td> <td>15</td> </tr> <tr> <td>←</td> <td>688</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>27</td> <td>↓</td> <td>27</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Permitted</td> <td colspan="2">V/C: 0.368</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">King Pine</td> </tr> <tr> <td>←</td> <td>7</td> <td>↑</td> <td>24</td> </tr> <tr> <td>→</td> <td>1</td> <td>↓</td> <td>889</td> </tr> <tr> <td>←</td> <td>9</td> <td>↓</td> <td>33</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	7	In	15	←	688	↑	0	→	27	↓	27	Protected		LOS: A		Permitted		V/C: 0.368		In		King Pine		←	7	↑	24	→	1	↓	889	←	9	↓	33	In		In		N/S		N/S		E/W		E/W	
In	42	In	10																																																																																																																																																																																																
←	0	↑	265																																																																																																																																																																																																
→	12	↓	3																																																																																																																																																																																																
Permitted		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.197																																																																																																																																																																																																	
In		Park																																																																																																																																																																																																	
←	87	↑	2																																																																																																																																																																																																
→	361	↓	1																																																																																																																																																																																																
←	11	↓	1																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	34	In	5																																																																																																																																																																																																
←	689	↑	0																																																																																																																																																																																																
→	7	↓	14																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.391																																																																																																																																																																																																	
In		Quarry																																																																																																																																																																																																	
←	41	↑	90																																																																																																																																																																																																
→	4	↓	926																																																																																																																																																																																																
←	33	↓	7																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	61	In	0																																																																																																																																																																																																
←	552	↑	0																																																																																																																																																																																																
→	0	↓	0																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.520																																																																																																																																																																																																	
In		Farrier																																																																																																																																																																																																	
←	37	↑	269																																																																																																																																																																																																
→	0	↓	624																																																																																																																																																																																																
←	165	↓	0																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	7	In	15																																																																																																																																																																																																
←	688	↑	0																																																																																																																																																																																																
→	27	↓	27																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Permitted		V/C: 0.368																																																																																																																																																																																																	
In		King Pine																																																																																																																																																																																																	
←	7	↑	24																																																																																																																																																																																																
→	1	↓	889																																																																																																																																																																																																
←	9	↓	33																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
<p><b>110</b>    <b>Park Dr &amp; Blyden Rd</b></p>	<p><b>111</b>    <b>Park Dr &amp; Quarry Way</b></p>	<p><b>112</b>    <b>Park Dr &amp; Farrier Rd</b></p>	<p><b>113</b>    <b>Park Dr &amp; King Pine Dr</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>3</td> <td>In</td> <td>0</td> </tr> <tr> <td>←</td> <td>454</td> <td>↑</td> <td>5</td> </tr> <tr> <td>→</td> <td>5</td> <td>↓</td> <td>36</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.274</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Shelton</td> </tr> <tr> <td>←</td> <td>8</td> <td>↑</td> <td>120</td> </tr> <tr> <td>→</td> <td>1</td> <td>↓</td> <td>683</td> </tr> <tr> <td>←</td> <td>68</td> <td>↓</td> <td>69</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	3	In	0	←	454	↑	5	→	5	↓	36	Protected		LOS: A		Protected		V/C: 0.274		In		Shelton		←	8	↑	120	→	1	↓	683	←	68	↓	69	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>12</td> <td>In</td> <td>63</td> </tr> <tr> <td>←</td> <td>457</td> <td>↑</td> <td>14</td> </tr> <tr> <td>→</td> <td>57</td> <td>↓</td> <td>26</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.318</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Victory</td> </tr> <tr> <td>←</td> <td>71</td> <td>↑</td> <td>37</td> </tr> <tr> <td>→</td> <td>5</td> <td>↓</td> <td>719</td> </tr> <tr> <td>←</td> <td>12</td> <td>↓</td> <td>6</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	12	In	63	←	457	↑	14	→	57	↓	26	Protected		LOS: A		Split Phase		V/C: 0.318		In		Victory		←	71	↑	37	→	5	↓	719	←	12	↓	6	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>165</td> <td>In</td> <td>14</td> </tr> <tr> <td>←</td> <td>0</td> <td>↑</td> <td>337</td> </tr> <tr> <td>→</td> <td>10</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">V/C: 0.320</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Park</td> </tr> <tr> <td>←</td> <td>245</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>446</td> <td>↓</td> <td>0</td> </tr> <tr> <td>←</td> <td>0</td> <td>↓</td> <td>0</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	165	In	14	←	0	↑	337	→	10	↓	0	Protected		LOS: A		Protected		V/C: 0.320		In		Park		←	245	↑	0	→	446	↓	0	←	0	↓	0	In		In		N/S		N/S		E/W		E/W		<table border="1"> <tr> <td>In</td> <td>32</td> <td>In</td> <td>2</td> </tr> <tr> <td>←</td> <td>550</td> <td>↑</td> <td>0</td> </tr> <tr> <td>→</td> <td>25</td> <td>↓</td> <td>15</td> </tr> <tr> <td colspan="2">Protected</td> <td colspan="2">LOS: A</td> </tr> <tr> <td colspan="2">Split Phase</td> <td colspan="2">V/C: 0.362</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">Twin Oaks</td> </tr> <tr> <td>←</td> <td>65</td> <td>↑</td> <td>66</td> </tr> <tr> <td>→</td> <td>2</td> <td>↓</td> <td>600</td> </tr> <tr> <td>←</td> <td>59</td> <td>↓</td> <td>26</td> </tr> <tr> <td colspan="2">In</td> <td colspan="2">In</td> </tr> <tr> <td colspan="2">N/S</td> <td colspan="2">N/S</td> </tr> <tr> <td colspan="2">E/W</td> <td colspan="2">E/W</td> </tr> </table>	In	32	In	2	←	550	↑	0	→	25	↓	15	Protected		LOS: A		Split Phase		V/C: 0.362		In		Twin Oaks		←	65	↑	66	→	2	↓	600	←	59	↓	26	In		In		N/S		N/S		E/W		E/W	
In	3	In	0																																																																																																																																																																																																
←	454	↑	5																																																																																																																																																																																																
→	5	↓	36																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.274																																																																																																																																																																																																	
In		Shelton																																																																																																																																																																																																	
←	8	↑	120																																																																																																																																																																																																
→	1	↓	683																																																																																																																																																																																																
←	68	↓	69																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	12	In	63																																																																																																																																																																																																
←	457	↑	14																																																																																																																																																																																																
→	57	↓	26																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.318																																																																																																																																																																																																	
In		Victory																																																																																																																																																																																																	
←	71	↑	37																																																																																																																																																																																																
→	5	↓	719																																																																																																																																																																																																
←	12	↓	6																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	165	In	14																																																																																																																																																																																																
←	0	↑	337																																																																																																																																																																																																
→	10	↓	0																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Protected		V/C: 0.320																																																																																																																																																																																																	
In		Park																																																																																																																																																																																																	
←	245	↑	0																																																																																																																																																																																																
→	446	↓	0																																																																																																																																																																																																
←	0	↓	0																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
In	32	In	2																																																																																																																																																																																																
←	550	↑	0																																																																																																																																																																																																
→	25	↓	15																																																																																																																																																																																																
Protected		LOS: A																																																																																																																																																																																																	
Split Phase		V/C: 0.362																																																																																																																																																																																																	
In		Twin Oaks																																																																																																																																																																																																	
←	65	↑	66																																																																																																																																																																																																
→	2	↓	600																																																																																																																																																																																																
←	59	↓	26																																																																																																																																																																																																
In		In																																																																																																																																																																																																	
N/S		N/S																																																																																																																																																																																																	
E/W		E/W																																																																																																																																																																																																	
<p><b>114</b>    <b>Park Dr &amp; Shelton</b></p>	<p><b>115</b>    <b>Park Dr &amp; Victory Lane</b></p>	<p><b>116</b>    <b>Park Dr &amp; Wykford Bl</b></p>	<p><b>117</b>    <b>Park Dr &amp; Twin Oaks/ Boardwalk</b></p>																																																																																																																																																																																																

**Figure D1**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Conditions**

<p>In 117 684 75  </p> <p>0 0 71        In</p> <p>LOS: A        V/C: 0.514</p>	<p>In 9 175 279  </p> <p>52 15 5        In</p> <p>LOS: A        V/C: 0.471</p>	<p>In 0 28 2  </p> <p>0 0 0        In</p> <p>LOS: A        V/C: 0.031</p>	<p>In 31 409 6  </p> <p>19 5 14        In</p> <p>LOS: A        V/C: 0.325</p>
<p><b>118 Park Dr &amp; Safeway</b></p> <p>In 38 8 49  </p> <p>48 342 55        In</p> <p>LOS: A        V/C: 0.293</p>	<p>In 118 326 219  </p> <p>153 167 116        In</p> <p>LOS: A        V/C: 0.573</p>	<p>In 51 817 0  </p> <p>79 0 133        In</p> <p>LOS: A        V/C: 0.371</p>	<p>In 14 468 9  </p> <p>14 17 49        In</p> <p>LOS: A        V/C: 0.439</p>
<p><b>122 Stanford Ranch Rd &amp; Darby Rd</b></p> <p>In 69 0 72  </p> <p>37 495 0        In</p> <p>LOS: A        V/C: 0.263</p>	<p>In 15 49 70  </p> <p>20 317 9        In</p> <p>LOS: A        V/C: 0.228</p>	<p>In 29 0 28  </p> <p>22 432 23        In</p> <p>LOS: A        V/C: 0.337</p>	<p>In 4 20 29  </p> <p>27 580 125        In</p> <p>LOS: B        V/C: 0.681</p>
<p><b>126 Stanford Ranch Rd &amp; Victory Ln</b></p> <p>In 28 23 12  </p> <p>56 676 80        In</p> <p>LOS: A        V/C: 0.480</p>	<p>In 34 2 35  </p> <p>121 1,025 28        In</p> <p>LOS: A        V/C: 0.444</p>	<p>In 73 354 293  </p> <p>384 638 83        In</p> <p>LOS: D        V/C: 0.866</p>	<p>In 111 6 44  </p> <p>192 888 31        In</p> <p>LOS: A        V/C: 0.539</p>
<p><b>130 Sunset Bl &amp; Fairway Dr</b></p> <p>In 19 103 126  </p> <p>29 529 6        In</p> <p>LOS: A        V/C: 0.349</p>	<p>In 137 206 185  </p> <p>214 339 70        In</p> <p>LOS: A        V/C: 0.467</p>	<p>In 356 0 159  </p> <p>559 196 0        In</p> <p>LOS: A        V/C: 0.455</p>	<p><b>131 Sunset Bl &amp; Little Rock</b></p> <p>In 146 383 226  </p> <p>122 539 285        In</p> <p>LOS: C        V/C: 0.793</p>
<p><b>131 Sunset Bl &amp; Little Rock</b></p> <p>In 19 103 126  </p> <p>29 529 6        In</p> <p>LOS: A        V/C: 0.349</p>	<p><b>132 Sunset Bl &amp; Park Dr</b></p> <p>In 137 206 185  </p> <p>214 339 70        In</p> <p>LOS: A        V/C: 0.467</p>	<p><b>133 Sunset Bl &amp; Pebble Creek</b></p> <p>In 356 0 159  </p> <p>559 196 0        In</p> <p>LOS: A        V/C: 0.455</p>	<p><b>134 Sunset Bl &amp; Stanford Ranch Rd</b></p> <p>In 146 383 226  </p> <p>122 539 285        In</p> <p>LOS: C        V/C: 0.793</p>
<p><b>134 Sunset Bl &amp; Stanford Ranch Rd</b></p> <p>In 146 383 226  </p> <p>122 539 285        In</p> <p>LOS: C        V/C: 0.793</p>	<p><b>135 Sunset Bl &amp; West Oaks Bl</b></p> <p>In 19 103 126  </p> <p>29 529 6        In</p> <p>LOS: A        V/C: 0.349</p>	<p><b>136 W Stanford Ranch Rd &amp; Sunset Bl</b></p> <p>In 137 206 185  </p> <p>214 339 70        In</p> <p>LOS: A        V/C: 0.467</p>	<p><b>137 W Stanford Ranch Rd &amp; Wildcat Bl</b></p> <p>In 356 0 159  </p> <p>559 196 0        In</p> <p>LOS: A        V/C: 0.455</p>





**Figure D2**  
**Existing PM Peak Hour Intersection Level of Service**  
**State Highway Intersections**

<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>125</td> <td>1,019</td> <td>0</td> </tr> <tr> <td></td> <td>185</td> <td>594</td> <td>0</td> <td>583</td> <td>0</td> <td>596</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: C</td> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: C</td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">Del: 26.1 sec</td> <td>E/W</td> <td>Protected</td> <td colspan="2">Del: 21.8 sec</td> </tr> </table>	In	0	0	0	In	125	1,019	0		185	594	0	583	0	596	In	N/S	Permitted	LOS: C		N/S	Permitted	LOS: C		E/W	Protected	Del: 26.1 sec		E/W	Protected	Del: 21.8 sec		<p>201</p> <p><b>Rocklin Rd &amp; I-80 EB</b></p>	<p>202</p> <p><b>Rocklin Rd &amp; I-80 WB</b></p>	<p>203</p> <p><b>Sierra College Bl &amp; I-80 WB</b></p>	<p>204</p> <p><b>Sierra College Bl &amp; I-80 EB</b></p>																																																																																																			
In	0	0	0	In	125	1,019	0																																																																																																																																
	185	594	0	583	0	596	In																																																																																																																																
N/S	Permitted	LOS: C		N/S	Permitted	LOS: C																																																																																																																																	
E/W	Protected	Del: 26.1 sec		E/W	Protected	Del: 21.8 sec																																																																																																																																	
<table border="1"> <tr> <td>In</td> <td>27</td> <td>1,437</td> <td>185</td> <td>In</td> <td>315</td> <td>136</td> <td>390</td> </tr> <tr> <td></td> <td>83</td> <td>191</td> <td>563</td> <td>292</td> <td>1,970</td> <td>44</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: D</td> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">Del: 39.4 sec</td> <td>E/W</td> <td>Protected</td> <td colspan="2">Del: 24.4 sec</td> </tr> </table>	In	27	1,437	185	In	315	136	390		83	191	563	292	1,970	44	In	N/S	Protected	LOS: D		N/S	Protected	LOS: C		E/W	Protected	Del: 39.4 sec		E/W	Protected	Del: 24.4 sec		<p>205</p> <p><b>SR 65 &amp; Sunset Blvd</b></p>	<p>210</p> <p><b>Blue Oaks Blvd &amp; SR 65 SB</b></p>	<p>211</p> <p><b>Blue Oaks Blvd &amp; SR 65 NB Off</b></p>	<p>212</p> <p><b>Pleasant Grove Blvd &amp; SR 65 NB</b></p>																																																																																																			
In	27	1,437	185	In	315	136	390																																																																																																																																
	83	191	563	292	1,970	44	In																																																																																																																																
N/S	Protected	LOS: D		N/S	Protected	LOS: C																																																																																																																																	
E/W	Protected	Del: 39.4 sec		E/W	Protected	Del: 24.4 sec																																																																																																																																	
<table border="1"> <tr> <td>Ig</td> <td>254</td> <td>0</td> <td>115</td> <td>In</td> <td>0</td> <td>1,430</td> <td>322</td> </tr> <tr> <td></td> <td>0</td> <td>1,461</td> <td>605</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: B</td> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">Del: 19.8 sec</td> <td>E/W</td> <td>Permitted</td> <td colspan="2">Del: 26.6 sec</td> </tr> </table>	Ig	254	0	115	In	0	1,430	322		0	1,461	605	0	0	0	In	N/S	Permitted	LOS: B		N/S	Protected	LOS: C		E/W	Protected	Del: 19.8 sec		E/W	Permitted	Del: 26.6 sec		<p>213</p> <p><b>Pleasant Grove Blvd &amp; SR 65 SB</b></p>	<table border="1"> <tr> <td>In</td> <td>304</td> <td>1,685</td> <td>0</td> <td>Ig</td> <td>937</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>392</td> <td>981</td> <td>1,671</td> <td>0</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td colspan="2">Del: 26.6 sec</td> <td>E/W</td> <td>Permitted</td> <td colspan="2">Del: 34.1 sec</td> </tr> </table>	In	304	1,685	0	Ig	937	0	0		0	0	392	981	1,671	0	In	N/S	Protected	LOS: C		N/S	Protected	LOS: C		E/W	Permitted	Del: 26.6 sec		E/W	Permitted	Del: 34.1 sec		<p>214</p> <p><b>Stanford Ranch Rd &amp; SR 65 NB</b></p>	<table border="1"> <tr> <td>In</td> <td>0</td> <td>1,475</td> <td>592</td> <td>Ig</td> <td>199</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>635</td> <td>0</td> <td>2,462</td> <td>469</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td colspan="2">Del: 34.1 sec</td> <td>E/W</td> <td>Permitted</td> <td colspan="2">Del: 34.1 sec</td> </tr> </table>	In	0	1,475	592	Ig	199	0	0		0	0	635	0	2,462	469	In	N/S	Protected	LOS: C		N/S	Protected	LOS: C		E/W	Permitted	Del: 34.1 sec		E/W	Permitted	Del: 34.1 sec		<p>215</p> <p><b>Stanford Ranch Rd &amp; SR 65 SB</b></p>	<table border="1"> <tr> <td>In</td> <td>8</td> <td>4</td> <td>4</td> <td>In</td> <td>76</td> <td>184</td> <td>76</td> </tr> <tr> <td></td> <td>5</td> <td>201</td> <td>181</td> <td>370</td> <td>5</td> <td>126</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Stop Sign</td> <td colspan="2">LOS: F[53.5]</td> <td>N/S</td> <td>Stop Sign</td> <td colspan="2">LOS: F[53.5]</td> </tr> <tr> <td>E/W</td> <td>Uncontrolled</td> <td colspan="2">Del: 22.3 sec</td> <td>E/W</td> <td>Uncontrolled</td> <td colspan="2">Del: 22.3 sec</td> </tr> </table>	In	8	4	4	In	76	184	76		5	201	181	370	5	126	In	N/S	Stop Sign	LOS: F[53.5]		N/S	Stop Sign	LOS: F[53.5]		E/W	Uncontrolled	Del: 22.3 sec		E/W	Uncontrolled	Del: 22.3 sec		<p>216</p> <p><b>Sierra College Blvd &amp; SR 193</b></p>
Ig	254	0	115	In	0	1,430	322																																																																																																																																
	0	1,461	605	0	0	0	In																																																																																																																																
N/S	Permitted	LOS: B		N/S	Protected	LOS: C																																																																																																																																	
E/W	Protected	Del: 19.8 sec		E/W	Permitted	Del: 26.6 sec																																																																																																																																	
In	304	1,685	0	Ig	937	0	0																																																																																																																																
	0	0	392	981	1,671	0	In																																																																																																																																
N/S	Protected	LOS: C		N/S	Protected	LOS: C																																																																																																																																	
E/W	Permitted	Del: 26.6 sec		E/W	Permitted	Del: 34.1 sec																																																																																																																																	
In	0	1,475	592	Ig	199	0	0																																																																																																																																
	0	0	635	0	2,462	469	In																																																																																																																																
N/S	Protected	LOS: C		N/S	Protected	LOS: C																																																																																																																																	
E/W	Permitted	Del: 34.1 sec		E/W	Permitted	Del: 34.1 sec																																																																																																																																	
In	8	4	4	In	76	184	76																																																																																																																																
	5	201	181	370	5	126	In																																																																																																																																
N/S	Stop Sign	LOS: F[53.5]		N/S	Stop Sign	LOS: F[53.5]																																																																																																																																	
E/W	Uncontrolled	Del: 22.3 sec		E/W	Uncontrolled	Del: 22.3 sec																																																																																																																																	

**Figure D3**  
**Existing PM Peak Hour Intersection Level of Service**  
**Loomis Intersections**

<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>405</td> <td>78</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>92</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>61</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>634</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>89</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase Del: 16.3 sec</p>	In	0	405	78					In	92			4							0										61										0										634										89										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>71</td> <td>224</td> <td>25</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>44</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>270</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>160</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>131</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>315</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>89</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 29.8 sec</p>	In	71	224	25					In	44			4							270										160										131										315										89										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>3</td> <td>298</td> <td>63</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>88</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>4</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>15</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>21</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>14</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>4</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase Del: 16.1 sec</p>	In	3	298	63					In	88			4							4										15										21										14										4										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>239</td> <td>28</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>32</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>83</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>95</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>67</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>91</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>362</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 30.5 sec</p>	In	0	239	28					In	32			4							83										95										67										91										362										In
In	0	405	78					In	92																																																																																																																																																																																																																																																																																		
		4							0																																																																																																																																																																																																																																																																																		
									61																																																																																																																																																																																																																																																																																		
									0																																																																																																																																																																																																																																																																																		
									634																																																																																																																																																																																																																																																																																		
									89																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	71	224	25					In	44																																																																																																																																																																																																																																																																																		
		4							270																																																																																																																																																																																																																																																																																		
									160																																																																																																																																																																																																																																																																																		
									131																																																																																																																																																																																																																																																																																		
									315																																																																																																																																																																																																																																																																																		
									89																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	3	298	63					In	88																																																																																																																																																																																																																																																																																		
		4							4																																																																																																																																																																																																																																																																																		
									15																																																																																																																																																																																																																																																																																		
									21																																																																																																																																																																																																																																																																																		
									14																																																																																																																																																																																																																																																																																		
									4																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	0	239	28					In	32																																																																																																																																																																																																																																																																																		
		4							83																																																																																																																																																																																																																																																																																		
									95																																																																																																																																																																																																																																																																																		
									67																																																																																																																																																																																																																																																																																		
									91																																																																																																																																																																																																																																																																																		
									362																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
<p><b>301 Sierra College Bl &amp; Brace Rd</b></p>	<p><b>302 Sierra College Bl &amp; Taylor Rd</b></p>	<p><b>304 Sierra College Bl &amp; King Rd</b></p>	<p><b>305 Taylor Rd &amp; King Rd</b></p>																																																																																																																																																																																																																																																																																								
<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>4</td> <td>353</td> <td>371</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>400</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>8</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>85</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>13</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>7</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: D  E/W Split Phase Del: 38.3 sec</p>	In	4	353	371					In	400			4							8										85										13										7										5										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>55</td> <td>43</td> <td>0</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>61</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>242</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: A  E/W Stop Sign Del: 10 sec</p>	In	55	43	0					In	0			4							0										0										61										0										242										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>57</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>114</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>64</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>150</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: B[15.0]  E/W Uncontrolled Del: 6.9 sec</p>	In	0	0	0					In	0										57										114										0										64										150										In	<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>387</td> <td>202</td> <td>48</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>140</td> </tr> <tr> <td></td> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>50</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>72</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>75</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>46</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>67</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 26 sec</p>	In	387	202	48					In	140			4							50										72										75										46										67										In
In	4	353	371					In	400																																																																																																																																																																																																																																																																																		
		4							8																																																																																																																																																																																																																																																																																		
									85																																																																																																																																																																																																																																																																																		
									13																																																																																																																																																																																																																																																																																		
									7																																																																																																																																																																																																																																																																																		
									5																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	55	43	0					In	0																																																																																																																																																																																																																																																																																		
		4							0																																																																																																																																																																																																																																																																																		
									0																																																																																																																																																																																																																																																																																		
									61																																																																																																																																																																																																																																																																																		
									0																																																																																																																																																																																																																																																																																		
									242																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	0	0	0					In	0																																																																																																																																																																																																																																																																																		
									57																																																																																																																																																																																																																																																																																		
									114																																																																																																																																																																																																																																																																																		
									0																																																																																																																																																																																																																																																																																		
									64																																																																																																																																																																																																																																																																																		
									150																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
In	387	202	48					In	140																																																																																																																																																																																																																																																																																		
		4							50																																																																																																																																																																																																																																																																																		
									72																																																																																																																																																																																																																																																																																		
									75																																																																																																																																																																																																																																																																																		
									46																																																																																																																																																																																																																																																																																		
									67																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
<p><b>306 Taylor Rd &amp; Horseshoe Bar</b></p>	<p><b>307 Rocklin Rd &amp; Barton Rd</b></p>	<p><b>308 Barton Rd &amp; Brace Rd</b></p>	<p><b>309 Horseshoe Bar Rd &amp; I-80 WB Ramp</b></p>																																																																																																																																																																																																																																																																																								
<p>EXPM</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>242</td> <td>157</td> <td></td> <td></td> <td></td> <td></td> <td>In</td> <td>398</td> </tr> <tr> <td></td> <td></td> <td>7</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>114</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>273</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>61</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Uncontrolled LOS: C[18.2]  E/W Stop Sign Del: 8.6 sec</p>	In	0	242	157					In	398			7							0										114										0										273										61										In																																																																																																																																																																																																																					
In	0	242	157					In	398																																																																																																																																																																																																																																																																																		
		7							0																																																																																																																																																																																																																																																																																		
									114																																																																																																																																																																																																																																																																																		
									0																																																																																																																																																																																																																																																																																		
									273																																																																																																																																																																																																																																																																																		
									61																																																																																																																																																																																																																																																																																		
									In																																																																																																																																																																																																																																																																																		
<p><b>310 Horseshoe Bar Rd &amp; I-80 EB Ramp</b></p>																																																																																																																																																																																																																																																																																											



**Figure D5**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Plus Project Conditions**

<p>GP08</p> <table border="1"> <tr> <td>Ov</td> <td>237 19 628</td> <td>In</td> <td>558 819 32</td> </tr> <tr> <td></td> <td>227 1,762 10</td> <td></td> <td>30 17 15</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: D</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.878</td> <td></td> </tr> </table>	Ov	237 19 628	In	558 819 32		227 1,762 10		30 17 15	N/S	Split Phase	LOS: D		E/W	Protected	V/C: 0.878		<table border="1"> <tr> <td>In</td> <td>90 769 53</td> <td>In</td> <td>24 27 205</td> </tr> <tr> <td></td> <td>254 32 242</td> <td></td> <td>89 686 100</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.463</td> <td></td> </tr> </table>	In	90 769 53	In	24 27 205		254 32 242		89 686 100	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.463		<table border="1"> <tr> <td>In</td> <td>317 55 54</td> <td>In</td> <td>55 366 61</td> </tr> <tr> <td></td> <td>210 309 53</td> <td></td> <td>104 65 45</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.622</td> <td></td> </tr> </table>	In	317 55 54	In	55 366 61		210 309 53		104 65 45	N/S	Split Phase	LOS: B		E/W	Protected	V/C: 0.622		<table border="1"> <tr> <td>In</td> <td>72 542 35</td> <td>In</td> <td>88 103 144</td> </tr> <tr> <td></td> <td>263 331 371</td> <td></td> <td>119 686 169</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: E</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.902</td> <td></td> </tr> </table>	In	72 542 35	In	88 103 144		263 331 371		119 686 169	N/S	Protected	LOS: E		E/W	Split Phase	V/C: 0.902	
Ov	237 19 628	In	558 819 32																																																																
	227 1,762 10		30 17 15																																																																
N/S	Split Phase	LOS: D																																																																	
E/W	Protected	V/C: 0.878																																																																	
In	90 769 53	In	24 27 205																																																																
	254 32 242		89 686 100																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.463																																																																	
In	317 55 54	In	55 366 61																																																																
	210 309 53		104 65 45																																																																
N/S	Split Phase	LOS: B																																																																	
E/W	Protected	V/C: 0.622																																																																	
In	72 542 35	In	88 103 144																																																																
	263 331 371		119 686 169																																																																
N/S	Protected	LOS: E																																																																	
E/W	Split Phase	V/C: 0.902																																																																	
<b>1 Granite Dr &amp; Rocklin Rd</b>	<b>2 Granite Dr &amp; Sierra College Bl</b>	<b>3 Granite Dr &amp; Sierra Meadows</b>	<b>4 Pacific St &amp; Del Mar/ Dominguez</b>																																																																
<table border="1"> <tr> <td>In</td> <td>47 1,091 104</td> <td>In</td> <td>47 6 70</td> </tr> <tr> <td></td> <td>39 12 327</td> <td></td> <td>218 1,151 30</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: D</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.809</td> <td></td> </tr> </table>	In	47 1,091 104	In	47 6 70		39 12 327		218 1,151 30	N/S	Protected	LOS: D		E/W	Split Phase	V/C: 0.809		<table border="1"> <tr> <td>In</td> <td>374 703 166</td> <td>In</td> <td>12 53 8</td> </tr> <tr> <td></td> <td>277 136 101</td> <td></td> <td>135 575 16</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.579</td> <td></td> </tr> </table>	In	374 703 166	In	12 53 8		277 136 101		135 575 16	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.579		<table border="1"> <tr> <td>In</td> <td>56 579 217</td> <td>In</td> <td>187 221 497</td> </tr> <tr> <td></td> <td>75 375 58</td> <td></td> <td>67 452 707</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.787</td> <td></td> </tr> </table>	In	56 579 217	In	187 221 497		75 375 58		67 452 707	N/S	Protected	LOS: C		E/W	Split Phase	V/C: 0.787		<table border="1"> <tr> <td>In</td> <td>10 880 185</td> <td>In</td> <td>146 44 123</td> </tr> <tr> <td></td> <td>6 19 26</td> <td></td> <td>25 829 107</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.612</td> <td></td> </tr> </table>	In	10 880 185	In	146 44 123		6 19 26		25 829 107	N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.612	
In	47 1,091 104	In	47 6 70																																																																
	39 12 327		218 1,151 30																																																																
N/S	Protected	LOS: D																																																																	
E/W	Split Phase	V/C: 0.809																																																																	
In	374 703 166	In	12 53 8																																																																
	277 136 101		135 575 16																																																																
N/S	Protected	LOS: A																																																																	
E/W	Split Phase	V/C: 0.579																																																																	
In	56 579 217	In	187 221 497																																																																
	75 375 58		67 452 707																																																																
N/S	Protected	LOS: C																																																																	
E/W	Split Phase	V/C: 0.787																																																																	
In	10 880 185	In	146 44 123																																																																
	6 19 26		25 829 107																																																																
N/S	Protected	LOS: B																																																																	
E/W	Split Phase	V/C: 0.612																																																																	
<b>5 Pacific St &amp; Farron St</b>	<b>6 Pacific St &amp; Midas Ave</b>	<b>7 Pacific St &amp; Rocklin Rd</b>	<b>8 Pacific St &amp; Sierra Meadows</b>																																																																
<table border="1"> <tr> <td>In</td> <td>0 961 99</td> <td>In</td> <td>79 0 171</td> </tr> <tr> <td></td> <td>0 0 0</td> <td></td> <td>1,122 147</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.554</td> <td></td> </tr> </table>	In	0 961 99	In	79 0 171		0 0 0		1,122 147	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.554		<table border="1"> <tr> <td>In</td> <td>0 0 0</td> <td>In</td> <td>0 820 40</td> </tr> <tr> <td></td> <td>70 1,108 265</td> <td></td> <td>196 0 41</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.462</td> <td></td> </tr> </table>	In	0 0 0	In	0 820 40		70 1,108 265		196 0 41	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.462		<table border="1"> <tr> <td>Ov</td> <td>401 8 74</td> <td>In</td> <td>82 365 8</td> </tr> <tr> <td></td> <td>252 845 103</td> <td></td> <td>103 5 7</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.450</td> <td></td> </tr> </table>	Ov	401 8 74	In	82 365 8		252 845 103		103 5 7	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.450		<table border="1"> <tr> <td>In</td> <td>0 0 0</td> <td>In</td> <td>0 840 0</td> </tr> <tr> <td></td> <td>0 1,339 0</td> <td></td> <td>0 0 0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.418</td> <td></td> </tr> </table>	In	0 0 0	In	0 840 0		0 1,339 0		0 0 0	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.418	
In	0 961 99	In	79 0 171																																																																
	0 0 0		1,122 147																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.554																																																																	
In	0 0 0	In	0 820 40																																																																
	70 1,108 265		196 0 41																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.462																																																																	
Ov	401 8 74	In	82 365 8																																																																
	252 845 103		103 5 7																																																																
N/S	Split Phase	LOS: A																																																																	
E/W	Protected	V/C: 0.450																																																																	
In	0 0 0	In	0 840 0																																																																
	0 1,339 0		0 0 0																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.418																																																																	
<b>9 Pacific St &amp; Woodside Dr</b>	<b>10 Rocklin Rd &amp; Aguilar Rd</b>	<b>11 Rocklin Rd &amp; El Don Dr</b>	<b>12 Rocklin Rd &amp; Fire Station No 1</b>																																																																
<table border="1"> <tr> <td>In</td> <td>41 1 78</td> <td>Ov</td> <td>61 600 9</td> </tr> <tr> <td></td> <td>46 981 27</td> <td></td> <td>15 0 4</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.306</td> <td></td> </tr> </table>	In	41 1 78	Ov	61 600 9		46 981 27		15 0 4	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.306		<table border="1"> <tr> <td>In</td> <td>76 609 203</td> <td>In</td> <td>96 136 51</td> </tr> <tr> <td></td> <td>2 314 486</td> <td></td> <td>353 632 87</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.493</td> <td></td> </tr> </table>	In	76 609 203	In	96 136 51		2 314 486		353 632 87	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.493		<table border="1"> <tr> <td>In</td> <td>0 0 0</td> <td>In</td> <td>0 871 144</td> </tr> <tr> <td></td> <td>0 1,262 34</td> <td></td> <td>26 0 162</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.636</td> <td></td> </tr> </table>	In	0 0 0	In	0 871 144		0 1,262 34		26 0 162	N/S	Protected	LOS: B		E/W	Protected	V/C: 0.636		<table border="1"> <tr> <td>In</td> <td>19 1,168 19</td> <td>In</td> <td>33 3 21</td> </tr> <tr> <td></td> <td>18 2 29</td> <td></td> <td>45 969 5</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.373</td> <td></td> </tr> </table>	In	19 1,168 19	In	33 3 21		18 2 29		45 969 5	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.373	
In	41 1 78	Ov	61 600 9																																																																
	46 981 27		15 0 4																																																																
N/S	Split Phase	LOS: A																																																																	
E/W	Protected	V/C: 0.306																																																																	
In	76 609 203	In	96 136 51																																																																
	2 314 486		353 632 87																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.493																																																																	
In	0 0 0	In	0 871 144																																																																
	0 1,262 34		26 0 162																																																																
N/S	Protected	LOS: B																																																																	
E/W	Protected	V/C: 0.636																																																																	
In	19 1,168 19	In	33 3 21																																																																
	18 2 29		45 969 5																																																																
N/S	Protected	LOS: A																																																																	
E/W	Split Phase	V/C: 0.373																																																																	
<b>13 Rocklin Rd &amp; Havenhurst Cir</b>	<b>14 Rocklin Rd &amp; Sierra College Bl</b>	<b>15 Rocklin Rd &amp; South Grove St</b>	<b>16 Sierra College Bl &amp; El Don Dr</b>																																																																
<table border="1"> <tr> <td>In</td> <td>92 1,105 0</td> <td>In</td> <td>0 0 0</td> </tr> <tr> <td></td> <td>90 0 96</td> <td></td> <td>62 931 0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.351</td> <td></td> </tr> </table>	In	92 1,105 0	In	0 0 0		90 0 96		62 931 0	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.351		<table border="1"> <tr> <td>In</td> <td>49 1,179 4</td> <td>In</td> <td>0 0 4</td> </tr> <tr> <td></td> <td>27 0 122</td> <td></td> <td>72 1,009 1</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.408</td> <td></td> </tr> </table>	In	49 1,179 4	In	0 0 4		27 0 122		72 1,009 1	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.408		<table border="1"> <tr> <td>In</td> <td>30 1,122 5</td> <td>In</td> <td>3 0 1</td> </tr> <tr> <td></td> <td>23 0 24</td> <td></td> <td>6 1,001 1</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.297</td> <td></td> </tr> </table>	In	30 1,122 5	In	3 0 1		23 0 24		6 1,001 1	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.297		<table border="1"> <tr> <td>Ig</td> <td>936 647 81</td> <td>In</td> <td>39 115 51</td> </tr> <tr> <td></td> <td>849 101 393</td> <td></td> <td>706 547 16</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.725</td> <td></td> </tr> </table>	Ig	936 647 81	In	39 115 51		849 101 393		706 547 16	N/S	Protected	LOS: C		E/W	Protected	V/C: 0.725	
In	92 1,105 0	In	0 0 0																																																																
	90 0 96		62 931 0																																																																
N/S	Protected	LOS: A																																																																	
E/W	Protected	V/C: 0.351																																																																	
In	49 1,179 4	In	0 0 4																																																																
	27 0 122		72 1,009 1																																																																
N/S	Protected	LOS: A																																																																	
E/W	Split Phase	V/C: 0.408																																																																	
In	30 1,122 5	In	3 0 1																																																																
	23 0 24		6 1,001 1																																																																
N/S	Protected	LOS: A																																																																	
E/W	Split Phase	V/C: 0.297																																																																	
Ig	936 647 81	In	39 115 51																																																																
	849 101 393		706 547 16																																																																
N/S	Protected	LOS: C																																																																	
E/W	Protected	V/C: 0.725																																																																	
<b>17 Sierra College Bl &amp; Nightwatch</b>	<b>18 Sierra College Bl &amp; Scarborough</b>	<b>19 Sierra College Bl &amp; Southside Ranch</b>	<b>20 Sunset Bl &amp; Pacific St</b>																																																																

**Figure D5**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Plus Project Conditions**

<table border="1"> <tr> <td>In</td> <td>394</td> <td>41</td> <td>51</td> <td>In</td> <td>106</td> <td>1,510</td> <td>203</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>360</td> <td>1,146</td> <td>112</td> <td></td> <td>127</td> <td>40</td> <td>187</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td colspan="2">LOS: F</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 1.084</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	394	41	51	In	106	1,510	203										360	1,146	112		127	40	187	N/S	Split Phase	LOS: F						E/W	Protected	V/C: 1.084						<table border="1"> <tr> <td>In</td> <td>113</td> <td>14</td> <td>101</td> <td>In</td> <td>97</td> <td>1,378</td> <td>68</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>95</td> <td>1,218</td> <td>23</td> <td></td> <td>24</td> <td>15</td> <td>20</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.559</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	113	14	101	In	97	1,378	68										95	1,218	23		24	15	20	N/S	Permitted	LOS: A						E/W	Protected	V/C: 0.559						<table border="1"> <tr> <td>In</td> <td>10</td> <td>52</td> <td>142</td> <td>In</td> <td>250</td> <td>1,432</td> <td>305</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>53</td> <td>1,264</td> <td>36</td> <td></td> <td>45</td> <td>23</td> <td>175</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: C</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.744</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	10	52	142	In	250	1,432	305										53	1,264	36		45	23	175	N/S	Protected	LOS: C						E/W	Protected	V/C: 0.744						<table border="1"> <tr> <td>In</td> <td>1,234</td> <td>289</td> <td>26</td> <td>In</td> <td>58</td> <td>712</td> <td>96</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>631</td> <td>495</td> <td>176</td> <td></td> <td>315</td> <td>263</td> <td>43</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.671</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	1,234	289	26	In	58	712	96										631	495	176		315	263	43	N/S	Protected	LOS: B						E/W	Protected	V/C: 0.671					
In	394	41	51	In	106	1,510	203																																																																																																																																																												
	360	1,146	112		127	40	187																																																																																																																																																												
N/S	Split Phase	LOS: F																																																																																																																																																																	
E/W	Protected	V/C: 1.084																																																																																																																																																																	
In	113	14	101	In	97	1,378	68																																																																																																																																																												
	95	1,218	23		24	15	20																																																																																																																																																												
N/S	Permitted	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.559																																																																																																																																																																	
In	10	52	142	In	250	1,432	305																																																																																																																																																												
	53	1,264	36		45	23	175																																																																																																																																																												
N/S	Protected	LOS: C																																																																																																																																																																	
E/W	Protected	V/C: 0.744																																																																																																																																																																	
In	1,234	289	26	In	58	712	96																																																																																																																																																												
	631	495	176		315	263	43																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.671																																																																																																																																																																	
<p><b>21 Sunset Bl &amp; Springview Dr</b></p>	<p><b>22 Sunset Bl &amp; Topaz Ave</b></p>	<p><b>23 Sunset Bl &amp; Whitney Bl</b></p>	<p><b>101 Blue Oaks Bl &amp; Lonetree</b></p>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>6</td> <td>1</td> <td>4</td> <td>In</td> <td>3</td> <td>824</td> <td>2</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>4</td> <td>660</td> <td>3</td> <td></td> <td>6</td> <td>0</td> <td>1</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.296</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	6	1	4	In	3	824	2										4	660	3		6	0	1	N/S	Split Phase	LOS: A						E/W	Protected	V/C: 0.296						<table border="1"> <tr> <td>In</td> <td>29</td> <td>776</td> <td>16</td> <td>In</td> <td>22</td> <td>0</td> <td>16</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>9</td> <td>0</td> <td>22</td> <td></td> <td>37</td> <td>591</td> <td>14</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.351</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	29	776	16	In	22	0	16										9	0	22		37	591	14	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.351						<table border="1"> <tr> <td>In</td> <td>13</td> <td>25</td> <td>222</td> <td>In</td> <td>354</td> <td>1</td> <td>3</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>13</td> <td>0</td> <td>2</td> <td></td> <td>0</td> <td>20</td> <td>3</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.416</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	13	25	222	In	354	1	3										13	0	2		0	20	3	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.416						<table border="1"> <tr> <td>In</td> <td>8</td> <td>1,391</td> <td>17</td> <td>In</td> <td>15</td> <td>1</td> <td>17</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>9</td> <td>1</td> <td>24</td> <td></td> <td>22</td> <td>601</td> <td>18</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.537</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	8	1,391	17	In	15	1	17										9	1	24		22	601	18	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.537					
In	6	1	4	In	3	824	2																																																																																																																																																												
	4	660	3		6	0	1																																																																																																																																																												
N/S	Split Phase	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.296																																																																																																																																																																	
In	29	776	16	In	22	0	16																																																																																																																																																												
	9	0	22		37	591	14																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.351																																																																																																																																																																	
In	13	25	222	In	354	1	3																																																																																																																																																												
	13	0	2		0	20	3																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.416																																																																																																																																																																	
In	8	1,391	17	In	15	1	17																																																																																																																																																												
	9	1	24		22	601	18																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.537																																																																																																																																																																	
<p><b>102 Blue Oaks Bl &amp; Market Place</b></p>	<p><b>103 Blue Oaks Bl &amp; Van Buren Way</b></p>	<p><b>104 Five Star &amp; Destiny Dr</b></p>	<p><b>105 Lonetree Bl &amp; Adams Dr</b></p>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>6</td> <td>703</td> <td>0</td> <td>In</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>38</td> <td>0</td> <td>331</td> <td></td> <td>34</td> <td>436</td> <td>0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.480</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	6	703	0	In	0	0	0										38	0	331		34	436	0	N/S	Protected	LOS: A						E/W	Protected	V/C: 0.480						<table border="1"> <tr> <td>In</td> <td>7</td> <td>1,477</td> <td>5</td> <td>In</td> <td>4</td> <td>1</td> <td>9</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>16</td> <td>1</td> <td>44</td> <td></td> <td>149</td> <td>723</td> <td>24</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.654</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	7	1,477	5	In	4	1	9										16	1	44		149	723	24	N/S	Protected	LOS: B						E/W	Split Phase	V/C: 0.654						<table border="1"> <tr> <td>In</td> <td>52</td> <td>1,346</td> <td>25</td> <td>In</td> <td>9</td> <td>5</td> <td>29</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>30</td> <td>2</td> <td>67</td> <td></td> <td>107</td> <td>615</td> <td>30</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.632</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	52	1,346	25	In	9	5	29										30	2	67		107	615	30	N/S	Protected	LOS: B						E/W	Split Phase	V/C: 0.632						<table border="1"> <tr> <td>In</td> <td>1</td> <td>1,028</td> <td>9</td> <td>In</td> <td>6</td> <td>1</td> <td>230</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>4</td> <td></td> <td>7</td> <td>411</td> <td>144</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.521</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	1	1,028	9	In	6	1	230										1	0	4		7	411	144	N/S	Protected	LOS: A						E/W	Protected	V/C: 0.521					
In	6	703	0	In	0	0	0																																																																																																																																																												
	38	0	331		34	436	0																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.480																																																																																																																																																																	
In	7	1,477	5	In	4	1	9																																																																																																																																																												
	16	1	44		149	723	24																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Split Phase	V/C: 0.654																																																																																																																																																																	
In	52	1,346	25	In	9	5	29																																																																																																																																																												
	30	2	67		107	615	30																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Split Phase	V/C: 0.632																																																																																																																																																																	
In	1	1,028	9	In	6	1	230																																																																																																																																																												
	1	0	4		7	411	144																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.521																																																																																																																																																																	
<p><b>106 Lonetree Bl &amp; Atherton Rd</b></p>	<p><b>107 Lonetree Bl &amp; Grand Canyon Dr</b></p>	<p><b>108 Lonetree Bl &amp; Redwood Dr</b></p>	<p><b>109 Lonetree Bl &amp; West Oaks Bl</b></p>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>320</td> <td>6</td> <td>84</td> <td>In</td> <td>64</td> <td>619</td> <td>14</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>216</td> <td>588</td> <td>11</td> <td></td> <td>2</td> <td>2</td> <td>5</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.646</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	320	6	84	In	64	619	14										216	588	11		2	2	5	N/S	Permitted	LOS: B						E/W	Protected	V/C: 0.646						<table border="1"> <tr> <td>In</td> <td>46</td> <td>1,339</td> <td>17</td> <td>In</td> <td>8</td> <td>0</td> <td>10</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>46</td> <td>4</td> <td>29</td> <td></td> <td>78</td> <td>1,144</td> <td>6</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.578</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	46	1,339	17	In	8	0	10										46	4	29		78	1,144	6	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.578						<table border="1"> <tr> <td>In</td> <td>72</td> <td>1,032</td> <td>0</td> <td>In</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>41</td> <td>0</td> <td>237</td> <td></td> <td>221</td> <td>798</td> <td>0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.673</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	72	1,032	0	In	0	0	0										41	0	237		221	798	0	N/S	Protected	LOS: B						E/W	Protected	V/C: 0.673						<table border="1"> <tr> <td>In</td> <td>7</td> <td>1,373</td> <td>27</td> <td>In</td> <td>16</td> <td>0</td> <td>15</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>7</td> <td>1</td> <td>9</td> <td></td> <td>24</td> <td>1,191</td> <td>17</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td colspan="2">V/C: 0.492</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	7	1,373	27	In	16	0	15										7	1	9		24	1,191	17	N/S	Protected	LOS: A						E/W	Permitted	V/C: 0.492					
In	320	6	84	In	64	619	14																																																																																																																																																												
	216	588	11		2	2	5																																																																																																																																																												
N/S	Permitted	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.646																																																																																																																																																																	
In	46	1,339	17	In	8	0	10																																																																																																																																																												
	46	4	29		78	1,144	6																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.578																																																																																																																																																																	
In	72	1,032	0	In	0	0	0																																																																																																																																																												
	41	0	237		221	798	0																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.673																																																																																																																																																																	
In	7	1,373	27	In	16	0	15																																																																																																																																																												
	7	1	9		24	1,191	17																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Permitted	V/C: 0.492																																																																																																																																																																	
<p><b>110 Park Dr &amp; Blaydon Rd</b></p>	<p><b>111 Park Dr &amp; Quarry Way</b></p>	<p><b>112 Park Dr &amp; Farrier Rd</b></p>	<p><b>113 Park Dr &amp; King Pine Dr</b></p>																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>3</td> <td>1,156</td> <td>6</td> <td>In</td> <td>1</td> <td>4</td> <td>11</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>8</td> <td>0</td> <td>46</td> <td></td> <td>71</td> <td>1,101</td> <td>14</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.355</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	3	1,156	6	In	1	4	11										8	0	46		71	1,101	14	N/S	Protected	LOS: A						E/W	Protected	V/C: 0.355						<table border="1"> <tr> <td>In</td> <td>32</td> <td>1,058</td> <td>91</td> <td>In</td> <td>127</td> <td>14</td> <td>26</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>91</td> <td>5</td> <td>12</td> <td></td> <td>37</td> <td>949</td> <td>6</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.436</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	32	1,058	91	In	127	14	26										91	5	12		37	949	6	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.436						<table border="1"> <tr> <td>In</td> <td>285</td> <td>0</td> <td>38</td> <td>In</td> <td>62</td> <td>921</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>334</td> <td>775</td> <td>0</td> <td></td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.608</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	285	0	38	In	62	921	0										334	775	0		0	0	0	N/S	Protected	LOS: B						E/W	Protected	V/C: 0.608						<table border="1"> <tr> <td>In</td> <td>32</td> <td>979</td> <td>25</td> <td>In</td> <td>2</td> <td>0</td> <td>77</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>65</td> <td>2</td> <td>59</td> <td></td> <td>66</td> <td>806</td> <td>21</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.534</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	32	979	25	In	2	0	77										65	2	59		66	806	21	N/S	Protected	LOS: A						E/W	Split Phase	V/C: 0.534					
In	3	1,156	6	In	1	4	11																																																																																																																																																												
	8	0	46		71	1,101	14																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Protected	V/C: 0.355																																																																																																																																																																	
In	32	1,058	91	In	127	14	26																																																																																																																																																												
	91	5	12		37	949	6																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.436																																																																																																																																																																	
In	285	0	38	In	62	921	0																																																																																																																																																												
	334	775	0		0	0	0																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																	
E/W	Protected	V/C: 0.608																																																																																																																																																																	
In	32	979	25	In	2	0	77																																																																																																																																																												
	65	2	59		66	806	21																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																	
E/W	Split Phase	V/C: 0.534																																																																																																																																																																	
<p><b>114 Park Dr &amp; Shelton</b></p>	<p><b>115 Park Dr &amp; Victory Lane</b></p>	<p><b>116 Park Dr &amp; Wykford Bl</b></p>	<p><b>117 Park Dr &amp; Twin Oaks/Boardwalk</b></p>																																																																																																																																																																

**Figure D5**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Plus Project Conditions**

<table border="1"> <tr><td>In</td><td>113</td><td>In</td><td>195</td></tr> <tr><td>↙ ↘</td><td>1,316</td><td>↙ ↘</td><td>0</td></tr> <tr><td>↖ ↗</td><td>71</td><td>↖ ↗</td><td>0</td></tr> <tr><td colspan="2">Park</td><td colspan="2">Safeway</td></tr> <tr><td>0</td><td>0</td><td>0</td><td>1,142</td></tr> <tr><td>0</td><td>70</td><td>1,142</td><td>105</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.627</td><td></td></tr> </table>	In	113	In	195	↙ ↘	1,316	↙ ↘	0	↖ ↗	71	↖ ↗	0	Park		Safeway		0	0	0	1,142	0	70	1,142	105	In	In	In	In	N/S	Protected	LOS: B		E/W	Protected	V/C: 0.627		<table border="1"> <tr><td>In</td><td>7</td><td>In</td><td>316</td></tr> <tr><td>↙ ↘</td><td>260</td><td>↙ ↘</td><td>21</td></tr> <tr><td>↖ ↗</td><td>176</td><td>↖ ↗</td><td>45</td></tr> <tr><td colspan="2">Five Star</td><td colspan="2">Victory</td></tr> <tr><td>38</td><td>6</td><td>361</td><td>57</td></tr> <tr><td>12</td><td>5</td><td>361</td><td>57</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.510</td><td></td></tr> </table>	In	7	In	316	↙ ↘	260	↙ ↘	21	↖ ↗	176	↖ ↗	45	Five Star		Victory		38	6	361	57	12	5	361	57	In	In	In	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.510		<table border="1"> <tr><td>In</td><td>0</td><td>In</td><td>3</td></tr> <tr><td>↙ ↘</td><td>32</td><td>↙ ↘</td><td>0</td></tr> <tr><td>↖ ↗</td><td>3</td><td>↖ ↗</td><td>1</td></tr> <tr><td colspan="2">Spring Creek</td><td colspan="2">Broken Rai</td></tr> <tr><td>5</td><td>0</td><td>0</td><td>33</td></tr> <tr><td>0</td><td>10</td><td>0</td><td>3</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Permitted</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.034</td><td></td></tr> </table>	In	0	In	3	↙ ↘	32	↙ ↘	0	↖ ↗	3	↖ ↗	1	Spring Creek		Broken Rai		5	0	0	33	0	10	0	3	In	In	In	In	N/S	Permitted	LOS: A		E/W	Permitted	V/C: 0.034		<table border="1"> <tr><td>In</td><td>89</td><td>In</td><td>11</td></tr> <tr><td>↙ ↘</td><td>1,012</td><td>↙ ↘</td><td>12</td></tr> <tr><td>↖ ↗</td><td>25</td><td>↖ ↗</td><td>5</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Cobblestone</td></tr> <tr><td>70</td><td>7</td><td>51</td><td>854</td></tr> <tr><td>110</td><td>110</td><td>51</td><td>854</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.529</td><td></td></tr> </table>	In	89	In	11	↙ ↘	1,012	↙ ↘	12	↖ ↗	25	↖ ↗	5	Stanford Ranch		Cobblestone		70	7	51	854	110	110	51	854	In	In	In	In	N/S	Protected	LOS: A		E/W	Permitted	V/C: 0.529	
In	113	In	195																																																																																																																																																
↙ ↘	1,316	↙ ↘	0																																																																																																																																																
↖ ↗	71	↖ ↗	0																																																																																																																																																
Park		Safeway																																																																																																																																																	
0	0	0	1,142																																																																																																																																																
0	70	1,142	105																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: B																																																																																																																																																	
E/W	Protected	V/C: 0.627																																																																																																																																																	
In	7	In	316																																																																																																																																																
↙ ↘	260	↙ ↘	21																																																																																																																																																
↖ ↗	176	↖ ↗	45																																																																																																																																																
Five Star		Victory																																																																																																																																																	
38	6	361	57																																																																																																																																																
12	5	361	57																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.510																																																																																																																																																	
In	0	In	3																																																																																																																																																
↙ ↘	32	↙ ↘	0																																																																																																																																																
↖ ↗	3	↖ ↗	1																																																																																																																																																
Spring Creek		Broken Rai																																																																																																																																																	
5	0	0	33																																																																																																																																																
0	10	0	3																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Permitted	LOS: A																																																																																																																																																	
E/W	Permitted	V/C: 0.034																																																																																																																																																	
In	89	In	11																																																																																																																																																
↙ ↘	1,012	↙ ↘	12																																																																																																																																																
↖ ↗	25	↖ ↗	5																																																																																																																																																
Stanford Ranch		Cobblestone																																																																																																																																																	
70	7	51	854																																																																																																																																																
110	110	51	854																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Permitted	V/C: 0.529																																																																																																																																																	
<p><b>118 Park Dr &amp; Safeway</b></p>	<p><b>119 South Whitney &amp; Five Star Bl</b></p>	<p><b>120 Spring Creek Dr &amp; Broken Rail Ln</b></p>	<p><b>121 Stanford Ranch Rd &amp; Cobblestone Dr</b></p>																																																																																																																																																
<table border="1"> <tr><td>In</td><td>33</td><td>In</td><td>62</td></tr> <tr><td>↙ ↘</td><td>7</td><td>↙ ↘</td><td>729</td></tr> <tr><td>↖ ↗</td><td>47</td><td>↖ ↗</td><td>39</td></tr> <tr><td colspan="2">Darby</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>42</td><td>73</td><td>4</td><td>29</td></tr> <tr><td>693</td><td>100</td><td>4</td><td>29</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Split Phase</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.415</td><td></td></tr> </table>	In	33	In	62	↙ ↘	7	↙ ↘	729	↖ ↗	47	↖ ↗	39	Darby		Stanford Ranch		42	73	4	29	693	100	4	29	In	In	In	In	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.415		<table border="1"> <tr><td>In</td><td>243</td><td>In</td><td>311</td></tr> <tr><td>↙ ↘</td><td>596</td><td>↙ ↘</td><td>549</td></tr> <tr><td>↖ ↗</td><td>425</td><td>↖ ↗</td><td>281</td></tr> <tr><td colspan="2">Park</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>237</td><td>217</td><td>491</td><td>191</td></tr> <tr><td>445</td><td>179</td><td>491</td><td>191</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.733</td><td></td></tr> </table>	In	243	In	311	↙ ↘	596	↙ ↘	549	↖ ↗	425	↖ ↗	281	Park		Stanford Ranch		237	217	491	191	445	179	491	191	In	In	In	In	N/S	Protected	LOS: C		E/W	Protected	V/C: 0.733		<table border="1"> <tr><td>In</td><td>3</td><td>In</td><td>38</td></tr> <tr><td>↙ ↘</td><td>1,655</td><td>↙ ↘</td><td>1</td></tr> <tr><td>↖ ↗</td><td>25</td><td>↖ ↗</td><td>74</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>79</td><td>95</td><td>1,176</td><td>49</td></tr> <tr><td>1</td><td>160</td><td>1,176</td><td>49</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td><td></td></tr> <tr><td>E/W</td><td>Split Phase</td><td>V/C: 0.609</td><td></td></tr> </table>	In	3	In	38	↙ ↘	1,655	↙ ↘	1	↖ ↗	25	↖ ↗	74	Stanford Ranch		Stanford Ranch		79	95	1,176	49	1	160	1,176	49	In	In	In	In	N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.609		<table border="1"> <tr><td>In</td><td>13</td><td>In</td><td>2</td></tr> <tr><td>↙ ↘</td><td>1,127</td><td>↙ ↘</td><td>11</td></tr> <tr><td>↖ ↗</td><td>12</td><td>↖ ↗</td><td>66</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Stoney</td></tr> <tr><td>7</td><td>17</td><td>92</td><td>876</td></tr> <tr><td>49</td><td>49</td><td>92</td><td>876</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.534</td><td></td></tr> </table>	In	13	In	2	↙ ↘	1,127	↙ ↘	11	↖ ↗	12	↖ ↗	66	Stanford Ranch		Stoney		7	17	92	876	49	49	92	876	In	In	In	In	N/S	Protected	LOS: A		E/W	Permitted	V/C: 0.534	
In	33	In	62																																																																																																																																																
↙ ↘	7	↙ ↘	729																																																																																																																																																
↖ ↗	47	↖ ↗	39																																																																																																																																																
Darby		Stanford Ranch																																																																																																																																																	
42	73	4	29																																																																																																																																																
693	100	4	29																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Split Phase	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.415																																																																																																																																																	
In	243	In	311																																																																																																																																																
↙ ↘	596	↙ ↘	549																																																																																																																																																
↖ ↗	425	↖ ↗	281																																																																																																																																																
Park		Stanford Ranch																																																																																																																																																	
237	217	491	191																																																																																																																																																
445	179	491	191																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: C																																																																																																																																																	
E/W	Protected	V/C: 0.733																																																																																																																																																	
In	3	In	38																																																																																																																																																
↙ ↘	1,655	↙ ↘	1																																																																																																																																																
↖ ↗	25	↖ ↗	74																																																																																																																																																
Stanford Ranch		Stanford Ranch																																																																																																																																																	
79	95	1,176	49																																																																																																																																																
1	160	1,176	49																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: B																																																																																																																																																	
E/W	Split Phase	V/C: 0.609																																																																																																																																																	
In	13	In	2																																																																																																																																																
↙ ↘	1,127	↙ ↘	11																																																																																																																																																
↖ ↗	12	↖ ↗	66																																																																																																																																																
Stanford Ranch		Stoney																																																																																																																																																	
7	17	92	876																																																																																																																																																
49	49	92	876																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Permitted	V/C: 0.534																																																																																																																																																	
<p><b>122 Stanford Ranch Rd &amp; Darby Rd</b></p>	<p><b>123 Stanford Ranch Rd &amp; Park Dr</b></p>	<p><b>124 Stanford Ranch Rd &amp; Plaza</b></p>	<p><b>125 Stanford Ranch Rd &amp; Stoney Dr</b></p>																																																																																																																																																
<table border="1"> <tr><td>In</td><td>340</td><td>In</td><td>262</td></tr> <tr><td>↙ ↘</td><td>0</td><td>↙ ↘</td><td>896</td></tr> <tr><td>↖ ↗</td><td>375</td><td>↖ ↗</td><td>0</td></tr> <tr><td colspan="2">Victory</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>212</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>927</td><td>0</td><td>0</td><td>0</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.590</td><td></td></tr> </table>	In	340	In	262	↙ ↘	0	↙ ↘	896	↖ ↗	375	↖ ↗	0	Victory		Stanford Ranch		212	0	0	0	927	0	0	0	In	In	In	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.590		<table border="1"> <tr><td>In</td><td>58</td><td>In</td><td>201</td></tr> <tr><td>↙ ↘</td><td>393</td><td>↙ ↘</td><td>561</td></tr> <tr><td>↖ ↗</td><td>161</td><td>↖ ↗</td><td>64</td></tr> <tr><td colspan="2">Park</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>155</td><td>0</td><td>512</td><td>150</td></tr> <tr><td>553</td><td>9</td><td>512</td><td>150</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.533</td><td></td></tr> </table>	In	58	In	201	↙ ↘	393	↙ ↘	561	↖ ↗	161	↖ ↗	64	Park		Stanford Ranch		155	0	512	150	553	9	512	150	In	In	In	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.533		<table border="1"> <tr><td>In</td><td>234</td><td>In</td><td>160</td></tr> <tr><td>↙ ↘</td><td>15</td><td>↙ ↘</td><td>863</td></tr> <tr><td>↖ ↗</td><td>137</td><td>↖ ↗</td><td>26</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Stanford Ranch</td></tr> <tr><td>161</td><td>377</td><td>36</td><td>83</td></tr> <tr><td>26</td><td>309</td><td>207</td><td>83</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Split Phase</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.565</td><td></td></tr> </table>	In	234	In	160	↙ ↘	15	↙ ↘	863	↖ ↗	137	↖ ↗	26	Stanford Ranch		Stanford Ranch		161	377	36	83	26	309	207	83	In	In	In	In	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.565		<table border="1"> <tr><td>In</td><td>4</td><td>In</td><td>58</td></tr> <tr><td>↙ ↘</td><td>20</td><td>↙ ↘</td><td>1,099</td></tr> <tr><td>↖ ↗</td><td>29</td><td>↖ ↗</td><td>439</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Stoney</td></tr> <tr><td>27</td><td>1,210</td><td>356</td><td>36</td></tr> <tr><td>534</td><td>534</td><td>356</td><td>36</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Split Phase</td><td>LOS: C</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.747</td><td></td></tr> </table>	In	4	In	58	↙ ↘	20	↙ ↘	1,099	↖ ↗	29	↖ ↗	439	Stanford Ranch		Stoney		27	1,210	356	36	534	534	356	36	In	In	In	In	N/S	Split Phase	LOS: C		E/W	Protected	V/C: 0.747	
In	340	In	262																																																																																																																																																
↙ ↘	0	↙ ↘	896																																																																																																																																																
↖ ↗	375	↖ ↗	0																																																																																																																																																
Victory		Stanford Ranch																																																																																																																																																	
212	0	0	0																																																																																																																																																
927	0	0	0																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.590																																																																																																																																																	
In	58	In	201																																																																																																																																																
↙ ↘	393	↙ ↘	561																																																																																																																																																
↖ ↗	161	↖ ↗	64																																																																																																																																																
Park		Stanford Ranch																																																																																																																																																	
155	0	512	150																																																																																																																																																
553	9	512	150																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.533																																																																																																																																																	
In	234	In	160																																																																																																																																																
↙ ↘	15	↙ ↘	863																																																																																																																																																
↖ ↗	137	↖ ↗	26																																																																																																																																																
Stanford Ranch		Stanford Ranch																																																																																																																																																	
161	377	36	83																																																																																																																																																
26	309	207	83																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Split Phase	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.565																																																																																																																																																	
In	4	In	58																																																																																																																																																
↙ ↘	20	↙ ↘	1,099																																																																																																																																																
↖ ↗	29	↖ ↗	439																																																																																																																																																
Stanford Ranch		Stoney																																																																																																																																																	
27	1,210	356	36																																																																																																																																																
534	534	356	36																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Split Phase	LOS: C																																																																																																																																																	
E/W	Protected	V/C: 0.747																																																																																																																																																	
<p><b>126 Stanford Ranch Rd &amp; Victory Ln</b></p>	<p><b>127 Stanford Ranch Rd &amp; West Oaks Bl</b></p>	<p><b>128 Sunset Bl &amp; Atherton</b></p>	<p><b>129 Sunset Bl &amp; Blue Oaks Bl</b></p>																																																																																																																																																
<table border="1"> <tr><td>In</td><td>25</td><td>In</td><td>11</td></tr> <tr><td>↙ ↘</td><td>16</td><td>↙ ↘</td><td>1,163</td></tr> <tr><td>↖ ↗</td><td>11</td><td>↖ ↗</td><td>156</td></tr> <tr><td colspan="2">Sunset</td><td colspan="2">Sunset</td></tr> <tr><td>54</td><td>119</td><td>24</td><td>143</td></tr> <tr><td>1,039</td><td>106</td><td>24</td><td>143</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.564</td><td></td></tr> </table>	In	25	In	11	↙ ↘	16	↙ ↘	1,163	↖ ↗	11	↖ ↗	156	Sunset		Sunset		54	119	24	143	1,039	106	24	143	In	In	In	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.564		<table border="1"> <tr><td>In</td><td>28</td><td>In</td><td>11</td></tr> <tr><td>↙ ↘</td><td>14</td><td>↙ ↘</td><td>1,271</td></tr> <tr><td>↖ ↗</td><td>14</td><td>↖ ↗</td><td>75</td></tr> <tr><td colspan="2">Little Rock</td><td colspan="2">Sunset</td></tr> <tr><td>87</td><td>32</td><td>0</td><td>25</td></tr> <tr><td>1,434</td><td>33</td><td>0</td><td>25</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Split Phase</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.441</td><td></td></tr> </table>	In	28	In	11	↙ ↘	14	↙ ↘	1,271	↖ ↗	14	↖ ↗	75	Little Rock		Sunset		87	32	0	25	1,434	33	0	25	In	In	In	In	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.441		<table border="1"> <tr><td>In</td><td>168</td><td>In</td><td>148</td></tr> <tr><td>↙ ↘</td><td>744</td><td>↙ ↘</td><td>863</td></tr> <tr><td>↖ ↗</td><td>363</td><td>↖ ↗</td><td>447</td></tr> <tr><td colspan="2">Park</td><td colspan="2">Sunset</td></tr> <tr><td>387</td><td>557</td><td>654</td><td>114</td></tr> <tr><td>969</td><td>309</td><td>654</td><td>114</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.740</td><td></td></tr> </table>	In	168	In	148	↙ ↘	744	↙ ↘	863	↖ ↗	363	↖ ↗	447	Park		Sunset		387	557	654	114	969	309	654	114	In	In	In	In	N/S	Protected	LOS: C		E/W	Protected	V/C: 0.740		<table border="1"> <tr><td>In</td><td>109</td><td>In</td><td>25</td></tr> <tr><td>↙ ↘</td><td>5</td><td>↙ ↘</td><td>1,163</td></tr> <tr><td>↖ ↗</td><td>23</td><td>↖ ↗</td><td>38</td></tr> <tr><td colspan="2">Pebble Creek</td><td colspan="2">Sunset</td></tr> <tr><td>166</td><td>26</td><td>12</td><td>13</td></tr> <tr><td>1,303</td><td>31</td><td>12</td><td>13</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Permitted</td><td>LOS: A</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.483</td><td></td></tr> </table>	In	109	In	25	↙ ↘	5	↙ ↘	1,163	↖ ↗	23	↖ ↗	38	Pebble Creek		Sunset		166	26	12	13	1,303	31	12	13	In	In	In	In	N/S	Permitted	LOS: A		E/W	Protected	V/C: 0.483	
In	25	In	11																																																																																																																																																
↙ ↘	16	↙ ↘	1,163																																																																																																																																																
↖ ↗	11	↖ ↗	156																																																																																																																																																
Sunset		Sunset																																																																																																																																																	
54	119	24	143																																																																																																																																																
1,039	106	24	143																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.564																																																																																																																																																	
In	28	In	11																																																																																																																																																
↙ ↘	14	↙ ↘	1,271																																																																																																																																																
↖ ↗	14	↖ ↗	75																																																																																																																																																
Little Rock		Sunset																																																																																																																																																	
87	32	0	25																																																																																																																																																
1,434	33	0	25																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Split Phase	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.441																																																																																																																																																	
In	168	In	148																																																																																																																																																
↙ ↘	744	↙ ↘	863																																																																																																																																																
↖ ↗	363	↖ ↗	447																																																																																																																																																
Park		Sunset																																																																																																																																																	
387	557	654	114																																																																																																																																																
969	309	654	114																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: C																																																																																																																																																	
E/W	Protected	V/C: 0.740																																																																																																																																																	
In	109	In	25																																																																																																																																																
↙ ↘	5	↙ ↘	1,163																																																																																																																																																
↖ ↗	23	↖ ↗	38																																																																																																																																																
Pebble Creek		Sunset																																																																																																																																																	
166	26	12	13																																																																																																																																																
1,303	31	12	13																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Permitted	LOS: A																																																																																																																																																	
E/W	Protected	V/C: 0.483																																																																																																																																																	
<p><b>130 Sunset Bl &amp; Fairway Dr</b></p>	<p><b>131 Sunset Bl &amp; Little Rock</b></p>	<p><b>132 Sunset Bl &amp; Park Dr</b></p>	<p><b>133 Sunset Bl &amp; Pebble Creek</b></p>																																																																																																																																																
<table border="1"> <tr><td>In</td><td>144</td><td>In</td><td>253</td></tr> <tr><td>↙ ↘</td><td>961</td><td>↙ ↘</td><td>818</td></tr> <tr><td>↖ ↗</td><td>291</td><td>↖ ↗</td><td>217</td></tr> <tr><td colspan="2">Stanford Ranch</td><td colspan="2">Sunset</td></tr> <tr><td>74</td><td>327</td><td>774</td><td>151</td></tr> <tr><td>794</td><td>774</td><td>774</td><td>151</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.801</td><td></td></tr> </table>	In	144	In	253	↙ ↘	961	↙ ↘	818	↖ ↗	291	↖ ↗	217	Stanford Ranch		Sunset		74	327	774	151	794	774	774	151	In	In	In	In	N/S	Protected	LOS: D		E/W	Protected	V/C: 0.801		<table border="1"> <tr><td>In</td><td>40</td><td>In</td><td>496</td></tr> <tr><td>↙ ↘</td><td>123</td><td>↙ ↘</td><td>822</td></tr> <tr><td>↖ ↗</td><td>877</td><td>↖ ↗</td><td>160</td></tr> <tr><td colspan="2">West Oaks</td><td colspan="2">Sunset</td></tr> <tr><td>42</td><td>46</td><td>117</td><td>101</td></tr> <tr><td>751</td><td>6</td><td>117</td><td>101</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: E</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.957</td><td></td></tr> </table>	In	40	In	496	↙ ↘	123	↙ ↘	822	↖ ↗	877	↖ ↗	160	West Oaks		Sunset		42	46	117	101	751	6	117	101	In	In	In	In	N/S	Protected	LOS: E		E/W	Protected	V/C: 0.957		<table border="1"> <tr><td>In</td><td>205</td><td>In</td><td>261</td></tr> <tr><td>↙ ↘</td><td>179</td><td>↙ ↘</td><td>563</td></tr> <tr><td>↖ ↗</td><td>156</td><td>↖ ↗</td><td>306</td></tr> <tr><td colspan="2">Sunset</td><td colspan="2">W Stanford Ranch</td></tr> <tr><td>341</td><td>87</td><td>522</td><td>220</td></tr> <tr><td>322</td><td>80</td><td>522</td><td>220</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.635</td><td></td></tr> </table>	In	205	In	261	↙ ↘	179	↙ ↘	563	↖ ↗	156	↖ ↗	306	Sunset		W Stanford Ranch		341	87	522	220	322	80	522	220	In	In	In	In	N/S	Protected	LOS: B		E/W	Protected	V/C: 0.635		<table border="1"> <tr><td>In</td><td>742</td><td>In</td><td>427</td></tr> <tr><td>↙ ↘</td><td>47</td><td>↙ ↘</td><td>182</td></tr> <tr><td>↖ ↗</td><td>408</td><td>↖ ↗</td><td>1</td></tr> <tr><td colspan="2">Wildcat</td><td colspan="2">W Stanford Ranch</td></tr> <tr><td>505</td><td>8</td><td>149</td><td>0</td></tr> <tr><td>307</td><td>7</td><td>149</td><td>0</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td><td></td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.730</td><td></td></tr> </table>	In	742	In	427	↙ ↘	47	↙ ↘	182	↖ ↗	408	↖ ↗	1	Wildcat		W Stanford Ranch		505	8	149	0	307	7	149	0	In	In	In	In	N/S	Protected	LOS: C		E/W	Protected	V/C: 0.730	
In	144	In	253																																																																																																																																																
↙ ↘	961	↙ ↘	818																																																																																																																																																
↖ ↗	291	↖ ↗	217																																																																																																																																																
Stanford Ranch		Sunset																																																																																																																																																	
74	327	774	151																																																																																																																																																
794	774	774	151																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: D																																																																																																																																																	
E/W	Protected	V/C: 0.801																																																																																																																																																	
In	40	In	496																																																																																																																																																
↙ ↘	123	↙ ↘	822																																																																																																																																																
↖ ↗	877	↖ ↗	160																																																																																																																																																
West Oaks		Sunset																																																																																																																																																	
42	46	117	101																																																																																																																																																
751	6	117	101																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: E																																																																																																																																																	
E/W	Protected	V/C: 0.957																																																																																																																																																	
In	205	In	261																																																																																																																																																
↙ ↘	179	↙ ↘	563																																																																																																																																																
↖ ↗	156	↖ ↗	306																																																																																																																																																
Sunset		W Stanford Ranch																																																																																																																																																	
341	87	522	220																																																																																																																																																
322	80	522	220																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: B																																																																																																																																																	
E/W	Protected	V/C: 0.635																																																																																																																																																	
In	742	In	427																																																																																																																																																
↙ ↘	47	↙ ↘	182																																																																																																																																																
↖ ↗	408	↖ ↗	1																																																																																																																																																
Wildcat		W Stanford Ranch																																																																																																																																																	
505	8	149	0																																																																																																																																																
307	7	149	0																																																																																																																																																
In	In	In	In																																																																																																																																																
N/S	Protected	LOS: C																																																																																																																																																	
E/W	Protected	V/C: 0.730																																																																																																																																																	
<p><b>134 Sunset Bl &amp; Stanford Ranch Rd</b></p>	<p><b>135 Sunset Bl &amp; West Oaks Bl</b></p>	<p><b>136 W Stanford Ranch Rd &amp; Sunset Bl</b></p>	<p><b>137 W Stanford Ranch Rd &amp; Wildcat Bl</b></p>																																																																																																																																																

**Figure D5**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Plus Project Conditions**

<table border="1"> <tr> <td>In</td> <td>7</td> <td>0</td> <td>4</td> <td>In</td> <td>12</td> <td>305</td> <td>75</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Bridlewood</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>7</td> <td>404</td> <td>55</td> <td></td> <td>70</td> <td>2</td> <td>72</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.302</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	7	0	4	In	12	305	75					Bridlewood					7	404	55		70	2	72					Whitney Ranch Pkwy				N/S	Permitted	LOS: A						E/W	Protected	V/C: 0.302						<table border="1"> <tr> <td>In</td> <td>7</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> <td>353</td> <td>24</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Painted Pony</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>2</td> <td>433</td> <td>44</td> <td></td> <td>31</td> <td>0</td> <td>21</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.207</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	7	0	0	In	0	353	24					Painted Pony					2	433	44		31	0	21					Whitney Ranch Pkwy				N/S	Split Phase	LOS: A						E/W	Protected	V/C: 0.207						<table border="1"> <tr> <td>In</td> <td>29</td> <td>2</td> <td>5</td> <td>In</td> <td>6</td> <td>373</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Spring Creek</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>27</td> <td>458</td> <td>16</td> <td></td> <td>13</td> <td>2</td> <td>2</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.191</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	29	2	5	In	6	373	1					Spring Creek					27	458	16		13	2	2					Whitney Ranch Pkwy				N/S	Permitted	LOS: A						E/W	Protected	V/C: 0.191						<table border="1"> <tr> <td>In</td> <td>0</td> <td>1,019</td> <td>35</td> <td>In</td> <td>23</td> <td>5</td> <td>149</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Bridlewood</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1</td> <td>23</td> <td>2</td> <td></td> <td>1</td> <td>850</td> <td>148</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.487</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	1,019	35	In	23	5	149					Bridlewood					1	23	2		1	850	148					Whitney Ranch Pkwy				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.487					
In	7	0	4	In	12	305	75																																																																																																																																																																																												
				Bridlewood																																																																																																																																																																																															
	7	404	55		70	2	72																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Permitted	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.302																																																																																																																																																																																																	
In	7	0	0	In	0	353	24																																																																																																																																																																																												
				Painted Pony																																																																																																																																																																																															
	2	433	44		31	0	21																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Split Phase	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.207																																																																																																																																																																																																	
In	29	2	5	In	6	373	1																																																																																																																																																																																												
				Spring Creek																																																																																																																																																																																															
	27	458	16		13	2	2																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Permitted	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.191																																																																																																																																																																																																	
In	0	1,019	35	In	23	5	149																																																																																																																																																																																												
				Bridlewood																																																																																																																																																																																															
	1	23	2		1	850	148																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.487																																																																																																																																																																																																	
<p><b>138</b> <b>Whitney Ranch Pkwy &amp; Bridlewood Dr</b></p>	<p><b>139</b> <b>Whitney Ranch Pkwy &amp; Painted Pony Ln</b></p>	<p><b>140</b> <b>Whitney Ranch Pkwy &amp; Spring Creek Dr</b></p>	<p><b>141</b> <b>Wildcat Bl &amp; Bridlewood Dr</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>288</td> <td>385</td> <td>158</td> <td>In</td> <td>176</td> <td>198</td> <td>49</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Wildcat</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>271</td> <td>313</td> <td>201</td> <td></td> <td>259</td> <td>238</td> <td>50</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.592</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	288	385	158	In	176	198	49					Wildcat					271	313	201		259	238	50					Whitney Ranch Pkwy				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.592						<table border="1"> <tr> <td>In</td> <td>12</td> <td>432</td> <td>72</td> <td>In</td> <td>116</td> <td>9</td> <td>447</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Wildcat</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>14</td> <td>6</td> <td>34</td> <td></td> <td>58</td> <td>315</td> <td>358</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>S High School Ent</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.628</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	12	432	72	In	116	9	447					Wildcat					14	6	34		58	315	358					S High School Ent				N/S	Protected	LOS: B						E/W	Protected	V/C: 0.628						<table border="1"> <tr> <td>In</td> <td>0</td> <td>422</td> <td>10</td> <td>In</td> <td>7</td> <td>0</td> <td>53</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Spring Creek</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>0</td> <td>314</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>N High School Ent</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.176</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	422	10	In	7	0	53					Spring Creek					0	0	0		0	314	1					N High School Ent				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.176						<table border="1"> <tr> <td>In</td> <td>31</td> <td>401</td> <td>17</td> <td>In</td> <td>12</td> <td>1</td> <td>38</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Wildcat</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>102</td> <td>3</td> <td>5</td> <td></td> <td>6</td> <td>429</td> <td>69</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Ranch View</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.263</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	31	401	17	In	12	1	38					Wildcat					102	3	5		6	429	69					Ranch View				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.263					
In	288	385	158	In	176	198	49																																																																																																																																																																																												
				Wildcat																																																																																																																																																																																															
	271	313	201		259	238	50																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.592																																																																																																																																																																																																	
In	12	432	72	In	116	9	447																																																																																																																																																																																												
				Wildcat																																																																																																																																																																																															
	14	6	34		58	315	358																																																																																																																																																																																												
				S High School Ent																																																																																																																																																																																															
N/S	Protected	LOS: B																																																																																																																																																																																																	
E/W	Protected	V/C: 0.628																																																																																																																																																																																																	
In	0	422	10	In	7	0	53																																																																																																																																																																																												
				Spring Creek																																																																																																																																																																																															
	0	0	0		0	314	1																																																																																																																																																																																												
				N High School Ent																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.176																																																																																																																																																																																																	
In	31	401	17	In	12	1	38																																																																																																																																																																																												
				Wildcat																																																																																																																																																																																															
	102	3	5		6	429	69																																																																																																																																																																																												
				Ranch View																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.263																																																																																																																																																																																																	
<p><b>142</b> <b>Wildcat Bl &amp; Whitney Ranch Pkwy</b></p>	<p><b>143</b> <b>Wildcat Bl &amp; S High School Entrance</b></p>	<p><b>144</b> <b>Wildcat Bl &amp; N High School Entrance</b></p>	<p><b>145</b> <b>Wildcat Bl &amp; Ranch View Dr</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>0</td> <td>789</td> <td>431</td> <td>In</td> <td>305</td> <td>0</td> <td>325</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Stanford Ranch</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>737</td> <td>342</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Crest</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: D</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.864</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	789	431	In	305	0	325					Stanford Ranch					0	0	0		737	342						Crest				N/S	Protected	LOS: D						E/W	Protected	V/C: 0.864						<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> <td>324</td> <td>96</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>368</td> <td>405</td> <td></td> <td>306</td> <td>0</td> <td>74</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Crest</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td colspan="2">LOS: C</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td colspan="2">V/C: 0.739</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	0	0	In	0	324	96					Whitney					0	368	405		306	0	74					Crest				N/S	Split Phase	LOS: C						E/W	Split Phase	V/C: 0.739						<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> <td>110</td> <td>115</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Stanford Ranch</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>169</td> <td>134</td> <td></td> <td>200</td> <td>0</td> <td>225</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Crest</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.328</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	0	0	In	0	110	115					Stanford Ranch					0	169	134		200	0	225					Crest				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.328						<table border="1"> <tr> <td>In</td> <td>36</td> <td>632</td> <td>68</td> <td>In</td> <td>89</td> <td>121</td> <td>216</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Dominguez</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>61</td> <td>276</td> <td>239</td> <td></td> <td>119</td> <td>447</td> <td>64</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Granite</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: D</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.817</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	36	632	68	In	89	121	216					Dominguez					61	276	239		119	447	64					Granite				N/S	Protected	LOS: D						E/W	Protected	V/C: 0.817					
In	0	789	431	In	305	0	325																																																																																																																																																																																												
				Stanford Ranch																																																																																																																																																																																															
	0	0	0		737	342																																																																																																																																																																																													
				Crest																																																																																																																																																																																															
N/S	Protected	LOS: D																																																																																																																																																																																																	
E/W	Protected	V/C: 0.864																																																																																																																																																																																																	
In	0	0	0	In	0	324	96																																																																																																																																																																																												
				Whitney																																																																																																																																																																																															
	0	368	405		306	0	74																																																																																																																																																																																												
				Crest																																																																																																																																																																																															
N/S	Split Phase	LOS: C																																																																																																																																																																																																	
E/W	Split Phase	V/C: 0.739																																																																																																																																																																																																	
In	0	0	0	In	0	110	115																																																																																																																																																																																												
				Stanford Ranch																																																																																																																																																																																															
	0	169	134		200	0	225																																																																																																																																																																																												
				Crest																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.328																																																																																																																																																																																																	
In	36	632	68	In	89	121	216																																																																																																																																																																																												
				Dominguez																																																																																																																																																																																															
	61	276	239		119	447	64																																																																																																																																																																																												
				Granite																																																																																																																																																																																															
N/S	Protected	LOS: D																																																																																																																																																																																																	
E/W	Protected	V/C: 0.817																																																																																																																																																																																																	
<p><b>152</b> <b>Stanford Ranch Rd &amp; Crest Dr</b></p>	<p><b>153</b> <b>Whitney Blvd &amp; Crest Dr</b></p>	<p><b>154</b> <b>Park Dr &amp; Crest Dr</b></p>	<p><b>161</b> <b>Granite Dr &amp; Dominguez Dr</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>77</td> <td>625</td> <td>54</td> <td>In</td> <td>79</td> <td>34</td> <td>34</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>387</td> <td>36</td> <td>403</td> <td></td> <td>195</td> <td>871</td> <td>29</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Dominguez</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.586</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	77	625	54	In	79	34	34					Sierra College Bl					387	36	403		195	871	29					Dominguez				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.586						<table border="1"> <tr> <td>In</td> <td>0</td> <td>95</td> <td>479</td> <td>In</td> <td>252</td> <td>0</td> <td>233</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Park</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>124</td> <td>439</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Valley View Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.516</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	95	479	In	252	0	233					Park					0	0	0		124	439						Valley View Pkwy				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.516						<table border="1"> <tr> <td>In</td> <td>6</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> <td>464</td> <td>12</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Nature Bl Wy</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>15</td> <td>869</td> <td>35</td> <td></td> <td>14</td> <td>0</td> <td>5</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Valley View Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td colspan="2">LOS: B</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.621</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	6	0	0	In	0	464	12					Nature Bl Wy					15	869	35		14	0	5					Valley View Pkwy				N/S	Split Phase	LOS: B						E/W	Protected	V/C: 0.621						<table border="1"> <tr> <td>In</td> <td>272</td> <td>268</td> <td>0</td> <td>In</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Valley View Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>367</td> <td>0</td> <td>500</td> <td></td> <td>233</td> <td>546</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.381</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	272	268	0	In	0	0	0					Valley View Pkwy					367	0	500		233	546	0					Sierra College Bl				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.381					
In	77	625	54	In	79	34	34																																																																																																																																																																																												
				Sierra College Bl																																																																																																																																																																																															
	387	36	403		195	871	29																																																																																																																																																																																												
				Dominguez																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.586																																																																																																																																																																																																	
In	0	95	479	In	252	0	233																																																																																																																																																																																												
				Park																																																																																																																																																																																															
	0	0	0		124	439																																																																																																																																																																																													
				Valley View Pkwy																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.516																																																																																																																																																																																																	
In	6	0	0	In	0	464	12																																																																																																																																																																																												
				Nature Bl Wy																																																																																																																																																																																															
	15	869	35		14	0	5																																																																																																																																																																																												
				Valley View Pkwy																																																																																																																																																																																															
N/S	Split Phase	LOS: B																																																																																																																																																																																																	
E/W	Protected	V/C: 0.621																																																																																																																																																																																																	
In	272	268	0	In	0	0	0																																																																																																																																																																																												
				Valley View Pkwy																																																																																																																																																																																															
	367	0	500		233	546	0																																																																																																																																																																																												
				Sierra College Bl																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.381																																																																																																																																																																																																	
<p><b>162</b> <b>Sierra College Bl &amp; Dominguez Dr</b></p>	<p><b>163</b> <b>Park Dr &amp; Valley View Pkwy</b></p>	<p><b>164</b> <b>Nature Trail Wy &amp; Valley View Pkwy</b></p>	<p><b>165</b> <b>Sierra College Bl &amp; Valley View Pkwy</b></p>																																																																																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>299</td> <td>29</td> <td>160</td> <td>In</td> <td>69</td> <td>1,017</td> <td>26</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>University</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>154</td> <td>441</td> <td>29</td> <td></td> <td>79</td> <td>36</td> <td>54</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.379</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	299	29	160	In	69	1,017	26					University					154	441	29		79	36	54					Whitney Ranch Pkwy				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.379						<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> <td>341</td> <td>423</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Whitney Ranch Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>429</td> <td>25</td> <td></td> <td>36</td> <td>0</td> <td>546</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>West Oaks</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.507</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	0	0	In	0	341	423					Whitney Ranch Pkwy					0	429	25		36	0	546					West Oaks				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.507						<table border="1"> <tr> <td>In</td> <td>0</td> <td>454</td> <td>0</td> <td>In</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Painted Pony</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>60</td> <td></td> <td>111</td> <td>606</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>West Oaks</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: A</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.265</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	0	454	0	In	0	0	0					Painted Pony					0	0	60		111	606	0					West Oaks				N/S	Protected	LOS: A						E/W	Protected	V/C: 0.265						<table border="1"> <tr> <td>In</td> <td>541</td> <td>21</td> <td>133</td> <td>In</td> <td>96</td> <td>145</td> <td>26</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Valley View Pkwy</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>498</td> <td>353</td> <td>124</td> <td></td> <td>76</td> <td>17</td> <td>33</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>Sierra College Bl</td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: D</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.819</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	In	541	21	133	In	96	145	26					Valley View Pkwy					498	353	124		76	17	33					Sierra College Bl				N/S	Protected	LOS: D						E/W	Protected	V/C: 0.819					
In	299	29	160	In	69	1,017	26																																																																																																																																																																																												
				University																																																																																																																																																																																															
	154	441	29		79	36	54																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.379																																																																																																																																																																																																	
In	0	0	0	In	0	341	423																																																																																																																																																																																												
				Whitney Ranch Pkwy																																																																																																																																																																																															
	0	429	25		36	0	546																																																																																																																																																																																												
				West Oaks																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.507																																																																																																																																																																																																	
In	0	454	0	In	0	0	0																																																																																																																																																																																												
				Painted Pony																																																																																																																																																																																															
	0	0	60		111	606	0																																																																																																																																																																																												
				West Oaks																																																																																																																																																																																															
N/S	Protected	LOS: A																																																																																																																																																																																																	
E/W	Protected	V/C: 0.265																																																																																																																																																																																																	
In	541	21	133	In	96	145	26																																																																																																																																																																																												
				Valley View Pkwy																																																																																																																																																																																															
	498	353	124		76	17	33																																																																																																																																																																																												
				Sierra College Bl																																																																																																																																																																																															
N/S	Protected	LOS: D																																																																																																																																																																																																	
E/W	Protected	V/C: 0.819																																																																																																																																																																																																	
<p><b>166</b> <b>University Ave &amp; Whitney Ranch Pkwy</b></p>	<p><b>167</b> <b>West Oaks Bl &amp; Whitney Ranch Pkwy</b></p>	<p><b>168</b> <b>West Oaks Bl &amp; Painted Pony Ln</b></p>	<p><b>169</b> <b>Laredo Dr &amp; Whitney Ranch Pkwy</b></p>																																																																																																																																																																																																



**Figure D5**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Existing Plus Project Conditions**

In	0	0	0	In	0	0	0	In	0	0	0
				Pacific	933	0	0	Pacific	0	0	0
				Rocklin	754	48	0	Rocklin	0	0	0
	0	0	0	Civic Center	4	0	84	Civic Center	0	0	0
	1,416	6	0	West Oaks	0	0	0	West Oaks	0	0	0
	In	In	In	Civic Center	1,447	52	In	Civic Center	1,447	52	In
N/S	Protected			LOS: A	N/S	Protected		LOS: A	N/S	Protected	
E/W	Protected			V/C: 0.560	E/W	Protected		V/C: 0.520	E/W	Protected	
170	Rocklin Rd & Civic Centr Dr			171	Pacific St & Civic Center Dr						

**Figure D6**  
**Existing Plus Project PM Peak Hour Intersection Level of Service**  
**State Highway Intersections**

<p>GP08</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>149</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>763</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>3</td> </tr> <tr> <td></td> <td>592</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>956</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> <td>398</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 31.8 sec</td> <td></td> <td></td> <td></td> </tr> </table>		In	0	0	0	In	149						763						3		592						956						0					In					398																			N/S	Protected	LOS: C				E/W	Protected	Del: 31.8 sec				<table border="1"> <tr> <td>In</td> <td>369</td> <td>88</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td></td> <td>1,148</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>247</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1,451</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1,047</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 23.7 sec</td> <td></td> <td></td> </tr> </table>		In	369	88	In	0		4			1,148					247		0					1,451					1,047				In																				N/S	Permitted	LOS: C			E/W	Protected	Del: 23.7 sec			<table border="1"> <tr> <td>In</td> <td>40</td> <td>1,160</td> <td>In</td> <td>228</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>38</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>276</td> </tr> <tr> <td></td> <td>94</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>255</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>Del: 26.8 sec</td> <td></td> <td></td> </tr> </table>		In	40	1,160	In	228					38					276		94					0					255				In																				N/S	Protected	LOS: C			E/W	Split Phase	Del: 26.8 sec			<table border="1"> <tr> <td>In</td> <td>85</td> <td>570</td> <td>In</td> <td>291</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>125</td> </tr> <tr> <td></td> <td>281</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>172</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>105</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 28.4 sec</td> <td></td> <td></td> </tr> </table>		In	85	570	In	291					0					125		281					172					105				In																				N/S	Protected	LOS: C			E/W	Protected	Del: 28.4 sec		
In	0	0	0	In	149																																																																																																																																																																																																																																																														
					763																																																																																																																																																																																																																																																														
					3																																																																																																																																																																																																																																																														
	592																																																																																																																																																																																																																																																																		
	956																																																																																																																																																																																																																																																																		
	0																																																																																																																																																																																																																																																																		
In					398																																																																																																																																																																																																																																																														
N/S	Protected	LOS: C																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 31.8 sec																																																																																																																																																																																																																																																																	
In	369	88	In	0																																																																																																																																																																																																																																																															
	4			1,148																																																																																																																																																																																																																																																															
				247																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	1,451																																																																																																																																																																																																																																																																		
	1,047																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Permitted	LOS: C																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 23.7 sec																																																																																																																																																																																																																																																																	
In	40	1,160	In	228																																																																																																																																																																																																																																																															
				38																																																																																																																																																																																																																																																															
				276																																																																																																																																																																																																																																																															
	94																																																																																																																																																																																																																																																																		
	0																																																																																																																																																																																																																																																																		
	255																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: C																																																																																																																																																																																																																																																																	
E/W	Split Phase	Del: 26.8 sec																																																																																																																																																																																																																																																																	
In	85	570	In	291																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
				125																																																																																																																																																																																																																																																															
	281																																																																																																																																																																																																																																																																		
	172																																																																																																																																																																																																																																																																		
	105																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: C																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 28.4 sec																																																																																																																																																																																																																																																																	
<b>201</b>	<b>Rocklin Rd &amp; I-80 EB</b>	<b>202</b>	<b>Rocklin Rd &amp; I-80 WB</b>	<b>203</b>	<b>Sierra College Bl &amp; I-80 WB</b>	<b>204</b>	<b>Sierra College Bl &amp; I-80 EB</b>																																																																																																																																																																																																																																																												
<table border="1"> <tr> <td>In</td> <td>28</td> <td>1,696</td> <td>In</td> <td>456</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>330</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>608</td> </tr> <tr> <td></td> <td>189</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>194</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>334</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: E</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 71.3 sec</td> <td></td> <td></td> </tr> </table>		In	28	1,696	In	456					330					608		189					194					334				In																				N/S	Protected	LOS: E			E/W	Protected	Del: 71.3 sec			<table border="1"> <tr> <td>Ig</td> <td>339</td> <td>368</td> <td>Ig</td> <td>931</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>763</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>441</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>888</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>217</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Ov</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 25.7 sec</td> <td></td> <td></td> </tr> </table>		Ig	339	368	Ig	931					763					441		0					888					217				Ov															N/S	Protected	LOS: C			E/W	Protected	Del: 25.7 sec			<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>Ig</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>2,035</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>207</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>993</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>272</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: A</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 7.4 sec</td> <td></td> <td></td> </tr> </table>		In	0	0	Ig	0					2,035					207		0					993					272				Ig																				N/S	Permitted	LOS: A			E/W	Protected	Del: 7.4 sec			<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>2,148</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1,369</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>282</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Ov</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: E</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 79.4 sec</td> <td></td> <td></td> </tr> </table>		In	0	0	In	0					2,148					0		0					1,369					282				Ov															N/S	Permitted	LOS: E			E/W	Protected	Del: 79.4 sec																								
In	28	1,696	In	456																																																																																																																																																																																																																																																															
				330																																																																																																																																																																																																																																																															
				608																																																																																																																																																																																																																																																															
	189																																																																																																																																																																																																																																																																		
	194																																																																																																																																																																																																																																																																		
	334																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: E																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 71.3 sec																																																																																																																																																																																																																																																																	
Ig	339	368	Ig	931																																																																																																																																																																																																																																																															
				763																																																																																																																																																																																																																																																															
				441																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	888																																																																																																																																																																																																																																																																		
	217																																																																																																																																																																																																																																																																		
Ov																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: C																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 25.7 sec																																																																																																																																																																																																																																																																	
In	0	0	Ig	0																																																																																																																																																																																																																																																															
				2,035																																																																																																																																																																																																																																																															
				207																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	993																																																																																																																																																																																																																																																																		
	272																																																																																																																																																																																																																																																																		
Ig																																																																																																																																																																																																																																																																			
N/S	Permitted	LOS: A																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 7.4 sec																																																																																																																																																																																																																																																																	
In	0	0	In	0																																																																																																																																																																																																																																																															
				2,148																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	1,369																																																																																																																																																																																																																																																																		
	282																																																																																																																																																																																																																																																																		
Ov																																																																																																																																																																																																																																																																			
N/S	Permitted	LOS: E																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 79.4 sec																																																																																																																																																																																																																																																																	
<b>205</b>	<b>SR 65 &amp; Sunset Blvd</b>	<b>210</b>	<b>Blue Oaks Blvd &amp; SR 65 SB</b>	<b>211</b>	<b>Blue Oaks Blvd &amp; SR 65 NB Off</b>	<b>212</b>	<b>Pleasant Grove Blvd &amp; SR 65 NB</b>																																																																																																																																																																																																																																																												
<table border="1"> <tr> <td>Ig</td> <td>221</td> <td>94</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>2,717</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>400</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>1,564</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>734</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>Del: 28.3 sec</td> <td></td> <td></td> </tr> </table>		Ig	221	94	In	0					2,717					400		0					1,564					734				In																				N/S	Permitted	LOS: C			E/W	Protected	Del: 28.3 sec			<table border="1"> <tr> <td>In</td> <td>244</td> <td>2,617</td> <td>Ig</td> <td>1,001</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>323</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>Del: 30.4 sec</td> <td></td> <td></td> </tr> </table>		In	244	2,617	Ig	1,001					0					0		0					0					323				Ig																				N/S	Protected	LOS: C			E/W	Permitted	Del: 30.4 sec			<table border="1"> <tr> <td>In</td> <td>0</td> <td>2,199</td> <td>Ig</td> <td>199</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>635</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: D</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>Del: 50.9 sec</td> <td></td> <td></td> </tr> </table>		In	0	2,199	Ig	199					0					0		0					0					635				Ig																				N/S	Protected	LOS: D			E/W	Permitted	Del: 50.9 sec			<table border="1"> <tr> <td>In</td> <td>8</td> <td>4</td> <td>In</td> <td>76</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>174</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>114</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>196</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>275</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>N/S</td> <td>Stop Sign</td> <td>LOS: F[187.2]</td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Uncontrolled</td> <td>Del: 84.7 sec</td> <td></td> <td></td> </tr> </table>		In	8	4	In	76					174					114		5					196					275				In																				N/S	Stop Sign	LOS: F[187.2]			E/W	Uncontrolled	Del: 84.7 sec														
Ig	221	94	In	0																																																																																																																																																																																																																																																															
				2,717																																																																																																																																																																																																																																																															
				400																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	1,564																																																																																																																																																																																																																																																																		
	734																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Permitted	LOS: C																																																																																																																																																																																																																																																																	
E/W	Protected	Del: 28.3 sec																																																																																																																																																																																																																																																																	
In	244	2,617	Ig	1,001																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	0																																																																																																																																																																																																																																																																		
	323																																																																																																																																																																																																																																																																		
Ig																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: C																																																																																																																																																																																																																																																																	
E/W	Permitted	Del: 30.4 sec																																																																																																																																																																																																																																																																	
In	0	2,199	Ig	199																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
				0																																																																																																																																																																																																																																																															
	0																																																																																																																																																																																																																																																																		
	0																																																																																																																																																																																																																																																																		
	635																																																																																																																																																																																																																																																																		
Ig																																																																																																																																																																																																																																																																			
N/S	Protected	LOS: D																																																																																																																																																																																																																																																																	
E/W	Permitted	Del: 50.9 sec																																																																																																																																																																																																																																																																	
In	8	4	In	76																																																																																																																																																																																																																																																															
				174																																																																																																																																																																																																																																																															
				114																																																																																																																																																																																																																																																															
	5																																																																																																																																																																																																																																																																		
	196																																																																																																																																																																																																																																																																		
	275																																																																																																																																																																																																																																																																		
In																																																																																																																																																																																																																																																																			
N/S	Stop Sign	LOS: F[187.2]																																																																																																																																																																																																																																																																	
E/W	Uncontrolled	Del: 84.7 sec																																																																																																																																																																																																																																																																	
<b>213</b>	<b>Pleasant Grove Blvd &amp; SR 65 SB</b>	<b>214</b>	<b>Stanford Ranch Rd &amp; SR 65 NB</b>	<b>215</b>	<b>Stanford Ranch Rd &amp; SR 65 SB</b>	<b>216</b>	<b>Sierra College Blvd &amp; SR 193</b>																																																																																																																																																																																																																																																												

**Figure D7**  
**Existing Plus Project PM Peak Hour Intersection Level of Service**  
**Loomis Intersections**

<p>GP08</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>102</td> </tr> <tr> <td></td> <td>759</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>251</td> <td></td> <td>86</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>899</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>148</td> </tr> <tr> <td></td> <td>60</td> <td></td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase Del: 18.1 sec</p>		In	0	In	102		759		0		251		86		0		899		0		148		60			<table border="1"> <tr> <td>In</td> <td>118</td> <td>In</td> <td>70</td> </tr> <tr> <td></td> <td>616</td> <td></td> <td>263</td> </tr> <tr> <td></td> <td>46</td> <td></td> <td>193</td> </tr> <tr> <td></td> <td>313</td> <td></td> <td>209</td> </tr> <tr> <td></td> <td>439</td> <td></td> <td>1,092</td> </tr> <tr> <td></td> <td>414</td> <td></td> <td>254</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected Del: 72.4 sec</p>		In	118	In	70		616		263		46		193		313		209		439		1,092		414		254	<table border="1"> <tr> <td>In</td> <td>17</td> <td>In</td> <td>157</td> </tr> <tr> <td></td> <td>486</td> <td></td> <td>2</td> </tr> <tr> <td></td> <td>347</td> <td></td> <td>15</td> </tr> <tr> <td></td> <td>32</td> <td></td> <td>1</td> </tr> <tr> <td></td> <td>20</td> <td></td> <td>603</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td>39</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 28.7 sec</p>		In	17	In	157		486		2		347		15		32		1		20		603		4		39	<table border="1"> <tr> <td>In</td> <td>53</td> <td>In</td> <td>31</td> </tr> <tr> <td></td> <td>241</td> <td></td> <td>112</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td>112</td> </tr> <tr> <td></td> <td>241</td> <td></td> <td>298</td> </tr> <tr> <td></td> <td>164</td> <td></td> <td>299</td> </tr> <tr> <td></td> <td>213</td> <td></td> <td>176</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 30.7 sec</p>		In	53	In	31		241		112		27		112		241		298		164		299		213		176								
In	0	In	102																																																																																																												
	759		0																																																																																																												
	251		86																																																																																																												
	0		899																																																																																																												
	0		148																																																																																																												
	60																																																																																																														
In	118	In	70																																																																																																												
	616		263																																																																																																												
	46		193																																																																																																												
	313		209																																																																																																												
	439		1,092																																																																																																												
	414		254																																																																																																												
In	17	In	157																																																																																																												
	486		2																																																																																																												
	347		15																																																																																																												
	32		1																																																																																																												
	20		603																																																																																																												
	4		39																																																																																																												
In	53	In	31																																																																																																												
	241		112																																																																																																												
	27		112																																																																																																												
	241		298																																																																																																												
	164		299																																																																																																												
	213		176																																																																																																												
<b>301</b>	<b>Sierra College Bl &amp; Brace Rd</b>	<b>302</b>	<b>Sierra College Bl &amp; Taylor Rd</b>	<b>304</b>	<b>Sierra College Bl &amp; King Rd</b>	<b>305</b>	<b>Taylor Rd &amp; King Rd</b>																																																																																																								
<table border="1"> <tr> <td>In</td> <td>4</td> <td>In</td> <td>300</td> </tr> <tr> <td></td> <td>388</td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>340</td> <td></td> <td>67</td> </tr> <tr> <td></td> <td>13</td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>7</td> <td></td> <td>538</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td>156</td> </tr> </table> <p>N/S Protected LOS: D  E/W Split Phase Del: 35.8 sec</p>		In	4	In	300		388		8		340		67		13		8		7		538		5		156	<table border="1"> <tr> <td>In</td> <td>47</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>72</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>56</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>192</td> </tr> <tr> <td></td> <td>512</td> <td></td> <td>43</td> </tr> <tr> <td></td> <td></td> <td></td> <td>0</td> </tr> </table> <p>N/S Stop Sign LOS: C  E/W Stop Sign Del: 20.7 sec</p>		In	47	In	0		72		0		0		0		56		0		0		192		512		43				0	<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>75</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>140</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>287</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>156</td> <td></td> <td>45</td> </tr> <tr> <td></td> <td></td> <td></td> <td>155</td> </tr> </table> <p>N/S Stop Sign LOS: D[ 30.7]  E/W Uncontrolled Del: 8.6 sec</p>		In	0	In	0		0		75		0		140		0		0		287		0		156		45				155	<table border="1"> <tr> <td>In</td> <td>363</td> <td>In</td> <td>133</td> </tr> <tr> <td></td> <td>246</td> <td></td> <td>53</td> </tr> <tr> <td></td> <td>44</td> <td></td> <td>73</td> </tr> <tr> <td></td> <td>53</td> <td></td> <td>88</td> </tr> <tr> <td></td> <td>47</td> <td></td> <td>249</td> </tr> <tr> <td></td> <td>92</td> <td></td> <td>178</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 26.3 sec</p>		In	363	In	133		246		53		44		73		53		88		47		249		92		178
In	4	In	300																																																																																																												
	388		8																																																																																																												
	340		67																																																																																																												
	13		8																																																																																																												
	7		538																																																																																																												
	5		156																																																																																																												
In	47	In	0																																																																																																												
	72		0																																																																																																												
	0		0																																																																																																												
	56		0																																																																																																												
	0		192																																																																																																												
	512		43																																																																																																												
			0																																																																																																												
In	0	In	0																																																																																																												
	0		75																																																																																																												
	0		140																																																																																																												
	0		0																																																																																																												
	287		0																																																																																																												
	156		45																																																																																																												
			155																																																																																																												
In	363	In	133																																																																																																												
	246		53																																																																																																												
	44		73																																																																																																												
	53		88																																																																																																												
	47		249																																																																																																												
	92		178																																																																																																												
<b>306</b>	<b>Taylor Rd &amp; Horseshoe Bar</b>	<b>307</b>	<b>Rocklin Rd &amp; Barton Rd</b>	<b>308</b>	<b>Barton Rd &amp; Brace Rd</b>	<b>309</b>	<b>Horseshoe Bar Rd &amp; I-80 WB Ramp</b>																																																																																																								
<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>284</td> </tr> <tr> <td></td> <td>261</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>207</td> <td></td> <td>82</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>265</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>37</td> </tr> </table> <p>N/S Uncontrolled LOS: C[ 16.6]  E/W Stop Sign Del: 6.9 sec</p>		In	0	In	284		261		0		207		82		0		0		0		265		0		37																																																																																						
In	0	In	284																																																																																																												
	261		0																																																																																																												
	207		82																																																																																																												
	0		0																																																																																																												
	0		265																																																																																																												
	0		37																																																																																																												
<b>310</b>	<b>Horseshoe Bar Rd &amp; I-80 EB Ramp</b>																																																																																																														

**Figure D8**  
**Existing Plus Project PM Peak Hour Intersection Level of Service**  
**Roseville, Lincoln, and Placer County Intersections**

Roseville Intersections																																																																																																																											
<table border="1"> <tr><td>In</td><td>119</td><td>85</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,309</td><td>385</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>176</td><td>581</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>161</td><td>487</td><td>356</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,285</td><td>356</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: E</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.92</td></tr> </table>	In	119	85	↓ ↓ ↓ ↓	1,309	385	↑ ↑ ↑ ↑	176	581	In			161	487	356	↓ ↓ ↓ ↓	1,285	356	↑ ↑ ↑ ↑			In			N/S	Protected	LOS: E	E/W	Protected	V/C: 0.92	<table border="1"> <tr><td>In</td><td>41</td><td>28</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,502</td><td>206</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>66</td><td>175</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>55</td><td>262</td><td>159</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,098</td><td>159</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td></tr> <tr><td>E/W</td><td>Split Phase</td><td>V/C: 0.65</td></tr> </table>	In	41	28	↓ ↓ ↓ ↓	1,502	206	↑ ↑ ↑ ↑	66	175	In			55	262	159	↓ ↓ ↓ ↓	1,098	159	↑ ↑ ↑ ↑			In			N/S	Protected	LOS: B	E/W	Split Phase	V/C: 0.65	<table border="1"> <tr><td>In</td><td>29</td><td>135</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,668</td><td>115</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>68</td><td>537</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>61</td><td>523</td><td>288</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,328</td><td>288</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td></tr> <tr><td>E/W</td><td>Split Phase</td><td>V/C: 0.86</td></tr> </table>	In	29	135	↓ ↓ ↓ ↓	1,668	115	↑ ↑ ↑ ↑	68	537	In			61	523	288	↓ ↓ ↓ ↓	1,328	288	↑ ↑ ↑ ↑			In			N/S	Protected	LOS: D	E/W	Split Phase	V/C: 0.86	<table border="1"> <tr><td>In</td><td>34</td><td>115</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>274</td><td>1,927</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>170</td><td>1,116</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>35</td><td>478</td><td>603</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,367</td><td>246</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>598</td><td>603</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.74</td></tr> </table>	In	34	115	↓ ↓ ↓ ↓	274	1,927	↑ ↑ ↑ ↑	170	1,116	In			35	478	603	↓ ↓ ↓ ↓	1,367	246	↑ ↑ ↑ ↑	598	603	In			N/S	Protected	LOS: C	E/W	Protected	V/C: 0.74
In	119	85																																																																																																																									
↓ ↓ ↓ ↓	1,309	385																																																																																																																									
↑ ↑ ↑ ↑	176	581																																																																																																																									
In																																																																																																																											
161	487	356																																																																																																																									
↓ ↓ ↓ ↓	1,285	356																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
In																																																																																																																											
N/S	Protected	LOS: E																																																																																																																									
E/W	Protected	V/C: 0.92																																																																																																																									
In	41	28																																																																																																																									
↓ ↓ ↓ ↓	1,502	206																																																																																																																									
↑ ↑ ↑ ↑	66	175																																																																																																																									
In																																																																																																																											
55	262	159																																																																																																																									
↓ ↓ ↓ ↓	1,098	159																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
In																																																																																																																											
N/S	Protected	LOS: B																																																																																																																									
E/W	Split Phase	V/C: 0.65																																																																																																																									
In	29	135																																																																																																																									
↓ ↓ ↓ ↓	1,668	115																																																																																																																									
↑ ↑ ↑ ↑	68	537																																																																																																																									
In																																																																																																																											
61	523	288																																																																																																																									
↓ ↓ ↓ ↓	1,328	288																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
In																																																																																																																											
N/S	Protected	LOS: D																																																																																																																									
E/W	Split Phase	V/C: 0.86																																																																																																																									
In	34	115																																																																																																																									
↓ ↓ ↓ ↓	274	1,927																																																																																																																									
↑ ↑ ↑ ↑	170	1,116																																																																																																																									
In																																																																																																																											
35	478	603																																																																																																																									
↓ ↓ ↓ ↓	1,367	246																																																																																																																									
↑ ↑ ↑ ↑	598	603																																																																																																																									
In																																																																																																																											
N/S	Protected	LOS: C																																																																																																																									
E/W	Protected	V/C: 0.74																																																																																																																									
<b>401 Pleasant Grove &amp; Fairway</b>	<b>402 Stanford Ranch &amp; Fairway</b>	<b>403 Stanford Ranch &amp; Five Star</b>	<b>404 Pleasant Grove &amp; Roseville Pkwy</b>																																																																																																																								
<table border="1"> <tr><td>In</td><td>352</td><td>777</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>754</td><td>1,360</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>907</td><td>99</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>347</td><td>396</td><td>13</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>688</td><td>13</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.83</td></tr> </table>	In	352	777	↓ ↓ ↓ ↓	754	1,360	↑ ↑ ↑ ↑	907	99	In			347	396	13	↓ ↓ ↓ ↓	688	13	↑ ↑ ↑ ↑			In			N/S	Protected	LOS: D	E/W	Protected	V/C: 0.83	<table border="1"> <tr><td>In</td><td>96</td><td>373</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>235</td><td>1,788</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>340</td><td>314</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>114</td><td>371</td><td>34</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,727</td><td>188</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>561</td><td>34</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.71</td></tr> </table>	In	96	373	↓ ↓ ↓ ↓	235	1,788	↑ ↑ ↑ ↑	340	314	In			114	371	34	↓ ↓ ↓ ↓	1,727	188	↑ ↑ ↑ ↑	561	34	In			N/S	Protected	LOS: C	E/W	Protected	V/C: 0.71	<table border="1"> <tr><td>In</td><td>137</td><td>31</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>224</td><td>2,052</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>58</td><td>163</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>49</td><td>482</td><td>325</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,815</td><td>163</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>318</td><td>325</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.68</td></tr> </table>	In	137	31	↓ ↓ ↓ ↓	224	2,052	↑ ↑ ↑ ↑	58	163	In			49	482	325	↓ ↓ ↓ ↓	1,815	163	↑ ↑ ↑ ↑	318	325	In			N/S	Protected	LOS: B	E/W	Protected	V/C: 0.68	<table border="1"> <tr><td>In</td><td>227</td><td>3</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>1,059</td><td>3</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>1</td><td>3</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>174</td><td>181</td><td>3</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>2</td><td>953</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td>3</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.60</td></tr> </table>	In	227	3	↓ ↓ ↓ ↓	1,059	3	↑ ↑ ↑ ↑	1	3	In			174	181	3	↓ ↓ ↓ ↓	2	953	↑ ↑ ↑ ↑		3	In			N/S	Protected	LOS: B	E/W	Permitted	V/C: 0.60
In	352	777																																																																																																																									
↓ ↓ ↓ ↓	754	1,360																																																																																																																									
↑ ↑ ↑ ↑	907	99																																																																																																																									
In																																																																																																																											
347	396	13																																																																																																																									
↓ ↓ ↓ ↓	688	13																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
In																																																																																																																											
N/S	Protected	LOS: D																																																																																																																									
E/W	Protected	V/C: 0.83																																																																																																																									
In	96	373																																																																																																																									
↓ ↓ ↓ ↓	235	1,788																																																																																																																									
↑ ↑ ↑ ↑	340	314																																																																																																																									
In																																																																																																																											
114	371	34																																																																																																																									
↓ ↓ ↓ ↓	1,727	188																																																																																																																									
↑ ↑ ↑ ↑	561	34																																																																																																																									
In																																																																																																																											
N/S	Protected	LOS: C																																																																																																																									
E/W	Protected	V/C: 0.71																																																																																																																									
In	137	31																																																																																																																									
↓ ↓ ↓ ↓	224	2,052																																																																																																																									
↑ ↑ ↑ ↑	58	163																																																																																																																									
In																																																																																																																											
49	482	325																																																																																																																									
↓ ↓ ↓ ↓	1,815	163																																																																																																																									
↑ ↑ ↑ ↑	318	325																																																																																																																									
In																																																																																																																											
N/S	Protected	LOS: B																																																																																																																									
E/W	Protected	V/C: 0.68																																																																																																																									
In	227	3																																																																																																																									
↓ ↓ ↓ ↓	1,059	3																																																																																																																									
↑ ↑ ↑ ↑	1	3																																																																																																																									
In																																																																																																																											
174	181	3																																																																																																																									
↓ ↓ ↓ ↓	2	953																																																																																																																									
↑ ↑ ↑ ↑		3																																																																																																																									
In																																																																																																																											
N/S	Protected	LOS: B																																																																																																																									
E/W	Permitted	V/C: 0.60																																																																																																																									
<b>405 Galleria &amp; Roseville Pkwy</b>	<b>406 Roseville Parkway &amp; Taylor</b>	<b>407 Roseville Parkway &amp; N. Sunrise</b>	<b>408 Sierra College &amp; Secret Ravine</b>																																																																																																																								
Lincoln and Placer County Intersections																																																																																																																											
<table border="1"> <tr><td>Ov</td><td>356</td><td>1</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>175</td><td>385</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>11</td><td>64</td></tr> <tr><td colspan="3">Ov</td></tr> <tr><td>393</td><td>5</td><td>76</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>138</td><td>76</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">Ov</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: A</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.528</td></tr> </table>	Ov	356	1	↓ ↓ ↓ ↓	175	385	↑ ↑ ↑ ↑	11	64	Ov			393	5	76	↓ ↓ ↓ ↓	138	76	↑ ↑ ↑ ↑			Ov			N/S	Protected	LOS: A	E/W	Protected	V/C: 0.528	<table border="1"> <tr><td>In</td><td>8</td><td>0</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>360</td><td>0</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>0</td><td>0</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>45</td><td>77</td><td>0</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>706</td><td>0</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td></td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Uncontrolled</td><td>LOS: C[16.4]</td></tr> <tr><td>E/W</td><td>Stop Sign</td><td>Del: 2.5 sec</td></tr> </table>	In	8	0	↓ ↓ ↓ ↓	360	0	↑ ↑ ↑ ↑	0	0	In			45	77	0	↓ ↓ ↓ ↓	706	0	↑ ↑ ↑ ↑			In			N/S	Uncontrolled	LOS: C[16.4]	E/W	Stop Sign	Del: 2.5 sec	<table border="1"> <tr><td>In</td><td>0</td><td>47</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>458</td><td>0</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td>104</td><td>136</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>0</td><td>0</td><td>120</td></tr> <tr><td>↓ ↓ ↓ ↓</td><td>0</td><td>811</td></tr> <tr><td>↑ ↑ ↑ ↑</td><td></td><td>120</td></tr> <tr><td colspan="3">In</td></tr> <tr><td>N/S</td><td>Uncontrolled</td><td>LOS: F[244.2]</td></tr> <tr><td>E/W</td><td>Stop Sign</td><td>Del: 27.3 sec</td></tr> </table>	In	0	47	↓ ↓ ↓ ↓	458	0	↑ ↑ ↑ ↑	104	136	In			0	0	120	↓ ↓ ↓ ↓	0	811	↑ ↑ ↑ ↑		120	In			N/S	Uncontrolled	LOS: F[244.2]	E/W	Stop Sign	Del: 27.3 sec																															
Ov	356	1																																																																																																																									
↓ ↓ ↓ ↓	175	385																																																																																																																									
↑ ↑ ↑ ↑	11	64																																																																																																																									
Ov																																																																																																																											
393	5	76																																																																																																																									
↓ ↓ ↓ ↓	138	76																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
Ov																																																																																																																											
N/S	Protected	LOS: A																																																																																																																									
E/W	Protected	V/C: 0.528																																																																																																																									
In	8	0																																																																																																																									
↓ ↓ ↓ ↓	360	0																																																																																																																									
↑ ↑ ↑ ↑	0	0																																																																																																																									
In																																																																																																																											
45	77	0																																																																																																																									
↓ ↓ ↓ ↓	706	0																																																																																																																									
↑ ↑ ↑ ↑																																																																																																																											
In																																																																																																																											
N/S	Uncontrolled	LOS: C[16.4]																																																																																																																									
E/W	Stop Sign	Del: 2.5 sec																																																																																																																									
In	0	47																																																																																																																									
↓ ↓ ↓ ↓	458	0																																																																																																																									
↑ ↑ ↑ ↑	104	136																																																																																																																									
In																																																																																																																											
0	0	120																																																																																																																									
↓ ↓ ↓ ↓	0	811																																																																																																																									
↑ ↑ ↑ ↑		120																																																																																																																									
In																																																																																																																											
N/S	Uncontrolled	LOS: F[244.2]																																																																																																																									
E/W	Stop Sign	Del: 27.3 sec																																																																																																																									
<b>501 E Joiner Pkwy &amp; Twelve Bridges</b>	<b>502 Sierra College &amp; Twelve Bridges</b>	<b>601 Sierra College &amp; English Colony</b>																																																																																																																									

**Figure D9**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Current General Plan**

<p>NP30</p> <table border="1"> <tr> <td>In</td> <td>286</td> <td>19</td> <td>614</td> <td>600</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>285</td> <td></td> <td>32</td> <td>1,112</td> </tr> <tr> <td></td> <td>1,497</td> <td>4</td> <td>30</td> <td>17</td> </tr> <tr> <td></td> <td>10</td> <td>4</td> <td>15</td> <td>15</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Split Phase LOS: D  E/W Protected V/C: 0.865</p>	In	286	19	614	600		↘ ↙	↘ ↙	↘ ↙	↘ ↙		285		32	1,112		1,497	4	30	17		10	4	15	15		In			In	<table border="1"> <tr> <td>In</td> <td>154</td> <td>1,292</td> <td>53</td> <td>24</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>353</td> <td></td> <td>231</td> <td>28</td> </tr> <tr> <td></td> <td>34</td> <td>98</td> <td>1,420</td> <td>118</td> </tr> <tr> <td></td> <td>260</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected V/C: 0.688</p>	In	154	1,292	53	24		↘ ↙	↘ ↙	↘ ↙	↘ ↙		353		231	28		34	98	1,420	118		260					In			In	<table border="1"> <tr> <td>In</td> <td>270</td> <td>55</td> <td>59</td> <td>59</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>188</td> <td></td> <td>61</td> <td>379</td> </tr> <tr> <td></td> <td>401</td> <td>4</td> <td>104</td> <td>65</td> </tr> <tr> <td></td> <td>53</td> <td>4</td> <td>45</td> <td>45</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Split Phase LOS: B  E/W Protected V/C: 0.612</p>	In	270	55	59	59		↘ ↙	↘ ↙	↘ ↙	↘ ↙		188		61	379		401	4	104	65		53	4	45	45		In			In	<table border="1"> <tr> <td>In</td> <td>122</td> <td>676</td> <td>70</td> <td>72</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>206</td> <td></td> <td>178</td> <td>218</td> </tr> <tr> <td></td> <td>217</td> <td>4</td> <td>182</td> <td>825</td> </tr> <tr> <td></td> <td>286</td> <td></td> <td>124</td> <td>124</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: E  E/W Split Phase V/C: 0.920</p>	In	122	676	70	72		↘ ↙	↘ ↙	↘ ↙	↘ ↙		206		178	218		217	4	182	825		286		124	124		In			In					
In	286	19	614	600																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	285		32	1,112																																																																																																																												
	1,497	4	30	17																																																																																																																												
	10	4	15	15																																																																																																																												
	In			In																																																																																																																												
In	154	1,292	53	24																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	353		231	28																																																																																																																												
	34	98	1,420	118																																																																																																																												
	260																																																																																																																															
	In			In																																																																																																																												
In	270	55	59	59																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	188		61	379																																																																																																																												
	401	4	104	65																																																																																																																												
	53	4	45	45																																																																																																																												
	In			In																																																																																																																												
In	122	676	70	72																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	206		178	218																																																																																																																												
	217	4	182	825																																																																																																																												
	286		124	124																																																																																																																												
	In			In																																																																																																																												
<b>1 Granite Dr &amp; Rocklin Rd</b>	<b>2 Granite Dr &amp; Sierra College Bl</b>	<b>3 Granite Dr &amp; Sierra Meadows</b>	<b>4 Pacific St &amp; Del Mar/ Dominguez</b>																																																																																																																													
<table border="1"> <tr> <td>In</td> <td>76</td> <td>1,548</td> <td>104</td> <td>47</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>50</td> <td></td> <td>70</td> <td>6</td> </tr> <tr> <td></td> <td>12</td> <td>165</td> <td>1,435</td> <td>30</td> </tr> <tr> <td></td> <td>319</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: E  E/W Split Phase V/C: 0.975</p>	In	76	1,548	104	47		↘ ↙	↘ ↙	↘ ↙	↘ ↙		50		70	6		12	165	1,435	30		319					In			In	<table border="1"> <tr> <td>In</td> <td>324</td> <td>942</td> <td>68</td> <td>36</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>403</td> <td></td> <td>8</td> <td>48</td> </tr> <tr> <td></td> <td>52</td> <td>143</td> <td>698</td> <td>16</td> </tr> <tr> <td></td> <td>124</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase V/C: 0.775</p>	In	324	942	68	36		↘ ↙	↘ ↙	↘ ↙	↘ ↙		403		8	48		52	143	698	16		124					In			In	<table border="1"> <tr> <td>In</td> <td>68</td> <td>858</td> <td>148</td> <td>182</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>94</td> <td></td> <td>724</td> <td>302</td> </tr> <tr> <td></td> <td>336</td> <td>1</td> <td>543</td> <td>923</td> </tr> <tr> <td></td> <td>2</td> <td>4</td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>Ov</td> </tr> </table> <p>N/S Protected LOS: E  E/W Split Phase V/C: 0.902</p>	In	68	858	148	182		↘ ↙	↘ ↙	↘ ↙	↘ ↙		94		724	302		336	1	543	923		2	4				In			Ov	<table border="1"> <tr> <td>In</td> <td>10</td> <td>971</td> <td>178</td> <td>119</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>6</td> <td></td> <td>134</td> <td>44</td> </tr> <tr> <td></td> <td>19</td> <td>25</td> <td>1,014</td> <td>111</td> </tr> <tr> <td></td> <td>26</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase V/C: 0.690</p>	In	10	971	178	119		↘ ↙	↘ ↙	↘ ↙	↘ ↙		6		134	44		19	25	1,014	111		26					In			In					
In	76	1,548	104	47																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	50		70	6																																																																																																																												
	12	165	1,435	30																																																																																																																												
	319																																																																																																																															
	In			In																																																																																																																												
In	324	942	68	36																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	403		8	48																																																																																																																												
	52	143	698	16																																																																																																																												
	124																																																																																																																															
	In			In																																																																																																																												
In	68	858	148	182																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	94		724	302																																																																																																																												
	336	1	543	923																																																																																																																												
	2	4																																																																																																																														
	In			Ov																																																																																																																												
In	10	971	178	119																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	6		134	44																																																																																																																												
	19	25	1,014	111																																																																																																																												
	26																																																																																																																															
	In			In																																																																																																																												
<b>5 Pacific St &amp; Farron St</b>	<b>6 Pacific St &amp; Midas Ave</b>	<b>7 Pacific St &amp; Rocklin Rd</b>	<b>8 Pacific St &amp; Sierra Meadows</b>																																																																																																																													
<table border="1"> <tr> <td>In</td> <td>0</td> <td>956</td> <td>124</td> <td>158</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>212</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1,222</td> <td>185</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected V/C: 0.665</p>	In	0	956	124	158		↘ ↙	↘ ↙	↘ ↙	↘ ↙		0		212	0		0	0	1,222	185		0					In			In	<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>70</td> <td></td> <td>84</td> <td>1,643</td> </tr> <tr> <td></td> <td>1,521</td> <td>267</td> <td>0</td> <td>67</td> </tr> <tr> <td></td> <td>341</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected V/C: 0.682</p>	In	0	0	0	0		↘ ↙	↘ ↙	↘ ↙	↘ ↙		70		84	1,643		1,521	267	0	67		341					In			In	<table border="1"> <tr> <td>Ov</td> <td>538</td> <td>10</td> <td>74</td> <td>32</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>312</td> <td></td> <td>1,076</td> <td>25</td> </tr> <tr> <td></td> <td>1,227</td> <td>99</td> <td>121</td> <td>6</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>15</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Split Phase LOS: C  E/W Protected V/C: 0.748</p>	Ov	538	10	74	32		↘ ↙	↘ ↙	↘ ↙	↘ ↙		312		1,076	25		1,227	99	121	6					15		In			In	<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>0</td> <td>1,144</td> </tr> <tr> <td></td> <td>1,446</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.482</p>	In	0	0	0	0		↘ ↙	↘ ↙	↘ ↙	↘ ↙		0		0	1,144		1,446	0	0	0		0					In			In					
In	0	956	124	158																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	0		212	0																																																																																																																												
	0	0	1,222	185																																																																																																																												
	0																																																																																																																															
	In			In																																																																																																																												
In	0	0	0	0																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	70		84	1,643																																																																																																																												
	1,521	267	0	67																																																																																																																												
	341																																																																																																																															
	In			In																																																																																																																												
Ov	538	10	74	32																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	312		1,076	25																																																																																																																												
	1,227	99	121	6																																																																																																																												
				15																																																																																																																												
	In			In																																																																																																																												
In	0	0	0	0																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	0		0	1,144																																																																																																																												
	1,446	0	0	0																																																																																																																												
	0																																																																																																																															
	In			In																																																																																																																												
<b>9 Pacific St &amp; Woodside Dr</b>	<b>10 Rocklin Rd &amp; Aguilar Rd</b>	<b>11 Rocklin Rd &amp; El Don Dr</b>	<b>12 Rocklin Rd &amp; Fire Station No 1</b>																																																																																																																													
<table border="1"> <tr> <td>In</td> <td>294</td> <td>1</td> <td>392</td> <td>274</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>241</td> <td></td> <td>9</td> <td>815</td> </tr> <tr> <td></td> <td>1,071</td> <td>15</td> <td>0</td> <td>4</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Split Phase LOS: C  E/W Protected V/C: 0.739</p>	In	294	1	392	274		↘ ↙	↘ ↙	↘ ↙	↘ ↙		241		9	815		1,071	15	0	4		27					In			In	<table border="1"> <tr> <td>In</td> <td>142</td> <td>989</td> <td>151</td> <td>70</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>16</td> <td></td> <td>83</td> <td>283</td> </tr> <tr> <td></td> <td>564</td> <td>635</td> <td>1,352</td> <td>241</td> </tr> <tr> <td></td> <td>904</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Ov</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected V/C: 0.958</p>	In	142	989	151	70		↘ ↙	↘ ↙	↘ ↙	↘ ↙		16		83	283		564	635	1,352	241		904					Ov					In			In	<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>122</td> <td>1,170</td> </tr> <tr> <td></td> <td>1,376</td> <td>31</td> <td>0</td> <td>120</td> </tr> <tr> <td></td> <td>28</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected V/C: 0.662</p>	In	0	0	0	0		↘ ↙	↘ ↙	↘ ↙	↘ ↙		0		122	1,170		1,376	31	0	120		28					In			In	<table border="1"> <tr> <td>In</td> <td>84</td> <td>1,895</td> <td>58</td> <td>52</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>59</td> <td></td> <td>45</td> <td>4</td> </tr> <tr> <td></td> <td>4</td> <td>56</td> <td>2,064</td> <td>32</td> </tr> <tr> <td></td> <td>36</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase V/C: 0.688</p>	In	84	1,895	58	52		↘ ↙	↘ ↙	↘ ↙	↘ ↙		59		45	4		4	56	2,064	32		36					In			In
In	294	1	392	274																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	241		9	815																																																																																																																												
	1,071	15	0	4																																																																																																																												
	27																																																																																																																															
	In			In																																																																																																																												
In	142	989	151	70																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	16		83	283																																																																																																																												
	564	635	1,352	241																																																																																																																												
	904																																																																																																																															
	Ov																																																																																																																															
	In			In																																																																																																																												
In	0	0	0	0																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	0		122	1,170																																																																																																																												
	1,376	31	0	120																																																																																																																												
	28																																																																																																																															
	In			In																																																																																																																												
In	84	1,895	58	52																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	59		45	4																																																																																																																												
	4	56	2,064	32																																																																																																																												
	36																																																																																																																															
	In			In																																																																																																																												
<b>13 Rocklin Rd &amp; Havenhurst Cir</b>	<b>14 Rocklin Rd &amp; Sierra College Bl</b>	<b>15 Rocklin Rd &amp; South Grove St</b>	<b>16 Sierra College Bl &amp; El Don Dr</b>																																																																																																																													
<table border="1"> <tr> <td>In</td> <td>81</td> <td>1,887</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>76</td> <td></td> <td>62</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>2,156</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>96</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.572</p>	In	81	1,887	0	0		↘ ↙	↘ ↙	↘ ↙	↘ ↙		76		62	0		0	2,156	0	0		96					In			In	<table border="1"> <tr> <td>In</td> <td>72</td> <td>1,937</td> <td>4</td> <td>0</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>40</td> <td></td> <td>4</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>21</td> <td>2,223</td> <td>1</td> </tr> <tr> <td></td> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.574</p>	In	72	1,937	4	0		↘ ↙	↘ ↙	↘ ↙	↘ ↙		40		4	0		0	21	2,223	1		2					In			In	<table border="1"> <tr> <td>In</td> <td>30</td> <td>1,881</td> <td>5</td> <td>4</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>23</td> <td></td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>85</td> <td>2,133</td> <td>1</td> </tr> <tr> <td></td> <td>37</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.568</p>	In	30	1,881	5	4		↘ ↙	↘ ↙	↘ ↙	↘ ↙		23		1	0		0	85	2,133	1		37					In			In	<table border="1"> <tr> <td>In</td> <td>1,445</td> <td>676</td> <td>61</td> <td>32</td> </tr> <tr> <td></td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> <td>↘ ↙</td> </tr> <tr> <td></td> <td>1,040</td> <td></td> <td>24</td> <td>111</td> </tr> <tr> <td></td> <td>114</td> <td>812</td> <td>615</td> <td>17</td> </tr> <tr> <td></td> <td>409</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: D  E/W Protected V/C: 0.878</p>	In	1,445	676	61	32		↘ ↙	↘ ↙	↘ ↙	↘ ↙		1,040		24	111		114	812	615	17		409					In			In					
In	81	1,887	0	0																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	76		62	0																																																																																																																												
	0	2,156	0	0																																																																																																																												
	96																																																																																																																															
	In			In																																																																																																																												
In	72	1,937	4	0																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	40		4	0																																																																																																																												
	0	21	2,223	1																																																																																																																												
	2																																																																																																																															
	In			In																																																																																																																												
In	30	1,881	5	4																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	23		1	0																																																																																																																												
	0	85	2,133	1																																																																																																																												
	37																																																																																																																															
	In			In																																																																																																																												
In	1,445	676	61	32																																																																																																																												
	↘ ↙	↘ ↙	↘ ↙	↘ ↙																																																																																																																												
	1,040		24	111																																																																																																																												
	114	812	615	17																																																																																																																												
	409																																																																																																																															
	In			In																																																																																																																												
<b>17 Sierra College Bl &amp; Nightwatch</b>	<b>18 Sierra College Bl &amp; Scarborough</b>	<b>19 Sierra College Bl &amp; Southside Ranch</b>	<b>20 Sunset Bl &amp; Pacific St</b>																																																																																																																													

**Figure D9**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Current General Plan**

<table border="1"> <tr> <td>In</td> <td>387</td> <td>In</td> <td>141</td> </tr> <tr> <td>←</td> <td>39</td> <td>→</td> <td>2,056</td> </tr> <tr> <td>↖</td> <td>134</td> <td>↗</td> <td>234</td> </tr> <tr> <td colspan="2">Springview</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>416</td> <td>→</td> <td>89</td> </tr> <tr> <td>↖</td> <td>1,384</td> <td>↗</td> <td>39</td> </tr> <tr> <td>↘</td> <td>120</td> <td>↙</td> <td>87</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Split Phase LOS: F  E/W Protected V/C: 1.054</p>	In	387	In	141	←	39	→	2,056	↖	134	↗	234	Springview		Sunset		←	416	→	89	↖	1,384	↗	39	↘	120	↙	87	In		In		<table border="1"> <tr> <td>In</td> <td>86</td> <td>In</td> <td>42</td> </tr> <tr> <td>←</td> <td>13</td> <td>→</td> <td>1,852</td> </tr> <tr> <td>↖</td> <td>8</td> <td>↗</td> <td>75</td> </tr> <tr> <td colspan="2">Topaz</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>206</td> <td>→</td> <td>26</td> </tr> <tr> <td>↖</td> <td>1,532</td> <td>↗</td> <td>16</td> </tr> <tr> <td>↘</td> <td>27</td> <td>↙</td> <td>18</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Permitted LOS: B  E/W Protected V/C: 0.681</p>	In	86	In	42	←	13	→	1,852	↖	8	↗	75	Topaz		Sunset		←	206	→	26	↖	1,532	↗	16	↘	27	↙	18	In		In		<table border="1"> <tr> <td>In</td> <td>62</td> <td>In</td> <td>250</td> </tr> <tr> <td>←</td> <td>73</td> <td>→</td> <td>1,806</td> </tr> <tr> <td>↖</td> <td>137</td> <td>↗</td> <td>432</td> </tr> <tr> <td colspan="2">Whitney</td> <td colspan="2">Sunset</td> </tr> <tr> <td>←</td> <td>143</td> <td>→</td> <td>44</td> </tr> <tr> <td>↖</td> <td>1,390</td> <td>↗</td> <td>110</td> </tr> <tr> <td>↘</td> <td>39</td> <td>↙</td> <td>354</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: F  E/W Protected V/C: 1.098</p>	In	62	In	250	←	73	→	1,806	↖	137	↗	432	Whitney		Sunset		←	143	→	44	↖	1,390	↗	110	↘	39	↙	354	In		In		<table border="1"> <tr> <td>In</td> <td>948</td> <td>In</td> <td>60</td> </tr> <tr> <td>←</td> <td>753</td> <td>→</td> <td>428</td> </tr> <tr> <td>↖</td> <td>45</td> <td>↗</td> <td>130</td> </tr> <tr> <td colspan="2">Blue Oaks</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>808</td> <td>→</td> <td>646</td> </tr> <tr> <td>↖</td> <td>597</td> <td>↗</td> <td>385</td> </tr> <tr> <td>↘</td> <td>499</td> <td>↙</td> <td>95</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected V/C: 0.958</p>	In	948	In	60	←	753	→	428	↖	45	↗	130	Blue Oaks		Blue Oaks		←	808	→	646	↖	597	↗	385	↘	499	↙	95	In		In	
In	387	In	141																																																																																																																																
←	39	→	2,056																																																																																																																																
↖	134	↗	234																																																																																																																																
Springview		Sunset																																																																																																																																	
←	416	→	89																																																																																																																																
↖	1,384	↗	39																																																																																																																																
↘	120	↙	87																																																																																																																																
In		In																																																																																																																																	
In	86	In	42																																																																																																																																
←	13	→	1,852																																																																																																																																
↖	8	↗	75																																																																																																																																
Topaz		Sunset																																																																																																																																	
←	206	→	26																																																																																																																																
↖	1,532	↗	16																																																																																																																																
↘	27	↙	18																																																																																																																																
In		In																																																																																																																																	
In	62	In	250																																																																																																																																
←	73	→	1,806																																																																																																																																
↖	137	↗	432																																																																																																																																
Whitney		Sunset																																																																																																																																	
←	143	→	44																																																																																																																																
↖	1,390	↗	110																																																																																																																																
↘	39	↙	354																																																																																																																																
In		In																																																																																																																																	
In	948	In	60																																																																																																																																
←	753	→	428																																																																																																																																
↖	45	↗	130																																																																																																																																
Blue Oaks		Blue Oaks																																																																																																																																	
←	808	→	646																																																																																																																																
↖	597	↗	385																																																																																																																																
↘	499	↙	95																																																																																																																																
In		In																																																																																																																																	
<p><b>21 Sunset Bl &amp; Springview Dr</b></p>	<p><b>22 Sunset Bl &amp; Topaz Ave</b></p>	<p><b>23 Sunset Bl &amp; Whitney Bl</b></p>	<p><b>101 Blue Oaks Bl &amp; Lonetree</b></p>																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>10</td> <td>In</td> <td>11</td> </tr> <tr> <td>←</td> <td>1</td> <td>→</td> <td>553</td> </tr> <tr> <td>↖</td> <td>15</td> <td>↗</td> <td>2</td> </tr> <tr> <td colspan="2">Market</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>17</td> <td>→</td> <td>8</td> </tr> <tr> <td>↖</td> <td>817</td> <td>↗</td> <td>0</td> </tr> <tr> <td>↘</td> <td>4</td> <td>↙</td> <td>1</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Split Phase LOS: A  E/W Protected V/C: 0.317</p>	In	10	In	11	←	1	→	553	↖	15	↗	2	Market		Blue Oaks		←	17	→	8	↖	817	↗	0	↘	4	↙	1	In		In		<table border="1"> <tr> <td>In</td> <td>9</td> <td>In</td> <td>27</td> </tr> <tr> <td>←</td> <td>496</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>40</td> <td>↗</td> <td>31</td> </tr> <tr> <td colspan="2">Van Buren</td> <td colspan="2">Blue Oaks</td> </tr> <tr> <td>←</td> <td>14</td> <td>→</td> <td>38</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>694</td> </tr> <tr> <td>↘</td> <td>25</td> <td>↙</td> <td>44</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.368</p>	In	9	In	27	←	496	→	0	↖	40	↗	31	Van Buren		Blue Oaks		←	14	→	38	↖	0	↗	694	↘	25	↙	44	In		In		<table border="1"> <tr> <td>In</td> <td>13</td> <td>In</td> <td>137</td> </tr> <tr> <td>←</td> <td>122</td> <td>→</td> <td>1</td> </tr> <tr> <td>↖</td> <td>80</td> <td>↗</td> <td>2</td> </tr> <tr> <td colspan="2">Five Star</td> <td colspan="2">Destiny</td> </tr> <tr> <td>←</td> <td>13</td> <td>→</td> <td>1</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>92</td> </tr> <tr> <td>↘</td> <td>3</td> <td>↙</td> <td>2</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.204</p>	In	13	In	137	←	122	→	1	↖	80	↗	2	Five Star		Destiny		←	13	→	1	↖	0	↗	92	↘	3	↙	2	In		In		<table border="1"> <tr> <td>In</td> <td>24</td> <td>In</td> <td>15</td> </tr> <tr> <td>←</td> <td>1,516</td> <td>→</td> <td>1</td> </tr> <tr> <td>↖</td> <td>17</td> <td>↗</td> <td>15</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">Adams</td> </tr> <tr> <td>←</td> <td>30</td> <td>→</td> <td>38</td> </tr> <tr> <td>↖</td> <td>1</td> <td>↗</td> <td>839</td> </tr> <tr> <td>↘</td> <td>36</td> <td>↙</td> <td>18</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Split Phase V/C: 0.636</p>	In	24	In	15	←	1,516	→	1	↖	17	↗	15	Lonetree		Adams		←	30	→	38	↖	1	↗	839	↘	36	↙	18	In		In	
In	10	In	11																																																																																																																																
←	1	→	553																																																																																																																																
↖	15	↗	2																																																																																																																																
Market		Blue Oaks																																																																																																																																	
←	17	→	8																																																																																																																																
↖	817	↗	0																																																																																																																																
↘	4	↙	1																																																																																																																																
In		In																																																																																																																																	
In	9	In	27																																																																																																																																
←	496	→	0																																																																																																																																
↖	40	↗	31																																																																																																																																
Van Buren		Blue Oaks																																																																																																																																	
←	14	→	38																																																																																																																																
↖	0	↗	694																																																																																																																																
↘	25	↙	44																																																																																																																																
In		In																																																																																																																																	
In	13	In	137																																																																																																																																
←	122	→	1																																																																																																																																
↖	80	↗	2																																																																																																																																
Five Star		Destiny																																																																																																																																	
←	13	→	1																																																																																																																																
↖	0	↗	92																																																																																																																																
↘	3	↙	2																																																																																																																																
In		In																																																																																																																																	
In	24	In	15																																																																																																																																
←	1,516	→	1																																																																																																																																
↖	17	↗	15																																																																																																																																
Lonetree		Adams																																																																																																																																	
←	30	→	38																																																																																																																																
↖	1	↗	839																																																																																																																																
↘	36	↙	18																																																																																																																																
In		In																																																																																																																																	
<p><b>102 Blue Oaks Bl &amp; Market Place</b></p>	<p><b>103 Blue Oaks Bl &amp; Van Buren Way</b></p>	<p><b>104 Five Star &amp; Destiny Dr</b></p>	<p><b>105 Lonetree Bl &amp; Adams Dr</b></p>																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>12</td> <td>In</td> <td>0</td> </tr> <tr> <td>←</td> <td>852</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>0</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">Atherton</td> </tr> <tr> <td>←</td> <td>39</td> <td>→</td> <td>34</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>698</td> </tr> <tr> <td>↘</td> <td>202</td> <td>↙</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.469</p>	In	12	In	0	←	852	→	0	↖	0	↗	0	Lonetree		Atherton		←	39	→	34	↖	0	↗	698	↘	202	↙	0	In		In		<table border="1"> <tr> <td>In</td> <td>14</td> <td>In</td> <td>4</td> </tr> <tr> <td>←</td> <td>1,627</td> <td>→</td> <td>1</td> </tr> <tr> <td>↖</td> <td>5</td> <td>↗</td> <td>7</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">Grand Canyon</td> </tr> <tr> <td>←</td> <td>27</td> <td>→</td> <td>200</td> </tr> <tr> <td>↖</td> <td>1</td> <td>↗</td> <td>938</td> </tr> <tr> <td>↘</td> <td>78</td> <td>↙</td> <td>17</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: D  E/W Split Phase V/C: 0.808</p>	In	14	In	4	←	1,627	→	1	↖	5	↗	7	Lonetree		Grand Canyon		←	27	→	200	↖	1	↗	938	↘	78	↙	17	In		In		<table border="1"> <tr> <td>In</td> <td>77</td> <td>In</td> <td>11</td> </tr> <tr> <td>←</td> <td>1,456</td> <td>→</td> <td>5</td> </tr> <tr> <td>↖</td> <td>51</td> <td>↗</td> <td>29</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">Redwood</td> </tr> <tr> <td>←</td> <td>89</td> <td>→</td> <td>141</td> </tr> <tr> <td>↖</td> <td>2</td> <td>↗</td> <td>807</td> </tr> <tr> <td>↘</td> <td>113</td> <td>↙</td> <td>30</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase V/C: 0.775</p>	In	77	In	11	←	1,456	→	5	↖	51	↗	29	Lonetree		Redwood		←	89	→	141	↖	2	↗	807	↘	113	↙	30	In		In		<table border="1"> <tr> <td>In</td> <td>1</td> <td>In</td> <td>8</td> </tr> <tr> <td>←</td> <td>1,048</td> <td>→</td> <td>1</td> </tr> <tr> <td>↖</td> <td>9</td> <td>↗</td> <td>263</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">West Oaks</td> </tr> <tr> <td>←</td> <td>1</td> <td>→</td> <td>7</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>672</td> </tr> <tr> <td>↘</td> <td>4</td> <td>↙</td> <td>254</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.580</p>	In	1	In	8	←	1,048	→	1	↖	9	↗	263	Lonetree		West Oaks		←	1	→	7	↖	0	↗	672	↘	4	↙	254	In		In	
In	12	In	0																																																																																																																																
←	852	→	0																																																																																																																																
↖	0	↗	0																																																																																																																																
Lonetree		Atherton																																																																																																																																	
←	39	→	34																																																																																																																																
↖	0	↗	698																																																																																																																																
↘	202	↙	0																																																																																																																																
In		In																																																																																																																																	
In	14	In	4																																																																																																																																
←	1,627	→	1																																																																																																																																
↖	5	↗	7																																																																																																																																
Lonetree		Grand Canyon																																																																																																																																	
←	27	→	200																																																																																																																																
↖	1	↗	938																																																																																																																																
↘	78	↙	17																																																																																																																																
In		In																																																																																																																																	
In	77	In	11																																																																																																																																
←	1,456	→	5																																																																																																																																
↖	51	↗	29																																																																																																																																
Lonetree		Redwood																																																																																																																																	
←	89	→	141																																																																																																																																
↖	2	↗	807																																																																																																																																
↘	113	↙	30																																																																																																																																
In		In																																																																																																																																	
In	1	In	8																																																																																																																																
←	1,048	→	1																																																																																																																																
↖	9	↗	263																																																																																																																																
Lonetree		West Oaks																																																																																																																																	
←	1	→	7																																																																																																																																
↖	0	↗	672																																																																																																																																
↘	4	↙	254																																																																																																																																
In		In																																																																																																																																	
<p><b>106 Lonetree Bl &amp; Atherton Rd</b></p>	<p><b>107 Lonetree Bl &amp; Grand Canyon Dr</b></p>	<p><b>108 Lonetree Bl &amp; Redwood Dr</b></p>	<p><b>109 Lonetree Bl &amp; West Oaks Bl</b></p>																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>53</td> <td>In</td> <td>21</td> </tr> <tr> <td>←</td> <td>2</td> <td>→</td> <td>318</td> </tr> <tr> <td>↖</td> <td>21</td> <td>↗</td> <td>7</td> </tr> <tr> <td colspan="2">Blaydon</td> <td colspan="2">Park</td> </tr> <tr> <td>←</td> <td>86</td> <td>→</td> <td>2</td> </tr> <tr> <td>↖</td> <td>597</td> <td>↗</td> <td>1</td> </tr> <tr> <td>↘</td> <td>11</td> <td>↙</td> <td>3</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Permitted LOS: A  E/W Protected V/C: 0.273</p>	In	53	In	21	←	2	→	318	↖	21	↗	7	Blaydon		Park		←	86	→	2	↖	597	↗	1	↘	11	↙	3	In		In		<table border="1"> <tr> <td>In</td> <td>41</td> <td>In</td> <td>6</td> </tr> <tr> <td>←</td> <td>1,027</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>13</td> <td>↗</td> <td>12</td> </tr> <tr> <td colspan="2">Park</td> <td colspan="2">Quarry</td> </tr> <tr> <td>←</td> <td>43</td> <td>→</td> <td>82</td> </tr> <tr> <td>↖</td> <td>4</td> <td>↗</td> <td>1,336</td> </tr> <tr> <td>↘</td> <td>31</td> <td>↙</td> <td>6</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.545</p>	In	41	In	6	←	1,027	→	0	↖	13	↗	12	Park		Quarry		←	43	→	82	↖	4	↗	1,336	↘	31	↙	6	In		In		<table border="1"> <tr> <td>In</td> <td>68</td> <td>In</td> <td>0</td> </tr> <tr> <td>←</td> <td>582</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>0</td> </tr> <tr> <td colspan="2">Park</td> <td colspan="2">Farrier</td> </tr> <tr> <td>←</td> <td>41</td> <td>→</td> <td>349</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>755</td> </tr> <tr> <td>↘</td> <td>244</td> <td>↙</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected V/C: 0.644</p>	In	68	In	0	←	582	→	0	↖	0	↗	0	Park		Farrier		←	41	→	349	↖	0	↗	755	↘	244	↙	0	In		In		<table border="1"> <tr> <td>In</td> <td>7</td> <td>In</td> <td>15</td> </tr> <tr> <td>←</td> <td>1,036</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>27</td> <td>↗</td> <td>31</td> </tr> <tr> <td colspan="2">Lonetree</td> <td colspan="2">King Pine</td> </tr> <tr> <td>←</td> <td>7</td> <td>→</td> <td>24</td> </tr> <tr> <td>↖</td> <td>1</td> <td>↗</td> <td>1,339</td> </tr> <tr> <td>↘</td> <td>9</td> <td>↙</td> <td>25</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Permitted V/C: 0.526</p>	In	7	In	15	←	1,036	→	0	↖	27	↗	31	Lonetree		King Pine		←	7	→	24	↖	1	↗	1,339	↘	9	↙	25	In		In	
In	53	In	21																																																																																																																																
←	2	→	318																																																																																																																																
↖	21	↗	7																																																																																																																																
Blaydon		Park																																																																																																																																	
←	86	→	2																																																																																																																																
↖	597	↗	1																																																																																																																																
↘	11	↙	3																																																																																																																																
In		In																																																																																																																																	
In	41	In	6																																																																																																																																
←	1,027	→	0																																																																																																																																
↖	13	↗	12																																																																																																																																
Park		Quarry																																																																																																																																	
←	43	→	82																																																																																																																																
↖	4	↗	1,336																																																																																																																																
↘	31	↙	6																																																																																																																																
In		In																																																																																																																																	
In	68	In	0																																																																																																																																
←	582	→	0																																																																																																																																
↖	0	↗	0																																																																																																																																
Park		Farrier																																																																																																																																	
←	41	→	349																																																																																																																																
↖	0	↗	755																																																																																																																																
↘	244	↙	0																																																																																																																																
In		In																																																																																																																																	
In	7	In	15																																																																																																																																
←	1,036	→	0																																																																																																																																
↖	27	↗	31																																																																																																																																
Lonetree		King Pine																																																																																																																																	
←	7	→	24																																																																																																																																
↖	1	↗	1,339																																																																																																																																
↘	9	↙	25																																																																																																																																
In		In																																																																																																																																	
<p><b>110 Park Dr &amp; Blaydon Rd</b></p>	<p><b>111 Park Dr &amp; Quarry Way</b></p>	<p><b>112 Park Dr &amp; Farrier Rd</b></p>	<p><b>113 Park Dr &amp; King Pine Dr</b></p>																																																																																																																																
<table border="1"> <tr> <td>In</td> <td>3</td> <td>In</td> <td>1</td> </tr> <tr> <td>←</td> <td>567</td> <td>→</td> <td>4</td> </tr> <tr> <td>↖</td> <td>6</td> <td>↗</td> <td>34</td> </tr> <tr> <td colspan="2">Park</td> <td colspan="2">Shelton</td> </tr> <tr> <td>←</td> <td>8</td> <td>→</td> <td>116</td> </tr> <tr> <td>↖</td> <td>0</td> <td>↗</td> <td>1,017</td> </tr> <tr> <td>↘</td> <td>67</td> <td>↙</td> <td>64</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.340</p>	In	3	In	1	←	567	→	4	↖	6	↗	34	Park		Shelton		←	8	→	116	↖	0	↗	1,017	↘	67	↙	64	In		In		<table border="1"> <tr> <td>In</td> <td>12</td> <td>In</td> <td>71</td> </tr> <tr> <td>←</td> <td>563</td> <td>→</td> <td>14</td> </tr> <tr> <td>↖</td> <td>61</td> <td>↗</td> <td>26</td> </tr> <tr> <td colspan="2">Park</td> <td colspan="2">Victory</td> </tr> <tr> <td>←</td> <td>75</td> <td>→</td> <td>37</td> </tr> <tr> <td>↖</td> <td>5</td> <td>↗</td> <td>1,032</td> </tr> <tr> <td>↘</td> <td>12</td> <td>↙</td> <td>6</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.406</p>	In	12	In	71	←	563	→	14	↖	61	↗	26	Park		Victory		←	75	→	37	↖	5	↗	1,032	↘	12	↙	6	In		In		<table border="1"> <tr> <td>In</td> <td>223</td> <td>In</td> <td>23</td> </tr> <tr> <td>←</td> <td>0</td> <td>→</td> <td>392</td> </tr> <tr> <td>↖</td> <td>15</td> <td>↗</td> <td>0</td> </tr> <tr> <td colspan="2">Wyckford</td> <td colspan="2">Park</td> </tr> <tr> <td>←</td> <td>348</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>677</td> <td>↗</td> <td>0</td> </tr> <tr> <td>↘</td> <td>0</td> <td>↙</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Protected V/C: 0.416</p>	In	223	In	23	←	0	→	392	↖	15	↗	0	Wyckford		Park		←	348	→	0	↖	677	↗	0	↘	0	↙	0	In		In		<table border="1"> <tr> <td>In</td> <td>32</td> <td>In</td> <td>2</td> </tr> <tr> <td>←</td> <td>598</td> <td>→</td> <td>0</td> </tr> <tr> <td>↖</td> <td>25</td> <td>↗</td> <td>4</td> </tr> <tr> <td colspan="2">Park</td> <td colspan="2">Twin Oaks</td> </tr> <tr> <td>←</td> <td>65</td> <td>→</td> <td>66</td> </tr> <tr> <td>↖</td> <td>2</td> <td>↗</td> <td>777</td> </tr> <tr> <td>↘</td> <td>59</td> <td>↙</td> <td>19</td> </tr> <tr> <td>In</td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: A  E/W Split Phase V/C: 0.402</p>	In	32	In	2	←	598	→	0	↖	25	↗	4	Park		Twin Oaks		←	65	→	66	↖	2	↗	777	↘	59	↙	19	In		In	
In	3	In	1																																																																																																																																
←	567	→	4																																																																																																																																
↖	6	↗	34																																																																																																																																
Park		Shelton																																																																																																																																	
←	8	→	116																																																																																																																																
↖	0	↗	1,017																																																																																																																																
↘	67	↙	64																																																																																																																																
In		In																																																																																																																																	
In	12	In	71																																																																																																																																
←	563	→	14																																																																																																																																
↖	61	↗	26																																																																																																																																
Park		Victory																																																																																																																																	
←	75	→	37																																																																																																																																
↖	5	↗	1,032																																																																																																																																
↘	12	↙	6																																																																																																																																
In		In																																																																																																																																	
In	223	In	23																																																																																																																																
←	0	→	392																																																																																																																																
↖	15	↗	0																																																																																																																																
Wyckford		Park																																																																																																																																	
←	348	→	0																																																																																																																																
↖	677	↗	0																																																																																																																																
↘	0	↙	0																																																																																																																																
In		In																																																																																																																																	
In	32	In	2																																																																																																																																
←	598	→	0																																																																																																																																
↖	25	↗	4																																																																																																																																
Park		Twin Oaks																																																																																																																																	
←	65	→	66																																																																																																																																
↖	2	↗	777																																																																																																																																
↘	59	↙	19																																																																																																																																
In		In																																																																																																																																	
<p><b>114 Park Dr &amp; Shelton</b></p>	<p><b>115 Park Dr &amp; Victory Lane</b></p>	<p><b>116 Park Dr &amp; Wyckford Bl</b></p>	<p><b>117 Park Dr &amp; Twin Oaks/ Boardwalk</b></p>																																																																																																																																

**Figure D9**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Current General Plan**

<table border="1"> <tr> <td>In</td> <td>115</td> <td>1,046</td> <td>85</td> <td>In</td> <td>219</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>70</td> <td></td> <td></td> <td></td> <td>1,281</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>109</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.727</td> <td></td> <td></td> <td></td> </tr> </table>	In	115	1,046	85	In	219		↙ ↘				↙ ↘		0	0	0		0		0	0	0		0		70				1,281						109	N/S	Protected	LOS: C				E/W	Protected	V/C: 0.727				<table border="1"> <tr> <td>In</td> <td>12</td> <td>179</td> <td>287</td> <td>In</td> <td>280</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>55</td> <td></td> <td></td> <td></td> <td>23</td> </tr> <tr> <td></td> <td>15</td> <td></td> <td></td> <td></td> <td>38</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> <td>6</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>246</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>32</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.553</td> <td></td> <td></td> <td></td> </tr> </table>	In	12	179	287	In	280		↙ ↘				↙ ↘		55				23		15				38		5				6						246						32	N/S	Protected	LOS: A				E/W	Protected	V/C: 0.553				<table border="1"> <tr> <td>In</td> <td>0</td> <td>36</td> <td>2</td> <td>In</td> <td>4</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>4</td> </tr> <tr> <td></td> <td>10</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>49</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>9</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>V/C: 0.053</td> <td></td> <td></td> <td></td> </tr> </table>	In	0	36	2	In	4		↙ ↘				↙ ↘		5				0		0				4		10				0						49						9	N/S	Permitted	LOS: A				E/W	Permitted	V/C: 0.053				<table border="1"> <tr> <td>In</td> <td>59</td> <td>490</td> <td>42</td> <td>In</td> <td>11</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> <td></td> <td>35</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> <td>11</td> </tr> <tr> <td></td> <td>8</td> <td></td> <td></td> <td></td> <td>15</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>659</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>19</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>V/C: 0.326</td> <td></td> <td></td> <td></td> </tr> </table>	In	59	490	42	In	11		↙ ↘				↙ ↘		27				35		5				11		8				15						659						19	N/S	Protected	LOS: A				E/W	Permitted	V/C: 0.326															
In	115	1,046	85	In	219																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	0	0	0		0																																																																																																																																																																																																																												
	0	0	0		0																																																																																																																																																																																																																												
	70				1,281																																																																																																																																																																																																																												
					109																																																																																																																																																																																																																												
N/S	Protected	LOS: C																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.727																																																																																																																																																																																																																															
In	12	179	287	In	280																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	55				23																																																																																																																																																																																																																												
	15				38																																																																																																																																																																																																																												
	5				6																																																																																																																																																																																																																												
					246																																																																																																																																																																																																																												
					32																																																																																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.553																																																																																																																																																																																																																															
In	0	36	2	In	4																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	5				0																																																																																																																																																																																																																												
	0				4																																																																																																																																																																																																																												
	10				0																																																																																																																																																																																																																												
					49																																																																																																																																																																																																																												
					9																																																																																																																																																																																																																												
N/S	Permitted	LOS: A																																																																																																																																																																																																																															
E/W	Permitted	V/C: 0.053																																																																																																																																																																																																																															
In	59	490	42	In	11																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	27				35																																																																																																																																																																																																																												
	5				11																																																																																																																																																																																																																												
	8				15																																																																																																																																																																																																																												
					659																																																																																																																																																																																																																												
					19																																																																																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																																																																															
E/W	Permitted	V/C: 0.326																																																																																																																																																																																																																															
118 Park Dr & Safeway	119 South Whitney & Five Star Bl	120 Spring Creek Dr & Broken Rail Ln	121 Stanford Ranch Rd & Cobblestone Dr																																																																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>49</td> <td>8</td> <td>47</td> <td>In</td> <td>69</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>80</td> <td></td> <td></td> <td></td> <td>674</td> </tr> <tr> <td></td> <td>1,116</td> <td></td> <td></td> <td></td> <td>39</td> </tr> <tr> <td></td> <td>235</td> <td></td> <td></td> <td></td> <td>80</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>2</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>30</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: B</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.655</td> <td></td> <td></td> <td></td> </tr> </table>	In	49	8	47	In	69		↙ ↘				↙ ↘		80				674		1,116				39		235				80						2						30	N/S	Split Phase	LOS: B				E/W	Protected	V/C: 0.655				<table border="1"> <tr> <td>In</td> <td>156</td> <td>379</td> <td>234</td> <td>In</td> <td>301</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>291</td> <td></td> <td></td> <td></td> <td>573</td> </tr> <tr> <td></td> <td>704</td> <td></td> <td></td> <td></td> <td>122</td> </tr> <tr> <td></td> <td>140</td> <td></td> <td></td> <td></td> <td>174</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>531</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>87</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.709</td> <td></td> <td></td> <td></td> </tr> </table>	In	156	379	234	In	301		↙ ↘				↙ ↘		291				573		704				122		140				174						531						87	N/S	Protected	LOS: C				E/W	Protected	V/C: 0.709				<table border="1"> <tr> <td>In</td> <td>61</td> <td>1,116</td> <td>40</td> <td>In</td> <td>64</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>85</td> <td></td> <td></td> <td></td> <td>2</td> </tr> <tr> <td></td> <td>2</td> <td></td> <td></td> <td></td> <td>90</td> </tr> <tr> <td></td> <td>202</td> <td></td> <td></td> <td></td> <td>126</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1,284</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>60</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.591</td> <td></td> <td></td> <td></td> </tr> </table>	In	61	1,116	40	In	64		↙ ↘				↙ ↘		85				2		2				90		202				126						1,284						60	N/S	Protected	LOS: A				E/W	Split Phase	V/C: 0.591				<table border="1"> <tr> <td>In</td> <td>14</td> <td>533</td> <td>11</td> <td>In</td> <td>4</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>17</td> <td></td> <td></td> <td></td> <td>12</td> </tr> <tr> <td></td> <td>17</td> <td></td> <td></td> <td></td> <td>81</td> </tr> <tr> <td></td> <td>50</td> <td></td> <td></td> <td></td> <td>17</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>92</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>671</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>132</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>V/C: 0.405</td> <td></td> <td></td> <td></td> </tr> </table>	In	14	533	11	In	4		↙ ↘				↙ ↘		17				12		17				81		50				17						92						671						132	N/S	Protected	LOS: A				E/W	Permitted	V/C: 0.405			
In	49	8	47	In	69																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	80				674																																																																																																																																																																																																																												
	1,116				39																																																																																																																																																																																																																												
	235				80																																																																																																																																																																																																																												
					2																																																																																																																																																																																																																												
					30																																																																																																																																																																																																																												
N/S	Split Phase	LOS: B																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.655																																																																																																																																																																																																																															
In	156	379	234	In	301																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	291				573																																																																																																																																																																																																																												
	704				122																																																																																																																																																																																																																												
	140				174																																																																																																																																																																																																																												
					531																																																																																																																																																																																																																												
					87																																																																																																																																																																																																																												
N/S	Protected	LOS: C																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.709																																																																																																																																																																																																																															
In	61	1,116	40	In	64																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	85				2																																																																																																																																																																																																																												
	2				90																																																																																																																																																																																																																												
	202				126																																																																																																																																																																																																																												
					1,284																																																																																																																																																																																																																												
					60																																																																																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																																																																															
E/W	Split Phase	V/C: 0.591																																																																																																																																																																																																																															
In	14	533	11	In	4																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	17				12																																																																																																																																																																																																																												
	17				81																																																																																																																																																																																																																												
	50				17																																																																																																																																																																																																																												
					92																																																																																																																																																																																																																												
					671																																																																																																																																																																																																																												
					132																																																																																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																																																																															
E/W	Permitted	V/C: 0.405																																																																																																																																																																																																																															
122 Stanford Ranch Rd & Darby Rd	123 Stanford Ranch Rd & Park Dr	124 Stanford Ranch Rd & Plaza	125 Stanford Ranch Rd & Stoney Dr																																																																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>97</td> <td>0</td> <td>76</td> <td>In</td> <td>77</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>57</td> <td></td> <td></td> <td></td> <td>994</td> </tr> <tr> <td></td> <td>1,046</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.341</td> <td></td> <td></td> <td></td> </tr> </table>	In	97	0	76	In	77		↙ ↘				↙ ↘		57				994		1,046				0		0				0						0						0	N/S	Protected	LOS: A				E/W	Protected	V/C: 0.341				<table border="1"> <tr> <td>In</td> <td>80</td> <td>104</td> <td>187</td> <td>In</td> <td>173</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>289</td> <td></td> <td></td> <td></td> <td>539</td> </tr> <tr> <td></td> <td>1,018</td> <td></td> <td></td> <td></td> <td>82</td> </tr> <tr> <td></td> <td>9</td> <td></td> <td></td> <td></td> <td>22</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>581</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>255</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.688</td> <td></td> <td></td> <td></td> </tr> </table>	In	80	104	187	In	173		↙ ↘				↙ ↘		289				539		1,018				82		9				22						581						255	N/S	Protected	LOS: B				E/W	Protected	V/C: 0.688				<table border="1"> <tr> <td>In</td> <td>209</td> <td>18</td> <td>185</td> <td>In</td> <td>537</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>227</td> <td></td> <td></td> <td></td> <td>1,825</td> </tr> <tr> <td></td> <td>1,212</td> <td></td> <td></td> <td></td> <td>21</td> </tr> <tr> <td></td> <td>68</td> <td></td> <td></td> <td></td> <td>392</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>104</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>78</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: E</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.953</td> <td></td> <td></td> <td></td> </tr> </table>	In	209	18	185	In	537		↙ ↘				↙ ↘		227				1,825		1,212				21		68				392						104						78	N/S	Split Phase	LOS: E				E/W	Protected	V/C: 0.953				<table border="1"> <tr> <td>In</td> <td>4</td> <td>20</td> <td>29</td> <td>In</td> <td>58</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>27</td> <td></td> <td></td> <td></td> <td>1,688</td> </tr> <tr> <td></td> <td>1,655</td> <td></td> <td></td> <td></td> <td>398</td> </tr> <tr> <td></td> <td>374</td> <td></td> <td></td> <td></td> <td>323</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>36</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>326</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: D</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.842</td> <td></td> <td></td> <td></td> </tr> </table>	In	4	20	29	In	58		↙ ↘				↙ ↘		27				1,688		1,655				398		374				323						36						326	N/S	Split Phase	LOS: D				E/W	Protected	V/C: 0.842									
In	97	0	76	In	77																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	57				994																																																																																																																																																																																																																												
	1,046				0																																																																																																																																																																																																																												
	0				0																																																																																																																																																																																																																												
					0																																																																																																																																																																																																																												
					0																																																																																																																																																																																																																												
N/S	Protected	LOS: A																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.341																																																																																																																																																																																																																															
In	80	104	187	In	173																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	289				539																																																																																																																																																																																																																												
	1,018				82																																																																																																																																																																																																																												
	9				22																																																																																																																																																																																																																												
					581																																																																																																																																																																																																																												
					255																																																																																																																																																																																																																												
N/S	Protected	LOS: B																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.688																																																																																																																																																																																																																															
In	209	18	185	In	537																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	227				1,825																																																																																																																																																																																																																												
	1,212				21																																																																																																																																																																																																																												
	68				392																																																																																																																																																																																																																												
					104																																																																																																																																																																																																																												
					78																																																																																																																																																																																																																												
N/S	Split Phase	LOS: E																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.953																																																																																																																																																																																																																															
In	4	20	29	In	58																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	27				1,688																																																																																																																																																																																																																												
	1,655				398																																																																																																																																																																																																																												
	374				323																																																																																																																																																																																																																												
					36																																																																																																																																																																																																																												
					326																																																																																																																																																																																																																												
N/S	Split Phase	LOS: D																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.842																																																																																																																																																																																																																															
126 Stanford Ranch Rd & Victory Ln	127 Stanford Ranch Rd & West Oaks Bl	128 Sunset Bl & Atherton	129 Sunset Bl & Blue Oaks Bl																																																																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>29</td> <td>19</td> <td>13</td> <td>In</td> <td>13</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>63</td> <td></td> <td></td> <td></td> <td>1,591</td> </tr> <tr> <td></td> <td>1,400</td> <td></td> <td></td> <td></td> <td>174</td> </tr> <tr> <td></td> <td>107</td> <td></td> <td></td> <td></td> <td>140</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>32</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>209</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.754</td> <td></td> <td></td> <td></td> </tr> </table>	In	29	19	13	In	13		↙ ↘				↙ ↘		63				1,591		1,400				174		107				140						32						209	N/S	Protected	LOS: C				E/W	Protected	V/C: 0.754				<table border="1"> <tr> <td>In</td> <td>43</td> <td>1</td> <td>26</td> <td>In</td> <td>4</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>146</td> <td></td> <td></td> <td></td> <td>1,791</td> </tr> <tr> <td></td> <td>1,631</td> <td></td> <td></td> <td></td> <td>75</td> </tr> <tr> <td></td> <td>49</td> <td></td> <td></td> <td></td> <td>39</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>25</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: B</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.621</td> <td></td> <td></td> <td></td> </tr> </table>	In	43	1	26	In	4		↙ ↘				↙ ↘		146				1,791		1,631				75		49				39						0						25	N/S	Split Phase	LOS: B				E/W	Protected	V/C: 0.621				<table border="1"> <tr> <td>In</td> <td>111</td> <td>440</td> <td>278</td> <td>In</td> <td>179</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>438</td> <td></td> <td></td> <td></td> <td>1,366</td> </tr> <tr> <td></td> <td>1,316</td> <td></td> <td></td> <td></td> <td>461</td> </tr> <tr> <td></td> <td>346</td> <td></td> <td></td> <td></td> <td>722</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>652</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>116</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: D</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.856</td> <td></td> <td></td> <td></td> </tr> </table>	In	111	440	278	In	179		↙ ↘				↙ ↘		438				1,366		1,316				461		346				722						652						116	N/S	Protected	LOS: D				E/W	Protected	V/C: 0.856				<table border="1"> <tr> <td>In</td> <td>146</td> <td>5</td> <td>58</td> <td>In</td> <td>62</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>205</td> <td></td> <td></td> <td></td> <td>1,695</td> </tr> <tr> <td></td> <td>1,472</td> <td></td> <td></td> <td></td> <td>73</td> </tr> <tr> <td></td> <td>31</td> <td></td> <td></td> <td></td> <td>26</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>12</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>29</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.720</td> <td></td> <td></td> <td></td> </tr> </table>	In	146	5	58	In	62		↙ ↘				↙ ↘		205				1,695		1,472				73		31				26						12						29	N/S	Permitted	LOS: C				E/W	Protected	V/C: 0.720									
In	29	19	13	In	13																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	63				1,591																																																																																																																																																																																																																												
	1,400				174																																																																																																																																																																																																																												
	107				140																																																																																																																																																																																																																												
					32																																																																																																																																																																																																																												
					209																																																																																																																																																																																																																												
N/S	Protected	LOS: C																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.754																																																																																																																																																																																																																															
In	43	1	26	In	4																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	146				1,791																																																																																																																																																																																																																												
	1,631				75																																																																																																																																																																																																																												
	49				39																																																																																																																																																																																																																												
					0																																																																																																																																																																																																																												
					25																																																																																																																																																																																																																												
N/S	Split Phase	LOS: B																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.621																																																																																																																																																																																																																															
In	111	440	278	In	179																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	438				1,366																																																																																																																																																																																																																												
	1,316				461																																																																																																																																																																																																																												
	346				722																																																																																																																																																																																																																												
					652																																																																																																																																																																																																																												
					116																																																																																																																																																																																																																												
N/S	Protected	LOS: D																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.856																																																																																																																																																																																																																															
In	146	5	58	In	62																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	205				1,695																																																																																																																																																																																																																												
	1,472				73																																																																																																																																																																																																																												
	31				26																																																																																																																																																																																																																												
					12																																																																																																																																																																																																																												
					29																																																																																																																																																																																																																												
N/S	Permitted	LOS: C																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.720																																																																																																																																																																																																																															
130 Sunset Bl & Fairway Dr	131 Sunset Bl & Little Rock	132 Sunset Bl & Park Dr	133 Sunset Bl & Pebble Creek																																																																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>137</td> <td>427</td> <td>254</td> <td>In</td> <td>225</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>91</td> <td></td> <td></td> <td></td> <td>1,163</td> </tr> <tr> <td></td> <td>1,059</td> <td></td> <td></td> <td></td> <td>348</td> </tr> <tr> <td></td> <td>396</td> <td></td> <td></td> <td></td> <td>502</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>599</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>290</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.718</td> <td></td> <td></td> <td></td> </tr> </table>	In	137	427	254	In	225		↙ ↘				↙ ↘		91				1,163		1,059				348		396				502						599						290	N/S	Protected	LOS: C				E/W	Protected	V/C: 0.718				<table border="1"> <tr> <td>In</td> <td>122</td> <td>153</td> <td>763</td> <td>In</td> <td>562</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>68</td> <td></td> <td></td> <td></td> <td>1,278</td> </tr> <tr> <td></td> <td>1,016</td> <td></td> <td></td> <td></td> <td>194</td> </tr> <tr> <td></td> <td>6</td> <td></td> <td></td> <td></td> <td>47</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>229</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>234</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 1.112</td> <td></td> <td></td> <td></td> </tr> </table>	In	122	153	763	In	562		↙ ↘				↙ ↘		68				1,278		1,016				194		6				47						229						234	N/S	Protected	LOS: F				E/W	Protected	V/C: 1.112				<table border="1"> <tr> <td>In</td> <td>377</td> <td>506</td> <td>439</td> <td>In</td> <td>322</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>789</td> <td></td> <td></td> <td></td> <td>518</td> </tr> <tr> <td></td> <td>483</td> <td></td> <td></td> <td></td> <td>222</td> </tr> <tr> <td></td> <td>130</td> <td></td> <td></td> <td></td> <td>105</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1,125</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>160</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: F</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 1.240</td> <td></td> <td></td> <td></td> </tr> </table>	In	377	506	439	In	322		↙ ↘				↙ ↘		789				518		483				222		130				105						1,125						160	N/S	Protected	LOS: F				E/W	Protected	V/C: 1.240				<table border="1"> <tr> <td>In</td> <td>505</td> <td>128</td> <td>603</td> <td>In</td> <td>355</td> </tr> <tr> <td></td> <td>↙ ↘</td> <td></td> <td></td> <td></td> <td>↙ ↘</td> </tr> <tr> <td></td> <td>601</td> <td></td> <td></td> <td></td> <td>259</td> </tr> <tr> <td></td> <td>649</td> <td></td> <td></td> <td></td> <td>1</td> </tr> <tr> <td></td> <td>13</td> <td></td> <td></td> <td></td> <td>14</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>441</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: D</td> <td></td> <td></td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.856</td> <td></td> <td></td> <td></td> </tr> </table>	In	505	128	603	In	355		↙ ↘				↙ ↘		601				259		649				1		13				14						441						0	N/S	Protected	LOS: D				E/W	Protected	V/C: 0.856									
In	137	427	254	In	225																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	91				1,163																																																																																																																																																																																																																												
	1,059				348																																																																																																																																																																																																																												
	396				502																																																																																																																																																																																																																												
					599																																																																																																																																																																																																																												
					290																																																																																																																																																																																																																												
N/S	Protected	LOS: C																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.718																																																																																																																																																																																																																															
In	122	153	763	In	562																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	68				1,278																																																																																																																																																																																																																												
	1,016				194																																																																																																																																																																																																																												
	6				47																																																																																																																																																																																																																												
					229																																																																																																																																																																																																																												
					234																																																																																																																																																																																																																												
N/S	Protected	LOS: F																																																																																																																																																																																																																															
E/W	Protected	V/C: 1.112																																																																																																																																																																																																																															
In	377	506	439	In	322																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	789				518																																																																																																																																																																																																																												
	483				222																																																																																																																																																																																																																												
	130				105																																																																																																																																																																																																																												
					1,125																																																																																																																																																																																																																												
					160																																																																																																																																																																																																																												
N/S	Protected	LOS: F																																																																																																																																																																																																																															
E/W	Protected	V/C: 1.240																																																																																																																																																																																																																															
In	505	128	603	In	355																																																																																																																																																																																																																												
	↙ ↘				↙ ↘																																																																																																																																																																																																																												
	601				259																																																																																																																																																																																																																												
	649				1																																																																																																																																																																																																																												
	13				14																																																																																																																																																																																																																												
					441																																																																																																																																																																																																																												
					0																																																																																																																																																																																																																												
N/S	Protected	LOS: D																																																																																																																																																																																																																															
E/W	Protected	V/C: 0.856																																																																																																																																																																																																																															
134 Sunset Bl & Stanford Ranch Rd	135 Sunset Bl & West Oaks Bl	136 W Stanford Ranch Rd & Sunset Bl	137 W Stanford Ranch Rd & Wildcat Bl																																																																																																																																																																																																																														

**Figure D9**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Current General Plan**

<p>In 7 0 3  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Bridlewood  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney Ranch Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 7 14  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>664 45  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>91 25  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Permitted LOS: A  E/W Protected V/C: 0.354</p>	<p>In 6 0 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Painted Pony  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney Ranch Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 1 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>606 16  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>85 18  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Split Phase LOS: A  E/W Protected V/C: 0.316</p>	<p>In 37 2 4  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Spring Creek  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney Ranch Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 13 417  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>43 1  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>755 13  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>16 2 2  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Permitted LOS: A  E/W Protected V/C: 0.311</p>	<p>In 1 1,187 44  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Bridlewood  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney Ranch Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 7 24  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>36 69  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>2 134  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: B  E/W Protected V/C: 0.617</p>
<p><b>138 Whitney Ranch Pkwy &amp; Bridlewood Dr</b></p>	<p><b>139 Whitney Ranch Pkwy &amp; Painted Pony Ln</b></p>	<p><b>140 Whitney Ranch Pkwy &amp; Spring Creek Dr</b></p>	<p><b>141 Wildcat Bl &amp; Bridlewood Dr</b></p>
<p>In 208 357 84  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Wildcat  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney Ranch Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 101 322 49  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>428 744 49  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>699 363  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>391 744 49  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: C  E/W Protected V/C: 0.717</p>	<p>In 47 593 11  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Wildcat  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">S High School Ent  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 0 1 102 147  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>24 68 1,103  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>1 36  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: A  E/W Protected V/C: 0.509</p>	<p>In 0 583 10  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Spring Creek  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">N High School Ent  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 7 0 53  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 0 1,102  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: A  E/W Protected V/C: 0.431</p>	<p>In 77 527 28  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Wildcat  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Ranch View  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 3 46 55  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>485 31 4  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>6 2  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: D  E/W Protected V/C: 0.827</p>
<p><b>142 Wildcat Bl &amp; Whitney Ranch Pkwy</b></p>	<p><b>143 Wildcat Bl &amp; S High School Entrance</b></p>	<p><b>144 Wildcat Bl &amp; N High School Entrance</b></p>	<p><b>145 Wildcat Bl &amp; Ranch View Dr</b></p>
<p>In 0 437 602  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Stanford Ranch  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Crest  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 407 141  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 548 292  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: F  E/W Protected V/C: 1.003</p>	<p>In 0 0 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Whitney  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Crest  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 0 138 26  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 410 58  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>330 410 58  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>564 410 58  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Split Phase LOS: D  E/W Split Phase V/C: 0.821</p>	<p>In 0 0 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Crest  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Park  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 0 96 63  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 24 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>263 36 4  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>36 24 0  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: A  E/W Protected V/C: 0.261</p>	<p>In 11 479 78  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Dominguez  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Granite  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 137 141 202  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>109 270 268  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>270 268  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: D  E/W Protected V/C: 0.802</p>
<p><b>152 Stanford Ranch Rd &amp; Crest Dr</b></p>	<p><b>153 Whitney Blvd &amp; Crest Dr</b></p>	<p><b>154 Park Dr &amp; Crest Dr</b></p>	<p><b>161 Granite Dr &amp; Dominguez Dr</b></p>
<p>In 121 1,241 66  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Sierra College Bl  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Dominguez  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 109 44 50  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>162 79 449  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>191 1,855 91  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>N/S Protected LOS: D  E/W Protected V/C: 0.864</p>	<p>In 0 25 653  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Park  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p style="text-align: center;">Valley View Pkwy  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>In 321 167 392  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 0 60 392  <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black;"></span></p> <p>0 0 60 392  </p>		



**Figure D9**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Current General Plan**

		In			In		
In	0	0	0	0	In	0	0
		1,036	141		In	0	0
		1,498	109	In	In	0	0
	6	4	0	109	In	0	0
	In	Civic Center	Rocklin		In	0	0
N/S	Protected	LOS: C			N/S	Protected	LOS: B
E/W	Protected	V/C: 0.701			E/W	Protected	V/C: 0.658
170	<b>Rocklin Rd &amp; Civic Centr Dr</b>			171	<b>Pacific St &amp; Civic Center Dr</b>		

**Figure D10**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Proposed General Plan**

GP30 In 316 19 594 Granite 606 1,194 32 Rocklin 301 1,653 10 In N/S Split Phase LOS: D E/W Protected V/C: 0.859	In 144 1,309 53 Sierra College 24 27 231 Granite 94 1,399 117 In N/S Protected LOS: B E/W Protected V/C: 0.655	In 268 55 64 Sierra Meadows 68 394 61 Granite 218 398 53 In N/S Split Phase LOS: B E/W Protected V/C: 0.608	In 68 745 69 Del Mar/Dominguez 72 162 202 Pacific 155 192 356 In N/S Protected LOS: E E/W Split Phase V/C: 0.957
<b>1 Granite Dr &amp; Rocklin Rd</b>	<b>2 Granite Dr &amp; Sierra College Bl</b>	<b>3 Granite Dr &amp; Sierra Meadows</b>	<b>4 Pacific St &amp; Del Mar/Dominguez</b>
In 54 1,572 104 Farron 47 6 70 Pacific 14 12 420 In N/S Protected LOS: F E/W Split Phase V/C: 1.120	In 437 994 138 Midias 33 105 8 Pacific 421 137 116 In N/S Protected LOS: C E/W Split Phase V/C: 0.753	In 94 838 210 Pacific 254 249 726 Rocklin 143 337 1 In N/S Protected LOS: D E/W Split Phase V/C: 0.832	In 10 1,138 174 Sierra Meadows 128 44 156 Pacific 6 19 26 In N/S Protected LOS: C E/W Split Phase V/C: 0.722
<b>5 Pacific St &amp; Farron St</b>	<b>6 Pacific St &amp; Midias Ave</b>	<b>7 Pacific St &amp; Rocklin Rd</b>	<b>8 Pacific St &amp; Sierra Meadows</b>
In 0 1,006 127 Woodside 161 0 199 Pacific 0 0 0 In N/S Protected LOS: B E/W Protected V/C: 0.640	In 0 0 0 Aguilar 0 1,651 84 Rocklin 70 1,580 342 In N/S Protected LOS: B E/W Protected V/C: 0.662	Ov 539 11 74 In 32 1,083 24 Rocklin 350 1,245 103 In N/S Split Phase LOS: C E/W Protected V/C: 0.711	In 0 0 0 Fire Station #1 0 1,165 0 Rocklin 0 0 0 In N/S Protected LOS: A E/W Protected V/C: 0.442
<b>9 Pacific St &amp; Woodside Dr</b>	<b>10 Rocklin Rd &amp; Aguilar Rd</b>	<b>11 Rocklin Rd &amp; El Don Dr</b>	<b>12 Rocklin Rd &amp; Fire Station No 1</b>
In 301 1 387 SC Driveaway 271 814 9 Rocklin 209 1,119 27 In N/S Split Phase LOS: B E/W Protected V/C: 0.674	In 140 967 151 Sierra College Bl 72 260 82 Rocklin 16 559 952 Ov N/S Protected LOS: E E/W Protected V/C: 0.935	In 0 0 0 In 0 1,175 167 Rocklin 0 1,334 37 In N/S Protected LOS: B E/W Protected V/C: 0.684	In 81 1,924 58 El Don 50 4 47 58 4 36 In N/S Protected LOS: B E/W Split Phase V/C: 0.659
<b>13 Rocklin Rd &amp; Havenhurst Cir</b>	<b>14 Rocklin Rd &amp; Sierra College Bl</b>	<b>15 Rocklin Rd &amp; South Grove St</b>	<b>16 Sierra College Bl &amp; El Don Dr</b>
In 81 1,919 0 Sierra College Bl 0 0 0 Nightwatch 73 0 96 In N/S Protected LOS: A E/W Protected V/C: 0.550	In 72 1,969 4 Sierra College Bl 0 0 4 Scarborough 39 0 14 In N/S Protected LOS: A E/W Split Phase V/C: 0.551	In 30 1,911 6 Sierra College Bl 4 0 1 Southside Ranch 23 0 38 In N/S Protected LOS: A E/W Split Phase V/C: 0.547	Ig 1,451 780 59 Sunset 33 111 22 Pacific 1,071 114 360 In N/S Protected LOS: D E/W Protected V/C: 0.848
<b>17 Sierra College Bl &amp; Nightwatch</b>	<b>18 Sierra College Bl &amp; Scarborough</b>	<b>19 Sierra College Bl &amp; Southside Ranch</b>	<b>20 Sunset Bl &amp; Pacific St</b>

**Figure D10**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Proposed General Plan**

<table border="1"> <tr> <td>In</td> <td>130</td> <td>In</td> <td>2,031</td> </tr> <tr> <td>Third</td> <td>130</td> <td>Sunset</td> <td>223</td> </tr> <tr> <td>Ig</td> <td>584</td> <td></td> <td></td> </tr> <tr> <td>46</td> <td></td> <td></td> <td></td> </tr> <tr> <td>90</td> <td></td> <td></td> <td></td> </tr> <tr> <td>662</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1,416</td> <td></td> <td></td> <td></td> </tr> <tr> <td>122</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>90</td> <td>In</td> <td>42</td> </tr> <tr> <td>Springview</td> <td>42</td> <td>80</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: F</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 1.138</td> <td></td> </tr> </table>	In	130	In	2,031	Third	130	Sunset	223	Ig	584			46				90				662				1,416				122				In	90	In	42	Springview	42	80	In	N/S	Split Phase	LOS: F		E/W	Protected	V/C: 1.138		<table border="1"> <tr> <td>In</td> <td>42</td> <td>In</td> <td>1,934</td> </tr> <tr> <td>Topaz</td> <td>42</td> <td>Sunset</td> <td>75</td> </tr> <tr> <td>In</td> <td>91</td> <td></td> <td></td> </tr> <tr> <td>13</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>187</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1,643</td> <td></td> <td></td> <td></td> </tr> <tr> <td>27</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>26</td> <td>In</td> <td>15</td> </tr> <tr> <td>Topaz</td> <td>15</td> <td>16</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.652</td> <td></td> </tr> </table>	In	42	In	1,934	Topaz	42	Sunset	75	In	91			13				2				187				1,643				27				In	26	In	15	Topaz	15	16	In	N/S	Permitted	LOS: B		E/W	Protected	V/C: 0.652		<table border="1"> <tr> <td>In</td> <td>233</td> <td>In</td> <td>1,921</td> </tr> <tr> <td>Whitney</td> <td>233</td> <td>Sunset</td> <td>507</td> </tr> <tr> <td>In</td> <td>26</td> <td></td> <td></td> </tr> <tr> <td>54</td> <td></td> <td></td> <td></td> </tr> <tr> <td>159</td> <td></td> <td></td> <td></td> </tr> <tr> <td>62</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1,563</td> <td></td> <td></td> <td></td> </tr> <tr> <td>50</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>48</td> <td>In</td> <td>34</td> </tr> <tr> <td>Whitney</td> <td>34</td> <td>439</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: F</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 1.156</td> <td></td> </tr> </table>	In	233	In	1,921	Whitney	233	Sunset	507	In	26			54				159				62				1,563				50				In	48	In	34	Whitney	34	439	In	N/S	Protected	LOS: F		E/W	Protected	V/C: 1.156		<table border="1"> <tr> <td>In</td> <td>61</td> <td>In</td> <td>432</td> </tr> <tr> <td>Lonetree</td> <td>61</td> <td>Blue Oaks</td> <td>132</td> </tr> <tr> <td>Ig</td> <td>941</td> <td></td> <td></td> </tr> <tr> <td>758</td> <td></td> <td></td> <td></td> </tr> <tr> <td>49</td> <td></td> <td></td> <td></td> </tr> <tr> <td>810</td> <td></td> <td></td> <td></td> </tr> <tr> <td>589</td> <td></td> <td></td> <td></td> </tr> <tr> <td>487</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>651</td> <td>In</td> <td>388</td> </tr> <tr> <td>Fairway</td> <td>388</td> <td>92</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: E</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.914</td> <td></td> </tr> </table>	In	61	In	432	Lonetree	61	Blue Oaks	132	Ig	941			758				49				810				589				487				In	651	In	388	Fairway	388	92	In	N/S	Protected	LOS: E		E/W	Protected	V/C: 0.914									
In	130	In	2,031																																																																																																																																																																																																								
Third	130	Sunset	223																																																																																																																																																																																																								
Ig	584																																																																																																																																																																																																										
46																																																																																																																																																																																																											
90																																																																																																																																																																																																											
662																																																																																																																																																																																																											
1,416																																																																																																																																																																																																											
122																																																																																																																																																																																																											
In	90	In	42																																																																																																																																																																																																								
Springview	42	80	In																																																																																																																																																																																																								
N/S	Split Phase	LOS: F																																																																																																																																																																																																									
E/W	Protected	V/C: 1.138																																																																																																																																																																																																									
In	42	In	1,934																																																																																																																																																																																																								
Topaz	42	Sunset	75																																																																																																																																																																																																								
In	91																																																																																																																																																																																																										
13																																																																																																																																																																																																											
2																																																																																																																																																																																																											
187																																																																																																																																																																																																											
1,643																																																																																																																																																																																																											
27																																																																																																																																																																																																											
In	26	In	15																																																																																																																																																																																																								
Topaz	15	16	In																																																																																																																																																																																																								
N/S	Permitted	LOS: B																																																																																																																																																																																																									
E/W	Protected	V/C: 0.652																																																																																																																																																																																																									
In	233	In	1,921																																																																																																																																																																																																								
Whitney	233	Sunset	507																																																																																																																																																																																																								
In	26																																																																																																																																																																																																										
54																																																																																																																																																																																																											
159																																																																																																																																																																																																											
62																																																																																																																																																																																																											
1,563																																																																																																																																																																																																											
50																																																																																																																																																																																																											
In	48	In	34																																																																																																																																																																																																								
Whitney	34	439	In																																																																																																																																																																																																								
N/S	Protected	LOS: F																																																																																																																																																																																																									
E/W	Protected	V/C: 1.156																																																																																																																																																																																																									
In	61	In	432																																																																																																																																																																																																								
Lonetree	61	Blue Oaks	132																																																																																																																																																																																																								
Ig	941																																																																																																																																																																																																										
758																																																																																																																																																																																																											
49																																																																																																																																																																																																											
810																																																																																																																																																																																																											
589																																																																																																																																																																																																											
487																																																																																																																																																																																																											
In	651	In	388																																																																																																																																																																																																								
Fairway	388	92	In																																																																																																																																																																																																								
N/S	Protected	LOS: E																																																																																																																																																																																																									
E/W	Protected	V/C: 0.914																																																																																																																																																																																																									
<p><b>21 Sunset Bl &amp; Springview Dr</b></p>	<p><b>22 Sunset Bl &amp; Topaz Ave</b></p>	<p><b>23 Sunset Bl &amp; Whitney Bl</b></p>	<p><b>101 Blue Oaks Bl &amp; Lonetree</b></p>																																																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>11</td> <td>In</td> <td>11</td> </tr> <tr> <td>Market</td> <td>11</td> <td>Blue Oaks</td> <td>2</td> </tr> <tr> <td>In</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>14</td> <td></td> <td></td> <td></td> </tr> <tr> <td>17</td> <td></td> <td></td> <td></td> </tr> <tr> <td>809</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>8</td> <td>In</td> <td>0</td> </tr> <tr> <td>Market</td> <td>0</td> <td>1</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Split Phase</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.298</td> <td></td> </tr> </table>	In	11	In	11	Market	11	Blue Oaks	2	In	1			14				17				809				4				In	8	In	0	Market	0	1	In	N/S	Split Phase	LOS: A		E/W	Protected	V/C: 0.298		<table border="1"> <tr> <td>In</td> <td>27</td> <td>In</td> <td>0</td> </tr> <tr> <td>Van Buren</td> <td>27</td> <td>Blue Oaks</td> <td>31</td> </tr> <tr> <td>In</td> <td>9</td> <td></td> <td></td> </tr> <tr> <td>501</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td></td> <td></td> <td></td> </tr> <tr> <td>14</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>26</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>38</td> <td>In</td> <td>687</td> </tr> <tr> <td>Van Buren</td> <td>687</td> <td>44</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.347</td> <td></td> </tr> </table>	In	27	In	0	Van Buren	27	Blue Oaks	31	In	9			501				40				14				0				26				In	38	In	687	Van Buren	687	44	In	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.347		<table border="1"> <tr> <td>In</td> <td>137</td> <td>In</td> <td>1</td> </tr> <tr> <td>Five Star</td> <td>137</td> <td>Destiny</td> <td>2</td> </tr> <tr> <td>In</td> <td>13</td> <td></td> <td></td> </tr> <tr> <td>122</td> <td></td> <td></td> <td></td> </tr> <tr> <td>80</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>1</td> <td>In</td> <td>93</td> </tr> <tr> <td>Five Star</td> <td>93</td> <td>2</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.193</td> <td></td> </tr> </table>	In	137	In	1	Five Star	137	Destiny	2	In	13			122				80				13				0				3				In	1	In	93	Five Star	93	2	In	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.193		<table border="1"> <tr> <td>In</td> <td>15</td> <td>In</td> <td>1</td> </tr> <tr> <td>Lonetree</td> <td>15</td> <td>Adams</td> <td>15</td> </tr> <tr> <td>In</td> <td>24</td> <td></td> <td></td> </tr> <tr> <td>1,522</td> <td></td> <td></td> <td></td> </tr> <tr> <td>17</td> <td></td> <td></td> <td></td> </tr> <tr> <td>30</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>36</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>38</td> <td>In</td> <td>846</td> </tr> <tr> <td>Lonetree</td> <td>846</td> <td>18</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: B</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.606</td> <td></td> </tr> </table>	In	15	In	1	Lonetree	15	Adams	15	In	24			1,522				17				30				1				36				In	38	In	846	Lonetree	846	18	In	N/S	Protected	LOS: B		E/W	Split Phase	V/C: 0.606													
In	11	In	11																																																																																																																																																																																																								
Market	11	Blue Oaks	2																																																																																																																																																																																																								
In	1																																																																																																																																																																																																										
14																																																																																																																																																																																																											
17																																																																																																																																																																																																											
809																																																																																																																																																																																																											
4																																																																																																																																																																																																											
In	8	In	0																																																																																																																																																																																																								
Market	0	1	In																																																																																																																																																																																																								
N/S	Split Phase	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.298																																																																																																																																																																																																									
In	27	In	0																																																																																																																																																																																																								
Van Buren	27	Blue Oaks	31																																																																																																																																																																																																								
In	9																																																																																																																																																																																																										
501																																																																																																																																																																																																											
40																																																																																																																																																																																																											
14																																																																																																																																																																																																											
0																																																																																																																																																																																																											
26																																																																																																																																																																																																											
In	38	In	687																																																																																																																																																																																																								
Van Buren	687	44	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.347																																																																																																																																																																																																									
In	137	In	1																																																																																																																																																																																																								
Five Star	137	Destiny	2																																																																																																																																																																																																								
In	13																																																																																																																																																																																																										
122																																																																																																																																																																																																											
80																																																																																																																																																																																																											
13																																																																																																																																																																																																											
0																																																																																																																																																																																																											
3																																																																																																																																																																																																											
In	1	In	93																																																																																																																																																																																																								
Five Star	93	2	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.193																																																																																																																																																																																																									
In	15	In	1																																																																																																																																																																																																								
Lonetree	15	Adams	15																																																																																																																																																																																																								
In	24																																																																																																																																																																																																										
1,522																																																																																																																																																																																																											
17																																																																																																																																																																																																											
30																																																																																																																																																																																																											
1																																																																																																																																																																																																											
36																																																																																																																																																																																																											
In	38	In	846																																																																																																																																																																																																								
Lonetree	846	18	In																																																																																																																																																																																																								
N/S	Protected	LOS: B																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.606																																																																																																																																																																																																									
<p><b>102 Blue Oaks Bl &amp; Market Place</b></p>	<p><b>103 Blue Oaks Bl &amp; Van Buren Way</b></p>	<p><b>104 Five Star &amp; Destiny Dr</b></p>	<p><b>105 Lonetree Bl &amp; Adams Dr</b></p>																																																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td>Lonetree</td> <td>0</td> <td>Atherton</td> <td>0</td> </tr> <tr> <td>In</td> <td>12</td> <td></td> <td></td> </tr> <tr> <td>857</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>39</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>202</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>37</td> <td>In</td> <td>709</td> </tr> <tr> <td>Lonetree</td> <td>709</td> <td>0</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.449</td> <td></td> </tr> </table>	In	0	In	0	Lonetree	0	Atherton	0	In	12			857				0				39				0				202				In	37	In	709	Lonetree	709	0	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.449		<table border="1"> <tr> <td>In</td> <td>4</td> <td>In</td> <td>4</td> </tr> <tr> <td>Lonetree</td> <td>4</td> <td>Grand Canyon</td> <td>6</td> </tr> <tr> <td>In</td> <td>14</td> <td></td> <td></td> </tr> <tr> <td>1,633</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> </tr> <tr> <td>28</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>77</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>200</td> <td>In</td> <td>943</td> </tr> <tr> <td>Lonetree</td> <td>943</td> <td>17</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.767</td> <td></td> </tr> </table>	In	4	In	4	Lonetree	4	Grand Canyon	6	In	14			1,633				5				28				1				77				In	200	In	943	Lonetree	943	17	In	N/S	Protected	LOS: C		E/W	Split Phase	V/C: 0.767		<table border="1"> <tr> <td>In</td> <td>11</td> <td>In</td> <td>5</td> </tr> <tr> <td>Lonetree</td> <td>11</td> <td>Redwood</td> <td>29</td> </tr> <tr> <td>In</td> <td>78</td> <td></td> <td></td> </tr> <tr> <td>1,462</td> <td></td> <td></td> <td></td> </tr> <tr> <td>51</td> <td></td> <td></td> <td></td> </tr> <tr> <td>90</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>113</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>141</td> <td>In</td> <td>813</td> </tr> <tr> <td>Lonetree</td> <td>813</td> <td>30</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: C</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.737</td> <td></td> </tr> </table>	In	11	In	5	Lonetree	11	Redwood	29	In	78			1,462				51				90				2				113				In	141	In	813	Lonetree	813	30	In	N/S	Protected	LOS: C		E/W	Split Phase	V/C: 0.737		<table border="1"> <tr> <td>In</td> <td>8</td> <td>In</td> <td>1</td> </tr> <tr> <td>Lonetree</td> <td>8</td> <td>West Oaks</td> <td>263</td> </tr> <tr> <td>In</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>1,053</td> <td></td> <td></td> <td></td> </tr> <tr> <td>9</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>7</td> <td>In</td> <td>685</td> </tr> <tr> <td>Lonetree</td> <td>685</td> <td>247</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.552</td> <td></td> </tr> </table>	In	8	In	1	Lonetree	8	West Oaks	263	In	1			1,053				9				1				0				4				In	7	In	685	Lonetree	685	247	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.552									
In	0	In	0																																																																																																																																																																																																								
Lonetree	0	Atherton	0																																																																																																																																																																																																								
In	12																																																																																																																																																																																																										
857																																																																																																																																																																																																											
0																																																																																																																																																																																																											
39																																																																																																																																																																																																											
0																																																																																																																																																																																																											
202																																																																																																																																																																																																											
In	37	In	709																																																																																																																																																																																																								
Lonetree	709	0	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.449																																																																																																																																																																																																									
In	4	In	4																																																																																																																																																																																																								
Lonetree	4	Grand Canyon	6																																																																																																																																																																																																								
In	14																																																																																																																																																																																																										
1,633																																																																																																																																																																																																											
5																																																																																																																																																																																																											
28																																																																																																																																																																																																											
1																																																																																																																																																																																																											
77																																																																																																																																																																																																											
In	200	In	943																																																																																																																																																																																																								
Lonetree	943	17	In																																																																																																																																																																																																								
N/S	Protected	LOS: C																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.767																																																																																																																																																																																																									
In	11	In	5																																																																																																																																																																																																								
Lonetree	11	Redwood	29																																																																																																																																																																																																								
In	78																																																																																																																																																																																																										
1,462																																																																																																																																																																																																											
51																																																																																																																																																																																																											
90																																																																																																																																																																																																											
2																																																																																																																																																																																																											
113																																																																																																																																																																																																											
In	141	In	813																																																																																																																																																																																																								
Lonetree	813	30	In																																																																																																																																																																																																								
N/S	Protected	LOS: C																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.737																																																																																																																																																																																																									
In	8	In	1																																																																																																																																																																																																								
Lonetree	8	West Oaks	263																																																																																																																																																																																																								
In	1																																																																																																																																																																																																										
1,053																																																																																																																																																																																																											
9																																																																																																																																																																																																											
1																																																																																																																																																																																																											
0																																																																																																																																																																																																											
4																																																																																																																																																																																																											
In	7	In	685																																																																																																																																																																																																								
Lonetree	685	247	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.552																																																																																																																																																																																																									
<p><b>106 Lonetree Bl &amp; Atherton Rd</b></p>	<p><b>107 Lonetree Bl &amp; Grand Canyon Dr</b></p>	<p><b>108 Lonetree Bl &amp; Redwood Dr</b></p>	<p><b>109 Lonetree Bl &amp; West Oaks Bl</b></p>																																																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>22</td> <td>In</td> <td>6</td> </tr> <tr> <td>Blaydon</td> <td>22</td> <td>Park</td> <td>0</td> </tr> <tr> <td>In</td> <td>53</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>21</td> <td></td> <td></td> <td></td> </tr> <tr> <td>319</td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td></td> <td></td> <td></td> </tr> <tr> <td>85</td> <td></td> <td></td> <td></td> </tr> <tr> <td>605</td> <td></td> <td></td> <td></td> </tr> <tr> <td>11</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>2</td> <td>In</td> <td>1</td> </tr> <tr> <td>Blaydon</td> <td>1</td> <td>3</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Permitted</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.262</td> <td></td> </tr> </table>	In	22	In	6	Blaydon	22	Park	0	In	53			2				21				319				7				85				605				11				In	2	In	1	Blaydon	1	3	In	N/S	Permitted	LOS: A		E/W	Protected	V/C: 0.262		<table border="1"> <tr> <td>In</td> <td>6</td> <td>In</td> <td>0</td> </tr> <tr> <td>Park</td> <td>6</td> <td>Quarry</td> <td>12</td> </tr> <tr> <td>In</td> <td>41</td> <td></td> <td></td> </tr> <tr> <td>1,023</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13</td> <td></td> <td></td> <td></td> </tr> <tr> <td>43</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td></td> <td></td> <td></td> </tr> <tr> <td>31</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>82</td> <td>In</td> <td>1,307</td> </tr> <tr> <td>Park</td> <td>1,307</td> <td>6</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.507</td> <td></td> </tr> </table>	In	6	In	0	Park	6	Quarry	12	In	41			1,023				13				43				4				31				In	82	In	1,307	Park	1,307	6	In	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.507		<table border="1"> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td>Park</td> <td>0</td> <td>Farrier</td> <td>0</td> </tr> <tr> <td>In</td> <td>61</td> <td></td> <td></td> </tr> <tr> <td>583</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>37</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>176</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>188</td> <td>In</td> <td>767</td> </tr> <tr> <td>Park</td> <td>767</td> <td>0</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.457</td> <td></td> </tr> </table>	In	0	In	0	Park	0	Farrier	0	In	61			583				0				37				0				176				In	188	In	767	Park	767	0	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.457		<table border="1"> <tr> <td>In</td> <td>15</td> <td>In</td> <td>0</td> </tr> <tr> <td>Lonetree</td> <td>15</td> <td>King Pine</td> <td>31</td> </tr> <tr> <td>In</td> <td>7</td> <td></td> <td></td> </tr> <tr> <td>1,032</td> <td></td> <td></td> <td></td> </tr> <tr> <td>27</td> <td></td> <td></td> <td></td> </tr> <tr> <td>7</td> <td></td> <td></td> <td></td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>9</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>24</td> <td>In</td> <td>1,308</td> </tr> <tr> <td>Lonetree</td> <td>1,308</td> <td>25</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Permitted</td> <td>V/C: 0.489</td> <td></td> </tr> </table>	In	15	In	0	Lonetree	15	King Pine	31	In	7			1,032				27				7				1				9				In	24	In	1,308	Lonetree	1,308	25	In	N/S	Protected	LOS: A		E/W	Permitted	V/C: 0.489	
In	22	In	6																																																																																																																																																																																																								
Blaydon	22	Park	0																																																																																																																																																																																																								
In	53																																																																																																																																																																																																										
2																																																																																																																																																																																																											
21																																																																																																																																																																																																											
319																																																																																																																																																																																																											
7																																																																																																																																																																																																											
85																																																																																																																																																																																																											
605																																																																																																																																																																																																											
11																																																																																																																																																																																																											
In	2	In	1																																																																																																																																																																																																								
Blaydon	1	3	In																																																																																																																																																																																																								
N/S	Permitted	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.262																																																																																																																																																																																																									
In	6	In	0																																																																																																																																																																																																								
Park	6	Quarry	12																																																																																																																																																																																																								
In	41																																																																																																																																																																																																										
1,023																																																																																																																																																																																																											
13																																																																																																																																																																																																											
43																																																																																																																																																																																																											
4																																																																																																																																																																																																											
31																																																																																																																																																																																																											
In	82	In	1,307																																																																																																																																																																																																								
Park	1,307	6	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.507																																																																																																																																																																																																									
In	0	In	0																																																																																																																																																																																																								
Park	0	Farrier	0																																																																																																																																																																																																								
In	61																																																																																																																																																																																																										
583																																																																																																																																																																																																											
0																																																																																																																																																																																																											
37																																																																																																																																																																																																											
0																																																																																																																																																																																																											
176																																																																																																																																																																																																											
In	188	In	767																																																																																																																																																																																																								
Park	767	0	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.457																																																																																																																																																																																																									
In	15	In	0																																																																																																																																																																																																								
Lonetree	15	King Pine	31																																																																																																																																																																																																								
In	7																																																																																																																																																																																																										
1,032																																																																																																																																																																																																											
27																																																																																																																																																																																																											
7																																																																																																																																																																																																											
1																																																																																																																																																																																																											
9																																																																																																																																																																																																											
In	24	In	1,308																																																																																																																																																																																																								
Lonetree	1,308	25	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Permitted	V/C: 0.489																																																																																																																																																																																																									
<p><b>110 Park Dr &amp; Blaydon Rd</b></p>	<p><b>111 Park Dr &amp; Quarry Way</b></p>	<p><b>112 Park Dr &amp; Farrier Rd</b></p>	<p><b>113 Park Dr &amp; King Pine Dr</b></p>																																																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>1</td> <td>In</td> <td>4</td> </tr> <tr> <td>Park</td> <td>1</td> <td>Shelton</td> <td>34</td> </tr> <tr> <td>In</td> <td>3</td> <td></td> <td></td> </tr> <tr> <td>567</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> </tr> <tr> <td>8</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>67</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>116</td> <td>In</td> <td>1,024</td> </tr> <tr> <td>Park</td> <td>1,024</td> <td>64</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.324</td> <td></td> </tr> </table>	In	1	In	4	Park	1	Shelton	34	In	3			567				6				8				0				67				In	116	In	1,024	Park	1,024	64	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.324		<table border="1"> <tr> <td>In</td> <td>72</td> <td>In</td> <td>14</td> </tr> <tr> <td>Park</td> <td>72</td> <td>Victory</td> <td>26</td> </tr> <tr> <td>In</td> <td>13</td> <td></td> <td></td> </tr> <tr> <td>562</td> <td></td> <td></td> <td></td> </tr> <tr> <td>61</td> <td></td> <td></td> <td></td> </tr> <tr> <td>75</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> </tr> <tr> <td>12</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>37</td> <td>In</td> <td>1,039</td> </tr> <tr> <td>Park</td> <td>1,039</td> <td>6</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.387</td> <td></td> </tr> </table>	In	72	In	14	Park	72	Victory	26	In	13			562				61				75				5				12				In	37	In	1,039	Park	1,039	6	In	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.387		<table border="1"> <tr> <td>In</td> <td>23</td> <td>In</td> <td>0</td> </tr> <tr> <td>Wykford</td> <td>23</td> <td>Park</td> <td>0</td> </tr> <tr> <td>In</td> <td>222</td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td></td> <td></td> <td></td> </tr> <tr> <td>348</td> <td></td> <td></td> <td></td> </tr> <tr> <td>683</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td>Wykford</td> <td>0</td> <td>0</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td>V/C: 0.395</td> <td></td> </tr> </table>	In	23	In	0	Wykford	23	Park	0	In	222			0				15				348				683				0				In	0	In	0	Wykford	0	0	In	N/S	Protected	LOS: A		E/W	Protected	V/C: 0.395		<table border="1"> <tr> <td>In</td> <td>2</td> <td>In</td> <td>0</td> </tr> <tr> <td>Park</td> <td>2</td> <td>Twin Oaks</td> <td>5</td> </tr> <tr> <td>In</td> <td>32</td> <td></td> <td></td> </tr> <tr> <td>591</td> <td></td> <td></td> <td></td> </tr> <tr> <td>25</td> <td></td> <td></td> <td></td> </tr> <tr> <td>65</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> </tr> <tr> <td>59</td> <td></td> <td></td> <td></td> </tr> <tr> <td>In</td> <td>66</td> <td>In</td> <td>782</td> </tr> <tr> <td>Park</td> <td>782</td> <td>19</td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td>LOS: A</td> <td></td> </tr> <tr> <td>E/W</td> <td>Split Phase</td> <td>V/C: 0.384</td> <td></td> </tr> </table>	In	2	In	0	Park	2	Twin Oaks	5	In	32			591				25				65				2				59				In	66	In	782	Park	782	19	In	N/S	Protected	LOS: A		E/W	Split Phase	V/C: 0.384									
In	1	In	4																																																																																																																																																																																																								
Park	1	Shelton	34																																																																																																																																																																																																								
In	3																																																																																																																																																																																																										
567																																																																																																																																																																																																											
6																																																																																																																																																																																																											
8																																																																																																																																																																																																											
0																																																																																																																																																																																																											
67																																																																																																																																																																																																											
In	116	In	1,024																																																																																																																																																																																																								
Park	1,024	64	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.324																																																																																																																																																																																																									
In	72	In	14																																																																																																																																																																																																								
Park	72	Victory	26																																																																																																																																																																																																								
In	13																																																																																																																																																																																																										
562																																																																																																																																																																																																											
61																																																																																																																																																																																																											
75																																																																																																																																																																																																											
5																																																																																																																																																																																																											
12																																																																																																																																																																																																											
In	37	In	1,039																																																																																																																																																																																																								
Park	1,039	6	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.387																																																																																																																																																																																																									
In	23	In	0																																																																																																																																																																																																								
Wykford	23	Park	0																																																																																																																																																																																																								
In	222																																																																																																																																																																																																										
0																																																																																																																																																																																																											
15																																																																																																																																																																																																											
348																																																																																																																																																																																																											
683																																																																																																																																																																																																											
0																																																																																																																																																																																																											
In	0	In	0																																																																																																																																																																																																								
Wykford	0	0	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Protected	V/C: 0.395																																																																																																																																																																																																									
In	2	In	0																																																																																																																																																																																																								
Park	2	Twin Oaks	5																																																																																																																																																																																																								
In	32																																																																																																																																																																																																										
591																																																																																																																																																																																																											
25																																																																																																																																																																																																											
65																																																																																																																																																																																																											
2																																																																																																																																																																																																											
59																																																																																																																																																																																																											
In	66	In	782																																																																																																																																																																																																								
Park	782	19	In																																																																																																																																																																																																								
N/S	Protected	LOS: A																																																																																																																																																																																																									
E/W	Split Phase	V/C: 0.384																																																																																																																																																																																																									
<p><b>114 Park Dr &amp; Shelton</b></p>	<p><b>115 Park Dr &amp; Victory Lane</b></p>	<p><b>116 Park Dr &amp; Wykford Bl</b></p>	<p><b>117 Park Dr &amp; Twin Oaks/Boardwalk</b></p>																																																																																																																																																																																																								

**Figure D10**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Proposed General Plan**

<p>In 115 4 1 1,040 84</p> <p>Park In 218 0 0</p> <p>Safeway 0 0 70 In</p> <p>LOS: B V/C: 0.676</p>	<p>In 11 4 1 177 338</p> <p>Five Star In 313 23 40</p> <p>Victory 55 16 5 In</p> <p>6 243 35 In</p> <p>LOS: A V/C: 0.583</p>	<p>In 0 7 36 2</p> <p>Spring Creek In 4 0 4</p> <p>Broken Rai 5 0 10 In</p> <p>LOS: A V/C: 0.049</p>	<p>In 59 4 1 491 42</p> <p>Stanford Ranch In 11 35 682 19 In</p> <p>Cobblestone 27 5 8 In</p> <p>14 682 19 In</p> <p>LOS: A V/C: 0.318</p>
<b>118</b> <b>Park Dr &amp; Safeway</b>	<b>119</b> <b>South Whitney &amp; Five Star Bl</b>	<b>120</b> <b>Spring Creek Dr &amp; Broken Rail Ln</b>	<b>121</b> <b>Stanford Ranch Rd &amp; Cobblestone Dr</b>
<p>In 49 7 47</p> <p>Darby In 67 660 37</p> <p>Stanford Ranch 80 1,104 170 In</p> <p>65 2 28 In</p> <p>LOS: A V/C: 0.582</p>	<p>In 157 377 234</p> <p>Park In 300 555 113</p> <p>Stanford Ranch 293 691 141 In</p> <p>175 537 86 In</p> <p>LOS: B V/C: 0.675</p>	<p>In 63 4 1 1,127 39</p> <p>Stanford Ranch In 63 2 89</p> <p>Plaza 85 2 201 In</p> <p>125 1,270 60 In</p> <p>LOS: A V/C: 0.561</p>	<p>In 15 4 1 532 11</p> <p>Stanford Ranch In 4 12 81</p> <p>Stoney 17 17 50 In</p> <p>92 694 133 In</p> <p>LOS: A V/C: 0.393</p>
<b>122</b> <b>Stanford Ranch Rd &amp; Darby Rd</b>	<b>123</b> <b>Stanford Ranch Rd &amp; Park Dr</b>	<b>124</b> <b>Stanford Ranch Rd &amp; Plaza</b>	<b>125</b> <b>Stanford Ranch Rd &amp; Stoney Dr</b>
<p>In 96 0 77</p> <p>Victory In 77 966 0</p> <p>Stanford Ranch 57 1,032 0 In</p> <p>0 0 0 In</p> <p>LOS: A V/C: 0.317</p>	<p>In 80 104 186</p> <p>West Oaks In 170 516 80</p> <p>Stanford Ranch 288 948 9 In</p> <p>22 583 249 In</p> <p>LOS: B V/C: 0.647</p>	<p>In 213 4 18 193</p> <p>In 541 1,830 21</p> <p>Sunset 228 1,187 68 In</p> <p>392 108 77 In</p> <p>LOS: E V/C: 0.910</p>	<p>In 4 4 20 29</p> <p>In 58 1,720 398</p> <p>Sunset 27 1,653 377 In</p> <p>303 36 338 Ov</p> <p>LOS: C V/C: 0.791</p>
<b>126</b> <b>Stanford Ranch Rd &amp; Victory Ln</b>	<b>127</b> <b>Stanford Ranch Rd &amp; West Oaks Bl</b>	<b>128</b> <b>Sunset Bl &amp; Atherton</b>	<b>129</b> <b>Sunset Bl &amp; Blue Oaks Bl</b>
<p>In 29 19 13</p> <p>In 13 1,669 183</p> <p>Sunset 63 1,463 106 In</p> <p>139 32 237 In</p> <p>LOS: C V/C: 0.743</p>	<p>In 43 1 26</p> <p>Little Rock In 4 1,769 75</p> <p>Sunset 146 1,638 49 In</p> <p>39 0 25 In</p> <p>LOS: A V/C: 0.583</p>	<p>In 92 4 1 422 249</p> <p>Park In 116 1,404 462</p> <p>Sunset 405 1,349 355 In</p> <p>737 602 117 In</p> <p>LOS: D V/C: 0.821</p>	<p>In 144 5 60</p> <p>Pebble Creek In 62 1,674 72</p> <p>Sunset 204 1,480 31 In</p> <p>26 12 29 In</p> <p>LOS: B V/C: 0.678</p>
<b>130</b> <b>Sunset Bl &amp; Fairway Dr</b>	<b>131</b> <b>Sunset Bl &amp; Little Rock</b>	<b>132</b> <b>Sunset Bl &amp; Park Dr</b>	<b>133</b> <b>Sunset Bl &amp; Pebble Creek</b>
<p>In 141 4 1 426 252</p> <p>Stanford Ranch In 235 1,196 381</p> <p>Sunset 93 1,091 377 In</p> <p>446 611 320 In</p> <p>LOS: B V/C: 0.699</p>	<p>In 123 153 760</p> <p>West Oaks In 564 1,290 193</p> <p>Sunset 68 1,025 6 In</p> <p>47 226 230 In</p> <p>LOS: F V/C: 1.051</p>	<p>In 377 4 1 516 412</p> <p>Sunset In 311 517 229</p> <p>W Stanford Ranch 790 493 122 In</p> <p>105 1,141 154 In</p> <p>LOS: F V/C: 1.164</p>	<p>In 510 129 568</p> <p>Wildcat In 345 247 1</p> <p>W Stanford Ranch 609 614 13 In</p> <p>14 442 0 In</p> <p>LOS: C V/C: 0.796</p>
<b>134</b> <b>Sunset Bl &amp; Stanford Ranch Rd</b>	<b>135</b> <b>Sunset Bl &amp; West Oaks Bl</b>	<b>136</b> <b>W Stanford Ranch Rd &amp; Sunset Bl</b>	<b>137</b> <b>W Stanford Ranch Rd &amp; Wildcat Bl</b>



**Figure D10**  
**P.M. Peak Hour Volumes and LOS - City of Rocklin Signalized Intersections**  
**Cumulative With Buildout of Proposed General Plan**

<table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="2">In</th> </tr> </thead> <tbody> <tr> <td>In</td> <td>0 0 0</td> <td>0</td> <td>1,093</td> </tr> <tr> <td></td> <td></td> <td>111</td> <td>142</td> </tr> <tr> <td></td> <td></td> <td colspan="2">Rocklin</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,515</td> <td>4</td> <td>115</td> </tr> <tr> <td></td> <td>7</td> <td></td> <td></td> </tr> <tr> <td></td> <td>In</td> <td></td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.676</td> </tr> </tbody> </table>				In		In	0 0 0	0	1,093			111	142			Rocklin			0	0	0		1,515	4	115		7				In		In	N/S	Protected	LOS: B		E/W	Protected	V/C: 0.676		<table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="2">In</th> </tr> </thead> <tbody> <tr> <td>In</td> <td>0 1,356 0</td> <td>0</td> <td>121</td> </tr> <tr> <td></td> <td></td> <td>111</td> <td>134</td> </tr> <tr> <td></td> <td></td> <td colspan="2">Civic Center</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1,603</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td>134</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td>In</td> </tr> <tr> <td>N/S</td> <td>Protected</td> <td colspan="2">LOS: B</td> </tr> <tr> <td>E/W</td> <td>Protected</td> <td colspan="2">V/C: 0.615</td> </tr> </tbody> </table>				In		In	0 1,356 0	0	121			111	134			Civic Center			0	0	0		0	0	1,603		0		134		In		In	N/S	Protected	LOS: B		E/W	Protected	V/C: 0.615	
		In																																																																																	
In	0 0 0	0	1,093																																																																																
		111	142																																																																																
		Rocklin																																																																																	
	0	0	0																																																																																
	1,515	4	115																																																																																
	7																																																																																		
	In		In																																																																																
N/S	Protected	LOS: B																																																																																	
E/W	Protected	V/C: 0.676																																																																																	
		In																																																																																	
In	0 1,356 0	0	121																																																																																
		111	134																																																																																
		Civic Center																																																																																	
	0	0	0																																																																																
	0	0	1,603																																																																																
	0		134																																																																																
	In		In																																																																																
N/S	Protected	LOS: B																																																																																	
E/W	Protected	V/C: 0.615																																																																																	
<b>170</b>	<b>Rocklin Rd &amp; Civic Centr Dr</b>	<b>171</b>	<b>Pacific St &amp; Civic Center Dr</b>																																																																																

**Figure D11**  
**Cumulative PM Peak Hour Intersection Level of Service**  
**State Highway Intersections**

<p>NP30</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>171</td> <td>1,635</td> <td>3</td> </tr> <tr> <td></td> <td>481</td> <td>1,218</td> <td>0</td> <td>561</td> <td>0</td> <td>625</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected Del: 66.9 sec</p>	In	0	0	0	171	1,635	3		481	1,218	0	561	0	625	In	0	0	0	0	0	0	<table border="1"> <tr> <td>In</td> <td>388</td> <td>1</td> <td>117</td> <td>0</td> <td>1,463</td> <td>681</td> </tr> <tr> <td></td> <td>0</td> <td>1,573</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Permitted LOS: E  E/W Protected Del: 67.5 sec</p>	In	388	1	117	0	1,463	681		0	1,573	0	0	0	0	In	0	0	0	0	0	0	<table border="1"> <tr> <td>In</td> <td>74</td> <td>1,694</td> <td>0</td> <td>264</td> <td>48</td> <td>584</td> </tr> <tr> <td></td> <td>80</td> <td>0</td> <td>327</td> <td>164</td> <td>1,318</td> <td>313</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 32.9 sec</p>	In	74	1,694	0	264	48	584		80	0	327	164	1,318	313	In	0	0	0	0	0	0	<table border="1"> <tr> <td>In</td> <td>131</td> <td>1,149</td> <td>322</td> <td>365</td> <td>0</td> <td>202</td> </tr> <tr> <td></td> <td>421</td> <td>180</td> <td>116</td> <td>0</td> <td>1,585</td> <td>89</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 28.2 sec</p>	In	131	1,149	322	365	0	202		421	180	116	0	1,585	89	In	0	0	0	0	0	0
In	0	0	0	171	1,635	3																																																																																	
	481	1,218	0	561	0	625																																																																																	
In	0	0	0	0	0	0																																																																																	
In	388	1	117	0	1,463	681																																																																																	
	0	1,573	0	0	0	0																																																																																	
In	0	0	0	0	0	0																																																																																	
In	74	1,694	0	264	48	584																																																																																	
	80	0	327	164	1,318	313																																																																																	
In	0	0	0	0	0	0																																																																																	
In	131	1,149	322	365	0	202																																																																																	
	421	180	116	0	1,585	89																																																																																	
In	0	0	0	0	0	0																																																																																	
<p><b>201 Rocklin Rd &amp; I-80 EB</b></p> <table border="1"> <tr> <td>In</td> <td>181</td> <td>0</td> <td>480</td> <td>203</td> <td>1,894</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1,619</td> <td>956</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 12.3 sec</p>	In	181	0	480	203	1,894	0		0	1,619	956	0	0	0	In	0	0	0	0	0	0	<p><b>202 Rocklin Rd &amp; I-80 WB</b></p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>652</td> <td>1,400</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1,750</td> <td>349</td> <td>697</td> <td>0</td> <td>117</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 14.4 sec</p>	In	0	0	0	652	1,400	0		0	1,750	349	697	0	117	In	0	0	0	0	0	0	<p><b>203 Sierra College Bl &amp; I-80 WB</b></p> <table border="1"> <tr> <td>In</td> <td>676</td> <td>0</td> <td>486</td> <td>703</td> <td>1,751</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1,571</td> <td>310</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 32.2 sec</p>	In	676	0	486	703	1,751	0		0	1,571	310	0	0	0	In	0	0	0	0	0	0	<p><b>204 Sierra College Bl &amp; I-80 EB</b></p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>413</td> <td>2,082</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1,454</td> <td>603</td> <td>373</td> <td>0</td> <td>228</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 16.1 sec</p>	In	0	0	0	413	2,082	0		0	1,454	603	373	0	228	In	0	0	0	0	0	0
In	181	0	480	203	1,894	0																																																																																	
	0	1,619	956	0	0	0																																																																																	
In	0	0	0	0	0	0																																																																																	
In	0	0	0	652	1,400	0																																																																																	
	0	1,750	349	697	0	117																																																																																	
In	0	0	0	0	0	0																																																																																	
In	676	0	486	703	1,751	0																																																																																	
	0	1,571	310	0	0	0																																																																																	
In	0	0	0	0	0	0																																																																																	
In	0	0	0	413	2,082	0																																																																																	
	0	1,454	603	373	0	228																																																																																	
In	0	0	0	0	0	0																																																																																	
<p><b>206 Sunset &amp; SR 65 SB</b></p> <table border="1"> <tr> <td>Ig</td> <td>169</td> <td>615</td> <td>126</td> <td>374</td> <td>1,121</td> <td>505</td> </tr> <tr> <td></td> <td>0</td> <td>438</td> <td>177</td> <td>573</td> <td>376</td> <td>744</td> </tr> <tr> <td>Ov</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 27 sec</p>	Ig	169	615	126	374	1,121	505		0	438	177	573	376	744	Ov	0	0	0	0	0	0	<p><b>207 Sunset &amp; SR 65 NB</b></p> <table border="1"> <tr> <td>Ig</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>1,836</td> <td>166</td> </tr> <tr> <td></td> <td>0</td> <td>1,539</td> <td>474</td> <td>123</td> <td>0</td> <td>438</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: D  E/W Protected Del: 41.5 sec</p>	Ig	0	0	0	0	1,836	166		0	1,539	474	123	0	438	In	0	0	0	0	0	0	<p><b>208 Whitney Ranch Pkwy &amp; SR 65 SB</b></p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>215</td> <td>2,377</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>2,042</td> <td>597</td> <td>603</td> <td>0</td> <td>767</td> </tr> <tr> <td>Ov</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Permitted LOS: B  E/W Protected Del: 19.2 sec</p>	In	0	0	0	215	2,377	0		0	2,042	597	603	0	767	Ov	0	0	0	0	0	0	<p><b>209 Whitney Ranch Pkwy &amp; SR 65 NB</b></p> <table border="1"> <tr> <td>Ig</td> <td>526</td> <td>0</td> <td>323</td> <td>0</td> <td>2,093</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>2,323</td> <td>395</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Permitted LOS: A  E/W Protected Del: 9.4 sec</p>	Ig	526	0	323	0	2,093	0		0	2,323	395	0	0	0	In	0	0	0	0	0	0
Ig	169	615	126	374	1,121	505																																																																																	
	0	438	177	573	376	744																																																																																	
Ov	0	0	0	0	0	0																																																																																	
Ig	0	0	0	0	1,836	166																																																																																	
	0	1,539	474	123	0	438																																																																																	
In	0	0	0	0	0	0																																																																																	
In	0	0	0	215	2,377	0																																																																																	
	0	2,042	597	603	0	767																																																																																	
Ov	0	0	0	0	0	0																																																																																	
Ig	526	0	323	0	2,093	0																																																																																	
	0	2,323	395	0	0	0																																																																																	
In	0	0	0	0	0	0																																																																																	
<p><b>210 Blue Oaks Blvd &amp; SR 65 SB</b></p> <table border="1"> <tr> <td>Ig</td> <td>179</td> <td>2,057</td> <td>0</td> <td>1,001</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>323</td> <td>1,048</td> <td>1,659</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: B  E/W Permitted Del: 14.3 sec</p>	Ig	179	2,057	0	1,001	0	0		0	0	323	1,048	1,659	0	In	0	0	0	0	0	0	<p><b>211 Blue Oaks Blvd &amp; SR 65 NB Off</b></p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>1,864</td> <td>619</td> <td>199</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>635</td> <td>0</td> <td>2,792</td> <td>524</td> </tr> <tr> <td>Ig</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: B  E/W Permitted Del: 10.2 sec</p>	In	0	1,864	619	199	0	0		0	0	635	0	2,792	524	Ig	0	0	0	0	0	0	<p><b>212 Pleasant Grove Blvd &amp; SR 65 NB</b></p> <table border="1"> <tr> <td>In</td> <td>8</td> <td>4</td> <td>4</td> <td>76</td> <td>371</td> <td>129</td> </tr> <tr> <td></td> <td>5</td> <td>522</td> <td>599</td> <td>1,078</td> <td>5</td> <td>298</td> </tr> <tr> <td>Ig</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> </table> <p>N/S Permitted LOS: C  E/W Protected Del: 34.8 sec</p>	In	8	4	4	76	371	129		5	522	599	1,078	5	298	Ig	0	0	0	0	0	0																						
Ig	179	2,057	0	1,001	0	0																																																																																	
	0	0	323	1,048	1,659	0																																																																																	
In	0	0	0	0	0	0																																																																																	
In	0	1,864	619	199	0	0																																																																																	
	0	0	635	0	2,792	524																																																																																	
Ig	0	0	0	0	0	0																																																																																	
In	8	4	4	76	371	129																																																																																	
	5	522	599	1,078	5	298																																																																																	
Ig	0	0	0	0	0	0																																																																																	
<p><b>214 Stanford Ranch Rd &amp; SR 65 NB</b></p>	<p><b>215 Stanford Ranch Rd &amp; SR 65 SB</b></p>	<p><b>216 Sierra College Blvd &amp; SR 65 SB</b></p>																																																																																					

**Figure D12**  
**Cumulative Plus Project PM Peak Hour Intersection Level of Service**  
**State Highway Intersections**

<p>GP30</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>169</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>1,645</td> <td>3</td> </tr> <tr> <td></td> <td>470</td> <td></td> <td></td> <td>590</td> <td>612</td> </tr> <tr> <td></td> <td>1,291</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td>0</td> <td></td> <td></td> <td>In</td> <td>0</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected Del: 65.9 sec</p>	In	0	0	0	In	169		0	0	0	1,645	3		470			590	612		1,291			0	0		0			0	0	In	0			In	0	<table border="1"> <tr> <td>In</td> <td>410</td> <td>1</td> <td>117</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td></td> <td>1,528</td> <td>655</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,635</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>721</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Permitted LOS: E  E/W Protected Del: 71.4 sec</p>	In	410	1	117	In	0		4			1,528	655		0			0	0		1,635			0	0		721			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>74</td> <td>1,686</td> <td>0</td> <td>In</td> <td>263</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>48</td> <td>579</td> </tr> <tr> <td></td> <td>58</td> <td></td> <td></td> <td>164</td> <td>301</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,315</td> <td>0</td> </tr> <tr> <td></td> <td>328</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 32.9 sec</p>	In	74	1,686	0	In	263		0			48	579		58			164	301		0			1,315	0		328			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>126</td> <td>1,142</td> <td>322</td> <td>In</td> <td>367</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>200</td> </tr> <tr> <td></td> <td>430</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>180</td> <td></td> <td></td> <td>0</td> <td>1,555</td> </tr> <tr> <td></td> <td>110</td> <td></td> <td></td> <td>0</td> <td>100</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 28.4 sec</p>	In	126	1,142	322	In	367		0			0	200		430			0	0		180			0	1,555		110			0	100	In				In							
In	0	0	0	In	169																																																																																																																																																				
	0	0	0	1,645	3																																																																																																																																																				
	470			590	612																																																																																																																																																				
	1,291			0	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
In	0			In	0																																																																																																																																																				
In	410	1	117	In	0																																																																																																																																																				
	4			1,528	655																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,635			0	0																																																																																																																																																				
	721			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	74	1,686	0	In	263																																																																																																																																																				
	0			48	579																																																																																																																																																				
	58			164	301																																																																																																																																																				
	0			1,315	0																																																																																																																																																				
	328			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	126	1,142	322	In	367																																																																																																																																																				
	0			0	200																																																																																																																																																				
	430			0	0																																																																																																																																																				
	180			0	1,555																																																																																																																																																				
	110			0	100																																																																																																																																																				
In				In																																																																																																																																																					
<b>201</b> Rocklin Rd & I-80 EB	<b>202</b> Rocklin Rd & I-80 WB	<b>203</b> Sierra College Bl & I-80 WB	<b>204</b> Sierra College Bl & I-80 EB																																																																																																																																																						
<table border="1"> <tr> <td>In</td> <td>177</td> <td>0</td> <td>482</td> <td>In</td> <td>206</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,897</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,593</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>964</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 12.3 sec</p>	In	177	0	482	In	206		0			1,897	0		0			0	0		1,593			0	0		964			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>655</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,406</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,724</td> <td></td> <td></td> <td>697</td> <td>119</td> </tr> <tr> <td></td> <td>352</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 14.5 sec</p>	In	0	0	0	In	655		0			1,406	0		0			0	0		1,724			697	119		352			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>678</td> <td>0</td> <td>483</td> <td>In</td> <td>707</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,758</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,562</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>311</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 32.5 sec</p>	In	678	0	483	In	707		0			1,758	0		0			0	0		1,562			0	0		311			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>417</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>2,091</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,445</td> <td></td> <td></td> <td>374</td> <td>0</td> </tr> <tr> <td></td> <td>599</td> <td></td> <td></td> <td>0</td> <td>227</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Protected Del: 16.2 sec</p>	In	0	0	0	In	417		0			2,091	0		0			0	0		1,445			374	0		599			0	227	In				In							
In	177	0	482	In	206																																																																																																																																																				
	0			1,897	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,593			0	0																																																																																																																																																				
	964			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	0	0	0	In	655																																																																																																																																																				
	0			1,406	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,724			697	119																																																																																																																																																				
	352			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	678	0	483	In	707																																																																																																																																																				
	0			1,758	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,562			0	0																																																																																																																																																				
	311			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	0	0	0	In	417																																																																																																																																																				
	0			2,091	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,445			374	0																																																																																																																																																				
	599			0	227																																																																																																																																																				
In				In																																																																																																																																																					
<b>206</b> Sunset & SR 65 SB	<b>207</b> Sunset & SR 65 NB	<b>208</b> Whitney Ranch Pkwy & SR 65 SB	<b>209</b> Whitney Ranch Pkwy & SR 65 NB																																																																																																																																																						
<table border="1"> <tr> <td>Ig</td> <td>172</td> <td>614</td> <td>127</td> <td>Ig</td> <td>375</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,122</td> <td>506</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>437</td> <td></td> <td></td> <td>566</td> <td>378</td> </tr> <tr> <td></td> <td>180</td> <td></td> <td></td> <td>742</td> <td>0</td> </tr> <tr> <td>Ov</td> <td></td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 27 sec</p>	Ig	172	614	127	Ig	375		0			1,122	506		0			0	0		437			566	378		180			742	0	Ov				0	0	In				In		<table border="1"> <tr> <td>Ig</td> <td>0</td> <td>0</td> <td>0</td> <td>Ig</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,838</td> <td>166</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1,534</td> <td></td> <td></td> <td>122</td> <td>427</td> </tr> <tr> <td></td> <td>477</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Protected LOS: D  E/W Protected Del: 41.3 sec</p>	Ig	0	0	0	Ig	0		0			1,838	166		0			0	0		1,534			122	427		477			0	0	In				In		<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>Ig</td> <td>213</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>2,418</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>2,049</td> <td></td> <td></td> <td>591</td> <td>771</td> </tr> <tr> <td></td> <td>602</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td>Ig</td> <td></td> </tr> </table> <p>N/S Permitted LOS: B  E/W Protected Del: 19.3 sec</p>	In	0	0	0	Ig	213		0			2,418	0		0			0	0		2,049			591	771		602			0	0	Ig				Ig		<table border="1"> <tr> <td>Ig</td> <td>526</td> <td>0</td> <td>334</td> <td>Ig</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>2,110</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>2,325</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>406</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> <td></td> </tr> </table> <p>N/S Permitted LOS: A  E/W Protected Del: 9.8 sec</p>	Ig	526	0	334	Ig	0		0			2,110	0		0			0	0		2,325			0	0		406			0	0	In				In	
Ig	172	614	127	Ig	375																																																																																																																																																				
	0			1,122	506																																																																																																																																																				
	0			0	0																																																																																																																																																				
	437			566	378																																																																																																																																																				
	180			742	0																																																																																																																																																				
Ov				0	0																																																																																																																																																				
In				In																																																																																																																																																					
Ig	0	0	0	Ig	0																																																																																																																																																				
	0			1,838	166																																																																																																																																																				
	0			0	0																																																																																																																																																				
	1,534			122	427																																																																																																																																																				
	477			0	0																																																																																																																																																				
In				In																																																																																																																																																					
In	0	0	0	Ig	213																																																																																																																																																				
	0			2,418	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	2,049			591	771																																																																																																																																																				
	602			0	0																																																																																																																																																				
Ig				Ig																																																																																																																																																					
Ig	526	0	334	Ig	0																																																																																																																																																				
	0			2,110	0																																																																																																																																																				
	0			0	0																																																																																																																																																				
	2,325			0	0																																																																																																																																																				
	406			0	0																																																																																																																																																				
In				In																																																																																																																																																					
<b>210</b> Blue Oaks Blvd & SR 65 SB	<b>211</b> Blue Oaks Blvd & SR 65 NB Off	<b>212</b> Pleasant Grove Blvd & SR 65 NB	<b>213</b> Pleasant Grove Blvd & SR 65 SB																																																																																																																																																						
<table border="1"> <tr> <td>Ig</td> <td>182</td> <td>2,097</td> <td>0</td> <td>Ig</td> <td>1,001</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>1,037</td> <td>1,669</td> </tr> <tr> <td></td> <td>323</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td>Ig</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Permitted Del: 14.3 sec</p>	Ig	182	2,097	0	Ig	1,001		0			0	0		0			1,037	1,669		323			0	0	Ig				Ig		<table border="1"> <tr> <td>In</td> <td>0</td> <td>1,900</td> <td>616</td> <td>Ig</td> <td>199</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>0</td> <td>2,803</td> </tr> <tr> <td></td> <td>635</td> <td></td> <td></td> <td>524</td> <td>0</td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td>Ig</td> <td></td> </tr> </table> <p>N/S Protected LOS: B  E/W Permitted Del: 10.1 sec</p>	In	0	1,900	616	Ig	199		0			0	0		0			0	2,803		635			524	0	Ig				Ig		<table border="1"> <tr> <td>In</td> <td>8</td> <td>4</td> <td>4</td> <td>Ig</td> <td>76</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td>371</td> <td>129</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td>528</td> <td>5</td> </tr> <tr> <td></td> <td>599</td> <td></td> <td></td> <td>1,080</td> <td>290</td> </tr> <tr> <td>Ig</td> <td></td> <td></td> <td></td> <td>Ig</td> <td></td> </tr> </table> <p>N/S Permitted LOS: C  E/W Protected Del: 34.9 sec</p>	In	8	4	4	Ig	76		0			371	129		5			528	5		599			1,080	290	Ig				Ig																																																														
Ig	182	2,097	0	Ig	1,001																																																																																																																																																				
	0			0	0																																																																																																																																																				
	0			1,037	1,669																																																																																																																																																				
	323			0	0																																																																																																																																																				
Ig				Ig																																																																																																																																																					
In	0	1,900	616	Ig	199																																																																																																																																																				
	0			0	0																																																																																																																																																				
	0			0	2,803																																																																																																																																																				
	635			524	0																																																																																																																																																				
Ig				Ig																																																																																																																																																					
In	8	4	4	Ig	76																																																																																																																																																				
	0			371	129																																																																																																																																																				
	5			528	5																																																																																																																																																				
	599			1,080	290																																																																																																																																																				
Ig				Ig																																																																																																																																																					
<b>214</b> Stanford Ranch Rd & SR 65 NB	<b>215</b> Stanford Ranch Rd & SR 65 SB	<b>216</b> Sierra College Blvd & SR 65 SB																																																																																																																																																							



**Figure D13**  
**Cumulative No Project PM Peak Hour Intersection Level of Service**  
**Loomis Intersections**

<p>NP30</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>1,164</td> <td>505</td> <td>In</td> <td>368</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>284</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>1,633</td> </tr> <tr> <td></td> <td>60</td> <td></td> <td></td> <td></td> <td>304</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Permitted LOS: D  E/W Protected Del: 36.7 sec</p>	In	0	1,164	505	In	368		↓	↓	↓		0		0	0	0		284		0	0	0		1,633		60				304		In				In	<p></p> <table border="1"> <tr> <td>In</td> <td>179</td> <td>1,022</td> <td>122</td> <td>In</td> <td>107</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>294</td> </tr> <tr> <td></td> <td>261</td> <td></td> <td></td> <td></td> <td>336</td> </tr> <tr> <td></td> <td>444</td> <td></td> <td></td> <td></td> <td>225</td> </tr> <tr> <td></td> <td>299</td> <td></td> <td></td> <td></td> <td>1,481</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>288</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected Del: 55.9 sec</p>	In	179	1,022	122	In	107		↓	↓	↓		294		261				336		444				225		299				1,481						288		In				In	<p></p> <table border="1"> <tr> <td>In</td> <td>18</td> <td>781</td> <td>346</td> <td>In</td> <td>150</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>4</td> </tr> <tr> <td></td> <td>173</td> <td></td> <td></td> <td></td> <td>15</td> </tr> <tr> <td></td> <td>46</td> <td></td> <td></td> <td></td> <td>2</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td>1,257</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>40</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: D  E/W Split Phase Del: 35.5 sec</p>	In	18	781	346	In	150		↓	↓	↓		4		173				15		46				2		4				1,257						40		In				In	<p></p> <table border="1"> <tr> <td>In</td> <td>101</td> <td>322</td> <td>33</td> <td>In</td> <td>35</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>96</td> </tr> <tr> <td></td> <td>91</td> <td></td> <td></td> <td></td> <td>121</td> </tr> <tr> <td></td> <td>291</td> <td></td> <td></td> <td></td> <td>286</td> </tr> <tr> <td></td> <td>235</td> <td></td> <td></td> <td></td> <td>473</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>237</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 30.3 sec</p>	In	101	322	33	In	35		↓	↓	↓		96		91				121		291				286		235				473						237		In				In						
In	0	1,164	505	In	368																																																																																																																																																																						
	↓	↓	↓		0																																																																																																																																																																						
	0	0	0		284																																																																																																																																																																						
	0	0	0		1,633																																																																																																																																																																						
	60				304																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	179	1,022	122	In	107																																																																																																																																																																						
	↓	↓	↓		294																																																																																																																																																																						
	261				336																																																																																																																																																																						
	444				225																																																																																																																																																																						
	299				1,481																																																																																																																																																																						
					288																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	18	781	346	In	150																																																																																																																																																																						
	↓	↓	↓		4																																																																																																																																																																						
	173				15																																																																																																																																																																						
	46				2																																																																																																																																																																						
	4				1,257																																																																																																																																																																						
					40																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	101	322	33	In	35																																																																																																																																																																						
	↓	↓	↓		96																																																																																																																																																																						
	91				121																																																																																																																																																																						
	291				286																																																																																																																																																																						
	235				473																																																																																																																																																																						
					237																																																																																																																																																																						
	In				In																																																																																																																																																																						
<p><b>301 Sierra College Bl &amp; Brace Rd</b></p>	<p><b>302 Sierra College Bl &amp; Taylor Rd</b></p>	<p><b>304 Sierra College Bl &amp; King Rd</b></p>	<p><b>305 Taylor Rd &amp; King Rd</b></p>																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>4</td> <td>470</td> <td>462</td> <td>In</td> <td>472</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>13</td> <td></td> <td></td> <td></td> <td>139</td> </tr> <tr> <td></td> <td>7</td> <td></td> <td></td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> <td>618</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>180</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: F  E/W Split Phase Del: 80.6 sec</p>	In	4	470	462	In	472		↓	↓	↓		8		13				139		7				8		5				618						180		In				In	<table border="1"> <tr> <td>In</td> <td>132</td> <td>104</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>429</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>261</td> </tr> <tr> <td></td> <td>507</td> <td></td> <td></td> <td></td> <td>112</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: C  E/W Stop Sign Del: 23.6 sec</p>	In	132	104	0	In	0		↓	↓	↓		0		429				0		0				261		507				112						0		In				In	<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>191</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>181</td> </tr> <tr> <td></td> <td>541</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>173</td> <td></td> <td></td> <td></td> <td>205</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: F[257.9]  E/W Uncontrolled Del: 61.9 sec</p>	In	0	0	0	In	0		↓	↓	↓		191		0				181		541				0		173				205						0		In				In	<table border="1"> <tr> <td>In</td> <td>537</td> <td>267</td> <td>47</td> <td>In</td> <td>140</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>49</td> </tr> <tr> <td></td> <td>82</td> <td></td> <td></td> <td></td> <td>70</td> </tr> <tr> <td></td> <td>46</td> <td></td> <td></td> <td></td> <td>291</td> </tr> <tr> <td></td> <td>174</td> <td></td> <td></td> <td></td> <td>563</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>175</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 26.4 sec</p>	In	537	267	47	In	140		↓	↓	↓		49		82				70		46				291		174				563						175		In				In
In	4	470	462	In	472																																																																																																																																																																						
	↓	↓	↓		8																																																																																																																																																																						
	13				139																																																																																																																																																																						
	7				8																																																																																																																																																																						
	5				618																																																																																																																																																																						
					180																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	132	104	0	In	0																																																																																																																																																																						
	↓	↓	↓		0																																																																																																																																																																						
	429				0																																																																																																																																																																						
	0				261																																																																																																																																																																						
	507				112																																																																																																																																																																						
					0																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	0	0	0	In	0																																																																																																																																																																						
	↓	↓	↓		191																																																																																																																																																																						
	0				181																																																																																																																																																																						
	541				0																																																																																																																																																																						
	173				205																																																																																																																																																																						
					0																																																																																																																																																																						
	In				In																																																																																																																																																																						
In	537	267	47	In	140																																																																																																																																																																						
	↓	↓	↓		49																																																																																																																																																																						
	82				70																																																																																																																																																																						
	46				291																																																																																																																																																																						
	174				563																																																																																																																																																																						
					175																																																																																																																																																																						
	In				In																																																																																																																																																																						
<p><b>306 Taylor Rd &amp; Horseshoe Bar</b></p>	<p><b>307 Rocklin Rd &amp; Barton Rd</b></p>	<p><b>308 Barton Rd &amp; Brace Rd</b></p>	<p><b>309 Horseshoe Bar Rd &amp; I-80 WB Ramp</b></p>																																																																																																																																																																								
<table border="1"> <tr> <td>In</td> <td>0</td> <td>450</td> <td>119</td> <td>In</td> <td>409</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>189</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>653</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>292</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Uncontrolled LOS: F[103.3]  E/W Stop Sign Del: 29.8 sec</p>	In	0	450	119	In	409		↓	↓	↓		0		0				189		0				0		0				653						292		In				In																																																																																																																																	
In	0	450	119	In	409																																																																																																																																																																						
	↓	↓	↓		0																																																																																																																																																																						
	0				189																																																																																																																																																																						
	0				0																																																																																																																																																																						
	0				653																																																																																																																																																																						
					292																																																																																																																																																																						
	In				In																																																																																																																																																																						
<p><b>310 Horseshoe Bar Rd &amp; I-80 EB Ramp</b></p>																																																																																																																																																																											

**Figure D14**  
**Cumulative Plus Project PM Peak Hour Intersection Level of Service**  
**Loomis Intersections**

<p>GP30</p> <table border="1"> <tr> <td>In</td> <td>0</td> <td>1,164</td> <td>510</td> <td>In</td> <td>369</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>289</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td>1,625</td> </tr> <tr> <td></td> <td>60</td> <td></td> <td></td> <td></td> <td>299</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Permitted LOS: D  E/W Protected Del: 37 sec</p>		In	0	1,164	510	In	369		↓	↓	↓		0		0	0	0		289		0	0	0		1,625		60				299		In				In	<table border="1"> <tr> <td>In</td> <td>189</td> <td>1,017</td> <td>120</td> <td>In</td> <td>108</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>302</td> </tr> <tr> <td></td> <td>272</td> <td></td> <td></td> <td></td> <td>332</td> </tr> <tr> <td></td> <td>450</td> <td></td> <td></td> <td></td> <td>226</td> </tr> <tr> <td></td> <td>315</td> <td></td> <td></td> <td></td> <td>1,476</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>287</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: E  E/W Protected Del: 56 sec</p>		In	189	1,017	120	In	108		↓	↓	↓		302		272				332		450				226		315				1,476		In				287						In	<table border="1"> <tr> <td>In</td> <td>16</td> <td>783</td> <td>347</td> <td>In</td> <td>151</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>4</td> </tr> <tr> <td></td> <td>187</td> <td></td> <td></td> <td></td> <td>15</td> </tr> <tr> <td></td> <td>21</td> <td></td> <td></td> <td></td> <td>2</td> </tr> <tr> <td></td> <td>4</td> <td></td> <td></td> <td></td> <td>1,246</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>39</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 34.6 sec</p>		In	16	783	347	In	151		↓	↓	↓		4		187				15		21				2		4				1,246						39		In				In	<table border="1"> <tr> <td>In</td> <td>101</td> <td>324</td> <td>33</td> <td>In</td> <td>35</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>96</td> </tr> <tr> <td></td> <td>92</td> <td></td> <td></td> <td></td> <td>121</td> </tr> <tr> <td></td> <td>290</td> <td></td> <td></td> <td></td> <td>288</td> </tr> <tr> <td></td> <td>234</td> <td></td> <td></td> <td></td> <td>473</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>244</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Protected Del: 30.3 sec</p>		In	101	324	33	In	35		↓	↓	↓		96		92				121		290				288		234				473						244		In				In												
In	0	1,164	510	In	369																																																																																																																																																																																
	↓	↓	↓		0																																																																																																																																																																																
	0	0	0		289																																																																																																																																																																																
	0	0	0		1,625																																																																																																																																																																																
	60				299																																																																																																																																																																																
	In				In																																																																																																																																																																																
In	189	1,017	120	In	108																																																																																																																																																																																
	↓	↓	↓		302																																																																																																																																																																																
	272				332																																																																																																																																																																																
	450				226																																																																																																																																																																																
	315				1,476																																																																																																																																																																																
	In				287																																																																																																																																																																																
					In																																																																																																																																																																																
In	16	783	347	In	151																																																																																																																																																																																
	↓	↓	↓		4																																																																																																																																																																																
	187				15																																																																																																																																																																																
	21				2																																																																																																																																																																																
	4				1,246																																																																																																																																																																																
					39																																																																																																																																																																																
	In				In																																																																																																																																																																																
In	101	324	33	In	35																																																																																																																																																																																
	↓	↓	↓		96																																																																																																																																																																																
	92				121																																																																																																																																																																																
	290				288																																																																																																																																																																																
	234				473																																																																																																																																																																																
					244																																																																																																																																																																																
	In				In																																																																																																																																																																																
<b>301</b>	<b>Sierra College Bl &amp; Brace Rd</b>	<b>302</b>	<b>Sierra College Bl &amp; Taylor Rd</b>	<b>304</b>	<b>Sierra College Bl &amp; King Rd</b>	<b>305</b>	<b>Taylor Rd &amp; King Rd</b>																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>4</td> <td>472</td> <td>462</td> <td>In</td> <td>479</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>13</td> <td></td> <td></td> <td></td> <td>139</td> </tr> <tr> <td></td> <td>7</td> <td></td> <td></td> <td></td> <td>8</td> </tr> <tr> <td></td> <td>5</td> <td></td> <td></td> <td></td> <td>616</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>182</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: F  E/W Split Phase Del: 81.9 sec</p>		In	4	472	462	In	479		↓	↓	↓		8		13				139		7				8		5				616						182		In				In	<table border="1"> <tr> <td>In</td> <td>122</td> <td>102</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>421</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>249</td> </tr> <tr> <td></td> <td>508</td> <td></td> <td></td> <td></td> <td>114</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: C  E/W Stop Sign Del: 22.5 sec</p>		In	122	102	0	In	0		↓	↓	↓		0		421				0		0				249		508				114						0		In				In	<table border="1"> <tr> <td>In</td> <td>0</td> <td>0</td> <td>0</td> <td>In</td> <td>0</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>186</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>182</td> </tr> <tr> <td></td> <td>541</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>171</td> <td></td> <td></td> <td></td> <td>214</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>122</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Stop Sign LOS: F[271.3]  E/W Uncontrolled Del: 65.7 sec</p>		In	0	0	0	In	0		↓	↓	↓		186		0				182		541				0		171				214						0						122		In				In	<table border="1"> <tr> <td>In</td> <td>536</td> <td>268</td> <td>47</td> <td>In</td> <td>140</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>49</td> </tr> <tr> <td></td> <td>81</td> <td></td> <td></td> <td></td> <td>70</td> </tr> <tr> <td></td> <td>46</td> <td></td> <td></td> <td></td> <td>293</td> </tr> <tr> <td></td> <td>173</td> <td></td> <td></td> <td></td> <td>568</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>175</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Protected LOS: C  E/W Split Phase Del: 26.4 sec</p>		In	536	268	47	In	140		↓	↓	↓		49		81				70		46				293		173				568						175		In				In
In	4	472	462	In	479																																																																																																																																																																																
	↓	↓	↓		8																																																																																																																																																																																
	13				139																																																																																																																																																																																
	7				8																																																																																																																																																																																
	5				616																																																																																																																																																																																
					182																																																																																																																																																																																
	In				In																																																																																																																																																																																
In	122	102	0	In	0																																																																																																																																																																																
	↓	↓	↓		0																																																																																																																																																																																
	421				0																																																																																																																																																																																
	0				249																																																																																																																																																																																
	508				114																																																																																																																																																																																
					0																																																																																																																																																																																
	In				In																																																																																																																																																																																
In	0	0	0	In	0																																																																																																																																																																																
	↓	↓	↓		186																																																																																																																																																																																
	0				182																																																																																																																																																																																
	541				0																																																																																																																																																																																
	171				214																																																																																																																																																																																
					0																																																																																																																																																																																
					122																																																																																																																																																																																
	In				In																																																																																																																																																																																
In	536	268	47	In	140																																																																																																																																																																																
	↓	↓	↓		49																																																																																																																																																																																
	81				70																																																																																																																																																																																
	46				293																																																																																																																																																																																
	173				568																																																																																																																																																																																
					175																																																																																																																																																																																
	In				In																																																																																																																																																																																
<b>306</b>	<b>Taylor Rd &amp; Horseshoe Bar</b>	<b>307</b>	<b>Rocklin Rd &amp; Barton Rd</b>	<b>308</b>	<b>Barton Rd &amp; Brace Rd</b>	<b>309</b>	<b>Horseshoe Bar Rd &amp; I-80 WB Ramp</b>																																																																																																																																																																														
<table border="1"> <tr> <td>In</td> <td>0</td> <td>449</td> <td>120</td> <td>In</td> <td>423</td> </tr> <tr> <td></td> <td>↓</td> <td>↓</td> <td>↓</td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>193</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td></td> <td></td> <td></td> <td>647</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>301</td> </tr> <tr> <td></td> <td>In</td> <td></td> <td></td> <td></td> <td>In</td> </tr> </table> <p>N/S Uncontrolled LOS: F[107.3]  E/W Stop Sign Del: 31.6 sec</p>		In	0	449	120	In	423		↓	↓	↓		0		0				193		0				0		0				647						301		In				In																																																																																																																																										
In	0	449	120	In	423																																																																																																																																																																																
	↓	↓	↓		0																																																																																																																																																																																
	0				193																																																																																																																																																																																
	0				0																																																																																																																																																																																
	0				647																																																																																																																																																																																
					301																																																																																																																																																																																
	In				In																																																																																																																																																																																
<b>310</b>	<b>Horseshoe Bar Rd &amp; I-80 EB Ramp</b>																																																																																																																																																																																				

**Figure D15**  
**Cumulative No Project PM Peak Hour Intersection Level of Service**  
**Roseville, Lincoln, and Placer County Intersections**

Roseville Intersections																																																																																																																																																			
<table border="1"> <tr><td>In</td><td>238</td><td>1,053</td><td>141</td><td>In</td><td>149</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>277</td><td>535</td><td>749</td><td>671</td><td>1,472</td><td>601</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: F</td><td>N/S</td><td>Protected</td><td>LOS: C</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 1.03</td><td>E/W</td><td>Split Phase</td><td>V/C: 0.74</td></tr> </table>	In	238	1,053	141	In	149	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	277	535	749	671	1,472	601	In	In	In	In	In	In	N/S	Protected	LOS: F	N/S	Protected	LOS: C	E/W	Protected	V/C: 1.03	E/W	Split Phase	V/C: 0.74	<table border="1"> <tr><td>In</td><td>45</td><td>940</td><td>72</td><td>In</td><td>20</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>64</td><td>424</td><td>297</td><td>342</td><td>1,062</td><td>262</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: C</td><td>N/S</td><td>Protected</td><td>LOS: B</td></tr> <tr><td>E/W</td><td>Split Phase</td><td>V/C: 0.74</td><td>E/W</td><td>Split Phase</td><td>V/C: 0.68</td></tr> </table>	In	45	940	72	In	20	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	64	424	297	342	1,062	262	In	In	In	In	In	In	N/S	Protected	LOS: C	N/S	Protected	LOS: B	E/W	Split Phase	V/C: 0.74	E/W	Split Phase	V/C: 0.68	<table border="1"> <tr><td>In</td><td>33</td><td>1,274</td><td>56</td><td>In</td><td>133</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>40</td><td>86</td><td>322</td><td>500</td><td>1,475</td><td>333</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td><td>N/S</td><td>Protected</td><td>LOS: F</td></tr> <tr><td>E/W</td><td>Split Phase</td><td>V/C: 0.68</td><td>E/W</td><td>Protected</td><td>V/C: 1.09</td></tr> </table>	In	33	1,274	56	In	133	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	40	86	322	500	1,475	333	In	In	In	In	In	In	N/S	Protected	LOS: B	N/S	Protected	LOS: F	E/W	Split Phase	V/C: 0.68	E/W	Protected	V/C: 1.09	<table border="1"> <tr><td>In</td><td>44</td><td>977</td><td>399</td><td>In</td><td>194</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>47</td><td>1,465</td><td>788</td><td>711</td><td>937</td><td>1,095</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: F</td><td>N/S</td><td>Protected</td><td>LOS: F</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 1.09</td><td>E/W</td><td>Protected</td><td>V/C: 1.09</td></tr> </table>	In	44	977	399	In	194	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	47	1,465	788	711	937	1,095	In	In	In	In	In	In	N/S	Protected	LOS: F	N/S	Protected	LOS: F	E/W	Protected	V/C: 1.09	E/W	Protected	V/C: 1.09
In	238	1,053	141	In	149																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
277	535	749	671	1,472	601																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: F	N/S	Protected	LOS: C																																																																																																																																														
E/W	Protected	V/C: 1.03	E/W	Split Phase	V/C: 0.74																																																																																																																																														
In	45	940	72	In	20																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
64	424	297	342	1,062	262																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: C	N/S	Protected	LOS: B																																																																																																																																														
E/W	Split Phase	V/C: 0.74	E/W	Split Phase	V/C: 0.68																																																																																																																																														
In	33	1,274	56	In	133																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
40	86	322	500	1,475	333																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: B	N/S	Protected	LOS: F																																																																																																																																														
E/W	Split Phase	V/C: 0.68	E/W	Protected	V/C: 1.09																																																																																																																																														
In	44	977	399	In	194																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
47	1,465	788	711	937	1,095																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: F	N/S	Protected	LOS: F																																																																																																																																														
E/W	Protected	V/C: 1.09	E/W	Protected	V/C: 1.09																																																																																																																																														
<b>401 Pleasant Grove &amp; Fairway</b>	<b>402 Stanford Ranch &amp; Fairway</b>	<b>403 Stanford Ranch &amp; Five Star</b>	<b>404 Pleasant Grove &amp; Roseville Pkwy</b>																																																																																																																																																
<table border="1"> <tr><td>In</td><td>378</td><td>843</td><td>1,008</td><td>In</td><td>607</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>669</td><td>1,702</td><td>875</td><td>591</td><td>772</td><td>34</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: E</td><td>N/S</td><td>Protected</td><td>LOS: D</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.99</td><td>E/W</td><td>Protected</td><td>V/C: 0.82</td></tr> </table>	In	378	843	1,008	In	607	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	669	1,702	875	591	772	34	In	In	In	In	In	In	N/S	Protected	LOS: E	N/S	Protected	LOS: D	E/W	Protected	V/C: 0.99	E/W	Protected	V/C: 0.82	<table border="1"> <tr><td>In</td><td>166</td><td>314</td><td>457</td><td>In</td><td>583</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>233</td><td>2,340</td><td>288</td><td>302</td><td>333</td><td>185</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td><td>N/S</td><td>Protected</td><td>LOS: F</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.82</td><td>E/W</td><td>Protected</td><td>V/C: 1.01</td></tr> </table>	In	166	314	457	In	583	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	233	2,340	288	302	333	185	In	In	In	In	In	In	N/S	Protected	LOS: D	N/S	Protected	LOS: F	E/W	Protected	V/C: 0.82	E/W	Protected	V/C: 1.01	<table border="1"> <tr><td>In</td><td>403</td><td>268</td><td>170</td><td>In</td><td>87</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>150</td><td>2,237</td><td>706</td><td>548</td><td>156</td><td>398</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: F</td><td>N/S</td><td>Protected</td><td>LOS: E</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 1.01</td><td>E/W</td><td>Permitted</td><td>V/C: 0.91</td></tr> </table>	In	403	268	170	In	87	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	150	2,237	706	548	156	398	In	In	In	In	In	In	N/S	Protected	LOS: F	N/S	Protected	LOS: E	E/W	Protected	V/C: 1.01	E/W	Permitted	V/C: 0.91	<table border="1"> <tr><td>In</td><td>367</td><td>1,555</td><td>1</td><td>In</td><td>3</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>737</td><td>2</td><td>179</td><td>209</td><td>1,483</td><td>3</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: E</td><td>N/S</td><td>Protected</td><td>LOS: E</td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.91</td><td>E/W</td><td>Permitted</td><td>V/C: 0.91</td></tr> </table>	In	367	1,555	1	In	3	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	737	2	179	209	1,483	3	In	In	In	In	In	In	N/S	Protected	LOS: E	N/S	Protected	LOS: E	E/W	Permitted	V/C: 0.91	E/W	Permitted	V/C: 0.91
In	378	843	1,008	In	607																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
669	1,702	875	591	772	34																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: E	N/S	Protected	LOS: D																																																																																																																																														
E/W	Protected	V/C: 0.99	E/W	Protected	V/C: 0.82																																																																																																																																														
In	166	314	457	In	583																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
233	2,340	288	302	333	185																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: D	N/S	Protected	LOS: F																																																																																																																																														
E/W	Protected	V/C: 0.82	E/W	Protected	V/C: 1.01																																																																																																																																														
In	403	268	170	In	87																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
150	2,237	706	548	156	398																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: F	N/S	Protected	LOS: E																																																																																																																																														
E/W	Protected	V/C: 1.01	E/W	Permitted	V/C: 0.91																																																																																																																																														
In	367	1,555	1	In	3																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
737	2	179	209	1,483	3																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: E	N/S	Protected	LOS: E																																																																																																																																														
E/W	Permitted	V/C: 0.91	E/W	Permitted	V/C: 0.91																																																																																																																																														
<b>405 Galleria &amp; Roseville Pkwy</b>	<b>406 Roseville Parkway &amp; Taylor</b>	<b>407 Roseville Parkway &amp; N. Sunrise</b>	<b>408 Sierra College &amp; Secret Ravine</b>																																																																																																																																																
Lincoln and Placer County Intersections																																																																																																																																																			
<table border="1"> <tr><td>Ov</td><td>418</td><td>228</td><td>57</td><td>Ov</td><td>92</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>647</td><td>763</td><td>3</td><td>12</td><td>950</td><td>156</td></tr> <tr><td>Ov</td><td>Ov</td><td>Ov</td><td>Ov</td><td>Ov</td><td>Ov</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td><td>N/S</td><td>Protected</td><td>LOS: B</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.832</td><td>E/W</td><td>Protected</td><td>V/C: 0.673</td></tr> </table>	Ov	418	228	57	Ov	92	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	647	763	3	12	950	156	Ov	Ov	Ov	Ov	Ov	Ov	N/S	Protected	LOS: D	N/S	Protected	LOS: B	E/W	Protected	V/C: 0.832	E/W	Protected	V/C: 0.673	<table border="1"> <tr><td>In</td><td>25</td><td>667</td><td>0</td><td>In</td><td>0</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>21</td><td>0</td><td>252</td><td>159</td><td>1,413</td><td>0</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: B</td><td>N/S</td><td>Protected</td><td>LOS: D</td></tr> <tr><td>E/W</td><td>Protected</td><td>V/C: 0.673</td><td>E/W</td><td>Permitted</td><td>V/C: 0.885</td></tr> </table>	In	25	667	0	In	0	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	21	0	252	159	1,413	0	In	In	In	In	In	In	N/S	Protected	LOS: B	N/S	Protected	LOS: D	E/W	Protected	V/C: 0.673	E/W	Permitted	V/C: 0.885	<table border="1"> <tr><td>In</td><td>0</td><td>984</td><td>196</td><td>Ov</td><td>247</td></tr> <tr><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td><td>↓ ↓ ↓ ↓ ↓</td></tr> <tr><td>0</td><td>0</td><td>0</td><td>0</td><td>1,813</td><td>45</td></tr> <tr><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td><td>In</td></tr> <tr><td>N/S</td><td>Protected</td><td>LOS: D</td><td>N/S</td><td>Protected</td><td>LOS: D</td></tr> <tr><td>E/W</td><td>Permitted</td><td>V/C: 0.885</td><td>E/W</td><td>Permitted</td><td>V/C: 0.885</td></tr> </table>	In	0	984	196	Ov	247	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	0	0	0	0	1,813	45	In	In	In	In	In	In	N/S	Protected	LOS: D	N/S	Protected	LOS: D	E/W	Permitted	V/C: 0.885	E/W	Permitted	V/C: 0.885																																					
Ov	418	228	57	Ov	92																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
647	763	3	12	950	156																																																																																																																																														
Ov	Ov	Ov	Ov	Ov	Ov																																																																																																																																														
N/S	Protected	LOS: D	N/S	Protected	LOS: B																																																																																																																																														
E/W	Protected	V/C: 0.832	E/W	Protected	V/C: 0.673																																																																																																																																														
In	25	667	0	In	0																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
21	0	252	159	1,413	0																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: B	N/S	Protected	LOS: D																																																																																																																																														
E/W	Protected	V/C: 0.673	E/W	Permitted	V/C: 0.885																																																																																																																																														
In	0	984	196	Ov	247																																																																																																																																														
↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓	↓ ↓ ↓ ↓ ↓																																																																																																																																														
0	0	0	0	1,813	45																																																																																																																																														
In	In	In	In	In	In																																																																																																																																														
N/S	Protected	LOS: D	N/S	Protected	LOS: D																																																																																																																																														
E/W	Permitted	V/C: 0.885	E/W	Permitted	V/C: 0.885																																																																																																																																														
<b>501 E Lincoln Pkwy &amp; Twelve Bridges</b>	<b>502 Sierra College &amp; Twelve Bridges</b>	<b>601 Sierra College &amp; English Colony</b>																																																																																																																																																	

**Figure D16**  
**Cumulative Plus Project PM Peak Hour Intersection Level of Service**  
**Roseville, Lincoln, and Placer County Intersections**

Roseville Intersections			
401	Pleasant Grove & Fairway	402	Stanford Ranch & Fairway
403	Stanford Ranch & Five Star	404	Pleasant Grove & Roseville Pkwy
405	Galleria & Roseville Pkwy	406	Roseville Parkway & Taylor
407	Roseville Parkway & N. Sunrise	408	Sierra College & Secret Ravine
Lincoln and Placer County Intersections			
501	E Lincoln Pkwy & Twelve Bridges	502	Sierra College & Twelve Bridges
601	Sierra College & English Colony		

**INTERSECTION LOS WORKSHEETS  
EXISTING CONDITIONS**

---



Existing PM                      Fri May 22, 2009 09:51:52                      Page 2-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----

Impact Analysis Report  
 Level Of Service

Intersection	Base Del/ LOS Veh	V/ C	Future Del/ LOS Veh	V/ C	Change in
# 1 Granite Dr & Rocklin Rd	B xxxxx	0.633	B xxxxx	0.633	+ 0.000 V/C
# 2 Granite Dr & Sierra College Bl	A xxxxx	0.560	A xxxxx	0.560	+ 0.000 V/C
# 3 Granite Dr & Sierra Meadows	A xxxxx	0.552	A xxxxx	0.552	+ 0.000 V/C
# 4 Pacific St & Del Mar/ Domingue	A xxxxx	0.569	A xxxxx	0.569	+ 0.000 V/C
# 5 Pacific St & Farron St	A xxxxx	0.515	A xxxxx	0.515	+ 0.000 V/C
# 6 Pacific St & Midas Ave	A xxxxx	0.500	A xxxxx	0.500	+ 0.000 V/C
# 7 Pacific St & Rocklin Rd	B xxxxx	0.688	B xxxxx	0.688	+ 0.000 V/C
# 8 Pacific St & Sierra Meadows	A xxxxx	0.411	A xxxxx	0.411	+ 0.000 V/C
# 9 Pacific St & Woodside Dr	A xxxxx	0.505	A xxxxx	0.505	+ 0.000 V/C
# 10 Rocklin Rd & Aguilar Rd	A xxxxx	0.520	A xxxxx	0.520	+ 0.000 V/C
# 11 Rocklin Rd & El Don Dr	B xxxxx	0.636	B xxxxx	0.636	+ 0.000 V/C
# 12 Rocklin Rd & Fire Station No 1	A xxxxx	0.243	A xxxxx	0.243	+ 0.000 V/C
# 13 Rocklin Rd & Havenhurst Cir	A xxxxx	0.482	A xxxxx	0.482	+ 0.000 V/C
# 14 Rocklin Rd & Sierra College Bl	B xxxxx	0.614	B xxxxx	0.614	+ 0.000 V/C
# 15 Rocklin Rd & South Grove St	A xxxxx	0.317	A xxxxx	0.317	+ 0.000 V/C
# 16 Sierra College Bl & El Don Dr	A xxxxx	0.387	A xxxxx	0.387	+ 0.000 V/C
# 17 Sierra College Bl & Nightwatch	B xxxxx	0.651	B xxxxx	0.651	+ 0.000 V/C
# 18 Sierra College Bl & Scarborough	A xxxxx	0.357	A xxxxx	0.357	+ 0.000 V/C
# 19 Sierra College Bl & Southside	B xxxxx	0.650	B xxxxx	0.650	+ 0.000 V/C
# 20 Sunset Bl & Pacific St	B xxxxx	0.635	B xxxxx	0.635	+ 0.000 V/C
# 21 Sunset Bl & Springview Dr	D xxxxx	0.824	D xxxxx	0.824	+ 0.000 V/C
# 22 Sunset Bl & Topaz Ave	A xxxxx	0.560	A xxxxx	0.560	+ 0.000 V/C
# 23 Sunset Bl & Whitney Bl	D xxxxx	0.805	D xxxxx	0.805	+ 0.000 V/C

Existing PM                      Fri May 22, 2009 09:51:52                      Page 2-2  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----

Intersection	Base Del/ LOS Veh	V/ C	Future Del/ LOS Veh	V/ C	Change in
#101 Blue Oaks Bl & Lonetree	A xxxxx	0.478	A xxxxx	0.478	+ 0.000 V/C
#102 Blue Oaks Bl & Market Place	A xxxxx	0.244	A xxxxx	0.244	+ 0.000 V/C
#103 Blue Oaks Bl & Van Buren Way	A xxxxx	0.287	A xxxxx	0.287	+ 0.000 V/C
#104 Five Star & Destiny Dr	A xxxxx	0.194	A xxxxx	0.194	+ 0.000 V/C
#105 Lonetree Bl & Adams Dr	A xxxxx	0.308	A xxxxx	0.308	+ 0.000 V/C
#106 Lonetree Bl & Atherton Rd	A xxxxx	0.272	A xxxxx	0.272	+ 0.000 V/C
#107 Lonetree Bl & Grand Canyon Dr	A xxxxx	0.469	A xxxxx	0.469	+ 0.000 V/C
#108 Lonetree Bl & Redwood Dr	A xxxxx	0.442	A xxxxx	0.442	+ 0.000 V/C
#109 Lonetree Bl & West Oaks Bl	A xxxxx	0.514	A xxxxx	0.514	+ 0.000 V/C
#110 Park Dr & Blaydon Rd	A xxxxx	0.197	A xxxxx	0.197	+ 0.000 V/C
#111 Park Dr & Quarry Way	A xxxxx	0.391	A xxxxx	0.391	+ 0.000 V/C
#112 Park Dr & Farrier Rd	A xxxxx	0.520	A xxxxx	0.520	+ 0.000 V/C
#113 Park Dr & King Pine Dr	A xxxxx	0.368	A xxxxx	0.368	+ 0.000 V/C
#114 Park Dr & Shelton	A xxxxx	0.274	A xxxxx	0.274	+ 0.000 V/C
#115 Park Dr & Victory Lane	A xxxxx	0.318	A xxxxx	0.318	+ 0.000 V/C
#116 Park Dr & Wykford Bl	A xxxxx	0.320	A xxxxx	0.320	+ 0.000 V/C
#117 Park Dr & Twin Oaks/ Boardwalk	A xxxxx	0.362	A xxxxx	0.362	+ 0.000 V/C
#118 Park Dr & Safeway	A xxxxx	0.514	A xxxxx	0.514	+ 0.000 V/C
#119 South Whitney & Five Star Bl	A xxxxx	0.471	A xxxxx	0.471	+ 0.000 V/C
#120 Spring Creek Dr & Broken Rail	A xxxxx	0.031	A xxxxx	0.031	+ 0.000 V/C
#121 Stanford Ranch Rd & Cobbleston	A xxxxx	0.325	A xxxxx	0.325	+ 0.000 V/C
#122 Stanford Ranch Rd & Darby Rd	A xxxxx	0.293	A xxxxx	0.293	+ 0.000 V/C
#123 Stanford Ranch Rd & Park Dr	A xxxxx	0.573	A xxxxx	0.573	+ 0.000 V/C
#124 Stanford Ranch Rd & Plaza	A xxxxx	0.371	A xxxxx	0.371	+ 0.000 V/C
#125 Stanford Ranch Rd & Stoney Dr	A xxxxx	0.439	A xxxxx	0.439	+ 0.000 V/C

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Intersection	Base			Future			Change in
	Del/ LOS	V/ Veh	C	Del/ LOS	V/ Veh	C	
#126 Stanford Ranch Rd & Victory Ln	A	xxxxx	0.263	A	xxxxx	0.263	+ 0.000 V/C
#127 Stanford Ranch Rd & West Oaks	A	xxxxx	0.228	A	xxxxx	0.228	+ 0.000 V/C
#128 Sunset Bl & Atherton	A	xxxxx	0.337	A	xxxxx	0.337	+ 0.000 V/C
#129 Sunset Bl & Blue Oaks Bl	B	xxxxx	0.681	B	xxxxx	0.681	+ 0.000 V/C
#130 Sunset Bl & Fairway Dr	A	xxxxx	0.480	A	xxxxx	0.480	+ 0.000 V/C
#131 Sunset Bl & Little Rock	A	xxxxx	0.444	A	xxxxx	0.444	+ 0.000 V/C
#132 Sunset Bl & Park Dr	D	xxxxx	0.866	D	xxxxx	0.866	+ 0.000 V/C
#133 Sunset Bl & Pebble Creek	A	xxxxx	0.539	A	xxxxx	0.539	+ 0.000 V/C
#134 Sunset Bl & Stanford Ranch Rd	C	xxxxx	0.793	C	xxxxx	0.793	+ 0.000 V/C
#135 Sunset Bl & West Oaks Bl	A	xxxxx	0.349	A	xxxxx	0.349	+ 0.000 V/C
#136 W Stanford Ranch Rd & Sunset B	A	xxxxx	0.467	A	xxxxx	0.467	+ 0.000 V/C
#137 W Stanford Ranch Rd & Wildcat	A	xxxxx	0.455	A	xxxxx	0.455	+ 0.000 V/C
#138 Whitney Ranch Pkwy & Bridlewoo	A	xxxxx	0.014	A	xxxxx	0.014	+ 0.000 V/C
#139 Whitney Ranch Pkwy & Painted P	A	xxxxx	0.007	A	xxxxx	0.007	+ 0.000 V/C
#140 Whitney Ranch Pkwy & Spring Cr	A	xxxxx	0.061	A	xxxxx	0.061	+ 0.000 V/C
#141 Wildcat Bl & Bridlewood Dr	A	xxxxx	0.264	A	xxxxx	0.264	+ 0.000 V/C
#142 Wildcat Bl & Whitney Ranch Pkw	A	xxxxx	0.179	A	xxxxx	0.179	+ 0.000 V/C
#143 Wildcat Bl & S High School Ent	A	xxxxx	0.173	A	xxxxx	0.173	+ 0.000 V/C
#144 Wildcat Bl & N High School Ent	A	xxxxx	0.167	A	xxxxx	0.167	+ 0.000 V/C
#145 Wildcat Bl & Ranch View Dr	A	xxxxx	0.180	A	xxxxx	0.180	+ 0.000 V/C
#201 Rocklin Rd & I-80 EB	C	26.1	0.746	C	26.1	0.746	+ 0.000 D/V
#202 Rocklin Rd & I-80 WB	C	21.8	0.681	C	21.8	0.681	+ 0.000 D/V
#203 Sierra College Bl & I-80 WB	B	19.2	0.616	B	19.2	0.616	+ 0.000 D/V
#204 Sierra College Bl & I-80 EB	C	20.6	0.478	C	20.6	0.478	+ 0.000 D/V

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Intersection	Base			Future			Change in
	Del/ LOS	V/ Veh	C	Del/ LOS	V/ Veh	C	
#205 SR 65 & Sunset Blvd	D	39.4	0.954	D	39.4	0.954	+ 0.000 D/V
#208 Whitney Ranch Pkwy & SR 65 SB		0.0	0.000		0.0	0.000	+ 0.000 D/V
#209 Whitney Ranch Pkwy & SR 65 NB	B	14.3	0.777	B	14.3	0.777	+ 0.000 D/V
#210 Blue Oaks Blvd & SR 65 SB	C	24.4	0.405	C	24.4	0.405	+ 0.000 D/V
#211 Blue Oaks Blvd & SR 65 NB Off	A	7.3	0.357	A	7.3	0.357	+ 0.000 D/V
#212 Pleasant Grove Blvd & SR 65 NB	C	27.2	0.887	C	27.2	0.887	+ 0.000 D/V
#213 Pleasant Grove Blvd & SR 65 SB	B	19.8	0.910	B	19.8	0.910	+ 0.000 D/V
#214 Stanford Ranch Rd & SR 65 NB	C	26.6	0.965	C	26.6	0.965	+ 0.000 D/V
#215 Stanford Ranch Rd & SR 65 SB	C	34.1	1.041	C	34.1	1.041	+ 0.000 D/V
#216 Sierra College Blvd & SR 193	F	53.5	0.944	F	53.5	0.944	+ 0.000 D/V
#301 Sierra College Bl & Brace Rd	B	16.3	0.362	B	16.3	0.362	+ 0.000 D/V
#302 Sierra College Bl & Taylor Rd	C	29.8	0.569	C	29.8	0.569	+ 0.000 D/V
#304 Sierra College Bl & King Rd	B	16.1	0.455	B	16.1	0.455	+ 0.000 D/V
#305 Taylor Rd & King Rd	C	30.5	0.586	C	30.5	0.586	+ 0.000 D/V
#306 Taylor Rd & Horseshoe Bar	D	38.3	0.844	D	38.3	0.844	+ 0.000 D/V
#501 E Lincoln Pkwy & Twelve Bridge	A	xxxxx	0.461	A	xxxxx	0.461	+ 0.000 V/C
#502 Sierra College & Twelve Bridge	B	12.0	0.085	B	12.0	0.085	+ 0.000 D/V
#601 Sierra College & English Colon	B	13.0	0.107	B	13.0	0.107	+ 0.000 D/V



City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #1 Granite Dr & Rocklin Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.633  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 62 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #2 Granite Dr & Sierra College Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.560  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 52 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #3 Granite Dr & Sierra Meadows

Cycle (sec): 100 Critical Vol./Cap.(X): 0.552
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 51 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #4 Pacific St & Del Mar/ Dominguez

Cycle (sec): 100 Critical Vol./Cap.(X): 0.569
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 53 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 7-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #5 Pacific St & Farron St  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.515  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 47 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	1	0	1	1	0	1

Volume Module:  
Base Vol: 102 856 30 104 925 44 27 12 61 70 6 47  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 102 856 30 104 925 44 27 12 61 70 6 47  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 102 856 30 104 925 44 27 12 61 70 6 47  
Reduc Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 102 856 30 104 925 44 27 12 61 70 6 47  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 102 856 30 104 925 44 27 12 61 70 6 47

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.93 0.07 1.00 2.00 1.00 1.00 0.16 0.84 1.00 0.11 0.89  
Final Sat.: 1375 2657 93 1375 2750 1375 1375 226 1149 1375 156 1219

Capacity Analysis Module:  
Vol/Sat: 0.07 0.32 0.32 0.08 0.34 0.03 0.02 0.05 0.05 0.05 0.04 0.04  
Crit Volume: 102 463 73 70  
Crit Moves: \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 8-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #6 Pacific St & Midas Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.500  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 46 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	1	0	1	1	0	1

Volume Module:  
Base Vol: 224 489 16 6 580 227 134 30 142 8 32 4  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 224 489 16 6 580 227 134 30 142 8 32 4  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 224 489 16 6 580 227 134 30 142 8 32 4  
Reduc Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 224 489 16 6 580 227 134 30 142 8 32 4  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 224 489 16 6 580 227 134 30 142 8 32 4

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.94 0.06 1.00 2.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Final Sat.: 1375 2663 87 1375 2750 1375 1375 1375 1375 1375 1375 1375

Capacity Analysis Module:  
Vol/Sat: 0.16 0.18 0.18 0.00 0.21 0.17 0.10 0.02 0.10 0.01 0.02 0.00  
Crit Volume: 224 290 142 32  
Crit Moves: \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 9-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #7 Pacific St & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.688  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 73 Level Of Service: B  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	0	1	1	0	1	0

Volume Module:  
Base Vol: 40 474 459 140 505 28 27 91 16 468 120 204  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 40 474 459 140 505 28 27 91 16 468 120 204  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 40 474 459 140 505 28 27 91 16 468 120 204  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 40 474 459 140 505 28 27 91 16 468 120 204  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 40 474 459 140 505 28 27 91 16 468 120 204

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 1.89 0.11 1.00 1.70 0.30 1.59 0.41 1.00  
Final Sat.: 1375 2750 1375 1375 2606 144 1375 2339 411 2189 561 1375

Capacity Analysis Module:  
Vol/Sat: 0.03 0.17 0.33 0.10 0.19 0.19 0.02 0.04 0.04 0.21 0.21 0.15  
Crit Volume: 459 140 54 294  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 10-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #8 Pacific St & Sierra Meadows  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.411  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Ovl			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	1	0	1	0	1

Volume Module:  
Base Vol: 25 517 102 85 578 10 6 19 26 122 44 81  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 25 517 102 85 578 10 6 19 26 122 44 81  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 25 517 102 85 578 10 6 19 26 122 44 81  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 25 517 102 85 578 10 6 19 26 122 44 81  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 25 517 102 85 578 10 6 19 26 122 44 81

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.67 0.33 1.00 1.97 0.03 1.00 0.42 0.58 1.00 0.35 0.65  
Final Sat.: 1375 2297 453 1375 2703 47 1375 581 794 1375 484 891

Capacity Analysis Module:  
Vol/Sat: 0.02 0.23 0.23 0.06 0.21 0.21 0.00 0.03 0.03 0.09 0.09 0.09  
Crit Volume: 310 85 45 125  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Existing PM Page 11-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #9 Pacific St & Woodside Dr  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.505  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 46 Level Of Service: A  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 0 1  
 -----  
 Volume Module:  
 Base Vol: 0 1170 136 50 779 0 0 0 84 0 43  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 0 1170 136 50 779 0 0 0 84 0 43  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 0 1170 136 50 779 0 0 0 84 0 43  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 0 1170 136 50 779 0 0 0 84 0 43  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 0 1170 136 50 779 0 0 0 84 0 43  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
 Final Sat.: 0 2850 1425 1425 2850 0 0 0 1425 0 1425  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.00 0.41 0.10 0.04 0.27 0.00 0.00 0.00 0.06 0.00 0.03  
 Crit Volume: 585 50 84  
 Crit Moves: \*\*\*\* \*\*

Existing PM Page 12-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #10 Rocklin Rd & Aguilar Rd  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.520  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 48 Level Of Service: A  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 1 0 0 0 1 0 0 0 0 0 1 0 1 1 0 1 0 2 0 0  
 -----  
 Volume Module:  
 Base Vol: 95 0 17 0 0 0 70 1098 111 21 1153 0  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 95 0 17 0 0 0 70 1098 111 21 1153 0  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 95 0 17 0 0 0 70 1098 111 21 1153 0  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 95 0 17 0 0 0 70 1098 111 21 1153 0  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 95 0 17 0 0 0 70 1098 111 21 1153 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 1.00 1.82 0.18 1.00 2.00 0.00  
 Final Sat.: 1425 0 1425 0 0 0 1425 2588 262 1425 2850 0  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.07 0.00 0.01 0.00 0.00 0.00 0.05 0.42 0.42 0.01 0.40 0.00  
 Crit Volume: 95 70 577  
 Crit Moves: \*\*\*\* \*\*

Existing PM Fri May 22, 2009 09:51:52 Page 13-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #11 Rocklin Rd & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.636  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 63 Level Of Service: B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Ovl			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	0	1	0	1	1	0	1

Volume Module:

Base Vol:	128	5	10	74	8	407	252	743	170	13	647	32
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	128	5	10	74	8	407	252	743	170	13	647	32
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	128	5	10	74	8	407	252	743	170	13	647	32
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	128	5	10	74	8	407	252	743	170	13	647	32
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	128	5	10	74	8	407	252	743	170	13	647	32

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.33	0.67	0.90	0.10	1.00	1.00	1.63	0.37	1.00	1.91	0.09
Final Sat.:	1375	458	917	1241	134	1375	1375	2238	512	1375	2620	130

Capacity Analysis Module:

Vol/Sat:	0.09	0.01	0.01	0.06	0.06	0.30	0.18	0.33	0.33	0.01	0.25	0.25
Crit Volume:	128			407		0				340		
Crit Moves:	****			****		****				****		

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 14-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #12 Rocklin Rd & Fire Station No 1  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.243  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 30 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	0	0	1	0	0	1

Volume Module:

Base Vol:	0	0	0	0	0	0	0	730	0	0	728	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	0	0	0	0	0	0	730	0	0	728	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	0	0	0	0	0	730	0	0	728	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	0	0	0	0	0	730	0	0	728	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	0	0	0	0	0	0	730	0	0	728	0

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	1.00	0.00	0.00	1.00	0.00	1.00	2.00	0.00	1.00	2.00	0.00
Final Sat.:	0	1500	0	0	1500	0	1500	3000	0	1500	3000	0

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.24	0.00	0.00	0.24	0.00
Crit Volume:	0			0				365		0		
Crit Moves:								****		****		

\*\*\*\*\*

Existing PM Page 15-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #13 Rocklin Rd & Havenhurst Cir  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.482  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 44 Level Of Service: A  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Split Phase Split Phase Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 0 0 1 0 0 0 1 0 0 1 0 1 0  
 -----  
 Volume Module:  
 Base Vol: 15 0 4 195 1 126 113 709 27 9 543 126  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 15 0 4 195 1 126 113 709 27 9 543 126  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 15 0 4 195 1 126 113 709 27 9 543 126  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 15 0 4 195 1 126 113 709 27 9 543 126  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 15 0 4 195 1 126 113 709 27 9 543 126  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 0.79 0.00 0.21 0.99 0.01 1.00 1.00 2.89 0.11 1.00 1.62 0.38  
 Final Sat.: 1086 0 289 1368 7 1375 1375 3974 151 1375 2232 518  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.01 0.00 0.01 0.14 0.14 0.09 0.08 0.18 0.18 0.01 0.24 0.24  
 Crit Volume: 19 196 113 335  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

Existing PM Page 16-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #14 Rocklin Rd & Sierra College Bl  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.614  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 59 Level Of Service: B  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected Protected  
 Rights: Include Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 1 1 0  
 -----  
 Volume Module:  
 Base Vol: 372 473 56 55 250 101 106 231 500 63 166 25  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 372 473 56 55 250 101 106 231 500 63 166 25  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 372 473 56 55 250 101 106 231 500 63 166 25  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 372 473 56 55 250 101 106 231 500 63 166 25  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 372 473 56 55 250 101 106 231 500 63 166 25  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 1.00 1.79 0.21 1.00 1.42 0.58 1.00 1.00 1.00 1.00 0.87 0.13  
 Final Sat.: 1375 2459 291 1375 1959 791 1375 1375 1375 1375 1195 180  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.27 0.19 0.19 0.04 0.13 0.13 0.08 0.17 0.36 0.05 0.14 0.14  
 Crit Volume: 372 176 106  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 17-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #15 Rocklin Rd & South Grove St  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.317  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	0	0	0	0	0	1	1	0	0

Volume Module:  
Base Vol: 34 0 42 0 0 0 0 654 34 66 751 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 34 0 42 0 0 0 0 654 34 66 751 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 34 0 42 0 0 0 0 654 34 66 751 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 34 0 42 0 0 0 0 654 34 66 751 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 34 0 42 0 0 0 0 654 34 66 751 0

Saturation Flow Module:  
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 1.90 0.10 1.00 2.00 0.00  
Final Sat.: 1425 0 1425 0 0 0 0 2709 141 1425 2850 0

Capacity Analysis Module:  
Vol/Sat: 0.02 0.00 0.03 0.00 0.00 0.00 0.00 0.24 0.24 0.05 0.26 0.00  
Crit Volume: 42 0 344 66  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 18-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #16 Sierra College Bl & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.387  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	0	1	0	0	1

Volume Module:  
Base Vol: 42 803 10 48 778 48 23 0 27 6 0 22  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 42 803 10 48 778 48 23 0 27 6 0 22  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 42 803 10 48 778 48 23 0 27 6 0 22  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 42 803 10 48 778 48 23 0 27 6 0 22  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 42 803 10 48 778 48 23 0 27 6 0 22

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.98 0.02 1.00 2.83 0.17 0.46 0.00 0.54 0.21 0.00 0.79  
Final Sat.: 1375 2716 34 1375 3885 240 633 0 743 295 0 1080

Capacity Analysis Module:  
Vol/Sat: 0.03 0.30 0.30 0.03 0.20 0.20 0.04 0.00 0.04 0.02 0.00 0.02  
Crit Volume: 407 48 50 28  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*



City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #17 Sierra College Bl & Nightwatch  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.651  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 65 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 4 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 4 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 4 rows (Vol/Sat, Crit Volume, Crit Moves).

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #18 Sierra College Bl & Scarborough  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.357  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 35 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 4 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 4 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 4 rows (Vol/Sat, Crit Volume, Crit Moves).

Existing PM Fri May 22, 2009 09:51:52 Page 21-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #19 Sierra College Bl & Southside Ranch  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.650  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 65 Level Of Service: B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	2	1	0	0	1	0	0

Volume Module:

Base Vol:	29	836	1	4	717	30	23	0	26	1	0	3
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	29	836	1	4	717	30	23	0	26	1	0	3
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	29	836	1	4	717	30	23	0	26	1	0	3
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	29	836	1	4	717	30	23	0	26	1	0	3
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	29	836	1	4	717	30	23	0	26	1	0	3

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.99	0.01	1.00	2.88	0.12	0.47	0.00	0.53	0.25	0.00	0.75
Final Sat.:	1375	1373	2	1375	3959	166	645	0	730	344	0	1031

Capacity Analysis Module:

Vol/Sat:	0.02	0.61	0.61	0.00	0.18	0.18	0.04	0.00	0.04	0.00	0.00	0.00
Crit Volume:		837	4					49			4	
Crit Moves:	****	****						****			****	

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 22-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #20 Sunset Bl & Pacific St  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.635  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 62 Level Of Service: B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Ignore			Ignore			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	1	1	0	2	0	1	1	1	0	2

Volume Module:

Base Vol:	699	539	22	78	504	647	435	106	316	38	107	54
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	699	539	22	78	504	647	435	106	316	38	107	54
User Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Volume:	699	539	22	78	504	0	435	106	0	38	107	54
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	699	539	22	78	504	0	435	106	0	38	107	54
PCE Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	1.00
FinalVolume:	699	539	22	78	504	0	435	106	0	38	107	54

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2.00	1.92	0.08	1.00	2.00	1.00	2.00	1.00	1.00	1.00	2.00	1.00
Final Sat.:	2750	2642	108	1375	2750	1375	2750	1375	1375	1375	2750	1375

Capacity Analysis Module:

Vol/Sat:	0.25	0.20	0.20	0.06	0.18	0.00	0.16	0.08	0.00	0.03	0.04	0.04
Crit Volume:	350			252			217					54
Crit Moves:	****			****			****					****

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 23-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #21 Sunset Bl & Springview Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.824  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 130 Level Of Service: D

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Ignore			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	1	0	0	1	0	1	0	1	1	0	1

Volume Module:

Base Vol:	62	28	90	57	32	325	306	751	96	220	1240	56
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	62	28	90	57	32	325	306	751	96	220	1240	56
User Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	62	28	90	57	32	0	306	751	96	220	1240	56
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	62	28	90	57	32	0	306	751	96	220	1240	56
PCE Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	62	28	90	57	32	0	306	751	96	220	1240	56

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.69	0.31	1.00	0.64	0.36	0.00	1.00	1.77	0.23	1.00	1.91	0.09
Final Sat.:	947	428	1375	881	494	0	1375	2438	312	1375	2631	119

Capacity Analysis Module:

Vol/Sat:	0.07	0.07	0.07	0.06	0.06	0.00	0.22	0.31	0.31	0.16	0.47	0.47
Crit Volume:	90		89		306							648
Crit Moves:	****		****		****							****

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 24-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #22 Sunset Bl & Topaz Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.560  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 42 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	0	0	1	1	0	1

Volume Module:

Base Vol:	25	15	26	12	13	69	85	862	23	68	1120	67
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	25	15	26	12	13	69	85	862	23	68	1120	67
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	25	15	26	12	13	69	85	862	23	68	1120	67
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	25	15	26	12	13	69	85	862	23	68	1120	67
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	25	15	26	12	13	69	85	862	23	68	1120	67

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.38	0.23	0.39	0.13	0.14	0.73	1.00	1.95	0.05	1.00	1.89	0.11
Final Sat.:	540	324	561	182	197	1046	1425	2776	74	1425	2689	161

Capacity Analysis Module:

Vol/Sat:	0.05	0.05	0.05	0.07	0.07	0.07	0.06	0.31	0.31	0.05	0.42	0.42
Crit Volume:	25		85		94							594
Crit Moves:	****		****		****							****

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #23 Sunset Bl & Whitney Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.805  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 117 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 10 columns for volume and 10 rows for various adjustment factors like Growth Adj, Initial Bse, User Adj, etc.

Saturation Flow Module: Table with 10 columns for Sat/Lane and 10 rows for Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #101 Blue Oaks Bl & Lonetree  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.478  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 44 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 10 columns for volume and 10 rows for various adjustment factors like Growth Adj, Initial Bse, User Adj, etc.

Saturation Flow Module: Table with 10 columns for Sat/Lane and 10 rows for Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #102 Blue Oaks Bl & Market Place

Cycle (sec): 100 Critical Vol./Cap.(X): 0.244
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 30 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #103 Blue Oaks Bl & Van Buren Way

Cycle (sec): 100 Critical Vol./Cap.(X): 0.287
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 32 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #104 Five Star & Destiny Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.194
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 28 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Capacity Analysis Module, Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #105 Lonetree Bl & Adams Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.308
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 33 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Capacity Analysis Module, Vol/Sat, Crit Volume, and Crit Moves.

Existing PM Fri May 22, 2009 09:51:52 Page 31-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #106 Lonetree Bl & Atherton Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.272  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 29 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	0	1	1	0	0	0	0	0

Volume Module:

Base Vol:	20	406	0	0	217	4	35	0	185	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	20	406	0	0	217	4	35	0	185	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	20	406	0	0	217	4	35	0	185	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	20	406	0	0	217	4	35	0	185	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	20	406	0	0	217	4	35	0	185	0	0	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	0.00	0.00	1.96	0.04	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	1425	2850	0	0	2798	52	1425	0	1425	0	0	0

Capacity Analysis Module:

Vol/Sat:	0.01	0.14	0.00	0.00	0.08	0.08	0.02	0.00	0.13	0.00	0.00	0.00
Crit Volume:	203			110			185	0				
Crit Moves:	****						****					

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 32-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #107 Lonetree Bl & Grand Canyon Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.469  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 43 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	1	0	0	1	0

Volume Module:

Base Vol:	161	668	42	5	788	8	20	1	66	14	2	4
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	161	668	42	5	788	8	20	1	66	14	2	4
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	161	668	42	5	788	8	20	1	66	14	2	4
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	161	668	42	5	788	8	20	1	66	14	2	4
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	161	668	42	5	788	8	20	1	66	14	2	4

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.88	0.12	1.00	1.98	0.02	0.95	0.05	1.00	0.70	0.10	0.20
Final Sat.:	1375	2587	163	1375	2722	28	1310	65	1375	963	138	275

Capacity Analysis Module:

Vol/Sat:	0.12	0.26	0.26	0.00	0.29	0.29	0.02	0.02	0.05	0.01	0.01	0.01
Crit Volume:	161			398			66		20			
Crit Moves:	****			****			****		****			

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 33-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #108 Lonetree Bl & Redwood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.442  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 41 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	1	0	0	1	0

Volume Module:

Base Vol:	133	538	30	15	625	39	49	4	99	29	6	9
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	133	538	30	15	625	39	49	4	99	29	6	9
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	133	538	30	15	625	39	49	4	99	29	6	9
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	133	538	30	15	625	39	49	4	99	29	6	9
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	133	538	30	15	625	39	49	4	99	29	6	9

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.89	0.11	1.00	1.88	0.12	0.92	0.08	1.00	0.66	0.14	0.20
Final Sat.:	1375	2605	145	1375	2588	162	1271	104	1375	906	188	281

Capacity Analysis Module:

Vol/Sat:	0.10	0.21	0.21	0.01	0.24	0.24	0.04	0.04	0.07	0.03	0.03	0.03
Crit Volume:	133			332			99		44			
Crit Moves:	***			***			***		***	***		

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 34-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #109 Lonetree Bl & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.514  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 47 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	0	1	0	2	1	0	2

Volume Module:

Base Vol:	7	367	115	9	396	1	1	0	4	212	1	6
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	7	367	115	9	396	1	1	0	4	212	1	6
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	7	367	115	9	396	1	1	0	4	212	1	6
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	7	367	115	9	396	1	1	0	4	212	1	6
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	7	367	115	9	396	1	1	0	4	212	1	6

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.76	0.24	1.00	2.00	1.00	1.00	2.00	1.00	1.00	2.00	1.00
Final Sat.:	1375	1047	328	1375	2750	1375	1375	2750	1375	1375	2750	1375

Capacity Analysis Module:

Vol/Sat:	0.01	0.35	0.35	0.01	0.14	0.00	0.00	0.00	0.00	0.15	0.00	0.00
Crit Volume:	482			9			4		212			
Crit Moves:	***			***			***		***	***		

\*\*\*\*\*



City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #110 Park Dr & Blaydon Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.197  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 23 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of traffic volume metrics.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of saturation flow metrics.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of capacity analysis metrics.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #111 Park Dr & Quarry Way

Cycle (sec): 100 Critical Vol./Cap.(X): 0.391  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of traffic volume metrics.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of saturation flow metrics.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 10 rows of capacity analysis metrics.

Existing PM Fri May 22, 2009 09:51:52 Page 37-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #112 Park Dr & Farrier Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.520  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	0	1	1	0	0	0	0	0

Volume Module:  
Base Vol: 269 624 0 0 552 61 37 0 165 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 269 624 0 0 552 61 37 0 165 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 269 624 0 0 552 61 37 0 165 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 269 624 0 0 552 61 37 0 165 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 269 624 0 0 552 61 37 0 165 0 0 0

Saturation Flow Module:  
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 0.00 0.00 1.80 0.20 1.00 0.00 1.00 0.00 0.00 0.00  
Final Sat.: 1425 2850 0 0 2566 284 1425 0 1425 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.19 0.22 0.00 0.00 0.22 0.22 0.03 0.00 0.12 0.00 0.00 0.00  
Crit Volume: 269 307 165 0  
Crit Moves: \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 38-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #113 Park Dr & King Pine Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.368  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 29 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Permitted			Permitted		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	1	0	0	1	0

Volume Module:  
Base Vol: 24 889 33 27 688 7 7 1 9 27 0 15  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 24 889 33 27 688 7 7 1 9 27 0 15  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 24 889 33 27 688 7 7 1 9 27 0 15  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 24 889 33 27 688 7 7 1 9 27 0 15  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 24 889 33 27 688 7 7 1 9 27 0 15

Saturation Flow Module:  
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.93 0.07 1.00 1.98 0.02 0.88 0.12 1.00 1.00 0.00 1.00  
Final Sat.: 1425 2748 102 1425 2821 29 1247 178 1425 1425 0 1425

Capacity Analysis Module:  
Vol/Sat: 0.02 0.32 0.32 0.02 0.24 0.24 0.01 0.01 0.01 0.02 0.00 0.01  
Crit Volume: 461 27 9 27  
Crit Moves: \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 39-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #114 Park Dr & Shelton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.274  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 1 0	1 0 2 1 0	1 0 0 1 0	1 0 1 0 1

Volume Module:

Base Vol:	120	683	69	5	454	3	8	1	68	36	5	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	120	683	69	5	454	3	8	1	68	36	5	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	120	683	69	5	454	3	8	1	68	36	5	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	120	683	69	5	454	3	8	1	68	36	5	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	120	683	69	5	454	3	8	1	68	36	5	0

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.72	0.28	1.00	2.98	0.02	1.00	0.01	0.99	1.00	1.00	1.00
Final Sat.:	1375	3747	378	1375	4098	27	1375	20	1355	1375	1375	1375

Capacity Analysis Module:

Vol/Sat:	0.09	0.18	0.18	0.00	0.11	0.11	0.01	0.05	0.05	0.03	0.00	0.00
Crit Volume:	120				152			69	36			
Crit Moves:	****				****			****	****			

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 40-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #115 Park Dr & Victory Lane  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.318  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Split Phase	Split Phase
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 1 0	1 0 2 1 0	0 1 0 0 1	0 1 0 0 1

Volume Module:

Base Vol:	37	719	6	57	457	12	71	5	12	26	14	63
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	37	719	6	57	457	12	71	5	12	26	14	63
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	37	719	6	57	457	12	71	5	12	26	14	63
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	37	719	6	57	457	12	71	5	12	26	14	63
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	37	719	6	57	457	12	71	5	12	26	14	63

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.98	0.02	1.00	2.92	0.08	0.93	0.07	1.00	0.65	0.35	1.00
Final Sat.:	1375	4091	34	1375	4019	106	1285	90	1375	894	481	1375

Capacity Analysis Module:

Vol/Sat:	0.03	0.18	0.18	0.04	0.11	0.11	0.06	0.06	0.01	0.03	0.03	0.05
Crit Volume:				242	57			76				63
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 41-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #116 Park Dr & Wykford Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.320  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	0 0 0 0 0	2 0 0 0 1	2 0 2 0 0	0 0 2 0 1

Volume Module:

Base Vol:	0	0	0	10	0	165	245	446	0	0	337	14
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	0	0	10	0	165	245	446	0	0	337	14
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	0	10	0	165	245	446	0	0	337	14
Reduce Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	0	10	0	165	245	446	0	0	337	14
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	0	0	10	0	165	245	446	0	0	337	14

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	0.00	0.00	2.00	0.00	1.00	2.00	2.00	0.00	0.00	2.00	1.00
Final Sat.:	0	0	0	2850	0	1425	2850	2850	0	0	2850	1425

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.00	0.00	0.12	0.09	0.16	0.00	0.00	0.12	0.01
Crit Volume:	0			165	123				169			
Crit Moves:	****			****	****				****			

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 42-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #117 Park Dr & Twin Oaks/ Boardwalk  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.362  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Split Phase	Split Phase
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 1 1 0	1 0 1 1 0	0 0 1! 0 0	0 1 0 0 1

Volume Module:

Base Vol:	66	600	26	25	550	32	65	2	59	15	0	2
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	66	600	26	25	550	32	65	2	59	15	0	2
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	66	600	26	25	550	32	65	2	59	15	0	2
Reduce Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	66	600	26	25	550	32	65	2	59	15	0	2
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	66	600	26	25	550	32	65	2	59	15	0	2

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.92	0.08	1.00	1.89	0.11	0.52	0.01	0.47	1.00	0.00	1.00
Final Sat.:	1375	2636	114	1375	2599	151	709	22	644	1375	0	1375

Capacity Analysis Module:

Vol/Sat:	0.05	0.23	0.23	0.02	0.21	0.21	0.09	0.09	0.09	0.01	0.00	0.00
Crit Volume:	66			291			126		15			
Crit Moves:	****			****			****		****			

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #118 Park Dr & Safeway

Cycle (sec): 100 Critical Vol./Cap.(X): 0.514  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 38 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #119 South Whitney & Five Star Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.471  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 43 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #120 Spring Creek Dr & Broken Rail Ln

Cycle (sec): 100 Critical Vol./Cap.(X): 0.031
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 15 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West bounds.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Volume, Crit Moves for Capacity Analysis Module.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #121 Stanford Ranch Rd & Cobblestone Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.325
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 28 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West bounds.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Volume, Crit Moves for Capacity Analysis Module.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #122 Stanford Ranch Rd & Darby Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.293  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 32 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #123 Stanford Ranch Rd & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.573  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 53 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #124 Stanford Ranch Rd & Plaza

Cycle (sec): 100 Critical Vol./Cap.(X): 0.371  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Rights, Min. Green, Y+R, Lanes).

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #125 Stanford Ranch Rd & Stoney Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.439  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Rights, Min. Green, Y+R, Lanes).

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, Crit Moves.



Existing PM Page 51-1

Fri May 22, 2009 09:51:52

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
-----

\*\*\*\*\*  
Intersection #126 Stanford Ranch Rd & Victory Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.263  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	0	1	0	1	1	0	3	0	0	3

-----

Volume Module:

Base Vol:	0	0	0	72	0	69	37	495	0	0	796	73
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	0	0	72	0	69	37	495	0	0	796	73
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	0	72	0	69	37	495	0	0	796	73
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	0	72	0	69	37	495	0	0	796	73
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	0	0	72	0	69	37	495	0	0	796	73

-----

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	0.00	0.00	1.00	1.00	1.00	1.00	3.00	0.00	1.00	3.00	1.00
Final Sat.:	0	0	0	1425	1425	1425	1425	4275	0	0	4275	1425

-----

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.05	0.00	0.05	0.03	0.12	0.00	0.00	0.19	0.05
Crit Volume:	0			72			37			265		
Crit Moves:				****			****			****		

\*\*\*\*\*

Existing PM Page 52-1

Fri May 22, 2009 09:51:52

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
-----

\*\*\*\*\*  
Intersection #127 Stanford Ranch Rd & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.228  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 30 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	1	0	2	0	1	1

-----

Volume Module:

Base Vol:	13	77	88	70	49	15	20	317	9	50	278	102
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	13	77	88	70	49	15	20	317	9	50	278	102
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	13	77	88	70	49	15	20	317	9	50	278	102
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	13	77	88	70	49	15	20	317	9	50	278	102
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	13	77	88	70	49	15	20	317	9	50	278	102

-----

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	1.00	1.00	2.00	1.00	1.00	3.00	1.00	1.00	3.00	1.00
Final Sat.:	1375	2750	1375	1375	2750	1375	1375	4125	1375	1375	4125	1375

-----

Capacity Analysis Module:

Vol/Sat:	0.01	0.03	0.06	0.05	0.02	0.01	0.01	0.08	0.01	0.04	0.07	0.07
Crit Volume:				88	70			106		50		
Crit Moves:				****	****		****			****		

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #128 Sunset Bl & Atherton

Cycle (sec): 100 Critical Vol./Cap.(X): 0.337  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns representing traffic volumes for different movements and approaches.

Saturation Flow Module table with 12 columns representing saturation flow rates and adjustments.

Capacity Analysis Module table with 12 columns representing volume-to-saturation ratios and critical volumes.

Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #129 Sunset Bl & Blue Oaks Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.681  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 71 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns representing traffic volumes for different movements and approaches.

Saturation Flow Module table with 12 columns representing saturation flow rates and adjustments.

Capacity Analysis Module table with 12 columns representing volume-to-saturation ratios and critical volumes.

Crit Moves: \*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 55-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #130 Sunset Bl & Fairway Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.480  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	0	0	1	1	0	2	1	0	1

Volume Module:

Base Vol:	124	42	139	12	23	28	56	676	80	159	858	12
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	124	42	139	12	23	28	56	676	80	159	858	12
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	124	42	139	12	23	28	56	676	80	159	858	12
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	124	42	139	12	23	28	56	676	80	159	858	12
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	124	42	139	12	23	28	56	676	80	159	858	12

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.00	1.00	0.19	0.37	0.44	1.00	2.00	1.00	1.00	1.97	0.03
Final Sat.:	1425	1425	1425	271	520	633	1425	2850	1425	1425	2811	39

Capacity Analysis Module:

Vol/Sat:	0.09	0.03	0.10	0.04	0.04	0.04	0.04	0.24	0.06	0.11	0.31	0.31
Crit Volume:	124			63			338		159			
Crit Moves:	****			****			****		****			

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 56-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #131 Sunset Bl & Little Rock  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.444  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 41 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	1	0	0	1	0	1	0	2	1	0	2

Volume Module:

Base Vol:	29	0	25	35	2	34	121	1025	28	75	1142	28
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	29	0	25	35	2	34	121	1025	28	75	1142	28
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	29	0	25	35	2	34	121	1025	28	75	1142	28
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	29	0	25	35	2	34	121	1025	28	75	1142	28
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	29	0	25	35	2	34	121	1025	28	75	1142	28

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.00	1.00	0.49	0.03	0.48	1.00	2.92	0.08	1.00	2.93	0.07
Final Sat.:	1375	0	1375	678	39	658	1375	4015	110	1375	4026	99

Capacity Analysis Module:

Vol/Sat:	0.02	0.00	0.02	0.05	0.05	0.05	0.09	0.26	0.26	0.05	0.28	0.28
Crit Volume:	29			71			121			390		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 57-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #132 Sunset Bl & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.866  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 170 Level Of Service: D

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Ignore			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	3	0	1	2	0	2	0	1	1	0

Volume Module:

Base Vol:	393	493	116	293	354	73	384	638	83	438	710	181
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	393	493	116	293	354	73	384	638	83	438	710	181
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Volume:	393	493	116	293	354	73	384	638	0	438	710	181
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	393	493	116	293	354	73	384	638	0	438	710	181
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
FinalVolume:	393	493	116	293	354	73	384	638	0	438	710	181

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	3.00	1.00	2.00	2.00	1.00	1.00	3.00	1.00	2.00	3.00	1.00
Final Sat.:	1375	4125	1375	2750	2750	1375	1375	4125	1375	2750	4125	1375

Capacity Analysis Module:

Vol/Sat:	0.29	0.12	0.08	0.11	0.13	0.05	0.28	0.15	0.00	0.16	0.17	0.13
Crit Volume:	393			177			384			237		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 58-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #133 Sunset Bl & Pebble Creek  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.539  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 40 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	0	0	1	0	0	1

Volume Module:

Base Vol:	26	12	29	44	6	111	192	888	31	54	1105	64
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	26	12	29	44	6	111	192	888	31	54	1105	64
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	26	12	29	44	6	111	192	888	31	54	1105	64
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	26	12	29	44	6	111	192	888	31	54	1105	64
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	26	12	29	44	6	111	192	888	31	54	1105	64

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.39	0.18	0.43	0.27	0.04	0.69	1.00	2.90	0.10	1.00	2.84	0.16
Final Sat.:	553	255	617	389	53	982	1425	4131	144	1425	4041	234

Capacity Analysis Module:

Vol/Sat:	0.05	0.05	0.05	0.11	0.11	0.11	0.13	0.21	0.21	0.04	0.27	0.27
Crit Volume:	26			161			192			390		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #134 Sunset Bl & Stanford Ranch Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.793  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 110 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #135 Sunset Bl & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.349  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 35 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #136 W Stanford Ranch Rd & Sunset Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.467  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 43 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #137 W Stanford Ranch Rd & Wildcat Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.455  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 42 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

Existing PM Fri May 22, 2009 09:51:52 Page 63-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #138 Whitney Ranch Pkwy & Bridlewood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.014  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 19 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	1	0	0	0	0	1	0	1	1	0	1

Volume Module:  
Base Vol: 2 1 0 0 0 0 7 7 5 1 0 8 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 2 1 0 0 0 0 7 7 5 1 0 8 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 2 1 0 0 0 0 7 7 5 1 0 8 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 2 1 0 0 0 0 7 7 5 1 0 8 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 2 1 0 0 0 0 7 7 5 1 0 8 0

Saturation Flow Module:  
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.67 0.33 0.00 0.00 0.00 1.00 1.00 1.67 0.33 1.00 2.00 0.00  
Final Sat.: 950 475 0 0 0 1425 1425 2375 475 1425 2850 0

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00  
Crit Volume: 2 7 7 4  
Crit Moves: \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 64-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #139 Whitney Ranch Pkwy & Painted Pony Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.007  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 23 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	1	0	1	0	1	0	0	0

Volume Module:  
Base Vol: 0 0 0 0 0 0 6 1 0 4 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 0 0 0 0 0 6 1 0 4 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 0 0 0 0 0 6 1 0 4 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 0 0 0 0 0 6 1 0 4 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 0 0 0 0 0 6 1 0 4 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 1.00 0.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 0.00  
Final Sat.: 0 1500 0 0 1500 1500 1500 1500 1500 1500 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00  
Crit Volume: 0 6 4 0  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #140 Whitney Ranch Pkwy & Spring Creek Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.061  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 20 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of traffic volume and adjustment factors.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of saturation flow and adjustment factors.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of capacity and volume data.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #141 Wildcat Bl & Bridlewood Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.264  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of traffic volume and adjustment factors.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of saturation flow and adjustment factors.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 12 rows of capacity and volume data.



Existing PM Fri May 22, 2009 09:51:52 Page 67-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #142 Wildcat Bl & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.179  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 28 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	2	0	3	0	1	2

Volume Module:  
Base Vol: 30 420 71 4 281 2 3 1 4 56 0 6  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 30 420 71 4 281 2 3 1 4 56 0 6  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 30 420 71 4 281 2 3 1 4 56 0 6  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 30 420 71 4 281 2 3 1 4 56 0 6  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 30 420 71 4 281 2 3 1 4 56 0 6

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 2.00 3.00 1.00 2.00 2.00 1.00  
Final Sat.: 1375 2750 1375 1375 2750 1375 2750 4125 1375 2750 2750 1375

Capacity Analysis Module:  
Vol/Sat: 0.02 0.15 0.05 0.00 0.10 0.00 0.00 0.00 0.00 0.02 0.00 0.00  
Crit Volume: 210 4 4 28  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 68-1

-----  
City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS  
-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #143 Wildcat Bl & S High School Entrance  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.173  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 22 Level Of Service: A  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	2	0	1	1	0	0	0	0	0	1

Volume Module:  
Base Vol: 0 331 94 1 272 0 0 0 0 80 0 4  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 331 94 1 272 0 0 0 0 80 0 4  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 331 94 1 272 0 0 0 0 80 0 4  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 331 94 1 272 0 0 0 0 80 0 4  
PCE Adj: 1.00 1.00 1.00 2.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 331 94 2 272 0 0 0 0 80 0 4

Saturation Flow Module:  
Sat/Lane: 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425 1425  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 2.00 1.00 0.01 1.99 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 2850 1425 21 2829 0 0 0 0 1425 0 1425

Capacity Analysis Module:  
Vol/Sat: 0.00 0.12 0.07 0.05 0.10 0.00 0.00 0.00 0.00 0.06 0.00 0.00  
Crit Volume: 166 1 0 80  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #144 Wildcat Bl & N High School Entrance

Cycle (sec): 100 Critical Vol./Cap.(X): 0.167  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 27 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Rights: Include), Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, PCE Adj, MLF Adj, and Final Volume for each approach.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat for each approach.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves for each approach.

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #145 Wildcat Bl & Ranch View Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.180  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 28 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Rights: Include), Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, PCE Adj, MLF Adj, and Final Volume for each approach.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat for each approach.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves for each approach.

\*\*\*\*\*

Existing PM Page 71-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 2000 HCM Operations Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #201 Rocklin Rd & I-80 EB  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.746  
 Loss Time (sec): 6 Average Delay (sec/veh): 26.1  
 Optimal Cycle: 48 Level Of Service: C  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Permitted Permitted Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 1 0 1 0 1 0 0 0 0 0 1 0 2 0 0 0 0 1 1 0  
 -----  
 Volume Module:  
 Base Vol: 583 0 596 0 0 0 185 594 0 0 1019 125  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 583 0 596 0 0 0 185 594 0 0 1019 125  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 583 0 596 0 0 0 185 594 0 0 1019 125  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 583 0 596 0 0 0 185 594 0 0 1019 125  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 583 0 596 0 0 0 185 594 0 0 1019 125  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
 Adjustment: 0.74 1.00 0.74 1.00 1.00 1.00 0.95 0.95 1.00 1.00 0.93 0.93  
 Lanes: 1.49 0.00 1.51 0.00 0.00 0.00 1.00 2.00 0.00 0.00 1.78 0.22  
 Final Sat.: 2107 0 2122 0 0 0 1805 3610 0 0 3164 388  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.28 0.00 0.28 0.00 0.00 0.00 0.10 0.16 0.00 0.00 0.32 0.32  
 Crit Moves: \*\*\*\*  
 Green/Cycle: 0.37 0.00 0.37 0.00 0.00 0.00 0.14 0.57 0.00 0.00 0.43 0.43  
 Volume/Cap: 0.75 0.00 0.76 0.00 0.00 0.00 0.75 0.29 0.00 0.00 0.75 0.75  
 Delay/Veh: 29.3 0.0 29.7 0.0 0.0 0.0 53.1 11.2 0.0 0.0 25.9 25.9  
 User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 AdjDel/Veh: 29.3 0.0 29.7 0.0 0.0 0.0 53.1 11.2 0.0 0.0 25.9 25.9  
 LOS by Move: C A C A A A D B A A C C  
 HCM2kAvgQ: 12 0 12 0 0 0 7 5 0 0 17 17  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*

Existing PM Page 72-1  
 -----  
 City of Rocklin General Plan Update  
 Existing Conditions (2008)  
 PM Peak Hour LOS  
 -----  
 Level Of Service Computation Report  
 2000 HCM Operations Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #202 Rocklin Rd & I-80 WB  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.681  
 Loss Time (sec): 6 Average Delay (sec/veh): 21.8  
 Optimal Cycle: 40 Level Of Service: C  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Permitted Permitted Protected Protected  
 Rights: Include Include Ignore Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 0 0 0 0 0 1 0 0 1 0 0 0 2 0 1 1 0 2 0 0  
 -----  
 Volume Module:  
 Base Vol: 0 0 0 58 1 271 0 711 570 497 1053 0  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 0 0 0 58 1 271 0 711 570 497 1053 0  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Volume: 0 0 0 58 1 271 0 711 0 497 1053 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 0 0 0 58 1 271 0 711 0 497 1053 0  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 FinalVolume: 0 0 0 58 1 271 0 711 0 497 1053 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
 Adjustment: 1.00 1.00 1.00 0.85 0.85 0.85 1.00 0.95 1.00 0.95 0.95 1.00  
 Lanes: 0.00 0.00 0.00 1.00 0.01 0.99 0.00 2.00 1.00 1.00 2.00 0.00  
 Final Sat.: 0 0 0 1615 6 1611 0 3610 1900 1805 3610 0  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.00 0.00 0.00 0.04 0.17 0.17 0.00 0.20 0.00 0.28 0.29 0.00  
 Crit Moves: \*\*\*\*  
 Green/Cycle: 0.00 0.00 0.00 0.25 0.25 0.25 0.00 0.29 0.00 0.40 0.69 0.00  
 Volume/Cap: 0.00 0.00 0.00 0.15 0.68 0.68 0.00 0.68 0.00 0.68 0.42 0.00  
 Delay/Veh: 0.0 0.0 0.0 29.6 38.9 38.9 0.0 33.3 0.0 27.1 6.8 0.0  
 User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 AdjDel/Veh: 0.0 0.0 0.0 29.6 38.9 38.9 0.0 33.3 0.0 27.1 6.8 0.0  
 LOS by Move: A A A A C D D A C A C A A  
 HCM2kAvgQ: 0 0 0 1 9 9 0 11 0 13 7 0  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*

Existing PM Fri May 22, 2009 09:51:52 Page 73-1
City of Rocklin General Plan Update
Existing Conditions (2008)
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #203 Sierra College Bl & I-80 WB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.616
Loss Time (sec): 9 Average Delay (sec/veh): 19.2
Optimal Cycle: 42 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Permitted), Rights (Include), Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

Existing PM Fri May 22, 2009 09:51:52 Page 74-1
City of Rocklin General Plan Update
Existing Conditions (2008)
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #204 Sierra College Bl & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.478
Loss Time (sec): 9 Average Delay (sec/veh): 20.6
Optimal Cycle: 33 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Permitted), Rights (Include), Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #205 SR 65 & Sunset Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.954
Loss Time (sec): 12 Average Delay (sec/veh): 39.4
Optimal Cycle: 142 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #208 Whitney Ranch Pkwy & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.000
Loss Time (sec): 0 Average Delay (sec/veh): 0.0
Optimal Cycle: 0 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

Existing PM Page 77-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)  
-----

Intersection #209 Whitney Ranch Pkwy & SR 65 NB  
-----

Cycle (sec):	100	Critical Vol./Cap.(X):	0.777
Loss Time (sec):	0	Average Delay (sec/veh):	14.3
Optimal Cycle:	102	Level Of Service:	B

-----

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Ignore	Ignore
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 0 0	0 0 2 1 0	0 0 0 0 1	0 0 0 0 1

-----

Volume Module:

Base Vol:	729 1658	0	0 1675	225	0 0 323	0 0 1001
Growth Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00 1.00 1.00
Initial Bse:	729 1658	0	0 1675	225	0 0 323	0 0 1001
User Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	0.00 1.00 1.00 0.00
PHF Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	0.00 1.00 1.00 0.00
PHF Volume:	729 1658	0	0 1675	225	0 0 0	0 0 0 0
Reduct Vol:	0 0 0	0	0 0 0	0	0 0 0	0 0 0 0
Reduced Vol:	729 1658	0	0 1675	225	0 0 0	0 0 0 0
PCE Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	0.00 1.00 1.00 0.00
MLF Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	0.00 1.00 1.00 0.00
FinalVolume:	729 1658	0	0 1675	225	0 0 0	0 0 0 0

-----

Saturation Flow Module:

Sat/Lane:	1900 1900	1900	1900 1900	1900	1900 1900	1900 1900 1900
Adjustment:	0.95 0.95	1.00	1.00 0.89	0.89	1.00 1.00	1.00 1.00 1.00
Lanes:	1.00 2.00	0.00	0.00 2.64	0.36	0.00 0.00	1.00 0.00 0.00 1.00
Final Sat.:	1805 3610	0	0 4490	603	0 0 1900	0 0 1900

-----

Capacity Analysis Module:

Vol/Sat:	0.40 0.46	0.00	0.00 0.37	0.37	0.00 0.00	0.00 0.00 0.00
Crit Moves:	***		***			
Green/Cycle:	0.52 1.00	0.00	0.00 0.48	0.48	0.00 0.00	0.00 0.00 0.00 0.00
Volume/Cap:	0.78 0.46	0.00	0.00 0.78	0.78	0.00 0.00	0.00 0.00 0.00 0.00
Delay/Veh:	23.5 0.1	0.0	0.0 23.2	23.2	0.0 0.0	0.0 0.0 0.0 0.0
User DelAdj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00 1.00 1.00 1.00
AdjDel/Veh:	23.5 0.1	0.0	0.0 23.2	23.2	0.0 0.0	0.0 0.0 0.0 0.0
LOS by Move:	C A A	A A C	C A A	A A A	A A A	A A A A
HCM2kAvgQ:	19 1	0	0 19	19	0 0	0 0 0 0

-----

Note: Queue reported is the number of cars per lane.  
-----

Existing PM Page 78-1

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)  
-----

Intersection #210 Blue Oaks Blvd & SR 65 SB  
-----

Cycle (sec):	100	Critical Vol./Cap.(X):	0.405
Loss Time (sec):	9	Average Delay (sec/veh):	24.4
Optimal Cycle:	29	Level Of Service:	C

-----

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Ovl	Ignore	Ovl	Ignore
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 0 0 2	1 0 2 0 1	0 0 4 0 1	2 0 2 0 1

-----

Volume Module:

Base Vol:	268	0 436	93 166	232	0 903	197	152 570	377
Growth Adj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00
Initial Bse:	268	0 436	93 166	232	0 903	197	152 570	377
User Adj:	1.00 1.00	1.00	1.00 1.00	0.00	1.00 1.00	1.00	1.00 1.00	0.00
PHF Adj:	1.00 1.00	1.00	1.00 1.00	0.00	1.00 1.00	1.00	1.00 1.00	0.00
PHF Volume:	268	0 436	93 166	0	0 903	197	152 570	0
Reduct Vol:	0 0 0	0	0 0 0	0	0 0 0	0	0 0 0	0
Reduced Vol:	268	0 436	93 166	0	0 903	197	152 570	0
PCE Adj:	1.00 1.00	1.00	1.00 1.00	0.00	1.00 1.00	1.00	1.00 1.00	0.00
MLF Adj:	1.00 1.00	1.00	1.00 1.00	0.00	1.00 1.00	1.00	1.00 1.00	0.00
FinalVolume:	268	0 436	93 166	0	0 903	197	152 570	0

-----

Saturation Flow Module:

Sat/Lane:	1900 1900	1900	1900 1900	1900	1900 1900	1900	1900 1900	1900
Adjustment:	0.95 1.00	0.75	0.95 0.95	1.00	1.00 0.91	0.85	0.92 0.95	1.00
Lanes:	1.00 0.00	2.00	1.00 2.00	1.00	0.00 4.00	1.00	2.00 2.00	1.00
Final Sat.:	1805	0 2842	1805 3610	1900	0 6916	1615	3502 3610	1900

-----

Capacity Analysis Module:

Vol/Sat:	0.15 0.00	0.15	0.05 0.05	0.00	0.00 0.13	0.12	0.04 0.16	0.00
Crit Moves:	***		***		***		***	
Green/Cycle:	0.37 0.00	0.43	0.15 0.11	0.00	0.00 0.32	0.69	0.11 0.43	0.00
Volume/Cap:	0.40 0.00	0.35	0.34 0.40	0.00	0.00 0.40	0.18	0.40 0.37	0.00
Delay/Veh:	24.0 0.0	19.1	38.5 41.8	0.0	0.0 26.5	5.6	42.4 19.5	0.0
User DelAdj:	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00	1.00 1.00	1.00
AdjDel/Veh:	24.0 0.0	19.1	38.5 41.8	0.0	0.0 26.5	5.6	42.4 19.5	0.0
LOS by Move:	C A B	D D A	A C A	A C A	A C A	A	D B A	A
HCM2kAvgQ:	6	0 5	3 3	0	0 6	2	3 6	0

-----

Note: Queue reported is the number of cars per lane.  
-----

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #211 Blue Oaks Blvd & SR 65 NB Off

Cycle (sec): 100 Critical Vol./Cap.(X): 0.357
Loss Time (sec): 6 Average Delay (sec/veh): 7.3
Optimal Cycle: 22 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #212 Pleasant Grove Blvd & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.887
Loss Time (sec): 6 Average Delay (sec/veh): 27.2
Optimal Cycle: 87 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #213 Pleasant Grove Blvd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.910
Loss Time (sec): 6 Average Delay (sec/veh): 19.8
Optimal Cycle: 100 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #214 Stanford Ranch Rd & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.965
Loss Time (sec): 3 Average Delay (sec/veh): 26.6
Optimal Cycle: 159 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.



City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report  
 2000 HCM Operations Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #215 Stanford Ranch Rd & SR 65 SB  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 1.041  
 Loss Time (sec): 3 Average Delay (sec/veh): 34.1  
 Optimal Cycle: 180 Level Of Service: C  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 Control: Protected Protected Permitted Permitted  
 Rights: Include Include Ignore Ignore  
 Lanes: 0 1 0 0 1 0 0 1 0 0 1 0 0 1  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 1  
 Volume Module:  
 Base Vol: 0 2462 469 592 1475 0 0 635 0 0 199  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 0 2462 469 592 1475 0 0 635 0 0 199  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 0 2462 469 592 1475 0 0 0 0 0 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 0 2462 469 592 1475 0 0 0 0 0 0  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Final Volume: 0 2462 469 592 1475 0 0 0 0 0 0  
 Saturation Flow Module:  
 Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
 Adjustment: 1.00 0.95 0.85 0.95 0.95 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 1.00 0.00 0.00 1.00  
 Final Sat.: 0 3610 1615 1805 3610 0 0 0 1900 0 0 1900  
 Capacity Analysis Module:  
 Vol/Sat: 0.00 0.68 0.29 0.33 0.41 0.00 0.00 0.00 0.00 0.00 0.00  
 Crit Moves: \*\*\*\*  
 Green/Cycle: 0.00 0.66 0.66 0.31 0.97 0.00 0.00 0.00 0.00 0.00 0.00  
 Volume/Cap: 0.00 1.04 0.44 1.04 0.42 0.00 0.00 0.00 0.00 0.00 0.00  
 Delay/Veh: 0.0 47.6 8.7 83.1 0.2 0.0 0.0 0.0 0.0 0.0 0.0  
 User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 AdjDel/Veh: 0.0 47.6 8.7 83.1 0.2 0.0 0.0 0.0 0.0 0.0 0.0  
 LOS by Move: A D A F A A A A A A A  
 HCM2kAvgQ: 0 52 7 27 2 0 0 0 0 0 0  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report  
 2000 HCM Unsignalized Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #216 Sierra College Blvd & SR 193  
 \*\*\*\*\*  
 Average Delay (sec/veh): 22.3 Worst Case Level Of Service: F[ 53.5]  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 Control: Stop Sign Stop Sign Uncontrolled Uncontrolled  
 Rights: Include Include Include Include  
 Lanes: 0 1 0 0 1 0 0 1 0 0 1 1 0 0 1 0  
 Volume Module:  
 Base Vol: 370 5 126 4 4 8 5 201 181 76 184 76  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 370 5 126 4 4 8 5 201 181 76 184 76  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 370 5 126 4 4 8 5 201 181 76 184 76  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Final Volume: 370 5 126 4 4 8 5 201 181 76 184 76  
 Critical Gap Module:  
 Critical Gap: 7.1 6.5 6.2 7.1 6.5 6.2 4.1 xxxx xxxxx 4.1 xxxx xxxxx  
 FollowUpTim: 3.5 4.0 3.3 3.5 4.0 3.3 2.2 xxxx xxxxx 2.2 xxxx xxxxx  
 Capacity Module:  
 Cnflct Vol: 591 623 201 741 766 222 260 xxxx xxxxx 382 xxxx xxxxx  
 Potent Cap.: 422 405 845 335 335 823 1316 xxxx xxxxx 1188 xxxx xxxxx  
 Move Cap.: 392 378 845 267 313 823 1316 xxxx xxxxx 1188 xxxx xxxxx  
 Volume/Cap: 0.94 0.01 0.15 0.01 0.01 0.01 0.00 xxxx xxxx 0.06 xxxx xxxx  
 Level Of Service Module:  
 2Way95thQ: xxxx xxxx 0.5 xxxx xxxx xxxxx 0.0 xxxx xxxxx 0.2 xxxx xxxxx  
 Control Del:xxxxx xxxxx 10.0 xxxxx xxxx xxxxx 7.7 xxxx xxxxx 8.2 xxxx xxxxx  
 LOS by Move: \* \* B \* \* \* A \* \* A \* \*  
 Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT  
 Shared Cap.: 392 xxxx xxxxx xxxx 427 xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx  
 SharedQueue: 10.9 xxxx xxxxx xxxxx 0.1 xxxxx xxxxx xxxx xxxxx xxxx xxxx xxxxx  
 Shrd ConDel: 68.1 xxxx xxxxx xxxxx 13.8 xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx  
 Shared LOS: F \* \* \* \* B \* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*  
 ApproachDel: 53.5 13.8  
 ApproachLOS: F B \* \*  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #301 Sierra College Bl & Brace Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.362
Loss Time (sec): 6 Average Delay (sec/veh): 16.3
Optimal Cycle: 22 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ. Rows for Capacity Analysis Module.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #302 Sierra College Bl & Taylor Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.569
Loss Time (sec): 12 Average Delay (sec/veh): 29.8
Optimal Cycle: 46 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ. Rows for Capacity Analysis Module.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #304 Sierra College Bl & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.455  
Loss Time (sec): 12 Average Delay (sec/veh): 16.1  
Optimal Cycle: 38 Level Of Service: B

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L, T, R), Control (Protected, Split Phase), Rights (Include), Min. Green, Y+R, Lanes.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #305 Taylor Rd & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.586  
Loss Time (sec): 12 Average Delay (sec/veh): 30.5  
Optimal Cycle: 47 Level Of Service: C

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L, T, R), Control (Protected, Split Phase), Rights (Include), Min. Green, Y+R, Lanes.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #306 Taylor Rd & Horseshoe Bar

Cycle (sec): 100 Critical Vol./Cap.(X): 0.844
Loss Time (sec): 9 Average Delay (sec/veh): 38.3
Optimal Cycle: 80 Level Of Service: D

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Conditions (2008) PM Peak Hour LOS

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #501 E Lincoln Pkwy & Twelve Bridges

Cycle (sec): 100 Critical Vol./Cap.(X): 0.461
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 42 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.



City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
 Level Of Service Computation Report  
 2000 HCM 4-Way Stop Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #307 Rocklin Rd & Barton Rd  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap. (X): 0.380  
 Loss Time (sec): 0 Average Delay (sec/veh): 10.0  
 Optimal Cycle: 0 Level Of Service: A  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Stop Sign Stop Sign Stop Sign Stop Sign  
 Rights: Include Include Include Include  
 Lanes: 0 0 1! 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 -----  
 Volume Module:  
 Base Vol: 153 68 0 0 0 43 55 61 0 242 0 0 0 0  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 153 68 0 0 0 43 55 61 0 242 0 0 0 0  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86  
 PHF Volume: 178 79 0 0 0 50 64 71 0 281 0 0 0 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 178 79 0 0 0 50 64 71 0 281 0 0 0 0  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 178 79 0 0 0 50 64 71 0 281 0 0 0 0  
 -----  
 Saturation Flow Module:  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 0.69 0.31 0.00 0.00 0.44 0.56 1.00 0.00 1.00 0.00 0.00 0.00  
 Final Sat.: 481 214 0 0 0 317 405 595 0 740 0 0 0 0  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.37 0.37 xxxx xxxx 0.16 0.16 0.12 xxxx 0.38 xxxx xxxx xxxx  
 Crit Moves: \*\*\*\*  
 Delay/Veh: 10.7 10.7 0.0 0.0 8.5 8.5 9.3 0.0 10.0 0.0 0.0 0.0  
 Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 AdjDel/Veh: 10.7 10.7 0.0 0.0 8.5 8.5 9.3 0.0 10.0 0.0 0.0 0.0  
 LOS by Move: B B \* \* A A A \* B \* \* \*  
 ApproachDel: 10.7 8.5 9.9  
 Delay Adj: 1.00 1.00  
 ApprAdjDel: 10.7 8.5 9.9  
 LOS by Appr: B A A A \*  
 AllWayAvgQ: 0.5 0.5 0.5 0.2 0.2 0.2 0.1 0.0 0.5 0.0 0.0 0.0  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*

City of Rocklin General Plan Update  
Existing Conditions (2008)  
PM Peak Hour LOS

-----  
 Level Of Service Computation Report  
 2000 HCM Unsignalized Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #308 Barton Rd & Brace Rd  
 \*\*\*\*\*  
 Average Delay (sec/veh): 6.9 Worst Case Level Of Service: B[ 15.0]  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Stop Sign Stop Sign Uncontrolled Uncontrolled  
 Rights: Include Include Include Include  
 Lanes: 0 0 1! 0 0 0 0 0 0 0 0 1 0 0 1 0 0 0 0 0  
 -----  
 Volume Module:  
 Base Vol: 143 0 72 0 0 0 0 0 64 150 114 57 0  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 143 0 72 0 0 0 0 0 64 150 114 57 0  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90  
 PHF Volume: 159 0 80 0 0 0 0 0 71 167 127 63 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
 FinalVolume: 159 0 80 0 0 0 0 0 71 167 127 63 0  
 -----  
 Critical Gap Module:  
 Critical Gp: 6.4 6.5 6.2 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 4.1 xxxxx xxxxx  
 FollowUpTim: 3.5 4.0 3.3 xxxxxx xxxxx xxxxxx xxxxxx xxxxx xxxxxx 2.2 xxxxx xxxxxx  
 -----  
 Capacity Module:  
 Cnflct Vol: 471 471 154 xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 238 xxxxx xxxxxx  
 Potent Cap.: 555 494 897 xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 1341 xxxxx xxxxxx  
 Move Cap.: 512 444 897 xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 1341 xxxxx xxxxxx  
 Volume/Cap: 0.31 0.00 0.09 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx 0.09 xxxxx xxxxx  
 -----  
 Level Of Service Module:  
 2Way95thQ: xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 0.3 xxxxx xxxxxx  
 Control Del: xxxxxx xxxxx xxxxxx xxxxxx xxxxx xxxxxx xxxxxx xxxxx xxxxxx 8.0 xxxxx xxxxxx  
 LOS by Move: \* \* \* \* \* \* \* \* \* \* A \* \* \*  
 Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT  
 Shared Cap.: xxxxx 598 xxxxxx xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx  
 SharedQueue: xxxxxx 1.9 xxxxxx xxxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 0.3 xxxxx xxxxxx  
 Shrd ConDel: xxxxxx 15.0 xxxxxx xxxxxx xxxxx xxxxxx xxxxx xxxxx xxxxxx 8.0 xxxxx xxxxxx  
 Shared LOS: \* B \* \* \* \* \* \* \* \* \* \* A \* \* \*  
 ApproachDel: 15.0 xxxxxxx xxxxxxx xxxxxxx  
 ApproachLOS: B \* \* \* \* \* \* \* \* \* \*  
 \*\*\*\*\*  
 Note: Queue reported is the number of cars per lane.  
 \*\*\*\*\*



City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C	
#401 Pleasant Grove & Fairway	B xxxxx	0.680	B xxxxx	0.680	+ 0.000 V/C
#402 Stanford Ranch & Fairway	A xxxxx	0.598	A xxxxx	0.598	+ 0.000 V/C
#403 Stanford Ranch & Five Star	A xxxxx	0.590	A xxxxx	0.590	+ 0.000 V/C
#404 Pleasant Grove & Roseville Pkw	C xxxxx	0.718	C xxxxx	0.718	+ 0.000 V/C
#405 Galleria & Roseville Pkwy	D xxxxx	0.813	D xxxxx	0.813	+ 0.000 V/C
#406 Roseville Parkway & Taylor	B xxxxx	0.656	B xxxxx	0.656	+ 0.000 V/C
#407 Roseville Parkway & N. Sunrise	C xxxxx	0.746	C xxxxx	0.746	+ 0.000 V/C
#408 Sierra College & Secret Ravine	A xxxxx	0.455	A xxxxx	0.455	+ 0.000 V/C

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #401 Pleasant Grove & Fairway  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.680  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 71 Level Of Service: B

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ovl			Ovl			Ovl			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	2	0	1	1	0	2	0	1	2	0

Volume Module:

Base Vol:	527	951	380	109	602	116	176	314	295	488	323	123
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	527	951	380	109	602	116	176	314	295	488	323	123
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	527	951	380	109	602	116	176	314	295	488	323	123
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	527	951	380	109	602	116	176	314	295	488	323	123
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	527	951	380	109	602	116	176	314	295	488	323	123

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2.00	2.00	1.00	1.00	2.00	1.00	2.00	2.00	1.00	2.00	2.00	1.00
Final Sat.:	2900	2900	1450	1450	2900	1450	2900	2900	1450	2900	2900	1450

Capacity Analysis Module:

Vol/Sat:	0.18	0.33	0.26	0.08	0.21	0.08	0.06	0.11	0.20	0.17	0.11	0.08
Crit Volume:	476			109			157			244		
Crit Moves:	****			****			****			****		

\*\*\*\*\*



City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #402 Stanford Ranch & Fairway  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.598  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 57 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #403 Stanford Ranch & Five Star  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.590  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 56 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 3 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 3 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 3 rows (Vol/Sat, Crit Volume, Crit Moves).

EX PM Fri May 22, 2009 10:11:28 Page 6-1

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #404 Pleasant Grove & Roseville Pkwy  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.718  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 81 Level Of Service: C

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ignore			Ignore			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	3	0	2	0	1	2	0	3	0	1	3	0

Volume Module:

Base Vol:	1253	324	599	142	236	35	36	1160	676	473	1360	94
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	1253	324	599	142	236	35	36	1160	676	473	1360	94
User Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Volume:	1253	324	0	142	236	0	36	1160	0	473	1360	0
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	1253	324	0	142	236	0	36	1160	0	473	1360	0
PCE Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
MLF Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
FinalVolume:	1253	324	0	142	236	0	36	1160	0	473	1360	0

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	3.00	2.00	1.00	2.00	3.00	1.00	2.00	3.00	1.00	3.00	3.00	1.00
Final Sat.:	4350	2900	1450	2900	4350	1450	2900	4350	1450	4350	4350	1450

Capacity Analysis Module:

Vol/Sat:	0.29	0.11	0.00	0.05	0.05	0.00	0.01	0.27	0.00	0.11	0.31	0.00
Crit Volume:	418			79			387			158		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

EX PM Fri May 22, 2009 10:11:28 Page 7-1

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #405 Galleria & Roseville Pkwy  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.813  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 122 Level Of Service: D

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ignore			Ignore			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	3	0	1	3	0	2	0	1	2	0

Volume Module:

Base Vol:	476	704	27	682	558	351	347	886	347	94	1464	717
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	476	704	27	682	558	351	347	886	347	94	1464	717
User Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Volume:	476	704	0	682	558	0	347	886	0	94	1464	0
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	476	704	0	682	558	0	347	886	0	94	1464	0
PCE Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
MLF Adj:	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
FinalVolume:	476	704	0	682	558	0	347	886	0	94	1464	0

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2.00	3.00	1.00	3.00	2.00	1.00	2.00	3.00	1.00	2.00	3.00	1.00
Final Sat.:	2900	4350	1450	4350	2900	1450	2900	4350	1450	2900	4350	1450

Capacity Analysis Module:

Vol/Sat:	0.16	0.16	0.00	0.16	0.19	0.00	0.12	0.20	0.00	0.03	0.34	0.00
Crit Volume:	238			279			174			488		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #406 Roseville Parkway & Taylor

Cycle (sec): 120 Critical Vol./Cap.(X): 0.656  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 66 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected), Rights (Ovl), Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #407 Roseville Parkway & N. Sunrise

Cycle (sec): 120 Critical Vol./Cap.(X): 0.746  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 90 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected), Rights (Ovl), Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Roseville Intersections: Existing Conditions  
PM Peak Hour LOS

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #408 Sierra College & Secret Ravine  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.455  
Loss Time (sec): 9 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Permitted			Permitted		
Rights:	Ovl			Ovl			Ovl			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	0	0	1	0	1	0	0

Volume Module:

Base Vol:	198	884	3	1	704	117	124	2	131	3	5	3
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	198	884	3	1	704	117	124	2	131	3	5	3
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	198	884	3	1	704	117	124	2	131	3	5	3
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	198	884	3	1	704	117	124	2	131	3	5	3
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	198	884	3	1	704	117	124	2	131	3	5	3

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	1.00	1.00	2.00	1.00	0.96	0.04	1.00	0.38	0.62	1.00
Final Sat.:	1500	3000	1500	1500	3000	1500	1447	53	1500	563	938	1500

Capacity Analysis Module:

Vol/Sat:	0.13	0.29	0.00	0.00	0.23	0.08	0.09	0.04	0.09	0.01	0.01	0.00
Crit Volume:	198			352			124			8		
Crit Moves:	****			****			****			****		

**INTERSECTION LOS WORKSHEETS  
EXISTING PLUS PROJECT CONDITIONS**

---



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
# 1 Granite Dr & Rocklin Rd	D	xxxxx 0.878	D	xxxxx 0.878	+ 0.000 V/C
# 2 Granite Dr & Sierra College Bl	A	xxxxx 0.463	A	xxxxx 0.463	+ 0.000 V/C
# 3 Granite Dr & Sierra Meadows	B	xxxxx 0.622	B	xxxxx 0.622	+ 0.000 V/C
# 4 Pacific St & Del Mar/ Domingue	E	xxxxx 0.902	E	xxxxx 0.902	+ 0.000 V/C
# 5 Pacific St & Farron St	D	xxxxx 0.809	D	xxxxx 0.809	+ 0.000 V/C
# 6 Pacific St & Midas Ave	A	xxxxx 0.579	A	xxxxx 0.579	+ 0.000 V/C
# 7 Pacific St & Rocklin Rd	C	xxxxx 0.787	C	xxxxx 0.787	+ 0.000 V/C
# 8 Pacific St & Sierra Meadows	B	xxxxx 0.612	B	xxxxx 0.612	+ 0.000 V/C
# 9 Pacific St & Woodside Dr	A	xxxxx 0.554	A	xxxxx 0.554	+ 0.000 V/C
# 10 Rocklin Rd & Aguilar Rd	A	xxxxx 0.462	A	xxxxx 0.462	+ 0.000 V/C
# 11 Rocklin Rd & El Don Dr	A	xxxxx 0.450	A	xxxxx 0.450	+ 0.000 V/C
# 12 Rocklin Rd & Fire Station No 1	A	xxxxx 0.418	A	xxxxx 0.418	+ 0.000 V/C
# 13 Rocklin Rd & Havenhurst Cir	A	xxxxx 0.306	A	xxxxx 0.306	+ 0.000 V/C
# 14 Rocklin Rd & Sierra College Bl	A	xxxxx 0.493	A	xxxxx 0.493	+ 0.000 V/C
# 15 Rocklin Rd & South Grove St	B	xxxxx 0.636	B	xxxxx 0.636	+ 0.000 V/C
# 16 Sierra College Bl & El Don Dr	A	xxxxx 0.373	A	xxxxx 0.373	+ 0.000 V/C
# 17 Sierra College Bl & Nightwatch	A	xxxxx 0.351	A	xxxxx 0.351	+ 0.000 V/C
# 18 Sierra College Bl & Scarboroug	A	xxxxx 0.408	A	xxxxx 0.408	+ 0.000 V/C
# 19 Sierra College Bl & Southside	A	xxxxx 0.297	A	xxxxx 0.297	+ 0.000 V/C
# 20 Sunset Bl & Pacific St	C	xxxxx 0.725	C	xxxxx 0.725	+ 0.000 V/C
# 21 Sunset Bl & Springview Dr	F	xxxxx 1.084	F	xxxxx 1.084	+ 0.000 V/C
# 22 Sunset Bl & Topaz Ave	A	xxxxx 0.559	A	xxxxx 0.559	+ 0.000 V/C
# 23 Sunset Bl & Whitney Bl	C	xxxxx 0.744	C	xxxxx 0.744	+ 0.000 V/C
#101 Blue Oaks Bl & Lonetree	B	xxxxx 0.671	B	xxxxx 0.671	+ 0.000 V/C

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
#102 Blue Oaks Bl & Market Place	A	xxxxx 0.296	A	xxxxx 0.296	+ 0.000 V/C
#103 Blue Oaks Bl & Van Buren Way	A	xxxxx 0.351	A	xxxxx 0.351	+ 0.000 V/C
#104 Five Star & Destiny Dr	A	xxxxx 0.416	A	xxxxx 0.416	+ 0.000 V/C
#105 Lonetree Bl & Adams Dr	A	xxxxx 0.537	A	xxxxx 0.537	+ 0.000 V/C
#106 Lonetree Bl & Atherton Rd	A	xxxxx 0.480	A	xxxxx 0.480	+ 0.000 V/C
#107 Lonetree Bl & Grand Canyon Dr	B	xxxxx 0.654	B	xxxxx 0.654	+ 0.000 V/C
#108 Lonetree Bl & Redwood Dr	B	xxxxx 0.632	B	xxxxx 0.632	+ 0.000 V/C
#109 Lonetree Bl & West Oaks Bl	A	xxxxx 0.521	A	xxxxx 0.521	+ 0.000 V/C
#110 Park Dr & Blaydon Rd	B	xxxxx 0.646	B	xxxxx 0.646	+ 0.000 V/C
#111 Park Dr & Quarry Way	A	xxxxx 0.578	A	xxxxx 0.578	+ 0.000 V/C
#112 Park Dr & Farrier Rd	B	xxxxx 0.673	B	xxxxx 0.673	+ 0.000 V/C
#113 Park Dr & King Pine Dr	A	xxxxx 0.492	A	xxxxx 0.492	+ 0.000 V/C
#114 Park Dr & Shelton	A	xxxxx 0.355	A	xxxxx 0.355	+ 0.000 V/C
#115 Park Dr & Victory Lane	A	xxxxx 0.436	A	xxxxx 0.436	+ 0.000 V/C
#116 Park Dr & Wykford Bl	B	xxxxx 0.608	B	xxxxx 0.608	+ 0.000 V/C
#117 Park Dr & Twin Oaks/ Boardwalk	A	xxxxx 0.534	A	xxxxx 0.534	+ 0.000 V/C
#118 Park Dr & Safeway	B	xxxxx 0.627	B	xxxxx 0.627	+ 0.000 V/C
#119 South Whitney & Five Star Bl	A	xxxxx 0.510	A	xxxxx 0.510	+ 0.000 V/C
#120 Spring Creek Dr & Broken Rail	A	xxxxx 0.034	A	xxxxx 0.034	+ 0.000 V/C
#121 Stanford Ranch Rd & Cobbleston	A	xxxxx 0.529	A	xxxxx 0.529	+ 0.000 V/C
#122 Stanford Ranch Rd & Darby Rd	A	xxxxx 0.415	A	xxxxx 0.415	+ 0.000 V/C
#123 Stanford Ranch Rd & Park Dr	C	xxxxx 0.733	C	xxxxx 0.733	+ 0.000 V/C
#124 Stanford Ranch Rd & Plaza	B	xxxxx 0.609	B	xxxxx 0.609	+ 0.000 V/C
#125 Stanford Ranch Rd & Stoney Dr	A	xxxxx 0.534	A	xxxxx 0.534	+ 0.000 V/C
#126 Stanford Ranch Rd & Victory Ln	A	xxxxx 0.590	A	xxxxx 0.590	+ 0.000 V/C

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Intersection	Base		Future		Change in
	LOS	Del/ Veh V/ C	LOS	Del/ Veh V/ C	
#127 Stanford Ranch Rd & West Oaks	A	xxxxx 0.533	A	xxxxx 0.533	+ 0.000 V/C
#128 Sunset Bl & Atherton	A	xxxxx 0.565	A	xxxxx 0.565	+ 0.000 V/C
#129 Sunset Bl & Blue Oaks Bl	C	xxxxx 0.747	C	xxxxx 0.747	+ 0.000 V/C
#130 Sunset Bl & Fairway Dr	A	xxxxx 0.564	A	xxxxx 0.564	+ 0.000 V/C
#131 Sunset Bl & Little Rock	A	xxxxx 0.441	A	xxxxx 0.441	+ 0.000 V/C
#132 Sunset Bl & Park Dr	C	xxxxx 0.740	C	xxxxx 0.740	+ 0.000 V/C
#133 Sunset Bl & Pebble Creek	A	xxxxx 0.483	A	xxxxx 0.483	+ 0.000 V/C
#134 Sunset Bl & Stanford Ranch Rd	D	xxxxx 0.801	D	xxxxx 0.801	+ 0.000 V/C
#135 Sunset Bl & West Oaks Bl	E	xxxxx 0.957	E	xxxxx 0.957	+ 0.000 V/C
#136 W Stanford Ranch Rd & Sunset B	B	xxxxx 0.635	B	xxxxx 0.635	+ 0.000 V/C
#137 W Stanford Ranch Rd & Wildcat	C	xxxxx 0.730	C	xxxxx 0.730	+ 0.000 V/C
#138 Whitney Ranch Pkwy & Bridlewoo	A	xxxxx 0.302	A	xxxxx 0.302	+ 0.000 V/C
#139 Whitney Ranch Pkwy & Painted P	A	xxxxx 0.207	A	xxxxx 0.207	+ 0.000 V/C
#140 Whitney Ranch Pkwy & Spring Cr	A	xxxxx 0.191	A	xxxxx 0.191	+ 0.000 V/C
#141 Wildcat Bl & Bridlewood Dr	A	xxxxx 0.487	A	xxxxx 0.487	+ 0.000 V/C
#142 Wildcat Bl & Whitney Ranch Pkw	A	xxxxx 0.592	A	xxxxx 0.592	+ 0.000 V/C
#143 Wildcat Bl & S High School Ent	B	xxxxx 0.628	B	xxxxx 0.628	+ 0.000 V/C
#144 Wildcat Bl & N High School Ent	A	xxxxx 0.176	A	xxxxx 0.176	+ 0.000 V/C
#145 Wildcat Bl & Ranch View Dr	A	xxxxx 0.263	A	xxxxx 0.263	+ 0.000 V/C
#152 Stanford Ranch Rd & Crest Dr	D	xxxxx 0.864	D	xxxxx 0.864	+ 0.000 V/C
#153 Whitney Blvd & Crest Dr	C	xxxxx 0.739	C	xxxxx 0.739	+ 0.000 V/C
#154 Park Dr & Crest Dr	A	xxxxx 0.328	A	xxxxx 0.328	+ 0.000 V/C
#161 Granite Dr & Dominguez Dr	D	xxxxx 0.817	D	xxxxx 0.817	+ 0.000 V/C
#162 Sierra College Bl & Dominguez	A	xxxxx 0.586	A	xxxxx 0.586	+ 0.000 V/C
#163 Park Dr & Valley View Pkwy	A	xxxxx 0.516	A	xxxxx 0.516	+ 0.000 V/C

Traffix 8.0.0715 (c) 2008 Dowling Assoc. Licensed to DKS ASSOC., SACRAMENTO

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Intersection	Base		Future		Change in
	LOS	Del/ Veh V/ C	LOS	Del/ Veh V/ C	
#164 Nature Trail Wy & Valley View	B	xxxxx 0.621	B	xxxxx 0.621	+ 0.000 V/C
#165 Sierra College Bl & Valley Vie	A	xxxxx 0.381	A	xxxxx 0.381	+ 0.000 V/C
#166 University Ave & Whitney Ranch	A	xxxxx 0.379	A	xxxxx 0.379	+ 0.000 V/C
#167 West Oaks Bl & Whitney Ranch P	A	xxxxx 0.507	A	xxxxx 0.507	+ 0.000 V/C
#168 West Oaks Bl & Painted Pony Ln	A	xxxxx 0.265	A	xxxxx 0.265	+ 0.000 V/C
#169 Laredo Dr & Whitney Ranch Pkwy	D	xxxxx 0.819	D	xxxxx 0.819	+ 0.000 V/C
#170 Rocklin Rd & Civic Centr Dr	A	xxxxx 0.560	A	xxxxx 0.560	+ 0.000 V/C
#171 Pacific St & Civic Center Dr	A	xxxxx 0.520	A	xxxxx 0.520	+ 0.000 V/C
#201 Rocklin Rd & I-80 EB	C	31.8 0.881	C	31.8 0.881	+ 0.000 D/V
#202 Rocklin Rd & I-80 WB	C	23.7 0.817	C	23.7 0.817	+ 0.000 D/V
#203 Sierra College Bl & I-80 WB	C	26.8 0.590	C	26.8 0.590	+ 0.000 D/V
#204 Sierra College Bl & I-80 EB	C	28.4 0.408	C	28.4 0.408	+ 0.000 D/V
#205 SR 65 & Sunset Blvd	E	71.3 1.097	E	71.3 1.097	+ 0.000 D/V
#208 Whitney Ranch Pkwy & SR 65 SB	B	16.7 0.566	B	16.7 0.566	+ 0.000 D/V
#209 Whitney Ranch Pkwy & SR 65 NB	A	9.6 0.494	A	9.6 0.494	+ 0.000 D/V
#210 Blue Oaks Blvd & SR 65 SB	C	25.7 0.519	C	25.7 0.519	+ 0.000 D/V
#211 Blue Oaks Blvd & SR 65 NB Off	A	7.4 0.642	A	7.4 0.642	+ 0.000 D/V
#212 Pleasant Grove Blvd & SR 65 NB	E	79.4 1.175	E	79.4 1.175	+ 0.000 D/V
#213 Pleasant Grove Blvd & SR 65 SB	C	28.3 1.016	C	28.3 1.016	+ 0.000 D/V
#214 Stanford Ranch Rd & SR 65 NB	C	30.4 0.998	C	30.4 0.998	+ 0.000 D/V
#215 Stanford Ranch Rd & SR 65 SB	D	50.9 1.129	D	50.9 1.129	+ 0.000 D/V
#301 Sierra College Bl & Brace Rd	B	18.1 0.569	B	18.1 0.569	+ 0.000 D/V
#302 Sierra College Bl & Taylor Rd	E	72.4 1.095	E	72.4 1.095	+ 0.000 D/V
#304 Sierra College Bl & King Rd	C	28.7 0.760	C	28.7 0.760	+ 0.000 D/V
#305 Taylor Rd & King Rd	C	30.7 0.523	C	30.7 0.523	+ 0.000 D/V

Traffix 8.0.0715 (c) 2008 Dowling Assoc. Licensed to DKS ASSOC., SACRAMENTO



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Intersection	Base		Future		Change in
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C	
#306 Taylor Rd & Horseshoe Bar	D 35.8	0.842	D 35.8	0.842	+ 0.000 D/V
#501 E Lincoln Pkwy & Twelve Bridge	A xxxxx	0.528	A xxxxx	0.528	+ 0.000 V/C
#502 Sierra College & Twelve Bridge	C 16.4	0.236	C 16.4	0.236	+ 0.000 D/V
#601 Sierra College & English Colon	F 244.2	1.182	F 244.2	1.182	+ 0.000 D/V

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1 Granite Dr & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.878  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: D

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Ovl			Include			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	0	1	0	1	1	0	1

-----

Volume Module:

Base Vol:	30	17	15	628	19	237	227	1762	10	32	819	558
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	30	17	15	628	19	237	227	1762	10	32	819	558
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
PHF Volume:	30	17	15	628	19	237	227	1762	10	32	819	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	30	17	15	628	19	237	227	1762	10	32	819	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
FinalVolume:	30	17	15	628	19	237	227	1762	10	32	819	0

-----

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.53	0.47	1.94	0.06	1.00	1.00	1.99	0.01	1.00	2.00	1.00
Final Sat.:	1450	770	680	2815	85	1450	1450	2884	16	1450	2900	1450

-----

Capacity Analysis Module:

Vol/Sat:	0.02	0.02	0.02	0.22	0.22	0.16	0.16	0.61	0.61	0.02	0.28	0.00
Crit Volume:	32			324				886		32		
Crit Moves:	***			***				***		***		

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #2 Granite Dr & Sierra College Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.463  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 42 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 3 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 89 686 100 53 769 90 254 32 242 205 27 24  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 89 686 100 53 769 90 254 32 242 205 27 24  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 89 686 100 53 769 90 254 32 242 205 27 24  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 89 686 100 53 769 90 254 32 242 205 27 24  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 89 686 100 53 769 90 254 32 242 205 27 24

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.62 0.38 1.00 3.00 1.00 1.00 1.00 2.00 1.00 1.00 1.00  
Final Sat.: 1450 3797 553 1450 4350 1450 1450 1450 2900 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.06 0.18 0.18 0.04 0.18 0.06 0.18 0.02 0.08 0.14 0.02 0.02  
Crit Volume: 89 256 121 205  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #3 Granite Dr & Sierra Meadows  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.622  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 60 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 1 0 1 0 0 1 0 1 0 1 1 0 0

Volume Module:  
Base Vol: 104 65 45 54 55 317 210 309 53 61 366 55  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 104 65 45 54 55 317 210 309 53 61 366 55  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 104 65 45 54 55 317 210 309 53 61 366 55  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 104 65 45 54 55 317 210 309 53 61 366 55  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 104 65 45 54 55 317 210 309 53 61 366 55

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.59 0.41 1.00 0.15 0.85 1.00 1.71 0.29 1.00 1.74 0.26  
Final Sat.: 1450 857 593 1450 214 1236 1450 2475 425 1450 2521 379

Capacity Analysis Module:  
Vol/Sat: 0.07 0.08 0.08 0.04 0.26 0.26 0.14 0.12 0.12 0.04 0.15 0.15  
Crit Volume: 110 372 210 211  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #4 Pacific St & Del Mar/ Dominguez  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.902  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 2 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 119 686 169 35 542 72 263 331 371 144 103 88  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 119 686 169 35 542 72 263 331 371 144 103 88  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 119 686 169 35 542 72 263 331 371 144 103 88  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 119 686 169 35 542 72 263 331 371 144 103 88  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 119 686 169 35 542 72 263 331 371 144 103 88

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.60 0.40 1.00 2.00 1.00 1.00 0.47 0.53 1.00 1.00 1.00  
Final Sat.: 1450 2327 573 1450 2900 1450 1450 684 766 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.08 0.29 0.29 0.02 0.19 0.05 0.18 0.48 0.48 0.10 0.07 0.06  
Crit Volume: 428 35 702 144  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #5 Pacific St & Farron St  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.809  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 119 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 2 0 1 1 0 0 1 0 1 0

Volume Module:  
Base Vol: 218 1151 30 104 1091 47 39 12 327 70 6 47  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 218 1151 30 104 1091 47 39 12 327 70 6 47  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 218 1151 30 104 1091 47 39 12 327 70 6 47  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 218 1151 30 104 1091 47 39 12 327 70 6 47  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 218 1151 30 104 1091 47 39 12 327 70 6 47

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.95 0.05 1.00 2.00 1.00 1.00 0.04 0.96 1.00 0.11 0.89  
Final Sat.: 1450 2826 74 1450 2900 1450 1450 51 1399 1450 164 1286

Capacity Analysis Module:  
Vol/Sat: 0.15 0.41 0.41 0.07 0.38 0.03 0.03 0.23 0.23 0.05 0.04 0.04  
Crit Volume: 218 546 339 70  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #6 Pacific St & Midas Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.579  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 54 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 2 0 1 1 0 1 1 0 1

Volume Module:  
Base Vol: 135 575 16 166 703 374 277 136 101 8 53 12  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 135 575 16 166 703 374 277 136 101 8 53 12  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 135 575 16 166 703 374 277 136 101 8 53 12  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 135 575 16 166 703 374 277 136 101 8 53 12  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 135 575 16 166 703 374 277 136 101 8 53 12

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.95 0.05 1.00 2.00 1.00 1.00 1.15 0.85 1.00 1.00 1.00  
Final Sat.: 1450 2821 79 1450 2900 1450 1450 1664 1236 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.09 0.20 0.20 0.11 0.24 0.26 0.19 0.08 0.08 0.01 0.04 0.01  
Crit Volume: 135 374 277 53  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #7 Pacific St & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.787  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 107 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Ovl Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 1 1 0 1 0 1 1 0 0 1

Volume Module:  
Base Vol: 67 452 707 217 579 56 75 375 58 497 221 187  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 67 452 707 217 579 56 75 375 58 497 221 187  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 67 452 707 217 579 56 75 375 58 497 221 187  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 67 452 707 217 579 56 75 375 58 497 221 187  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 67 452 707 217 579 56 75 375 58 497 221 187

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 1.82 0.18 1.00 1.73 0.27 1.38 0.62 1.00  
Final Sat.: 1450 2900 1450 1450 2644 256 1450 2512 388 2007 893 1450

Capacity Analysis Module:  
Vol/Sat: 0.05 0.16 0.49 0.15 0.22 0.22 0.05 0.15 0.15 0.25 0.25 0.13  
Crit Volume: 707 217 217 0  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #8 Pacific St & Sierra Meadows  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.612  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 59 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0

Volume Module:  
Base Vol: 25 829 107 185 880 10 6 19 26 123 44 146  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 25 829 107 185 880 10 6 19 26 123 44 146  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 25 829 107 185 880 10 6 19 26 123 44 146  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 25 829 107 185 880 10 6 19 26 123 44 146  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 25 829 107 185 880 10 6 19 26 123 44 146

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.77 0.23 1.00 1.98 0.02 1.00 0.42 0.58 1.00 0.23 0.77  
Final Sat.: 1450 2568 332 1450 2867 33 1450 612 838 1450 336 1114

Capacity Analysis Module:  
Vol/Sat: 0.02 0.32 0.32 0.13 0.31 0.31 0.00 0.03 0.03 0.08 0.13 0.13  
Crit Volume: 468 185 45 190  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #9 Pacific St & Woodside Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.554  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 51 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 1 0 0 0 1

Volume Module:  
Base Vol: 0 1122 147 99 961 0 0 0 0 0 171 0 79  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 1122 147 99 961 0 0 0 0 0 171 0 79  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 1122 147 99 961 0 0 0 0 0 171 0 79  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 1122 147 99 961 0 0 0 0 0 171 0 79  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 1122 147 99 961 0 0 0 0 0 171 0 79

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 3000 1500 1500 3000 0 0 0 0 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.37 0.10 0.07 0.32 0.00 0.00 0.00 0.00 0.11 0.00 0.05  
Crit Volume: 561 99 0 171  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #10 Rocklin Rd & Aguilar Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.462
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 42 Level Of Service: A

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #11 Rocklin Rd & El Don Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.450
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 41 Level Of Service: A

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #12 Rocklin Rd & Fire Station No 1  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.418  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 0 1 0 0 1 0 0 0 1 0 2 0 0 1 0 2 0 0

Volume Module:  
Base Vol: 0 0 0 0 0 0 0 0 1339 0 0 840 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 0 0 0 0 0 0 0 1339 0 0 840 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 0 0 0 0 0 0 0 1339 0 0 840 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 0 0 0 0 0 0 0 1339 0 0 840 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 0 0 0 0 0 0 0 1339 0 0 840 0

Saturation Flow Module:  
Sat/Lane: 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 1.00 0.00 0.00 1.00 0.00 1.00 2.00 0.00 1.00 2.00 0.00  
Final Sat.: 0 1600 0 0 1600 0 1600 3200 0 1600 3200 0

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.42 0.00 0.00 0.26 0.00  
Crit Volume: 0 0 0 0 0 0 0 670 0 0 0 0  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #13 Rocklin Rd & Havenhurst Cir  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.306  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Ovl  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 1 0 0 1 1 0 2 1 0 1 0 2 1 0 1 0 2 1 0

Volume Module:  
Base Vol: 15 0 4 78 1 41 46 981 27 9 600 61  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 15 0 4 78 1 41 46 981 27 9 600 61  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 15 0 4 78 1 41 46 981 27 9 600 61  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 15 0 4 78 1 41 46 981 27 9 600 61  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 15 0 4 78 1 41 46 981 27 9 600 61

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.79 0.00 0.21 0.99 0.01 1.00 1.00 2.92 0.08 1.00 2.72 0.28  
Final Sat.: 1145 0 305 1432 18 1450 1450 4233 117 1450 3949 401

Capacity Analysis Module:  
Vol/Sat: 0.01 0.00 0.01 0.05 0.05 0.03 0.03 0.23 0.23 0.01 0.15 0.15  
Crit Volume: 19 79 336 9  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\* Intersection #14 Rocklin Rd & Sierra College Bl \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.493
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 45 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Ovl Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 2 0 3 0 1 2 0 3 0 1 2 0 2 0 1 2 0 1 1 0

Volume Module:
Base Vol: 353 632 87 203 609 76 2 314 486 51 136 96
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 353 632 87 203 609 76 2 314 486 51 136 96
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 353 632 87 203 609 76 2 314 486 51 136 96
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 353 632 87 203 609 76 2 314 486 51 136 96
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 353 632 87 203 609 76 2 314 486 51 136 96

Saturation Flow Module:
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 2.00 2.00 1.00 2.00 1.17 0.83
Final Sat.: 2900 4350 1450 2900 4350 1450 2900 2900 1450 2900 1700 1200

Capacity Analysis Module:
Vol/Sat: 0.12 0.15 0.06 0.07 0.14 0.05 0.00 0.11 0.34 0.02 0.08 0.08
Crit Volume: 0 203 486 25
Crit Moves: \*\*\*\* \*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\* Intersection #15 Rocklin Rd & South Grove St \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.636
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 63 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 0 0 1 0 0 0 0 0 0 0 0 0 1 1 0 1 0 2 0 0

Volume Module:
Base Vol: 26 0 162 0 0 0 0 0 1262 34 144 871 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 26 0 162 0 0 0 0 0 1262 34 144 871 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 26 0 162 0 0 0 0 0 1262 34 144 871 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 26 0 162 0 0 0 0 0 1262 34 144 871 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 26 0 162 0 0 0 0 0 1262 34 144 871 0

Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 1.95 0.05 1.00 2.00 0.00
Final Sat.: 1500 0 1500 0 0 0 0 2921 79 1500 3000 0

Capacity Analysis Module:
Vol/Sat: 0.02 0.00 0.11 0.00 0.00 0.00 0.00 0.43 0.43 0.10 0.29 0.00
Crit Volume: 162 0 648 144
Crit Moves: \*\*\*\* \*\*\*\*



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #16 Sierra College Bl & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.373  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 3 0 1 1 0 3 0 1 0 0 1 0 0 0 0 0 0 0

Volume Module:  
Base Vol: 45 969 5 19 1168 19 18 2 29 21 3 33  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 45 969 5 19 1168 19 18 2 29 21 3 33  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 45 969 5 19 1168 19 18 2 29 21 3 33  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 45 969 5 19 1168 19 18 2 29 21 3 33  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 45 969 5 19 1168 19 18 2 29 21 3 33

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 3.00 1.00 1.00 3.00 1.00 0.37 0.04 0.59 0.37 0.05 0.58  
Final Sat.: 1450 4350 1450 1450 4350 1450 533 59 858 534 76 839

Capacity Analysis Module:  
Vol/Sat: 0.03 0.22 0.00 0.01 0.27 0.01 0.03 0.03 0.03 0.04 0.04 0.04  
Crit Volume: 45 389 49 57  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #17 Sierra College Bl & Nightwatch  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.351  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 35 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 3 0 0 0 0 3 0 1 1 0 0 0 1 0 0 0 0 0

Volume Module:  
Base Vol: 62 931 0 0 1105 92 90 0 96 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 62 931 0 0 1105 92 90 0 96 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 62 931 0 0 1105 92 90 0 96 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 62 931 0 0 1105 92 90 0 96 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 62 931 0 0 1105 92 90 0 96 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 3.00 0.00 0.00 3.00 1.00 1.00 0.00 1.00 0.00 0.00 0.00  
Final Sat.: 1500 4500 0 0 4500 1500 1500 0 1500 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.04 0.21 0.00 0.00 0.25 0.06 0.06 0.00 0.06 0.00 0.00 0.00  
Crit Volume: 62 368 96 0  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #18 Sierra College Bl & Scarborough

Cycle (sec): 100 Critical Vol./Cap.(X): 0.408
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 38 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 3 0 1 1 0 3 0 1 1 0 1 0 1 1 0

Volume Module:
Base Vol: 72 1009 1 4 1179 49 27 0 122 4 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 72 1009 1 4 1179 49 27 0 122 4 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 72 1009 1 4 1179 49 27 0 122 4 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 72 1009 1 4 1179 49 27 0 122 4 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 72 1009 1 4 1179 49 27 0 122 4 0 0

Saturation Flow Module:
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 3.00 1.00 1.00 3.00 1.00 1.00 1.00 1.00 1.00 2.00 0.00
Final Sat.: 1450 4350 1450 1450 4350 1450 1450 1450 1450 2900 0

Capacity Analysis Module:
Vol/Sat: 0.05 0.23 0.00 0.00 0.27 0.03 0.02 0.00 0.08 0.00 0.00 0.00
Crit Volume: 72 393 122 4
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #19 Sierra College Bl & Southside Ranch

Cycle (sec): 100 Critical Vol./Cap.(X): 0.297
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 32 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 3 0 1 1 0 3 0 1 0 0 1 0 0 0 0 1 0 0

Volume Module:
Base Vol: 6 1001 1 5 1122 30 23 0 24 1 0 3
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 6 1001 1 5 1122 30 23 0 24 1 0 3
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 6 1001 1 5 1122 30 23 0 24 1 0 3
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 6 1001 1 5 1122 30 23 0 24 1 0 3
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 6 1001 1 5 1122 30 23 0 24 1 0 3

Saturation Flow Module:
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 3.00 1.00 1.00 3.00 1.00 0.49 0.00 0.51 0.25 0.00 0.75
Final Sat.: 1450 4350 1450 1450 4350 1450 710 0 740 363 0 1088

Capacity Analysis Module:
Vol/Sat: 0.00 0.23 0.00 0.00 0.26 0.02 0.03 0.00 0.03 0.00 0.00 0.00
Crit Volume: 6 374 47 4
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #20 Sunset Bl & Pacific St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.725
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 83 Level Of Service: C

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #21 Sunset Bl & Springview Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 1.084
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #22 Sunset Bl & Topaz Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.559  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 42 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 0 1 0 0 1 0 2 1 0 1 0 2 1 0

Volume Module:  
Base Vol: 24 15 20 101 14 113 95 1218 23 68 1378 97  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 24 15 20 101 14 113 95 1218 23 68 1378 97  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 24 15 20 101 14 113 95 1218 23 68 1378 97  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 24 15 20 101 14 113 95 1218 23 68 1378 97  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 24 15 20 101 14 113 95 1218 23 68 1378 97

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.41 0.25 0.34 0.44 0.06 0.50 1.00 2.94 0.06 1.00 2.80 0.20  
Final Sat.: 610 381 508 664 92 743 1500 4417 83 1500 4204 296

Capacity Analysis Module:  
Vol/Sat: 0.04 0.04 0.04 0.15 0.15 0.15 0.06 0.28 0.28 0.05 0.33 0.33  
Crit Volume: 24 228 95 492  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #23 Sunset Bl & Whitney Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.744  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 89 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 1 0 1 0 0 1 0 1 0 2 1 0 1 0 2 1 0

Volume Module:  
Base Vol: 45 23 175 142 52 10 53 1264 36 305 1432 250  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 45 23 175 142 52 10 53 1264 36 305 1432 250  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 45 23 175 142 52 10 53 1264 36 305 1432 250  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 45 23 175 142 52 10 53 1264 36 305 1432 250  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 45 23 175 142 52 10 53 1264 36 305 1432 250

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.12 0.88 1.00 0.84 0.16 1.00 2.92 0.08 1.00 2.55 0.45  
Final Sat.: 1450 168 1282 1450 1216 234 1450 4230 120 1450 3703 647

Capacity Analysis Module:  
Vol/Sat: 0.03 0.14 0.14 0.10 0.04 0.04 0.04 0.30 0.30 0.21 0.39 0.39  
Crit Volume: 198 142 433 305  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #101 Blue Oaks Bl & Lonetree  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.671  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 69 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Ignore Ignore Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 2 0 1 1 0 2 0 1 2 0 2 0 1 1 0 2 0 1

Volume Module:  
Base Vol: 315 263 43 26 289 1234 631 495 176 96 712 58  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 315 263 43 26 289 1234 631 495 176 96 712 58  
User Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Volume: 315 263 43 26 289 0 631 495 0 96 712 58  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 315 263 43 26 289 0 631 495 0 96 712 58  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00  
FinalVolume: 315 263 43 26 289 0 631 495 0 96 712 58

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 2.00 2.00 1.00 1.00 2.00 1.00 2.00 2.00 1.00 1.00 2.00 1.00  
Final Sat.: 2900 2900 1450 1450 2900 1450 2900 2900 1450 1450 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.11 0.09 0.03 0.02 0.10 0.00 0.22 0.17 0.00 0.07 0.25 0.04  
Crit Volume: 158 145 316 356  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #102 Blue Oaks Bl & Market Place  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.296  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 32 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 1 0 0 1 0 1 0 0 1 1 0 1 1 0 1 0 1 1 0

Volume Module:  
Base Vol: 6 0 1 4 1 6 4 660 3 2 824 3  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 6 0 1 4 1 6 4 660 3 2 824 3  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 6 0 1 4 1 6 4 660 3 2 824 3  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 6 0 1 4 1 6 4 660 3 2 824 3  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 6 0 1 4 1 6 4 660 3 2 824 3

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.80 0.20 1.00 1.00 1.99 0.01 1.00 1.99 0.01  
Final Sat.: 1450 0 1450 1160 290 1450 1450 2887 13 1450 2889 11

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.23 0.23 0.00 0.29 0.29  
Crit Volume: 6 6 4 414  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #103 Blue Oaks Bl & Van Buren Way  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.351  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 35 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 0 1 0 0

Volume Module:  
Base Vol: 37 591 14 16 776 29 9 0 22 16 0 22  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 37 591 14 16 776 29 9 0 22 16 0 22  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 37 591 14 16 776 29 9 0 22 16 0 22  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 37 591 14 16 776 29 9 0 22 16 0 22  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 37 591 14 16 776 29 9 0 22 16 0 22

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.95 0.05 1.00 1.93 0.07 0.29 0.00 0.71 0.42 0.00 0.58  
Final Sat.: 1450 2833 67 1450 2796 104 421 0 1029 611 0 839

Capacity Analysis Module:  
Vol/Sat: 0.03 0.21 0.21 0.01 0.28 0.28 0.02 0.00 0.02 0.03 0.00 0.03  
Crit Volume: 37 403 31 38  
Crit Moves: \*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #104 Five Star & Destiny Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.416  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 0 1 0 0 1

Volume Module:  
Base Vol: 0 20 3 222 25 13 13 0 2 3 1 354  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 20 3 222 25 13 13 0 2 3 1 354  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 20 3 222 25 13 13 0 2 3 1 354  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 20 3 222 25 13 13 0 2 3 1 354  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 20 3 222 25 13 13 0 2 3 1 354

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.74 0.26 1.00 1.32 0.68 0.87 0.00 0.13 0.75 0.25 1.00  
Final Sat.: 1450 2522 378 1450 1908 992 1257 0 193 1088 363 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.01 0.01 0.15 0.01 0.01 0.01 0.00 0.01 0.00 0.00 0.24  
Crit Volume: 12 222 15 354  
Crit Moves: \*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #105 Lonetree Bl & Adams Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.537  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 49 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0 0 1 0 0 0

Volume Module:  
Base Vol: 22 601 18 17 1391 8 9 1 24 17 1 15  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 22 601 18 17 1391 8 9 1 24 17 1 15  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 22 601 18 17 1391 8 9 1 24 17 1 15  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 22 601 18 17 1391 8 9 1 24 17 1 15  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 22 601 18 17 1391 8 9 1 24 17 1 15

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.94 0.06 1.00 1.99 0.01 0.90 0.10 1.00 0.52 0.03 0.45  
Final Sat.: 1450 2816 84 1450 2883 17 1305 145 1450 747 44 659

Capacity Analysis Module:  
Vol/Sat: 0.02 0.21 0.21 0.01 0.48 0.48 0.01 0.01 0.02 0.02 0.02 0.02  
Crit Volume: 22 700 24 33  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #106 Lonetree Bl & Atherton Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.480  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 0 0 0 1 1 0 1 0 0 0 1 0 0 0 0 0

Volume Module:  
Base Vol: 34 436 0 0 703 6 38 0 331 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 34 436 0 0 703 6 38 0 331 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 34 436 0 0 703 6 38 0 331 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 34 436 0 0 703 6 38 0 331 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 34 436 0 0 703 6 38 0 331 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 0.00 0.00 1.98 0.02 1.00 0.00 1.00 0.00 0.00 0.00  
Final Sat.: 1500 3000 0 0 2975 25 1500 0 1500 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.02 0.15 0.00 0.00 0.24 0.24 0.03 0.00 0.22 0.00 0.00 0.00  
Crit Volume: 34 355 331 0  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #107 Lonetree Bl & Grand Canyon Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.654  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 66 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0 0 1 0 0 0

Volume Module:  
Base Vol: 149 723 24 5 1477 7 16 1 44 9 1 4  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 149 723 24 5 1477 7 16 1 44 9 1 4  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 149 723 24 5 1477 7 16 1 44 9 1 4  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 149 723 24 5 1477 7 16 1 44 9 1 4  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 149 723 24 5 1477 7 16 1 44 9 1 4

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.94 0.06 1.00 1.99 0.01 0.94 0.06 1.00 0.64 0.07 0.29  
Final Sat.: 1450 2807 93 1450 2886 14 1365 85 1450 932 104 414

Capacity Analysis Module:  
Vol/Sat: 0.10 0.26 0.26 0.00 0.51 0.51 0.01 0.01 0.03 0.01 0.01 0.01  
Crit Volume: 149 742 44 14  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #108 Lonetree Bl & Redwood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.632  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 62 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0 0 1 0 0 0

Volume Module:  
Base Vol: 107 615 30 25 1346 52 30 2 67 29 5 9  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 107 615 30 25 1346 52 30 2 67 29 5 9  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 107 615 30 25 1346 52 30 2 67 29 5 9  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 107 615 30 25 1346 52 30 2 67 29 5 9  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 107 615 30 25 1346 52 30 2 67 29 5 9

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.91 0.09 1.00 1.93 0.07 0.94 0.06 1.00 0.67 0.12 0.21  
Final Sat.: 1450 2765 135 1450 2792 108 1359 91 1450 978 169 303

Capacity Analysis Module:  
Vol/Sat: 0.07 0.22 0.22 0.02 0.48 0.48 0.02 0.02 0.05 0.03 0.03 0.03  
Crit Volume: 107 699 67 43  
Crit Moves: \*\*\*\*



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #109 Lonetree Bl & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.521  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 48 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 7 411 144 9 1028 1 1 1 0 4 230 1 6  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 7 411 144 9 1028 1 1 1 0 4 230 1 6  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 7 411 144 9 1028 1 1 1 0 4 230 1 6  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 7 411 144 9 1028 1 1 1 0 4 230 1 6  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 7 411 144 9 1028 1 1 1 0 4 230 1 6

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 2.00 1.00 1.00 1.00 1.00  
Final Sat.: 1450 2900 1450 1450 2900 1450 1450 2900 1450 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.14 0.10 0.01 0.35 0.00 0.00 0.00 0.00 0.16 0.00 0.00  
Crit Volume: 7 514 4 230  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #110 Park Dr & Blaydon Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.646  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 53 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 0 1 0 0 1 0 1 1 0

Volume Module:  
Base Vol: 2 2 5 84 6 320 216 588 11 14 619 64  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 2 2 5 84 6 320 216 588 11 14 619 64  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 2 2 5 84 6 320 216 588 11 14 619 64  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 2 2 5 84 6 320 216 588 11 14 619 64  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 2 2 5 84 6 320 216 588 11 14 619 64

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.22 0.22 0.56 0.20 0.01 0.79 1.00 1.96 0.04 1.00 1.81 0.19  
Final Sat.: 333 333 833 307 22 1171 1500 2945 55 1500 2719 281

Capacity Analysis Module:  
Vol/Sat: 0.01 0.01 0.01 0.27 0.27 0.27 0.14 0.20 0.20 0.01 0.23 0.23  
Crit Volume: 2 410 216 342  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #111 Park Dr & Quarry Way  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.578  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 54 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0 0 0 0

Volume Module:  
Base Vol: 78 1144 6 17 1339 46 46 4 29 10 0 8  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 78 1144 6 17 1339 46 46 4 29 10 0 8  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 78 1144 6 17 1339 46 46 4 29 10 0 8  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 78 1144 6 17 1339 46 46 4 29 10 0 8  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 78 1144 6 17 1339 46 46 4 29 10 0 8

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.99 0.01 1.00 1.93 0.07 0.92 0.08 1.00 0.56 0.00 0.44  
Final Sat.: 1450 2885 15 1450 2804 96 1334 116 1450 806 0 644

Capacity Analysis Module:  
Vol/Sat: 0.05 0.40 0.40 0.01 0.48 0.48 0.03 0.03 0.02 0.01 0.00 0.01  
Crit Volume: 78 693 50 18  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #112 Park Dr & Farrier Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.673  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 57 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 0 0 0 1 1 0 1 0 0 0 0 0

Volume Module:  
Base Vol: 221 798 0 0 1032 72 41 0 237 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 221 798 0 0 1032 72 41 0 237 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 221 798 0 0 1032 72 41 0 237 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 221 798 0 0 1032 72 41 0 237 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 221 798 0 0 1032 72 41 0 237 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 0.00 0.00 1.87 0.13 1.00 0.00 1.00 0.00 0.00 0.00  
Final Sat.: 1500 3000 0 0 2804 196 1500 0 1500 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.15 0.27 0.00 0.00 0.37 0.37 0.03 0.00 0.16 0.00 0.00 0.00  
Crit Volume: 221 552 237 0  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #113 Park Dr & King Pine Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.492  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 24 1191 17 27 1373 7 7 1 9 15 0 16  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 24 1191 17 27 1373 7 7 1 9 15 0 16  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 24 1191 17 27 1373 7 7 1 9 15 0 16  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 24 1191 17 27 1373 7 7 1 9 15 0 16  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 24 1191 17 27 1373 7 7 1 9 15 0 16

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.97 0.03 1.00 1.99 0.01 0.88 0.12 1.00 1.00 0.00 1.00  
Final Sat.: 1500 2958 42 1500 2985 15 1313 188 1500 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.02 0.40 0.40 0.02 0.46 0.46 0.01 0.01 0.01 0.01 0.00 0.01  
Crit Volume: 24 690 9 15  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #114 Park Dr & Shelton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.355  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 35 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 2 1 0 1 0 0 1 0 1 0 1 0 1

Volume Module:  
Base Vol: 71 1101 14 6 1156 3 8 0 46 11 4 1  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 71 1101 14 6 1156 3 8 0 46 11 4 1  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 71 1101 14 6 1156 3 8 0 46 11 4 1  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 71 1101 14 6 1156 3 8 0 46 11 4 1  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 71 1101 14 6 1156 3 8 0 46 11 4 1

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.96 0.04 1.00 2.99 0.01 1.00 0.00 1.00 1.00 1.00  
Final Sat.: 1450 4295 55 1450 4339 11 1450 0 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.05 0.26 0.26 0.00 0.27 0.27 0.01 0.00 0.03 0.01 0.00 0.00  
Crit Volume: 71 386 46 11  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #115 Park Dr & Victory Lane  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.436  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 40 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 2 1 0 0 1 0 0 1 0 1 0 0 1

Volume Module:  
Base Vol: 37 949 6 91 1058 32 91 5 12 26 14 127  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 37 949 6 91 1058 32 91 5 12 26 14 127  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 37 949 6 91 1058 32 91 5 12 26 14 127  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 37 949 6 91 1058 32 91 5 12 26 14 127  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 37 949 6 91 1058 32 91 5 12 26 14 127

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.98 0.02 1.00 2.91 0.09 0.95 0.05 1.00 0.65 0.35 1.00  
Final Sat.: 1450 4323 27 1450 4222 128 1374 76 1450 943 508 1450

Capacity Analysis Module:  
Vol/Sat: 0.03 0.22 0.22 0.06 0.25 0.25 0.07 0.07 0.01 0.03 0.03 0.09  
Crit Volume: 318 91 96 127  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #116 Park Dr & Wykford Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.608  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 0 0 0 2 0 0 0 1 2 0 2 0 0 0 0 2 0 1

Volume Module:  
Base Vol: 0 0 0 0 38 0 285 334 775 0 0 921 62  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 0 0 0 38 0 285 334 775 0 0 921 62  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 0 0 0 38 0 285 334 775 0 0 921 62  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 0 0 0 38 0 285 334 775 0 0 921 62  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 0 0 0 38 0 285 334 775 0 0 921 62

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 0.00 0.00 2.00 0.00 1.00 2.00 2.00 0.00 0.00 2.00 1.00  
Final Sat.: 0 0 0 3000 0 1500 3000 3000 0 0 3000 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.01 0.00 0.19 0.11 0.26 0.00 0.00 0.31 0.04  
Crit Volume: 0 285 167 461  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #117 Park Dr & Twin Oaks/ Boardwalk  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.534  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 49 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0 0 1

Volume Module:  
Base Vol: 66 806 21 25 979 32 65 2 59 77 0 2  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 66 806 21 25 979 32 65 2 59 77 0 2  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 66 806 21 25 979 32 65 2 59 77 0 2  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 66 806 21 25 979 32 65 2 59 77 0 2  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 66 806 21 25 979 32 65 2 59 77 0 2

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.95 0.05 1.00 1.94 0.06 0.52 0.01 0.47 1.00 0.00 1.00  
Final Sat.: 1450 2826 74 1450 2808 92 748 23 679 1450 0 1450

Capacity Analysis Module:  
Vol/Sat: 0.05 0.29 0.29 0.02 0.35 0.35 0.09 0.09 0.09 0.05 0.00 0.00  
Crit Volume: 66 506 126 77  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #118 Park Dr & Safeway  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.627  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 61 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 1 0 1 0 1 1 0 0 0 0 0 1

Volume Module:  
Base Vol: 0 1142 105 71 1316 113 0 0 70 0 0 195  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 1142 105 71 1316 113 0 0 70 0 0 195  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 1142 105 71 1316 113 0 0 70 0 0 195  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 1142 105 71 1316 113 0 0 70 0 0 195  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 1142 105 71 1316 113 0 0 70 0 0 195

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 1.83 0.17 1.00 1.84 0.16 0.00 0.00 1.00 0.00 0.00 1.00  
Final Sat.: 0 2656 244 1450 2671 229 0 0 1450 0 0 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.43 0.43 0.05 0.49 0.49 0.00 0.00 0.05 0.00 0.00 0.13  
Crit Volume: 0 715 0 195  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #119 South Whitney & Five Star Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.510  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 46 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 6 361 57 176 260 7 38 12 5 45 21 316  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 6 361 57 176 260 7 38 12 5 45 21 316  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 6 361 57 176 260 7 38 12 5 45 21 316  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 6 361 57 176 260 7 38 12 5 45 21 316  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 6 361 57 176 260 7 38 12 5 45 21 316

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.73 0.27 1.00 1.95 0.05 1.00 0.71 0.29 1.00 1.00 1.00  
Final Sat.: 1450 2505 395 1450 2824 76 1450 1024 426 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.14 0.14 0.12 0.09 0.09 0.03 0.01 0.01 0.03 0.01 0.22  
Crit Volume: 209 176 38 316  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #120 Spring Creek Dr & Broken Rail Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.034  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 15 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Permitted Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 0 1 0 0 1 0 0 0 0 0 0 0 1 0 0

Volume Module:  
Base Vol: 0 33 3 3 32 0 5 0 10 1 0 3  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 33 3 3 32 0 5 0 10 1 0 3  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 33 3 3 32 0 5 0 10 1 0 3  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 33 3 3 32 0 5 0 10 1 0 3  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 33 3 3 32 0 5 0 10 1 0 3

Saturation Flow Module:  
Sat/Lane: 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600 1600  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 0.92 0.08 0.09 0.91 0.00 0.33 0.00 0.67 0.25 0.00 0.75  
Final Sat.: 0 1467 133 137 1463 0 533 0 1067 400 0 1200

Capacity Analysis Module:  
Vol/Sat: 0.00 0.02 0.02 0.02 0.02 0.00 0.01 0.00 0.01 0.00 0.00 0.00  
Crit Volume: 36 3 15 1  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #121 Stanford Ranch Rd & Cobblestone Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.529  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 0 1 0 0

Volume Module:  
Base Vol: 51 854 35 25 1012 89 70 7 110 5 12 11  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 51 854 35 25 1012 89 70 7 110 5 12 11  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 51 854 35 25 1012 89 70 7 110 5 12 11  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 51 854 35 25 1012 89 70 7 110 5 12 11  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 51 854 35 25 1012 89 70 7 110 5 12 11

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.92 0.08 1.00 1.84 0.16 0.37 0.04 0.59 0.18 0.43 0.39  
Final Sat.: 1500 2882 118 1500 2757 243 561 56 882 268 643 589

Capacity Analysis Module:  
Vol/Sat: 0.03 0.30 0.30 0.02 0.37 0.37 0.12 0.12 0.12 0.02 0.02 0.02  
Crit Volume: 51 551 187 5  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #122 Stanford Ranch Rd & Darby Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.415  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 1 0 0 1 0 0 1 0 0 1 0 1 1 0

Volume Module:  
Base Vol: 73 4 29 47 7 33 42 693 100 39 729 62  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 73 4 29 47 7 33 42 693 100 39 729 62  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 73 4 29 47 7 33 42 693 100 39 729 62  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 73 4 29 47 7 33 42 693 100 39 729 62  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 73 4 29 47 7 33 42 693 100 39 729 62

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.95 0.05 1.00 0.54 0.08 0.38 1.00 1.75 0.25 1.00 1.84 0.16  
Final Sat.: 1375 75 1450 783 117 550 1450 2534 366 1450 2673 227

Capacity Analysis Module:  
Vol/Sat: 0.05 0.05 0.02 0.06 0.06 0.06 0.03 0.27 0.27 0.03 0.27 0.27  
Crit Volume: 77 87 42 396  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #123 Stanford Ranch Rd & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.733  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 85 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 2 0 2 0 1 1 0 2 0 1

Volume Module:  
Base Vol: 217 491 191 425 596 243 237 445 179 281 549 311  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 217 491 191 425 596 243 237 445 179 281 549 311  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 217 491 191 425 596 243 237 445 179 281 549 311  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 217 491 191 425 596 243 237 445 179 281 549 311  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 217 491 191 425 596 243 237 445 179 281 549 311

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 2.00 2.00 1.00 1.00 2.00 1.00 1.00 2.00 1.00  
Final Sat.: 1450 2900 1450 2900 2900 1450 1450 2900 1450 1450 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.15 0.17 0.13 0.15 0.21 0.17 0.16 0.15 0.12 0.19 0.19 0.21  
Crit Volume: 217 298 237 311  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #124 Stanford Ranch Rd & Plaza  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.609  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 2 1 0 1 1 0 0 1 0 1 0 0 1

Volume Module:  
Base Vol: 95 1176 49 25 1655 3 79 1 160 74 1 38  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 95 1176 49 25 1655 3 79 1 160 74 1 38  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 95 1176 49 25 1655 3 79 1 160 74 1 38  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 95 1176 49 25 1655 3 79 1 160 74 1 38  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 95 1176 49 25 1655 3 79 1 160 74 1 38

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.88 0.12 1.00 2.99 0.01 1.97 0.03 1.00 0.99 0.01 1.00  
Final Sat.: 1450 4176 174 1450 4342 8 2864 36 1450 1431 19 1450

Capacity Analysis Module:  
Vol/Sat: 0.07 0.28 0.28 0.02 0.38 0.38 0.03 0.03 0.11 0.05 0.05 0.03  
Crit Volume: 95 553 160 75  
Crit Moves: \*\*\*\*



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #125 Stanford Ranch Rd & Stoney Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.534  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 40 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 0 0 1 0 0

Volume Module:  
Base Vol: 92 876 112 12 1127 13 7 17 49 66 11 2  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 92 876 112 12 1127 13 7 17 49 66 11 2  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 92 876 112 12 1127 13 7 17 49 66 11 2  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 92 876 112 12 1127 13 7 17 49 66 11 2  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 92 876 112 12 1127 13 7 17 49 66 11 2

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.77 0.23 1.00 1.98 0.02 0.10 0.23 0.67 0.84 0.14 0.02  
Final Sat.: 1500 2660 340 1500 2966 34 144 349 1007 1253 209 38

Capacity Analysis Module:  
Vol/Sat: 0.06 0.33 0.33 0.01 0.38 0.38 0.05 0.05 0.05 0.05 0.05 0.05  
Crit Volume: 92 570 73 66  
Crit Moves: \*\*\* \*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #126 Stanford Ranch Rd & Victory Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.590  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 56 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 0 0 0 1 0 1 0 1 1 0 3 0 0 0 0 3 0 1

Volume Module:  
Base Vol: 0 0 0 375 0 340 212 927 0 0 896 262  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 0 0 375 0 340 212 927 0 0 896 262  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 0 0 375 0 340 212 927 0 0 896 262  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 0 0 375 0 340 212 927 0 0 896 262  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 0 0 375 0 340 212 927 0 0 896 262

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 0.00 0.00 1.00 1.00 1.00 1.00 3.00 0.00 0.00 3.00 1.00  
Final Sat.: 0 0 0 1500 1500 1500 1500 4500 0 0 4500 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.00 0.25 0.00 0.23 0.14 0.21 0.00 0.00 0.20 0.17  
Crit Volume: 0 375 212 299  
Crit Moves: \*\*\* \*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #127 Stanford Ranch Rd & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.533  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 49 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 1 0 3 0 1 1 0 3 0 1

Volume Module:  
Base Vol: 0 512 150 161 393 58 155 553 9 64 561 201  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 512 150 161 393 58 155 553 9 64 561 201  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 512 150 161 393 58 155 553 9 64 561 201  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 512 150 161 393 58 155 553 9 64 561 201  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 512 150 161 393 58 155 553 9 64 561 201

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 3.00 1.00 1.00 3.00 1.00  
Final Sat.: 1450 2900 1450 1450 2900 1450 1450 4350 1450 1450 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.18 0.10 0.11 0.14 0.04 0.11 0.13 0.01 0.04 0.13 0.14  
Crit Volume: 256 161 155 201  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #128 Sunset Bl & Atherton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.565  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 52 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 1 0 0 1 1 0 0 1 0 1 0 3 0 1 1 0 3 0 1

Volume Module:  
Base Vol: 207 36 83 137 15 234 161 377 26 26 863 160  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 207 36 83 137 15 234 161 377 26 26 863 160  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 207 36 83 137 15 234 161 377 26 26 863 160  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 207 36 83 137 15 234 161 377 26 26 863 160  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 207 36 83 137 15 234 161 377 26 26 863 160

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.70 0.30 1.00 1.00 0.06 0.94 1.00 3.00 1.00 1.00 3.00 1.00  
Final Sat.: 2470 430 1450 1450 87 1363 1450 4350 1450 1450 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.08 0.08 0.06 0.09 0.17 0.17 0.11 0.09 0.02 0.02 0.20 0.11  
Crit Volume: 122 249 161 288  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #129 Sunset Bl & Blue Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.747  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 90 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Ignore Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 1 0 0 1 1 0 0 1 0 1 1

Volume Module:  
Base Vol: 356 36 212 29 20 4 27 1210 534 439 1099 58  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 356 36 212 29 20 4 27 1210 534 439 1099 58  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Volume: 356 36 212 29 20 4 27 1210 0 439 1099 58  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 356 36 212 29 20 4 27 1210 0 439 1099 58  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
FinalVolume: 356 36 212 29 20 4 27 1210 0 439 1099 58

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.82 0.18 1.00 1.00 0.83 0.17 1.00 3.00 1.00 1.00 3.00 1.00  
Final Sat.: 2634 266 1450 1450 1208 242 1450 4350 1450 1450 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.14 0.14 0.15 0.02 0.02 0.02 0.02 0.28 0.00 0.30 0.25 0.04  
Crit Volume: 212 29 403 439  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #130 Sunset Bl & Fairway Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.564  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 43 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 0 1 0 0 1 0 0 1 1

Volume Module:  
Base Vol: 119 24 143 11 16 25 54 1039 106 156 1163 11  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 119 24 143 11 16 25 54 1039 106 156 1163 11  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 119 24 143 11 16 25 54 1039 106 156 1163 11  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 119 24 143 11 16 25 54 1039 106 156 1163 11  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 119 24 143 11 16 25 54 1039 106 156 1163 11

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.00 1.00 0.21 0.31 0.48 1.00 2.00 1.00 1.00 1.98 0.02  
Final Sat.: 1500 1500 1500 317 462 721 1500 3000 1500 1500 2972 28

Capacity Analysis Module:  
Vol/Sat: 0.08 0.02 0.10 0.03 0.03 0.03 0.04 0.35 0.07 0.10 0.39 0.39  
Crit Volume: 119 52 520 156  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #131 Sunset Bl & Little Rock  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.441  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 41 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 1 0 0 1 0 0 1 0 0 1 0 2 1 0 1 0 2 1 0

Volume Module:  
Base Vol: 32 0 25 14 1 28 87 1434 33 75 1271 11  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 32 0 25 14 1 28 87 1434 33 75 1271 11  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 32 0 25 14 1 28 87 1434 33 75 1271 11  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 32 0 25 14 1 28 87 1434 33 75 1271 11  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 32 0 25 14 1 28 87 1434 33 75 1271 11

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.33 0.02 0.65 1.00 2.93 0.07 1.00 2.97 0.03  
Final Sat.: 1450 0 1450 472 34 944 1450 4252 98 1450 4313 37

Capacity Analysis Module:  
Vol/Sat: 0.02 0.00 0.02 0.03 0.03 0.03 0.06 0.34 0.34 0.05 0.29 0.29  
Crit Volume: 32 43 489 75  
Crit Moves: \*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #132 Sunset Bl & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.740  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 88 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected Protected  
Rights: Include Include Ignore Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 3 0 1 2 0 3 0 1 2 0 3 0 1 2 0 3 0 1

Volume Module:  
Base Vol: 557 654 114 363 744 168 387 969 309 447 863 148  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 557 654 114 363 744 168 387 969 309 447 863 148  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Volume: 557 654 114 363 744 168 387 969 0 447 863 148  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 557 654 114 363 744 168 387 969 0 447 863 148  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
FinalVolume: 557 654 114 363 744 168 387 969 0 447 863 148

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
Final Sat.: 2900 4350 1450 2900 4350 1450 2900 4350 1450 2900 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.19 0.15 0.08 0.13 0.17 0.12 0.13 0.22 0.00 0.15 0.20 0.10  
Crit Volume: 279 248 323 224  
Crit Moves: \*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #133 Sunset Bl & Pebble Creek

Cycle (sec): 100 Critical Vol./Cap.(X): 0.483
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 36 Level Of Service: A

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns representing different traffic movements and 10 rows of volume and adjustment factors.

Saturation Flow Module table with 12 columns and 5 rows showing saturation flow rates and adjustments.

Capacity Analysis Module table with 12 columns and 4 rows showing volume-to-saturation ratios and critical moves.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report Circular 212 Planning Method (Base Volume Alternative)

Intersection #134 Sunset Bl & Stanford Ranch Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.801
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 115 Level Of Service: D

Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns representing different traffic movements and 10 rows of volume and adjustment factors.

Saturation Flow Module table with 12 columns and 5 rows showing saturation flow rates and adjustments.

Capacity Analysis Module table with 12 columns and 4 rows showing volume-to-saturation ratios and critical moves.

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #135 Sunset Bl & West Oaks Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.957  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Ignore Ignore  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 1 0 3 0 1 1 0 3 0 1

Volume Module:  
Base Vol: 46 117 101 877 123 40 42 751 6 160 822 496  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 46 117 101 877 123 40 42 751 6 160 822 496  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
PHF Volume: 46 117 101 877 123 40 42 751 0 160 822 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 46 117 101 877 123 40 42 751 0 160 822 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
FinalVolume: 46 117 101 877 123 40 42 751 0 160 822 0

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 3.00 1.00 1.00 3.00 1.00  
Final Sat.: 1450 2900 1450 1450 2900 1450 1450 4350 1450 1450 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.03 0.04 0.07 0.60 0.04 0.03 0.03 0.17 0.00 0.11 0.19 0.00  
Crit Volume: 101 877 250 160  
Crit Moves: \*\*\*\* \*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #136 W Stanford Ranch Rd & Sunset Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.635  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 62 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 3 0 1 2 0 2 1 0 1 0 2 0 1 2 0 2 0 1

Volume Module:  
Base Vol: 87 522 220 156 179 205 341 322 80 306 563 261  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 87 522 220 156 179 205 341 322 80 306 563 261  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 87 522 220 156 179 205 341 322 80 306 563 261  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 87 522 220 156 179 205 341 322 80 306 563 261  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 87 522 220 156 179 205 341 322 80 306 563 261

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 2.00 3.00 1.00 2.00 2.00 1.00 1.00 2.00 1.00 2.00 2.00 1.00  
Final Sat.: 2900 4350 1450 2900 2900 1450 1450 2900 1450 2900 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.03 0.12 0.15 0.05 0.06 0.14 0.24 0.11 0.06 0.11 0.19 0.18  
Crit Volume: 220 78 341 282  
Crit Moves: \*\*\*\* \*\*

GP08 F Fri May 22, 2009 10:25:30 Page 62-1

-----  
City of Rocklin General Plan Update  
Existing Plus Project Conditions  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #137 W Stanford Ranch Rd & Wildcat Bl  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 0.730  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 84 Level Of Service: C  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 2 0 1 0 2 2 0 2 0 1 1 0 3 0 1  
-----  
Volume Module:  
Base Vol: 8 149 0 408 47 742 505 307 7 1 182 427  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 8 149 0 408 47 742 505 307 7 1 182 427  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 8 149 0 408 47 742 505 307 7 1 182 427  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 8 149 0 408 47 742 505 307 7 1 182 427  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 8 149 0 408 47 742 505 307 7 1 182 427  
-----  
Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 2.00 1.00 2.00 2.00 2.00 1.00 1.00 3.00 1.00  
Final Sat.: 1450 2900 1450 2900 1450 2900 2900 2900 1450 1450 4350 1450  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.01 0.05 0.00 0.14 0.03 0.26 0.17 0.11 0.00 0.00 0.04 0.29  
Crit Volume: 8 371 253 427  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\*  
\*\*\*\*\*

GP08 F Fri May 22, 2009 10:25:30 Page 63-1

-----  
City of Rocklin General Plan Update  
Existing Plus Project Conditions  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #138 Whitney Ranch Pkwy & Bridlewood Dr  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 0.302  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 27 Level Of Service: A  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Permitted Permitted Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 0 1 0 0 1 0 1 1 0 1 0 1 1 0  
-----  
Volume Module:  
Base Vol: 70 2 72 4 0 7 7 404 55 75 305 12  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 70 2 72 4 0 7 7 404 55 75 305 12  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 70 2 72 4 0 7 7 404 55 75 305 12  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 70 2 72 4 0 7 7 404 55 75 305 12  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 70 2 72 4 0 7 7 404 55 75 305 12  
-----  
Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.49 0.01 0.50 0.36 0.00 0.64 1.00 1.76 0.24 1.00 1.92 0.08  
Final Sat.: 729 21 750 545 0 955 1500 2641 359 1500 2886 114  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.10 0.10 0.10 0.01 0.00 0.01 0.00 0.15 0.15 0.05 0.11 0.11  
Crit Volume: 144 4 230 75  
Crit Moves: \*\*\*\* \*\*\*\*  
\*\*\*\*\*

GP08 F                                  Fri May 22, 2009 10:25:30                                  Page 64-1

-----

                                City of Rocklin General Plan Update  
                                Existing Plus Project Conditions

-----

                                Level Of Service Computation Report  
                                Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*

Intersection #139 Whitney Ranch Pkwy & Painted Pony Ln

\*\*\*\*\*

Cycle (sec):                                  100                                  Critical Vol./Cap.(X):                                  0.207  
Loss Time (sec):                                  0                                  Average Delay (sec/veh):                                  xxxxxx  
Optimal Cycle:                                  29                                  Level Of Service:                                  A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	1	0	0	0	1	1	0	1	1	0	1

-----

Volume Module:

Base Vol:	31	0	21	0	0	7	2	433	44	24	353	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	31	0	21	0	0	7	2	433	44	24	353	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	31	0	21	0	0	7	2	433	44	24	353	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	31	0	21	0	0	7	2	433	44	24	353	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	31	0	21	0	0	7	2	433	44	24	353	0

-----

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.00	1.00	0.00	0.00	1.00	1.00	1.82	0.18	1.00	2.00	0.00
Final Sat.:	1450	0	1450	0	0	1450	1450	2632	268	1450	2900	0

-----

Capacity Analysis Module:

Vol/Sat:	0.02	0.00	0.01	0.00	0.00	0.00	0.00	0.16	0.16	0.02	0.12	0.00
Crit Volume:	31					7		239	24			
Crit Moves:	***					***		***	***			

\*\*\*\*\*

GP08 F                                  Fri May 22, 2009 10:25:30                                  Page 65-1

-----

                                City of Rocklin General Plan Update  
                                Existing Plus Project Conditions

-----

                                Level Of Service Computation Report  
                                Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*

Intersection #140 Whitney Ranch Pkwy & Spring Creek Dr

\*\*\*\*\*

Cycle (sec):                                  100                                  Critical Vol./Cap.(X):                                  0.191  
Loss Time (sec):                                  0                                  Average Delay (sec/veh):                                  xxxxxx  
Optimal Cycle:                                  23                                  Level Of Service:                                  A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	1	0	1	1	0	1

-----

Volume Module:

Base Vol:	13	2	2	5	2	29	27	458	16	1	373	6
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	13	2	2	5	2	29	27	458	16	1	373	6
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	13	2	2	5	2	29	27	458	16	1	373	6
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	13	2	2	5	2	29	27	458	16	1	373	6
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	13	2	2	5	2	29	27	458	16	1	373	6

-----

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.76	0.12	0.12	0.14	0.06	0.80	1.00	1.93	0.07	1.00	1.97	0.03
Final Sat.:	1147	176	176	208	83	1208	1500	2899	101	1500	2953	47

-----

Capacity Analysis Module:

Vol/Sat:	0.01	0.01	0.01	0.02	0.02	0.02	0.02	0.16	0.16	0.00	0.13	0.13
Crit Volume:	13					36		237	1			
Crit Moves:	***					***		***	***			

\*\*\*\*\*



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #141 Wildcat Bl & Bridlewood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.487  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 44 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 0 1 1 0 0 1 0

Volume Module:  
Base Vol: 1 850 148 35 1019 0 1 23 2 149 5 23  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 1 850 148 35 1019 0 1 23 2 149 5 23  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 1 850 148 35 1019 0 1 23 2 149 5 23  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 1 850 148 35 1019 0 1 23 2 149 5 23  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 1 850 148 35 1019 0 1 23 2 149 5 23

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.70 0.30 1.00 2.00 0.00 1.00 1.00 1.00 1.00 0.18 0.82  
Final Sat.: 1450 2470 430 1450 2900 0 1450 1450 1450 1450 259 1191

Capacity Analysis Module:  
Vol/Sat: 0.00 0.34 0.34 0.02 0.35 0.00 0.00 0.02 0.00 0.10 0.02 0.02  
Crit Volume: 499 35 23 149  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #142 Wildcat Bl & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.592  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 56 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 2 0 3 0 1 2 0 2 0 1

Volume Module:  
Base Vol: 259 238 50 158 385 288 271 313 201 49 198 176  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 259 238 50 158 385 288 271 313 201 49 198 176  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 259 238 50 158 385 288 271 313 201 49 198 176  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 259 238 50 158 385 288 271 313 201 49 198 176  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 259 238 50 158 385 288 271 313 201 49 198 176

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 2.00 3.00 1.00 2.00 2.00 1.00  
Final Sat.: 1450 2900 1450 1450 2900 1450 2900 4350 1450 2900 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.18 0.08 0.03 0.11 0.13 0.20 0.09 0.07 0.14 0.02 0.07 0.12  
Crit Volume: 259 288 136 176  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #143 Wildcat Bl & S High School Entrance  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.628  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 61 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 58 315 358 72 432 12 14 6 34 447 9 116  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 58 315 358 72 432 12 14 6 34 447 9 116  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 58 315 358 72 432 12 14 6 34 447 9 116  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 58 315 358 72 432 12 14 6 34 447 9 116  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 58 315 358 72 432 12 14 6 34 447 9 116

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 1.00 1.00 1.00 1.00  
Final Sat.: 1450 2900 1450 1450 2900 1450 1450 1450 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.04 0.11 0.25 0.05 0.15 0.01 0.01 0.00 0.02 0.31 0.01 0.08  
Crit Volume: 358 72 34 447  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #144 Wildcat Bl & N High School Entrance  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.176  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 28 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 1 0 0 0 1

Volume Module:  
Base Vol: 0 314 1 10 422 0 0 0 0 0 53 0 7  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 314 1 10 422 0 0 0 0 0 53 0 7  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 314 1 10 422 0 0 0 0 0 53 0 7  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 314 1 10 422 0 0 0 0 0 53 0 7  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 314 1 10 422 0 0 0 0 0 53 0 7

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 3000 1500 1500 3000 0 0 0 0 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.10 0.00 0.01 0.14 0.00 0.00 0.00 0.00 0.04 0.00 0.00  
Crit Volume: 0 211 0 53  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #145 Wildcat Bl & Ranch View Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.263  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 1 0

Volume Module:  
Base Vol: 6 429 69 17 401 31 102 3 5 38 1 12  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 6 429 69 17 401 31 102 3 5 38 1 12  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 6 429 69 17 401 31 102 3 5 38 1 12  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 6 429 69 17 401 31 102 3 5 38 1 12  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 6 429 69 17 401 31 102 3 5 38 1 12

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.72 0.28 1.00 1.86 0.14 1.00 0.38 0.62 1.00 0.08 0.92  
Final Sat.: 1450 2498 402 1450 2692 208 1450 544 906 1450 112 1338

Capacity Analysis Module:  
Vol/Sat: 0.00 0.17 0.17 0.01 0.15 0.15 0.07 0.01 0.01 0.03 0.01 0.01  
Crit Volume: 249 17 102 13  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #152 Stanford Ranch Rd & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.864  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 167 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 1 0 1 0 2 0 0 0 0 0 0 1 0 0 0 1

Volume Module:  
Base Vol: 0 737 342 431 789 0 0 0 0 0 325 0 305  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 737 342 431 789 0 0 0 0 0 325 0 305  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 737 342 431 789 0 0 0 0 0 325 0 305  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 737 342 431 789 0 0 0 0 0 325 0 305  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 737 342 431 789 0 0 0 0 0 325 0 305

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 1.37 0.63 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 2049 951 1500 3000 0 0 0 0 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.36 0.36 0.29 0.26 0.00 0.00 0.00 0.00 0.22 0.00 0.20  
Crit Volume: 540 431 0 325  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #153 Whitney Blvd & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.739  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 87 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 1 0 0 0 0 0 0 1 0 0 1 0

Volume Module:  
Base Vol: 306 0 74 0 0 0 0 0 368 405 96 324 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 306 0 74 0 0 0 0 0 368 405 96 324 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 306 0 74 0 0 0 0 0 368 405 96 324 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 306 0 74 0 0 0 0 0 368 405 96 324 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 306 0 74 0 0 0 0 0 368 405 96 324 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.81 0.00 0.19 0.00 0.00 0.00 0.00 0.00 1.00 1.00 1.00 1.00 0.00  
Final Sat.: 1208 0 292 0 0 0 0 0 1500 1500 1500 1500 0

Capacity Analysis Module:  
Vol/Sat: 0.25 0.00 0.25 0.00 0.00 0.00 0.00 0.25 0.27 0.06 0.22 0.00  
Crit Volume: 380 0 405 324  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #154 Park Dr & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.328  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 0 1 0 0 0 0 0 0 0 1 1 0 1 0 2 0 0

Volume Module:  
Base Vol: 200 0 225 0 0 0 0 0 169 134 115 110 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 200 0 225 0 0 0 0 0 169 134 115 110 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 200 0 225 0 0 0 0 0 169 134 115 110 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 200 0 225 0 0 0 0 0 169 134 115 110 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 200 0 225 0 0 0 0 0 169 134 115 110 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 0.12 0.88 1.00 2.00 0.00  
Final Sat.: 1500 0 1500 0 0 0 0 1673 1327 1500 3000 0

Capacity Analysis Module:  
Vol/Sat: 0.13 0.00 0.15 0.00 0.00 0.00 0.00 0.10 0.10 0.08 0.04 0.00  
Crit Volume: 225 0 152 115  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #161 Granite Dr & Dominguez Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.817  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 124 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 0 1 0

Volume Module:  
Base Vol: 119 447 64 68 632 36 61 276 239 216 121 89  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 119 447 64 68 632 36 61 276 239 216 121 89  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 119 447 64 68 632 36 61 276 239 216 121 89  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 119 447 64 68 632 36 61 276 239 216 121 89  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 119 447 64 68 632 36 61 276 239 216 121 89

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.75 0.25 1.00 1.89 0.11 1.00 0.54 0.46 1.00 0.58 0.42  
Final Sat.: 1450 2537 363 1450 2744 156 1450 777 673 1450 835 615

Capacity Analysis Module:  
Vol/Sat: 0.08 0.18 0.18 0.05 0.23 0.23 0.04 0.36 0.36 0.15 0.14 0.14  
Crit Volume: 119 334 515 216  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #162 Sierra College Bl & Dominguez Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.586  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 55 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 2 1 0 2 0 1 1 0 2 0 1 1 0

Volume Module:  
Base Vol: 195 871 29 54 625 77 387 36 403 34 34 79  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 195 871 29 54 625 77 387 36 403 34 34 79  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 195 871 29 54 625 77 387 36 403 34 34 79  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 195 871 29 54 625 77 387 36 403 34 34 79  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 195 871 29 54 625 77 387 36 403 34 34 79

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.90 0.10 1.00 2.67 0.33 2.00 1.00 1.00 2.00 1.00 1.00  
Final Sat.: 1450 4210 140 1450 3873 477 2900 1450 1450 2900 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.13 0.21 0.21 0.04 0.16 0.16 0.13 0.02 0.28 0.01 0.02 0.05  
Crit Volume: 195 234 403 17  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #163 Park Dr & Valley View Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.516  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 47 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Ignore Include Include Ignore  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 0 1

Volume Module:  
Base Vol: 0 124 439 479 95 0 0 0 0 0 233 0 252  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 124 439 479 95 0 0 0 0 0 233 0 252  
User Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00  
PHF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00  
PHF Volume: 0 124 0 479 95 0 0 0 0 0 233 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 124 0 479 95 0 0 0 0 0 233 0 0  
PCE Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00  
MLF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00  
FinalVolume: 0 124 0 479 95 0 0 0 0 0 233 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 3000 1500 1500 3000 0 0 0 0 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.04 0.00 0.32 0.03 0.00 0.00 0.00 0.00 0.16 0.00 0.00  
Crit Volume: 62 479 0 233  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #164 Nature Trail Wy & Valley View Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.621  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 60 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Split Phase Split Phase Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 0 1 0 0 0 0 1 1 0 1 0 1 1 0 1 0 0

Volume Module:  
Base Vol: 14 0 5 0 0 0 6 15 869 35 12 464 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 14 0 5 0 0 0 6 15 869 35 12 464 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 14 0 5 0 0 0 6 15 869 35 12 464 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 14 0 5 0 0 0 6 15 869 35 12 464 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 14 0 5 0 0 0 6 15 869 35 12 464 0

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00  
Final Sat.: 1450 0 1450 0 0 1450 1450 1450 1450 1450 1450 0

Capacity Analysis Module:  
Vol/Sat: 0.01 0.00 0.00 0.00 0.00 0.00 0.01 0.60 0.02 0.01 0.32 0.00  
Crit Volume: 14 6 869 12  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #165 Sierra College Bl & Valley View Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.381  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Ignore Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 2 0 0 0 0 2 0 0 0 1

Volume Module:  
Base Vol: 233 546 0 0 0 268 272 367 0 500 0 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 233 546 0 0 0 268 272 367 0 500 0 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
PHF Volume: 233 546 0 0 0 268 272 367 0 0 0 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 233 546 0 0 0 268 272 367 0 0 0 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
FinalVolume: 233 546 0 0 0 268 272 367 0 0 0 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 2.00 2.00 0.00 0.00 2.00 1.00 2.00 0.00 1.00 0.00 0.00 0.00 0.00  
Final Sat.: 3000 3000 0 0 0 3000 1500 3000 0 1500 0 0 0

Capacity Analysis Module:  
Vol/Sat: 0.08 0.18 0.00 0.00 0.09 0.18 0.12 0.00 0.00 0.00 0.00 0.00 0.00  
Crit Volume: 116 272 184 0  
Crit Moves: \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #166 University Ave & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.379  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 2 0 1 2 0 2 0 1 2 0 3 0 1

Volume Module:  
Base Vol: 79 36 54 160 29 299 154 441 29 26 1017 69  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 79 36 54 160 29 299 154 441 29 26 1017 69  
User Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 79 36 54 160 29 0 154 441 29 26 1017 69  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 79 36 54 160 29 0 154 441 29 26 1017 69  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 79 36 54 160 29 0 154 441 29 26 1017 69

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 2.00 2.00 1.00 2.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
Final Sat.: 2900 2900 1450 2900 2900 1450 2900 4350 1450 2900 4350 1450

Capacity Analysis Module:  
Vol/Sat: 0.03 0.01 0.04 0.06 0.01 0.00 0.05 0.10 0.02 0.01 0.23 0.05  
Crit Volume: 54 80 77 339  
Crit Moves: \*\*\*\* \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #167 West Oaks Bl & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.507  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 46 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Ovl Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 0 1 0 0 0 0 0 0 0 2 0 1 1 0 2 0 0

Volume Module:  
Base Vol: 36 0 546 0 0 0 0 0 429 25 423 341 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 36 0 546 0 0 0 0 0 429 25 423 341 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 36 0 546 0 0 0 0 0 429 25 423 341 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 36 0 546 0 0 0 0 0 429 25 423 341 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 36 0 546 0 0 0 0 0 429 25 423 341 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 2.00 1.00 1.00 2.00 0.00  
Final Sat.: 1500 0 1500 0 0 0 0 3000 1500 1500 3000 0

Capacity Analysis Module:  
Vol/Sat: 0.02 0.00 0.36 0.00 0.00 0.00 0.00 0.14 0.02 0.28 0.11 0.00  
Crit Volume: 546 0 214 0  
Crit Moves: \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #168 West Oaks Bl & Painted Pony Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.265  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 0 1 1 0 2 0 1 1 0 1 0 1 1 0 1 0 1

Volume Module:  
Base Vol: 111 606 0 0 0 454 0 0 0 0 60 0 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 111 606 0 0 454 0 0 0 0 60 0 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 111 606 0 0 454 0 0 0 60 0 0 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 111 606 0 0 454 0 0 0 60 0 0 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 111 606 0 0 454 0 0 0 60 0 0 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Final Sat.: 1500 3000 1500 1500 3000 1500 1500 1500 1500 1500 1500 1500 1500 1500

Capacity Analysis Module:  
Vol/Sat: 0.07 0.20 0.00 0.00 0.15 0.00 0.00 0.00 0.04 0.00 0.00 0.00  
Crit Volume: 111 227 60 0  
Crit Moves: \*\*\*\*

\*\*\*\*\*



City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #169 Laredo Dr & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.819  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 126 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 0 1 1 0 1 0 1 1 0 2 0 2

Volume Module:  
Base Vol: 76 17 33 133 21 541 498 353 124 26 145 96  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 76 17 33 133 21 541 498 353 124 26 145 96  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 76 17 33 133 21 541 498 353 124 26 145 96  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 76 17 33 133 21 541 498 353 124 26 145 96  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 76 17 33 133 21 541 498 353 124 26 145 96

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 2.00 1.00 1.00 2.00 2.00  
Final Sat.: 1450 1450 1450 1450 1450 1450 2900 1450 1450 2900 2900

Capacity Analysis Module:  
Vol/Sat: 0.05 0.01 0.02 0.09 0.01 0.37 0.34 0.12 0.09 0.02 0.05 0.03  
Crit Volume: 76 541 498 73  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #170 Rocklin Rd & Civic Centr Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.560  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 52 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 0 1 0 0 0 0 0 0 0 2 0 1 1 0 2 0 0

Volume Module:  
Base Vol: 4 0 84 0 0 0 0 0 1416 6 48 754 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 4 0 84 0 0 0 0 0 1416 6 48 754 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 4 0 84 0 0 0 0 0 1416 6 48 754 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 4 0 84 0 0 0 0 0 1416 6 48 754 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 4 0 84 0 0 0 0 0 1416 6 48 754 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 2.00 1.00 1.00 2.00 0.00  
Final Sat.: 1500 0 1500 0 0 0 0 3000 1500 1500 3000 0

Capacity Analysis Module:  
Vol/Sat: 0.00 0.00 0.06 0.00 0.00 0.00 0.00 0.47 0.00 0.03 0.25 0.00  
Crit Volume: 84 0 708 48  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #171 Pacific St & Civic Center Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.520  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 47 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 1 1

Volume Module:  
Base Vol: 0 1447 52 0 933 0 0 0 0 56 0 0 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 0 1447 52 0 933 0 0 0 0 56 0 0 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 0 1447 52 0 933 0 0 0 0 56 0 0 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 0 1447 52 0 933 0 0 0 0 56 0 0 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 0 1447 52 0 933 0 0 0 0 56 0 0 0

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 0.00 1.00 0.00 1.00  
Final Sat.: 0 3000 1500 1500 3000 0 0 0 0 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.00 0.48 0.03 0.00 0.31 0.00 0.00 0.00 0.00 0.04 0.00 0.00  
Crit Volume: 724 0 0 0 56  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #201 Rocklin Rd & I-80 EB  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.881  
Loss Time (sec): 6 Average Delay (sec/veh): 31.8  
Optimal Cycle: 84 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 0 1 0 0 0 0 0 1 0 2 0 0 0 0 1 0 1 0

Volume Module:  
Base Vol: 683 0 398 0 0 0 592 956 0 3 763 149  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 683 0 398 0 0 0 592 956 0 3 763 149  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 683 0 398 0 0 0 592 956 0 3 763 149  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 683 0 398 0 0 0 592 956 0 3 763 149  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 683 0 398 0 0 0 592 956 0 3 763 149

Saturation Flow Module:  
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
Adjustment: 0.92 1.00 0.92 1.00 1.00 1.00 0.95 0.95 1.00 0.93 0.93 0.93  
Lanes: 1.63 0.00 1.37 0.00 0.00 0.00 1.00 2.00 0.00 0.01 1.67 0.32  
Final Sat.: 2839 0 2380 0 0 0 1805 3610 0 12 2938 574

Capacity Analysis Module:  
Vol/Sat: 0.24 0.00 0.17 0.00 0.00 0.00 0.33 0.26 0.00 0.26 0.26 0.26  
Crit Volume: \*\*\*\* \*\*  
Green/Cycle: 0.27 0.00 0.27 0.00 0.00 0.00 0.37 0.67 0.00 0.30 0.30 0.30  
Volume/Cap: 0.89 0.00 0.62 0.00 0.00 0.00 0.90 0.39 0.00 0.85 0.85 0.85  
Delay/Veh: 44.1 0.0 32.8 0.0 0.0 0.0 44.6 7.5 0.0 39.3 39.3 39.3  
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
AdjDel/Veh: 44.1 0.0 32.8 0.0 0.0 0.0 44.6 7.5 0.0 39.3 39.3 39.3  
LOS by Move: D A C A A A D A A D D D  
HCM2kAvgQ: 16 0 9 0 0 0 21 7 0 17 17 17

\*\*\*\*\*  
Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #202 Rocklin Rd & I-80 WB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.817
Loss Time (sec): 6 Average Delay (sec/veh): 23.7
Optimal Cycle: 62 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected
Rights: Include Include Ignore Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 0 0 0 0 0 1 0 0 1 0 0 0 2 0 1 1 0 2 0 0

Volume Module:
Base Vol: 0 0 0 88 1 369 0 1451 1047 247 1148 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 0 0 88 1 369 0 1451 1047 247 1148 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00
PHF Volume: 0 0 0 88 1 369 0 1451 0 247 1148 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 0 0 88 1 369 0 1451 0 247 1148 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00
FinalVolume: 0 0 0 88 1 369 0 1451 0 247 1148 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 1.00 1.00 0.85 0.85 0.85 1.00 0.95 1.00 0.95 0.95 1.00
Lanes: 0.00 0.00 0.00 1.00 0.01 0.99 0.00 2.00 1.00 1.00 2.00 0.00
Final Sat.: 0 0 0 1615 4 1611 0 3610 1900 1805 3610 0

Capacity Analysis Module:
Vol/Sat: 0.00 0.00 0.00 0.05 0.23 0.23 0.00 0.40 0.00 0.14 0.32 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.00 0.00 0.28 0.28 0.28 0.00 0.49 0.00 0.17 0.66 0.00
Volume/Cap: 0.00 0.00 0.00 0.19 0.82 0.82 0.00 0.82 0.00 0.82 0.48 0.00
Delay/Veh: 0.0 0.0 0.0 27.6 44.6 44.6 0.0 24.7 0.0 55.9 8.7 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 0.0 0.0 27.6 44.6 44.6 0.0 24.7 0.0 55.9 8.7 0.0
LOS by Move: A A A C D D A C A E A A
HCM2kAvgQ: 0 0 0 2 13 13 0 22 0 10 9 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #203 Sierra College Bl & I-80 WB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.590
Loss Time (sec): 9 Average Delay (sec/veh): 26.8
Optimal Cycle: 40 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 3 0 1 0 0 3 0 1 1 0 0 0 1 2 0 0 1 1

Volume Module:
Base Vol: 135 580 272 0 1160 40 94 0 255 276 38 228
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 135 580 272 0 1160 40 94 0 255 276 38 228
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 135 580 272 0 1160 40 94 0 255 276 38 228
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 135 580 272 0 1160 40 94 0 255 276 38 228
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 135 580 272 0 1160 40 94 0 255 276 38 228

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 0.91 0.85 1.00 0.91 0.85 0.95 1.00 0.85 0.92 0.87 0.87
Lanes: 1.00 3.00 1.00 0.00 3.00 1.00 1.00 0.00 1.00 2.00 0.29 1.71
Final Sat.: 1805 5187 1615 0 5187 1615 1805 0 1615 3502 473 2837

Capacity Analysis Module:
Vol/Sat: 0.07 0.11 0.17 0.00 0.22 0.02 0.05 0.00 0.16 0.08 0.08 0.08
Crit Moves: \*\*\*\*
Green/Cycle: 0.13 0.51 0.51 0.00 0.38 0.38 0.27 0.00 0.27 0.14 0.14 0.14
Volume/Cap: 0.59 0.22 0.33 0.00 0.59 0.07 0.19 0.00 0.59 0.58 0.59 0.59
Delay/Veh: 45.2 13.8 14.9 0.0 25.3 19.8 28.5 0.0 34.0 42.3 42.6 42.6
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 45.2 13.8 14.9 0.0 25.3 19.8 28.5 0.0 34.0 42.3 42.6 42.6
LOS by Move: D B B A C B C A C D D D
HCM2kAvgQ: 5 4 5 0 11 1 2 0 8 5 5 5

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #204 Sierra College Bl & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.408
Loss Time (sec): 9 Average Delay (sec/veh): 28.4
Optimal Cycle: 30 Level Of Service: C

Table with columns for Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #205 SR 65 & Sunset Blvd

Cycle (sec): 100 Critical Vol./Cap.(X): 1.097
Loss Time (sec): 12 Average Delay (sec/veh): 71.3
Optimal Cycle: 180 Level Of Service: E

Table with columns for Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #208 Whitney Ranch Pkwy & SR 65 SB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.566
Loss Time (sec): 0 Average Delay (sec/veh): 16.7
Optimal Cycle: 53 Level Of Service: B

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 2 0 3 0 1 2 0 3 0 1 1 1 0 0 1 1 1 0 1 0

Volume Module:
Base Vol: 0 0 0 419 0 0 0 0 0 0 0 0 0 0 685
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 0 0 419 0 0 0 0 0 0 0 0 0 0 685
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 0 0 0 419 0 0 0 0 0 0 0 0 0 0 685
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 0 0 419 0 0 0 0 0 0 0 0 0 0 685
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 0 0 0 419 0 0 0 0 0 0 0 0 0 0 685

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.97 0.91 1.00 0.92 0.91 1.00 1.00 1.00 1.00 0.95 0.95 0.81
Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Final Sat.: 3686 5187 1900 3502 5187 1900 1900 1900 1900 1805 1805 1534

Capacity Analysis Module:
Vol/Sat: 0.00 0.00 0.00 0.12 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.45
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.00 0.00 0.21 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.79
Volume/Cap: 0.00 0.00 0.00 0.57 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.57
Delay/Veh: 0.0 0.0 0.0 36.4 0.0 0.0 0.0 0.0 0.0 0.0 0.0 4.7
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 0.0 0.0 36.4 0.0 0.0 0.0 0.0 0.0 0.0 0.0 4.7
LOS by Move: A A A D A A A A A A A A
HCM2kAvgQ: 0 0 0 7 0 0 0 0 0 0 0 9

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #209 Whitney Ranch Pkwy & SR 65 NB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.494
Loss Time (sec): 0 Average Delay (sec/veh): 9.6
Optimal Cycle: 45 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Ignore Ignore
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 1 1 0 0 0 2 1 0 0 0 1 0 0 0 0 0 1 0

Volume Module:
Base Vol: 0 0 205 0 0 0 0 0 419 0 0 0 685 709
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 0 205 0 0 0 0 0 419 0 0 0 685 709
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Volume: 0 0 205 0 0 0 0 0 419 0 0 0 685 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 0 205 0 0 0 0 0 419 0 0 0 685 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
FinalVolume: 0 0 205 0 0 0 0 0 419 0 0 0 685 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 0.95 0.81 1.00 0.91 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.00 1.00 0.00 3.00 0.00 0.00 1.00 0.00 0.00 1.00 0.00
Final Sat.: 1900 1805 1534 0 5187 0 0 1900 0 0 1900 0

Capacity Analysis Module:
Vol/Sat: 0.00 0.00 0.13 0.00 0.00 0.00 0.00 0.00 0.22 0.00 0.00 0.36 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.00 0.27 0.00 0.00 0.00 0.00 0.73 0.00 0.00 0.73 0.00
Volume/Cap: 0.00 0.00 0.49 0.00 0.00 0.00 0.00 0.30 0.00 0.00 0.49 0.00
Delay/Veh: 0.0 0.0 31.6 0.0 0.0 0.0 0.0 4.8 0.0 0.0 6.0 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 0.0 31.6 0.0 0.0 0.0 0.0 4.8 0.0 0.0 6.0 0.0
LOS by Move: A A C A A A A A A A A A
HCM2kAvgQ: 0 0 6 0 0 0 0 4 0 0 9 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #210 Blue Oaks Blvd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.519
Loss Time (sec): 9 Average Delay (sec/veh): 25.7
Optimal Cycle: 35 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Ovl Ignore Ovl Ignore
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 0 0 2 1 0 2 0 1 0 0 4 0 1 2 0 2 0 1

Volume Module:
Base Vol: 209 0 641 70 368 339 0 888 217 441 763 931
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 209 0 641 70 368 339 0 888 217 441 763 931
User Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00
PHF Volume: 209 0 641 70 368 0 0 888 217 441 763 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 209 0 641 70 368 0 0 888 217 441 763 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00
FinalVolume: 209 0 641 70 368 0 0 888 217 441 763 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 1.00 0.75 0.95 0.95 1.00 1.00 0.91 0.85 0.92 0.95 1.00
Lanes: 1.00 0.00 2.00 1.00 2.00 1.00 0.00 4.00 1.00 2.00 2.00 1.00
Final Sat.: 1805 0 2842 1805 3610 1900 0 6916 1615 3502 3610 1900

Capacity Analysis Module:
Vol/Sat: 0.12 0.00 0.23 0.04 0.10 0.00 0.00 0.13 0.13 0.13 0.21 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.22 0.00 0.54 0.12 0.20 0.00 0.00 0.25 0.47 0.24 0.49 0.00
Volume/Cap: 0.52 0.00 0.41 0.33 0.52 0.00 0.00 0.52 0.29 0.52 0.43 0.00
Delay/Veh: 35.3 0.0 13.6 41.4 36.6 0.0 0.0 32.8 16.4 33.4 16.6 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 35.3 0.0 13.6 41.4 36.6 0.0 0.0 32.8 16.4 33.4 16.6 0.0
LOS by Move: D A B D D A A C B C B A
HCM2kAvgQ: 6 0 7 2 6 0 0 7 4 7 8 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #211 Blue Oaks Blvd & SR 65 NB Off

Cycle (sec): 100 Critical Vol./Cap.(X): 0.642
Loss Time (sec): 6 Average Delay (sec/veh): 7.4
Optimal Cycle: 36 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected
Rights: Ignore Include Ignore Ignore
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 0 0 1 0 0 0 0 0 0 0 2 0 1 1 0 2 0 0

Volume Module:
Base Vol: 58 0 384 0 0 0 0 0 993 272 207 2035 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 58 0 384 0 0 0 0 0 993 272 207 2035 0
User Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Volume: 58 0 0 0 0 0 0 0 993 0 207 2035 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 58 0 0 0 0 0 0 0 993 0 207 2035 0
PCE Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
MLF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
FinalVolume: 58 0 0 0 0 0 0 0 993 0 207 2035 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.77 1.00 1.00 1.00 1.00 1.00 1.00 0.95 1.00 0.95 0.95 1.00
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 0.00 2.00 1.00 1.00 2.00 0.00
Final Sat.: 1461 0 1900 0 0 0 0 3610 1900 1805 3610 0

Capacity Analysis Module:
Vol/Sat: 0.04 0.00 0.00 0.00 0.00 0.00 0.00 0.28 0.00 0.11 0.56 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.06 0.00 0.00 0.00 0.00 0.00 0.00 0.62 0.00 0.26 0.88 0.00
Volume/Cap: 0.64 0.00 0.00 0.00 0.00 0.00 0.00 0.44 0.00 0.44 0.64 0.00
Delay/Veh: 60.5 0.0 0.0 0.0 0.0 0.0 0.0 10.1 0.0 31.7 2.2 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 60.5 0.0 0.0 0.0 0.0 0.0 0.0 10.1 0.0 31.7 2.2 0.0
LOS by Move: E A A A A A A B A C A A
HCM2kAvgQ: 3 0 0 0 0 0 0 8 0 6 10 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #212 Pleasant Grove Blvd & SR 65 NB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.175
Loss Time (sec): 6 Average Delay (sec/veh): 79.4
Optimal Cycle: 180 Level Of Service: E

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected
Rights: Ovl Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 2 0 0 0 1 0 0 0 0 0 0 0 1 1 0 1 0 2 0 0

Volume Module:
Base Vol: 351 0 823 0 0 0 0 0 1369 282 0 2148 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 351 0 823 0 0 0 0 0 1369 282 0 2148 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 351 0 823 0 0 0 0 0 1369 282 0 2148 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 351 0 823 0 0 0 0 0 1369 282 0 2148 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 351 0 823 0 0 0 0 0 1369 282 0 2148 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.59 1.00 0.85 1.00 1.00 1.00 1.00 0.93 0.93 1.00 0.95 1.00
Lanes: 2.00 0.00 1.00 0.00 0.00 0.00 0.00 1.66 0.34 1.00 2.00 0.00
Final Sat.: 2241 0 1615 0 0 0 0 2916 601 1900 3610 0

Capacity Analysis Module:
Vol/Sat: 0.16 0.00 0.51 0.00 0.00 0.00 0.00 0.47 0.47 0.00 0.60 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.43 0.00 0.43 0.00 0.00 0.00 0.00 0.51 0.51 0.00 0.51 0.00
Volume/Cap: 0.36 0.00 1.18 0.00 0.00 0.00 0.00 0.93 0.93 0.00 1.18 0.00
Delay/Veh: 19.2 0.0 121.7 0.0 0.0 0.0 0.0 31.9 31.9 0.0 110 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 19.2 0.0 121.7 0.0 0.0 0.0 0.0 31.9 31.9 0.0 110 0.0
LOS by Move: B A F A A A A C C A F A
HCM2kAvgQ: 4 0 43 0 0 0 0 29 29 0 58 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #213 Pleasant Grove Blvd & SR 65 SB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.016
Loss Time (sec): 6 Average Delay (sec/veh): 28.3
Optimal Cycle: 180 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Permitted Permitted Protected Protected
Rights: Include Ignore Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 0 0 0 0 0 1 0 0 0 1 0 0 1 1 0 1 0 2 0 0

Volume Module:
Base Vol: 0 0 0 94 0 221 0 1564 734 400 2717 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 0 0 94 0 221 0 1564 734 400 2717 0
User Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 0 0 0 94 0 0 0 1564 734 400 2717 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 0 0 94 0 0 0 1564 734 400 2717 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 0 0 0 94 0 0 0 1564 734 400 2717 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 1.00 1.00 0.77 1.00 1.00 1.00 0.90 0.90 0.95 0.95 1.00
Lanes: 0.00 0.00 0.00 1.00 0.00 1.00 0.00 1.36 0.64 1.00 2.00 0.00
Final Sat.: 0 0 0 1461 0 1900 0 2339 1098 1805 3610 0

Capacity Analysis Module:
Vol/Sat: 0.00 0.00 0.00 0.06 0.00 0.00 0.00 0.67 0.67 0.22 0.75 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.00 0.00 0.06 0.00 0.00 0.00 0.66 0.66 0.22 0.88 0.00
Volume/Cap: 0.00 0.00 0.00 1.02 0.00 0.00 0.00 1.02 1.02 1.02 0.86 0.00
Delay/Veh: 0.0 0.0 0.0 144.7 0.0 0.0 0.0 40.0 40.0 88.4 5.6 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 0.0 0.0 144.7 0.0 0.0 0.0 40.0 40.0 88.4 5.6 0.0
LOS by Move: A A A F A A A D D F A A
HCM2kAvgQ: 0 0 0 6 0 0 0 47 47 19 25 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #214 Stanford Ranch Rd & SR 65 NB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.998
Loss Time (sec): 3 Average Delay (sec/veh): 30.4
Optimal Cycle: 180 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted
Rights: Include Include Ignore Ignore
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 2 0 0 0 0 2 1 0 0 0 0 0 1

Volume Module:
Base Vol: 738 1499 0 0 2617 244 0 0 323 0 0 1001
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 738 1499 0 0 2617 244 0 0 323 0 0 1001
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Volume: 738 1499 0 0 2617 244 0 0 0 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 738 1499 0 0 2617 244 0 0 0 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
FinalVolume: 738 1499 0 0 2617 244 0 0 0 0 0 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 0.95 1.00 1.00 0.90 0.90 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 2.00 0.00 0.00 2.74 0.26 0.00 0.00 1.00 0.00 0.00 1.00
Final Sat.: 1805 3610 0 0 4683 437 0 0 1900 0 0 1900

Capacity Analysis Module:
Vol/Sat: 0.41 0.42 0.00 0.00 0.56 0.56 0.00 0.00 0.00 0.00 0.00 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.41 0.97 0.00 0.00 0.56 0.56 0.00 0.00 0.00 0.00 0.00 0.00
Volume/Cap: 1.00 0.43 0.00 0.00 1.00 1.00 0.00 0.00 0.00 0.00 0.00 0.00
Delay/Veh: 61.9 0.2 0.0 0.0 38.2 38.2 0.0 0.0 0.0 0.0 0.0 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 61.9 0.2 0.0 0.0 38.2 38.2 0.0 0.0 0.0 0.0 0.0 0.0
LOS by Move: E A A A D D A A A A A A
HCM2kAvgQ: 30 2 0 0 40 40 0 0 0 0 0 0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\* Intersection #215 Stanford Ranch Rd & SR 65 SB \*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.129
Loss Time (sec): 3 Average Delay (sec/veh): 50.9
Optimal Cycle: 180 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Permitted Permitted
Rights: Include Include Ignore Ignore
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 0 0 2 0 1 1 0 2 0 0 0 0 0 0 1

Volume Module:
Base Vol: 0 2342 402 806 2199 0 0 0 635 0 0 199
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 2342 402 806 2199 0 0 0 635 0 0 199
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
PHF Volume: 0 2342 402 806 2199 0 0 0 0 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 0 2342 402 806 2199 0 0 0 0 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00
FinalVolume: 0 2342 402 806 2199 0 0 0 0 0 0 0

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 1.00 0.95 0.85 0.95 0.95 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 0.00 2.00 1.00 1.00 2.00 0.00 0.00 0.00 1.00 0.00 0.00 1.00
Final Sat.: 0 3610 1615 1805 3610 0 0 0 1900 0 0 1900

Capacity Analysis Module:
Vol/Sat: 0.00 0.65 0.25 0.45 0.61 0.00 0.00 0.00 0.00 0.00 0.00 0.00
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.57 0.57 0.40 0.97 0.00 0.00 0.00 0.00 0.00 0.00 0.00
Volume/Cap: 0.00 1.13 0.43 1.13 0.63 0.00 0.00 0.00 0.00 0.00 0.00 0.00
Delay/Veh: 0.0 86.2 12.4 105.4 0.5 0.0 0.0 0.0 0.0 0.0 0.0 0.0
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 0.0 86.2 12.4 105.4 0.5 0.0 0.0 0.0 0.0 0.0 0.0 0.0
LOS by Move: A F B F A A A A A A A A
HCM2kAvgQ: 0 58 7 40 4 0 0 0 0 0 0 0

Note: Queue reported is the number of cars per lane.



City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #301 Sierra College Bl & Brace Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.569
Loss Time (sec): 6 Average Delay (sec/veh): 18.1
Optimal Cycle: 31 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module table with 4 columns: Approach and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module table with 4 columns: Approach and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach and 4 rows: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #302 Sierra College Bl & Taylor Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 1.095
Loss Time (sec): 12 Average Delay (sec/veh): 72.4
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module table with 4 columns: Approach and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module table with 4 columns: Approach and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach and 4 rows: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #304 Sierra College Bl & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.760
Loss Time (sec): 12 Average Delay (sec/veh): 28.7
Optimal Cycle: 69 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 0 1 0 1 0 0 1 0 0 0

Volume Module:
Base Vol: 1 603 39 347 486 17 32 20 4 15 2 157
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 1 603 39 347 486 17 32 20 4 15 2 157
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 1 603 39 347 486 17 32 20 4 15 2 157
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 1 603 39 347 486 17 32 20 4 15 2 157
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 1 603 39 347 486 17 32 20 4 15 2 157

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 0.99 0.99 0.95 1.00 1.00 0.96 0.96 0.96 0.87 0.87 0.87
Lanes: 1.00 0.94 0.06 1.00 0.97 0.03 0.57 0.36 0.07 0.09 0.01 0.90
Final Sat.: 1805 1769 114 1805 1827 64 1045 653 131 143 19 1499

Capacity Analysis Module:
Vol/Sat: 0.00 0.34 0.34 0.19 0.27 0.27 0.03 0.03 0.03 0.10 0.10 0.10
Crit Moves: \*\*\*\*
Green/Cycle: 0.00 0.45 0.45 0.25 0.70 0.70 0.04 0.04 0.04 0.14 0.14 0.14
Volume/Cap: 0.38 0.76 0.76 0.76 0.38 0.38 0.76 0.76 0.76 0.76 0.76 0.76
Delay/Veh: 122.9 27.1 27.1 41.8 6.3 6.3 83.6 83.6 83.6 55.3 55.3 55.3
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 122.9 27.1 27.1 41.8 6.3 6.3 83.6 83.6 83.6 55.3 55.3 55.3
LOS by Move: F C C D A A F F E E E
HCM2kAvgQ: 0 18 18 12 6 6 3 3 3 7 7 7

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Operations Method (Base Volume Alternative)

Intersection #305 Taylor Rd & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.523
Loss Time (sec): 12 Average Delay (sec/veh): 30.7
Optimal Cycle: 42 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 1 0 1 1 0 1 0 1 0 1

Volume Module:
Base Vol: 298 299 176 27 241 53 241 164 213 112 112 31
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 298 299 176 27 241 53 241 164 213 112 112 31
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 298 299 176 27 241 53 241 164 213 112 112 31
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 298 299 176 27 241 53 241 164 213 112 112 31
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 298 299 176 27 241 53 241 164 213 112 112 31

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 1.00 0.85 0.95 0.92 0.92 0.95 1.00 0.85 0.95 0.97 0.97
Lanes: 1.00 1.00 1.00 1.00 1.64 0.36 1.00 1.00 1.00 1.00 0.78 0.22
Final Sat.: 1805 1900 1615 1805 2879 633 1805 1900 1615 1805 1439 398

Capacity Analysis Module:
Vol/Sat: 0.17 0.16 0.11 0.01 0.08 0.08 0.13 0.09 0.13 0.06 0.08 0.08
Crit Moves: \*\*\*\*
Green/Cycle: 0.32 0.43 0.43 0.04 0.16 0.16 0.26 0.27 0.27 0.13 0.15 0.15
Volume/Cap: 0.52 0.36 0.25 0.36 0.52 0.52 0.52 0.31 0.48 0.48 0.52 0.52
Delay/Veh: 28.9 19.2 18.1 49.6 39.4 39.4 33.1 29.1 31.1 42.0 41.1 41.1
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 28.9 19.2 18.1 49.6 39.4 39.4 33.1 29.1 31.1 42.0 41.1 41.1
LOS by Move: C B B D D D C C C D D D
HCM2kAvgQ: 8 6 3 1 5 5 7 4 6 4 5 5

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #306 Taylor Rd & Horseshoe Bar  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.842  
Loss Time (sec): 9 Average Delay (sec/veh): 35.8  
Optimal Cycle: 80 Level Of Service: D

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Split Phase Split Phase  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 1 0 1 0 0 1 0 0 1

Volume Module:  
Base Vol: 8 538 156 340 388 4 13 7 5 67 8 300  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 8 538 156 340 388 4 13 7 5 67 8 300  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 8 538 156 340 388 4 13 7 5 67 8 300  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 8 538 156 340 388 4 13 7 5 67 8 300  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 8 538 156 340 388 4 13 7 5 67 8 300

Saturation Flow Module:  
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
Adjustment: 0.95 0.97 0.97 0.95 1.00 1.00 0.95 0.95 0.95 0.96 0.96 0.85  
Lanes: 1.00 0.78 0.22 1.00 0.99 0.01 0.52 0.28 0.20 0.89 0.11 1.00  
Final Sat.: 1805 1423 413 1805 1879 19 937 505 360 1624 194 1615

Capacity Analysis Module:  
Vol/Sat: 0.00 0.38 0.38 0.19 0.21 0.21 0.01 0.01 0.01 0.04 0.04 0.19  
Crit Moves: \*\*\*\*  
Green/Cycle: 0.01 0.45 0.45 0.22 0.66 0.66 0.02 0.02 0.02 0.22 0.22 0.22  
Volume/Cap: 0.31 0.84 0.84 0.84 0.31 0.31 0.84 0.84 0.84 0.19 0.19 0.84  
Delay/Veh: 55.7 32.2 32.2 51.8 7.5 7.5 149.2 149 149.2 31.9 31.9 53.6  
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
AdjDel/Veh: 55.7 32.2 32.2 51.8 7.5 7.5 149.2 149 149.2 31.9 31.9 53.6  
LOS by Move: E C C D A A F F F C C D  
HCM2kAvgQ: 1 21 21 13 5 5 2 2 2 2 2 12

Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*

City of Rocklin General Plan Update  
Existing Plus Project Conditions

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #501 E Lincoln Pkwy & Twelve Bridges  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.528  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 48 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
Rights: Ovl Ovl Ovl Ovl  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 0 1 1 0 1 0 1 1 0 2 0 1 1

Volume Module:  
Base Vol: 5 138 76 11 175 356 393 273 1 64 385 1  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 5 138 76 11 175 356 393 273 1 64 385 1  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 5 138 76 11 175 356 393 273 1 64 385 1  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 5 138 76 11 175 356 393 273 1 64 385 1  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 5 138 76 11 175 356 393 273 1 64 385 1

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 2.00 1.00 1.00 2.00 1.00  
Final Sat.: 1450 1450 1450 1450 1450 1450 2900 1450 1450 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.00 0.10 0.05 0.01 0.12 0.25 0.27 0.09 0.00 0.04 0.13 0.00  
Crit Volume: 5 175 393 192  
Crit Moves: \*\*\*\*

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #502 Sierra College & Twelve Bridges

Average Delay (sec/veh): 2.5 Worst Case Level Of Service: C [ 16.4]

Table with columns: Approach, Movement, Control, Rights, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Final Volume.

Critical Gap Module: Critical Gp, FollowUpTim.

Capacity Module: Cnflct Vol, Potent Cap., Move Cap., Volume/Cap.

Level Of Service Module: 2Way95thQ, Control Del, LOS by Move, Movement, Shared Cap., Shared Queue, Shrd ConDel, Shared LOS, ApproachDel, ApproachLOS.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #601 Sierra College & English Colony

Average Delay (sec/veh): 27.3 Worst Case Level Of Service: F[244.2]

Table with columns: Approach, Movement, Control, Rights, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Final Volume.

Critical Gap Module: Critical Gp, FollowUpTim.

Capacity Module: Cnflct Vol, Potent Cap., Move Cap., Volume/Cap.

Level Of Service Module: 2Way95thQ, Control Del, LOS by Move, Movement, Shared Cap., Shared Queue, Shrd ConDel, Shared LOS, ApproachDel, ApproachLOS.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM 4-Way Stop Method (Base Volume Alternative)

Intersection #307 Rocklin Rd & Barton Rd

Cycle (sec): 100 Critical Vol./Cap. (X): 0.839
Loss Time (sec): 0 Average Delay (sec/veh): 20.7
Optimal Cycle: 0 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Stop Sign Stop Sign Stop Sign Stop Sign
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Lanes: 1 0 1 0 0 0 0 0 1 0 0 0 0 0

Volume Module:
Base Vol: 192 43 0 0 72 47 56 0 512 0 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 192 43 0 0 72 47 56 0 512 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86 0.86
PHF Volume: 223 50 0 0 84 55 65 0 595 0 0 0
Reduced Vol: 223 50 0 0 84 55 65 0 595 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 223 50 0 0 84 55 65 0 595 0 0 0

Saturation Flow Module:
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.00 0.00 0.00 0.61 0.39 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.: 501 536 0 0 334 218 569 0 709 0 0 0

Capacity Analysis Module:
Vol/Sat: 0.45 0.09 xxxx xxxx 0.25 0.25 0.11 xxxx 0.84 xxxx xxxx xxxx
Crit Moves: \*\*\*\*
Delay/Veh: 14.6 9.7 0.0 0.0 11.0 11.0 9.7 0.0 27.3 0.0 0.0 0.0
Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 14.6 9.7 0.0 0.0 11.0 11.0 9.7 0.0 27.3 0.0 0.0 0.0
LOS by Move: B A \* \* B A \* D \* \* \*
ApproachDel: 13.7 11.0 25.6
Delay Adj: 1.00 1.00
ApprAdjDel: 13.7 11.0 25.6
LOS by Appr: B D
AllWayAvgQ: 0.7 0.1 0.0 0.3 0.3 0.3 0.1 0.0 3.9 0.0 0.0 0.0

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #308 Barton Rd & Brace Rd

Average Delay (sec/veh): 8.6 Worst Case Level Of Service: D [ 30.7]

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Stop Sign Stop Sign Uncontrolled Uncontrolled
Rights: Include Include Include Include
Lanes: 0 0 1! 0 0 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0

Volume Module:
Base Vol: 155 0 45 0 0 0 0 287 156 140 75 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 155 0 45 0 0 0 0 287 156 140 75 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90 0.90
PHF Volume: 172 0 50 0 0 0 0 319 173 156 83 0
Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 172 0 50 0 0 0 0 319 173 156 83 0

Critical Gap Module:
Critical Gp: 6.4 6.5 6.2 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 4.1 xxxxx xxxxx
FollowUpTim: 3.5 4.0 3.3 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 2.2 xxxxx xxxxx

Capacity Module:
Cnflct Vol: 800 800 406 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 492 xxxxx xxxxx
Potent Cap.: 357 320 650 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 1082 xxxxx xxxxx
Move Cap.: 314 270 650 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 1082 xxxxx xxxxx
Volume/Cap: 0.55 0.00 0.08 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 0.14 xxxxx xxxxx

Level Of Service Module:
2Way95thQ: xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx 0.5 xxxxx xxxxx
Control Del:xxxxx xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx 8.9 xxxxx xxxxx
LOS by Move: \*
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxx 355 xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx
SharedQueue:xxxxx 4.0 xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx 0.5 xxxxx xxxxx
Shrd ConDel:xxxxx 30.7 xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx 8.9 xxxxx xxxxx
Shared LOS: \* D \*
ApproachDel: 30.7 xxxxxxx xxxxxxx xxxxxxx
ApproachLOS: D \*

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #309 Horseshoe Bar Rd & I-80 WB Ramp

Cycle (sec): 100 Critical Vol./Cap. (X): 0.359
Loss Time (sec): 0 Average Delay (sec/veh): 26.3
Optimal Cycle: 36 Level Of Service: C

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Protected Protected Split Phase Split Phase
Rights: Include Ignore Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 1 1 0 1 0 1 1 0 0 1 0

Volume Module:
Base Vol: 88 249 178 44 246 363 53 47 92 73 53 133
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 88 249 178 44 246 363 53 47 92 73 53 133
User Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.96 0.96 0.96 0.96 0.96 0.00 0.96 0.96 0.96 0.96 0.96 0.96
PHF Volume: 92 259 185 46 256 0 55 49 96 76 55 139
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 92 259 185 46 256 0 55 49 96 76 55 139
PCE Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 92 259 185 46 256 0 55 49 96 76 55 139

Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjustment: 0.95 0.89 0.89 0.95 1.00 1.00 0.97 0.97 0.85 0.95 0.89 0.89
Lanes: 1.00 1.17 0.83 1.00 1.00 1.00 0.53 0.47 1.00 1.00 0.28 0.72
Final Sat.: 1805 1973 1410 1805 1900 1900 981 870 1615 1805 483 1213

Capacity Analysis Module:
Vol/Sat: 0.05 0.13 0.13 0.03 0.13 0.00 0.06 0.06 0.06 0.04 0.11 0.11
Crit Moves: \*\*\*\*
Green/Cycle: 0.14 0.43 0.43 0.08 0.38 0.00 0.17 0.17 0.17 0.32 0.32 0.32
Volume/Cap: 0.36 0.30 0.30 0.36 0.36 0.00 0.34 0.34 0.36 0.13 0.36 0.36
Delay/Veh: 39.7 18.6 18.6 44.2 22.9 0.0 37.6 37.6 37.9 24.4 26.7 26.7
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 39.7 18.6 18.6 44.2 22.9 0.0 37.6 37.6 37.9 24.4 26.7 26.7
LOS by Move: D B B D C A D D D C C C
HCM2kAvgQ: 3 5 5 2 6 0 3 3 3 2 5 5

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update Existing Plus Project Conditions

Level Of Service Computation Report

2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #310 Horseshoe Bar Rd & I-80 EB Ramp

Average Delay (sec/veh): 6.9 Worst Case Level Of Service: C [ 16.6]

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Uncontrolled Uncontrolled Stop Sign Stop Sign
Rights: Include Include Include Include
Lanes: 0 0 1 0 1 0 1 0 0 0 0 0 0 0 0 1

Volume Module:
Base Vol: 0 265 37 207 261 0 0 0 0 82 0 284
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 265 37 207 261 0 0 0 0 82 0 284
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 0.94 0.94 0.94 0.94 0.94 0.94 0.94 0.94 0.94 0.94 0.94 0.94
PHF Volume: 0 282 39 220 278 0 0 0 0 87 0 302
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 0 282 39 220 278 0 0 0 0 87 0 302

Critical Gap Module:
Critical Gp:xxxxx xxxx xxxxx 4.1 xxxx xxxxx xxxxx xxxx xxxxx 6.4 xxxx 6.2
FollowUpTim:xxxxx xxxx xxxxx 2.2 xxxx xxxxx xxxxx xxxx xxxxx 3.5 xxxx 3.3

Capacity Module:
Cnflct Vol: xxxx xxxx xxxxx 321 xxxx xxxxx xxxx xxxx xxxxx 1000 xxxx 282
Potent Cap.: xxxx xxxx xxxxx 1250 xxxx xxxxx xxxx xxxx xxxxx 272 xxxx 762
Move Cap.: xxxx xxxx xxxxx 1250 xxxx xxxxx xxxx xxxx xxxxx 230 xxxx 762
Volume/Cap: xxxx xxxx xxxx 0.18 xxxx xxxx xxxx xxxx xxxx 0.38 xxxx 0.40

Level Of Service Module:
2Way95thQ: xxxx xxxx xxxxx 0.6 xxxx xxxxx xxxx xxxx xxxxx 1.7 xxxx 1.9
Control Del:xxxxx xxxx xxxxx 8.5 xxxx xxxxx xxxxx xxxx xxxxx 29.9 xxxxx 12.8
LOS by Move: \* \* \* A \* \* \* D \* B
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx
SharedQueue:xxxxx xxxx xxxxx 0.6 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx
Shrd ConDel:xxxxx xxxx xxxxx 8.5 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx
Shared LOS: \* \* \* A \* \* \* \* \*
ApproachDel: xxxxxx xxxxxx xxxxxx 16.6
ApproachLOS: \* \* \* C

Note: Queue reported is the number of cars per lane.

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in	
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C		
#401 Pleasant Grove & Fairway	E xxxxx	0.922	E xxxxx	0.922	+ 0.000	V/C
#402 Stanford Ranch & Fairway	B xxxxx	0.654	B xxxxx	0.654	+ 0.000	V/C
#403 Stanford Ranch & Five Star	D xxxxx	0.858	D xxxxx	0.858	+ 0.000	V/C
#404 Pleasant Grove & Roseville Pkw	C xxxxx	0.744	C xxxxx	0.744	+ 0.000	V/C
#405 Galleria & Roseville Pkwy	D xxxxx	0.829	D xxxxx	0.829	+ 0.000	V/C
#406 Roseville Parkway & Taylor	C xxxxx	0.714	C xxxxx	0.714	+ 0.000	V/C
#407 Roseville Parkway & N. Sunrise	B xxxxx	0.677	B xxxxx	0.677	+ 0.000	V/C
#408 Sierra College & Secret Ravine	A xxxxx	0.595	A xxxxx	0.595	+ 0.000	V/C

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #401 Pleasant Grove & Fairway  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.922  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: E

Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected  
 Rights: Ovl Ovl Ovl Ovl  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 2 0 2 0 1 1 0 2 0 1 2 0 2 0 1 2 0 2 0 1

Volume Module:  
 Base Vol: 487 1285 356 176 1309 119 161 296 264 581 385 85  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 487 1285 356 176 1309 119 161 296 264 581 385 85  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 487 1285 356 176 1309 119 161 296 264 581 385 85  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 487 1285 356 176 1309 119 161 296 264 581 385 85  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 487 1285 356 176 1309 119 161 296 264 581 385 85

Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 2.00 1.00 1.00 2.00 1.00 2.00 2.00 1.00 2.00 2.00 1.00  
 Final Sat.: 2900 2900 1450 1450 2900 1450 2900 2900 1450 2900 2900 1450

Capacity Analysis Module:  
 Vol/Sat: 0.17 0.44 0.25 0.12 0.45 0.08 0.06 0.10 0.18 0.20 0.13 0.06  
 Crit Volume: 244 655 148 291  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #402 Stanford Ranch & Fairway  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.654  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 66 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module: Table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #403 Stanford Ranch & Five Star  
\*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.858  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 161 Level Of Service: D

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module: Table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*



GP08 Fri May 22, 2009 10:32:58 Page 6-1

-----  
 Rocklin General Plan Update  
 Existing Plus Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #404 Pleasant Grove & Roseville Pkwy  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 0.744  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 89 Level Of Service: C  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ignore Ignore Ignore Ignore  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 3 0 2 0 1 2 0 3 0 1 2 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 478 246 603 170 274 34 35 1367 598 1116 1927 115  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 478 246 603 170 274 34 35 1367 598 1116 1927 115  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 478 246 0 170 274 0 35 1367 0 1116 1927 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 478 246 0 170 274 0 35 1367 0 1116 1927 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 478 246 0 170 274 0 35 1367 0 1116 1927 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 3.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00 3.00 3.00 1.00  
 Final Sat.: 4350 2900 1450 2900 4350 1450 2900 4350 1450 4350 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.11 0.08 0.00 0.06 0.06 0.00 0.01 0.31 0.00 0.26 0.44 0.00  
 Crit Volume: 159 91 456 372  
 Crit Moves: \*\*\*\*

GP08 Fri May 22, 2009 10:32:58 Page 7-1

-----  
 Rocklin General Plan Update  
 Existing Plus Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #405 Galleria & Roseville Pkwy  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 0.829  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 133 Level Of Service: D  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ignore Ignore Ignore Ignore  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 2 0 3 0 1 3 0 2 0 1 2 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 396 688 13 907 754 352 347 1160 523 99 1360 777  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 396 688 13 907 754 352 347 1160 523 99 1360 777  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 396 688 0 907 754 0 347 1160 0 99 1360 0  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 396 688 0 907 754 0 347 1160 0 99 1360 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 396 688 0 907 754 0 347 1160 0 99 1360 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 3.00 1.00 3.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
 Final Sat.: 2900 4350 1450 4350 2900 1450 2900 4350 1450 2900 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.14 0.16 0.00 0.21 0.26 0.00 0.12 0.27 0.00 0.03 0.31 0.00  
 Crit Volume: 198 377 174 453  
 Crit Moves: \*\*\*\*

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #406 Roseville Parkway & Taylor

Cycle (sec): 120 Critical Vol./Cap.(X): 0.714  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 80 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update  
Existing Plus Project  
Roseville Intersections

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #407 Roseville Parkway & N. Sunrise

Cycle (sec): 120 Critical Vol./Cap.(X): 0.677  
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 71 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

GP08 Fri May 22, 2009 10:32:58 Page 10-1
Rocklin General Plan Update
Existing Plus Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)
Intersection #408 Sierra College & Secret Ravine
Cycle (sec): 120 Critical Vol./Cap.(X): 0.595
Loss Time (sec): 9 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 46 Level Of Service: A
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Protected Protected Permitted Permitted
Rights: Ovl Ovl Ovl Ovl
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 2 0 1 1 0 2 0 1 0 1 0 1 0 0 1
Volume Module:
Base Vol: 181 953 3 1 1059 227 174 2 127 3 5 3
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 181 953 3 1 1059 227 174 2 127 3 5 3
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 181 953 3 1 1059 227 174 2 127 3 5 3
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 181 953 3 1 1059 227 174 2 127 3 5 3
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 181 953 3 1 1059 227 174 2 127 3 5 3
Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 1.00 0.16 0.84 0.38 0.62 1.00
Final Sat.: 1500 3000 1500 1500 3000 1500 1500 243 1257 563 938 1500
Capacity Analysis Module:
Vol/Sat: 0.12 0.32 0.00 0.00 0.35 0.15 0.12 0.01 0.10 0.01 0.01 0.00
Crit Volume: 181 530 174 8
Crit Moves: \*\*\*\*



**INTERSECTION LOS WORKSHEETS  
2030 CUMULATIVE NO PROJECT CONDITIONS**

---



City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C	
# 1 Granite Dr & Rocklin Rd	D xxxxx	0.865	D xxxxx	0.865	+ 0.000 V/C
# 2 Granite Dr & Sierra College Bl	B xxxxx	0.688	B xxxxx	0.688	+ 0.000 V/C
# 3 Granite Dr & Sierra Meadows	B xxxxx	0.612	B xxxxx	0.612	+ 0.000 V/C
# 4 Pacific St & Del Mar/ Domingue	E xxxxx	0.920	E xxxxx	0.920	+ 0.000 V/C
# 5 Pacific St & Farron St	E xxxxx	0.975	E xxxxx	0.975	+ 0.000 V/C
# 6 Pacific St & Midas Ave	C xxxxx	0.775	C xxxxx	0.775	+ 0.000 V/C
# 7 Pacific St & Rocklin Rd	E xxxxx	0.902	E xxxxx	0.902	+ 0.000 V/C
# 8 Pacific St & Sierra Meadows	B xxxxx	0.690	B xxxxx	0.690	+ 0.000 V/C
# 9 Pacific St & Woodside Dr	B xxxxx	0.665	B xxxxx	0.665	+ 0.000 V/C
# 10 Rocklin Rd & Aguilar Rd	B xxxxx	0.682	B xxxxx	0.682	+ 0.000 V/C
# 11 Rocklin Rd & El Don Dr	C xxxxx	0.748	C xxxxx	0.748	+ 0.000 V/C
# 12 Rocklin Rd & Fire Station No 1	A xxxxx	0.482	A xxxxx	0.482	+ 0.000 V/C
# 13 Rocklin Rd & Havenhurst Cir	C xxxxx	0.739	C xxxxx	0.739	+ 0.000 V/C
# 14 Rocklin Rd & Sierra College Bl	E xxxxx	0.958	E xxxxx	0.958	+ 0.000 V/C
# 15 Rocklin Rd & South Grove St	B xxxxx	0.662	B xxxxx	0.662	+ 0.000 V/C
# 16 Sierra College Bl & El Don Dr	B xxxxx	0.688	B xxxxx	0.688	+ 0.000 V/C
# 17 Sierra College Bl & Nightwatch	A xxxxx	0.572	A xxxxx	0.572	+ 0.000 V/C
# 18 Sierra College Bl & Scarboroug	A xxxxx	0.574	A xxxxx	0.574	+ 0.000 V/C
# 19 Sierra College Bl & Southside	A xxxxx	0.568	A xxxxx	0.568	+ 0.000 V/C
# 20 Sunset Bl & Pacific St	D xxxxx	0.878	D xxxxx	0.878	+ 0.000 V/C
# 21 Sunset Bl & Springview Dr	F xxxxx	1.054	F xxxxx	1.054	+ 0.000 V/C
# 22 Sunset Bl & Topaz Ave	B xxxxx	0.681	B xxxxx	0.681	+ 0.000 V/C
# 23 Sunset Bl & Whitney Bl	F xxxxx	1.098	F xxxxx	1.098	+ 0.000 V/C

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C	
#101 Blue Oaks Bl & Lonetree	E xxxxx	0.958	E xxxxx	0.958	+ 0.000 V/C
#102 Blue Oaks Bl & Market Place	A xxxxx	0.317	A xxxxx	0.317	+ 0.000 V/C
#103 Blue Oaks Bl & Van Buren Way	A xxxxx	0.368	A xxxxx	0.368	+ 0.000 V/C
#104 Five Star & Destiny Dr	A xxxxx	0.204	A xxxxx	0.204	+ 0.000 V/C
#105 Lonetree Bl & Adams Dr	B xxxxx	0.636	B xxxxx	0.636	+ 0.000 V/C
#106 Lonetree Bl & Atherton Rd	A xxxxx	0.469	A xxxxx	0.469	+ 0.000 V/C
#107 Lonetree Bl & Grand Canyon Dr	D xxxxx	0.808	D xxxxx	0.808	+ 0.000 V/C
#108 Lonetree Bl & Redwood Dr	C xxxxx	0.775	C xxxxx	0.775	+ 0.000 V/C
#109 Lonetree Bl & West Oaks Bl	A xxxxx	0.580	A xxxxx	0.580	+ 0.000 V/C
#110 Park Dr & Blaydon Rd	A xxxxx	0.273	A xxxxx	0.273	+ 0.000 V/C
#111 Park Dr & Quarry Way	A xxxxx	0.545	A xxxxx	0.545	+ 0.000 V/C
#112 Park Dr & Farrier Rd	B xxxxx	0.644	B xxxxx	0.644	+ 0.000 V/C
#113 Park Dr & King Pine Dr	A xxxxx	0.526	A xxxxx	0.526	+ 0.000 V/C
#114 Park Dr & Shelton	A xxxxx	0.340	A xxxxx	0.340	+ 0.000 V/C
#115 Park Dr & Victory Lane	A xxxxx	0.406	A xxxxx	0.406	+ 0.000 V/C
#116 Park Dr & Wykford Bl	A xxxxx	0.416	A xxxxx	0.416	+ 0.000 V/C
#117 Park Dr & Twin Oaks/ Boardwalk	A xxxxx	0.402	A xxxxx	0.402	+ 0.000 V/C
#118 Park Dr & Safeway	C xxxxx	0.727	C xxxxx	0.727	+ 0.000 V/C
#119 South Whitney & Five Star Bl	A xxxxx	0.553	A xxxxx	0.553	+ 0.000 V/C
#120 Spring Creek Dr & Broken Rail	A xxxxx	0.053	A xxxxx	0.053	+ 0.000 V/C
#121 Stanford Ranch Rd & Cobbleston	A xxxxx	0.326	A xxxxx	0.326	+ 0.000 V/C
#122 Stanford Ranch Rd & Darby Rd	B xxxxx	0.655	B xxxxx	0.655	+ 0.000 V/C
#123 Stanford Ranch Rd & Park Dr	C xxxxx	0.709	C xxxxx	0.709	+ 0.000 V/C
#124 Stanford Ranch Rd & Plaza	A xxxxx	0.591	A xxxxx	0.591	+ 0.000 V/C
#125 Stanford Ranch Rd & Stoney Dr	A xxxxx	0.405	A xxxxx	0.405	+ 0.000 V/C

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
#126 Stanford Ranch Rd & Victory Ln	A	xxxxx 0.341	A	xxxxx 0.341	+ 0.000 V/C
#127 Stanford Ranch Rd & West Oaks	B	xxxxx 0.688	B	xxxxx 0.688	+ 0.000 V/C
#128 Sunset Bl & Atherton	E	xxxxx 0.953	E	xxxxx 0.953	+ 0.000 V/C
#129 Sunset Bl & Blue Oaks Bl	D	xxxxx 0.842	D	xxxxx 0.842	+ 0.000 V/C
#130 Sunset Bl & Fairway Dr	C	xxxxx 0.754	C	xxxxx 0.754	+ 0.000 V/C
#131 Sunset Bl & Little Rock	B	xxxxx 0.621	B	xxxxx 0.621	+ 0.000 V/C
#132 Sunset Bl & Park Dr	D	xxxxx 0.856	D	xxxxx 0.856	+ 0.000 V/C
#133 Sunset Bl & Pebble Creek	C	xxxxx 0.720	C	xxxxx 0.720	+ 0.000 V/C
#134 Sunset Bl & Stanford Ranch Rd	C	xxxxx 0.718	C	xxxxx 0.718	+ 0.000 V/C
#135 Sunset Bl & West Oaks Bl	F	xxxxx 1.112	F	xxxxx 1.112	+ 0.000 V/C
#136 W Stanford Ranch Rd & Sunset B	F	xxxxx 1.240	F	xxxxx 1.240	+ 0.000 V/C
#137 W Stanford Ranch Rd & Wildcat	D	xxxxx 0.856	D	xxxxx 0.856	+ 0.000 V/C
#138 Whitney Ranch Pkwy & Bridlewoo	A	xxxxx 0.354	A	xxxxx 0.354	+ 0.000 V/C
#139 Whitney Ranch Pkwy & Painted P	A	xxxxx 0.316	A	xxxxx 0.316	+ 0.000 V/C
#140 Whitney Ranch Pkwy & Spring Cr	A	xxxxx 0.311	A	xxxxx 0.311	+ 0.000 V/C
#141 Wildcat Bl & Bridlewood Dr	B	xxxxx 0.617	B	xxxxx 0.617	+ 0.000 V/C
#142 Wildcat Bl & Whitney Ranch Pkw	C	xxxxx 0.717	C	xxxxx 0.717	+ 0.000 V/C
#143 Wildcat Bl & S High School Ent	A	xxxxx 0.509	A	xxxxx 0.509	+ 0.000 V/C
#144 Wildcat Bl & N High School Ent	A	xxxxx 0.431	A	xxxxx 0.431	+ 0.000 V/C
#145 Wildcat Bl & Ranch View Dr	D	xxxxx 0.827	D	xxxxx 0.827	+ 0.000 V/C
#152 Stanford Ranch Rd & Crest Dr	F	xxxxx 1.003	F	xxxxx 1.003	+ 0.000 V/C
#153 Whitney Blvd & Crest Dr	D	xxxxx 0.821	D	xxxxx 0.821	+ 0.000 V/C
#154 Park Dr & Crest Dr	A	xxxxx 0.261	A	xxxxx 0.261	+ 0.000 V/C
#161 Granite Dr & Dominguez Dr	D	xxxxx 0.802	D	xxxxx 0.802	+ 0.000 V/C

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
#162 Sierra College Bl & Dominguez	D	xxxxx 0.864	D	xxxxx 0.864	+ 0.000 V/C
#163 Park Dr & Valley View Pkwy	A	xxxxx 0.596	A	xxxxx 0.596	+ 0.000 V/C
#164 Nature Trail Wy & Valley View	C	xxxxx 0.746	C	xxxxx 0.746	+ 0.000 V/C
#165 Sierra College Bl & Valley Vie	B	xxxxx 0.646	B	xxxxx 0.646	+ 0.000 V/C
#166 University Ave & Whitney Ranch	B	xxxxx 0.667	B	xxxxx 0.667	+ 0.000 V/C
#167 West Oaks Bl & Whitney Ranch P	B	xxxxx 0.675	B	xxxxx 0.675	+ 0.000 V/C
#168 West Oaks Bl & Painted Pony Ln	A	xxxxx 0.307	A	xxxxx 0.307	+ 0.000 V/C
#169 Laredo Dr & Whitney Ranch Pkwy	A	xxxxx 0.487	A	xxxxx 0.487	+ 0.000 V/C
#170 Rocklin Rd & Civic Centr Dr	C	xxxxx 0.701	C	xxxxx 0.701	+ 0.000 V/C
#171 Pacific St & Civic Center Dr	B	xxxxx 0.658	B	xxxxx 0.658	+ 0.000 V/C
#201 Rocklin Rd & I-80 EB	E	66.9 1.104	E	66.9 1.104	+ 0.000 D/V
#202 Rocklin Rd & I-80 WB	E	67.5 1.121	E	67.5 1.121	+ 0.000 D/V
#203 Sierra College Bl & I-80 WB	C	32.9 0.865	C	32.9 0.865	+ 0.000 D/V
#204 Sierra College Bl & I-80 EB	C	28.2 0.626	C	28.2 0.626	+ 0.000 D/V
#206 Sunset & SR 65 SB	B	12.3 0.704	B	12.3 0.704	+ 0.000 D/V
#207 Sunset & SR 65 NB	B	14.4 0.727	B	14.4 0.727	+ 0.000 D/V
#208 Whitney Ranch Pkwy & SR 65 SB	C	32.2 0.961	C	32.2 0.961	+ 0.000 D/V
#209 Whitney Ranch Pkwy & SR 65 NB	B	16.1 0.833	B	16.1 0.833	+ 0.000 D/V
#210 Blue Oaks Blvd & SR 65 SB	C	27.0 0.585	C	27.0 0.585	+ 0.000 D/V
#211 Blue Oaks Blvd & SR 65 NB Off	D	41.5 1.083	D	41.5 1.083	+ 0.000 D/V
#212 Pleasant Grove Blvd & SR 65 NB	B	19.2 0.775	B	19.2 0.775	+ 0.000 D/V
#213 Pleasant Grove Blvd & SR 65 SB	A	9.4 0.627	A	9.4 0.627	+ 0.000 D/V
#214 Stanford Ranch Rd & SR 65 NB	B	14.3 0.740	B	14.3 0.740	+ 0.000 D/V
#215 Stanford Ranch Rd & SR 65 SB	B	10.2 0.761	B	10.2 0.761	+ 0.000 D/V
#301 Sierra College Bl & Brace Rd	D	36.7 0.947	D	36.7 0.947	+ 0.000 D/V



City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Intersection	Base		Future		Change in	
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C		
#302 Sierra College Bl & Taylor Rd	E 55.9	1.020	E 55.9	1.020	+ 0.000	D/V
#304 Sierra College Bl & King Rd	D 35.5	0.882	D 35.5	0.882	+ 0.000	D/V
#305 Taylor Rd & King Rd	C 30.3	0.568	C 30.3	0.568	+ 0.000	D/V
#306 Taylor Rd & Horseshoe Bar	F 80.6	1.095	F 80.6	1.095	+ 0.000	D/V
#501 E Lincoln Pkwy & Twelve Bridge	D xxxxx	0.832	D xxxxx	0.832	+ 0.000	V/C
#1216 Sierra College Blvd & SR 193	C 34.8	0.927	C 34.8	0.927	+ 0.000	D/V
#1502 Sierra College & Twelve Bridge	B xxxxx	0.673	B xxxxx	0.673	+ 0.000	V/C
#1601 Sierra College & English Colon	D xxxxx	0.885	D xxxxx	0.885	+ 0.000	V/C

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1 Granite Dr & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.865  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 169 Level Of Service: D  
\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	0	1	0	1	1	0	1

Volume Module:  
Base Vol: 30 17 15 614 19 286 285 1497 10 32 1112 600  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 30 17 15 614 19 286 285 1497 10 32 1112 600  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 30 17 15 614 19 286 285 1497 10 32 1112 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 30 17 15 614 19 286 285 1497 10 32 1112 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 30 17 15 614 19 286 285 1497 10 32 1112 0

Saturation Flow Module:  
Sat/Lane: 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375 1375  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.53 0.47 1.94 0.06 1.00 1.00 1.99 0.01 1.00 2.00 1.00  
Final Sat.: 1375 730 645 2667 83 1375 1375 2732 18 1375 2750 1375

Capacity Analysis Module:  
Vol/Sat: 0.02 0.02 0.02 0.23 0.23 0.21 0.21 0.55 0.55 0.02 0.40 0.00  
Crit Volume: 32 317 285 556  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 4-1

-----

   City of Rocklin General Plan Update  
   2030 No Project Conditions  
   PM Peak Hour LOS (Published Circular 212 Capacities)

-----

   Level Of Service Computation Report  
   Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*

Intersection #2 Granite Dr & Sierra College Bl

\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.688  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      73                      Level Of Service:                      B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	1	0	3	1	0	1	2	1	0

-----

Volume Module:

Base Vol:	98	1420	118	53	1292	154	353	34	260	231	28	24
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	98	1420	118	53	1292	154	353	34	260	231	28	24
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	98	1420	118	53	1292	154	353	34	260	231	28	24
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	98	1420	118	53	1292	154	353	34	260	231	28	24
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	98	1420	118	53	1292	154	353	34	260	231	28	24

-----

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.77	0.23	1.00	3.00	1.00	1.00	1.00	2.00	1.00	1.00	1.00
Final Sat.:	1375	3809	316	1375	4125	1375	1375	1375	2750	1375	1375	1375

-----

Capacity Analysis Module:

Vol/Sat:	0.07	0.37	0.37	0.04	0.31	0.11	0.26	0.02	0.09	0.17	0.02	0.02
Crit Volume:		513	53				353				28	
Crit Moves:		****	****				****				****	

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 5-1

-----

   City of Rocklin General Plan Update  
   2030 No Project Conditions  
   PM Peak Hour LOS (Published Circular 212 Capacities)

-----

   Level Of Service Computation Report  
   Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*

Intersection #3 Granite Dr & Sierra Meadows

\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.612  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      59                      Level Of Service:                      B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	0	1	0	1	1	0	1	1	0	1

-----

Volume Module:

Base Vol:	104	65	45	59	55	270	188	401	53	61	379	59
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	104	65	45	59	55	270	188	401	53	61	379	59
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	104	65	45	59	55	270	188	401	53	61	379	59
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	104	65	45	59	55	270	188	401	53	61	379	59
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	104	65	45	59	55	270	188	401	53	61	379	59

-----

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.59	0.41	1.00	0.17	0.83	1.00	1.77	0.23	1.00	1.73	0.27
Final Sat.:	1375	813	563	1375	233	1142	1375	2429	321	1375	2380	370

-----

Capacity Analysis Module:

Vol/Sat:	0.08	0.08	0.08	0.04	0.24	0.24	0.14	0.17	0.17	0.04	0.16	0.16
Crit Volume:		110				325	188				219	
Crit Moves:		****				****	****				****	

\*\*\*\*\*



NP30 Future Geo Fri May 22, 2009 10:42:39 Page 8-1
City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #6 Pacific St & Midas Ave

Cycle (sec): 100 Critical Vol./Cap.(X): 0.775
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 101 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

NP30 Future Geo Fri May 22, 2009 10:42:39 Page 9-1
City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #7 Pacific St & Rocklin Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.902
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: E

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #8 Pacific St & Sierra Meadows  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.690  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 74 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Protected, Split Phase, and Include movements.

Volume Module: Table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for North, South, East, West bounds.

Saturation Flow Module: Table with columns for Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for North, South, East, West bounds.

Capacity Analysis Module: Table with columns for Vol/Sat, Crit Volume, Crit Moves. Includes data for North, South, East, West bounds.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #9 Pacific St & Woodside Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.665  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 68 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Protected, Split Phase, and Include movements.

Volume Module: Table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for North, South, East, West bounds.

Saturation Flow Module: Table with columns for Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for North, South, East, West bounds.

Capacity Analysis Module: Table with columns for Vol/Sat, Crit Volume, Crit Moves. Includes data for North, South, East, West bounds.

NP30 Future Geo Fri May 22, 2009 10:42:39 Page 12-1

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #10 Rocklin Rd & Aguilar Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.682  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 72 Level Of Service: B

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected		Protected	Protected
Rights:	Include		Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 0 0 1	0 0 0 0 0	1 0 2 1 0	1 0 3 0 0

Volume Module:

Base Vol:	267	0	67	0	0	70	1521	341	84	1643	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	267	0	67	0	0	70	1521	341	84	1643	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	267	0	67	0	0	70	1521	341	84	1643	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	267	0	67	0	0	70	1521	341	84	1643	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	267	0	67	0	0	70	1521	341	84	1643	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.00	1.00	0.00	0.00	0.00	1.00	2.45	0.55	1.00	3.00
Final Sat.:	1425	0	1425	0	0	1425	3492	783	1425	4275	0

Capacity Analysis Module:

Vol/Sat:	0.19	0.00	0.05	0.00	0.00	0.05	0.44	0.44	0.06	0.38	0.00
Crit Volume:	267			0			621	84			
Crit Moves:	****						****	****			

\*\*\*\*\*

NP30 Future Geo Fri May 22, 2009 10:42:39 Page 13-1

City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #11 Rocklin Rd & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.748  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 90 Level Of Service: C

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Split Phase		Split Phase	Protected
Rights:	Include		Ovl	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 0 1 0	0 1 0 0 1	1 0 2 1 0	1 0 2 1 0

Volume Module:

Base Vol:	121	6	15	74	10	538	312	1227	99	25	1076	32
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	121	6	15	74	10	538	312	1227	99	25	1076	32
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	121	6	15	74	10	538	312	1227	99	25	1076	32
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	121	6	15	74	10	538	312	1227	99	25	1076	32
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	121	6	15	74	10	538	312	1227	99	25	1076	32

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.29	0.71	0.88	0.12	1.00	1.00	2.78	0.22	1.00	2.91	0.09
Final Sat.:	1375	393	982	1211	164	1375	1375	3817	308	1375	4006	119

Capacity Analysis Module:

Vol/Sat:	0.09	0.02	0.02	0.06	0.06	0.39	0.23	0.32	0.32	0.02	0.27	0.27
Crit Volume:	121			538	0							369
Crit Moves:	****			****	****							****

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 14-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #12 Rocklin Rd & Fire Station No 1  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.482  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      44                      Level Of Service:                      A  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Protected                      Protected  
Rights:                      Include                      Include                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      0 0 1 0 0                      0 0 1 0 0                      1 0 2 0 0                      1 0 2 0 0  
-----  
Volume Module:  
Base Vol:                      0 0 0                      0 0 0                      0 1446                      0 0 1144 0  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      0 0 0                      0 0 0                      0 1446                      0 0 1144 0  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      0 0 0                      0 0 0                      0 1446                      0 0 1144 0  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0 0  
Reduced Vol:                      0 0 0                      0 0 0                      0 1446                      0 0 1144 0  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      0 0 0                      0 0 0                      0 1446                      0 0 1144 0  
-----  
Saturation Flow Module:  
Sat/Lane:                      1500 1500 1500                      1500 1500 1500                      1500 1500 1500                      1500 1500 1500  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      0.00 1.00 0.00                      0.00 1.00 0.00                      1.00 2.00 0.00                      1.00 2.00 0.00  
Final Sat.:                      0 1500 0                      0 1500 0                      1500 3000                      0 1500 3000 0  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.00 0.00 0.00                      0.00 0.00 0.00                      0.00 0.48 0.00                      0.00 0.38 0.00  
Crit Volume:                      0                      0                      723                      0  
Crit Moves:                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 15-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #13 Rocklin Rd & Havenhurst Cir  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.739  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      87                      Level Of Service:                      C  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Split Phase                      Split Phase                      Protected                      Protected  
Rights:                      Include                      Include                      Include                      Ovl  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      0 0 1 0 0                      0 1 0 0 1                      1 0 2 1 0                      1 0 2 1 0  
-----  
Volume Module:  
Base Vol:                      15 0 4                      392 1 294                      241 1071 27                      9 815 274  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      15 0 4                      392 1 294                      241 1071 27                      9 815 274  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      15 0 4                      392 1 294                      241 1071 27                      9 815 274  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0 0  
Reduced Vol:                      15 0 4                      392 1 294                      241 1071 27                      9 815 274  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      15 0 4                      392 1 294                      241 1071 27                      9 815 274  
-----  
Saturation Flow Module:  
Sat/Lane:                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      0.79 0.00 0.21                      0.99 0.01 1.00                      1.00 2.93 0.07                      1.00 2.25 0.75  
Final Sat.:                      1086 0 289                      1372 3 1375                      1375 4024 101                      1375 3087 1038  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.01 0.00 0.01                      0.29 0.29 0.21                      0.18 0.27 0.27                      0.01 0.26 0.26  
Crit Volume:                      19                      393                      241                      363  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*





City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #16 Sierra College Bl & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.688  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 73 Level Of Service: B

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	3	0	1	1	0	3	0	1	0	0

Volume Module:

Base Vol:	56	2064	32	58	1895	84	59	4	36	45	4	52
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	56	2064	32	58	1895	84	59	4	36	45	4	52
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	56	2064	32	58	1895	84	59	4	36	45	4	52
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	56	2064	32	58	1895	84	59	4	36	45	4	52
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	56	2064	32	58	1895	84	59	4	36	45	4	52

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	3.00	1.00	1.00	3.00	1.00	0.60	0.04	0.36	0.45	0.04	0.51
Final Sat.:	1375	4125	1375	1375	4125	1375	819	56	500	613	54	708

Capacity Analysis Module:

Vol/Sat:	0.04	0.50	0.02	0.04	0.46	0.06	0.07	0.07	0.07	0.07	0.07	0.07
Crit Volume:	688			58					99			101
Crit Moves:	****			****					****			****

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #17 Sierra College Bl & Nightwatch  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.572  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 53 Level Of Service: A

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	3	0	0	0	0	0	3	0	1	0

Volume Module:

Base Vol:	62	2156	0	0	1887	81	76	0	96	0	0	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	62	2156	0	0	1887	81	76	0	96	0	0	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	62	2156	0	0	1887	81	76	0	96	0	0	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	62	2156	0	0	1887	81	76	0	96	0	0	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	62	2156	0	0	1887	81	76	0	96	0	0	0

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	3.00	0.00	0.00	3.00	1.00	1.00	0.00	1.00	0.00	0.00	0.00
Final Sat.:	1425	4275	0	0	4275	1425	1425	0	1425	0	0	0

Capacity Analysis Module:

Vol/Sat:	0.04	0.50	0.00	0.00	0.44	0.06	0.05	0.00	0.07	0.00	0.00	0.00
Crit Volume:	719			0					96			0
Crit Moves:	****			****					****			****

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 20-1

-----  
 City of Rocklin General Plan Update  
 2030 No Project Conditions  
 PM Peak Hour LOS (Published Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #18 Sierra College Bl & Scarborough  
 \*\*\*\*\*  
 Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.574  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      53                      Level Of Service:                      A  
 \*\*\*\*\*  
 Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
 Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
 -----  
 Control:                      Protected                      Protected                      Split Phase                      Split Phase  
 Rights:                      Include                      Include                      Include                      Include  
 Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
 Lanes:                      1 0 3 0 1                      1 0 3 0 1                      1 0 1 0 1                      1 0 1 1 0  
 -----  
 Volume Module:  
 Base Vol:                      21 2223                      1                      4 1937                      72                      40 0                      2                      4 0 0  
 Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 Initial Bse:                      21 2223                      1                      4 1937                      72                      40 0                      2                      4 0 0  
 User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 PHF Volume:                      21 2223                      1                      4 1937                      72                      40 0                      2                      4 0 0  
 Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Reduced Vol:                      21 2223                      1                      4 1937                      72                      40 0                      2                      4 0 0  
 PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 FinalVolume:                      21 2223                      1                      4 1937                      72                      40 0                      2                      4 0 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane:                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375  
 Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 Lanes:                      1.00 3.00                      1.00                      1.00 3.00                      1.00                      1.00 1.00                      1.00                      1.00 2.00                      0.00  
 Final Sat.:                      1375 4125                      1375                      1375 4125                      1375                      1375 1375                      1375                      1375 2750                      0  
 -----  
 Capacity Analysis Module:  
 Vol/Sat:                      0.02 0.54                      0.00                      0.00 0.47                      0.05                      0.03 0.00                      0.00                      0.00 0.00                      0.00  
 Crit Volume:                      741                      4                      40                      4  
 Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
 \*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 21-1

-----  
 City of Rocklin General Plan Update  
 2030 No Project Conditions  
 PM Peak Hour LOS (Published Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #19 Sierra College Bl & Southside Ranch  
 \*\*\*\*\*  
 Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.568  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      53                      Level Of Service:                      A  
 \*\*\*\*\*  
 Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
 Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
 -----  
 Control:                      Protected                      Protected                      Split Phase                      Split Phase  
 Rights:                      Include                      Include                      Include                      Include  
 Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
 Lanes:                      1 0 3 0 1                      1 0 3 0 1                      0 0 1! 0 0                      0 0 1! 0 0  
 -----  
 Volume Module:  
 Base Vol:                      85 2133                      1                      5 1881                      30                      23 0                      37                      1 0 4  
 Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 Initial Bse:                      85 2133                      1                      5 1881                      30                      23 0                      37                      1 0 4  
 User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 PHF Volume:                      85 2133                      1                      5 1881                      30                      23 0                      37                      1 0 4  
 Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Reduced Vol:                      85 2133                      1                      5 1881                      30                      23 0                      37                      1 0 4  
 PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 FinalVolume:                      85 2133                      1                      5 1881                      30                      23 0                      37                      1 0 4  
 -----  
 Saturation Flow Module:  
 Sat/Lane:                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375  
 Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
 Lanes:                      1.00 3.00                      1.00                      1.00 3.00                      1.00                      0.38 0.00                      0.62                      0.20 0.00                      0.80  
 Final Sat.:                      1375 4125                      1375                      1375 4125                      1375                      527 0                      848                      275 0                      1100  
 -----  
 Capacity Analysis Module:  
 Vol/Sat:                      0.06 0.52                      0.00                      0.00 0.46                      0.02                      0.04 0.00                      0.04                      0.00 0.00                      0.00  
 Crit Volume:                      711                      5                      60                      60  
 Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
 \*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #20 Sunset Bl & Pacific St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.878  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Ignored, etc.), and Rights (Include, Ignore, etc.).

Volume Module table showing Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, and Final Volume for various approaches.

Saturation Flow Module table showing Sat/Lane, Adjustment, Lanes, and Final Sat for various approaches.

Capacity Analysis Module table showing Vol/Sat, Crit Volume, and Crit Moves for various approaches.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #21 Sunset Bl & Springview Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 1.054  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Split Phase, Protected, etc.), and Rights (Include, Ignore, etc.).

Volume Module table showing Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, and Final Volume for various approaches.

Saturation Flow Module table showing Sat/Lane, Adjustment, Lanes, and Final Sat for various approaches.

Capacity Analysis Module table showing Vol/Sat, Crit Volume, and Crit Moves for various approaches.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #22 Sunset Bl & Topaz Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.681  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for volume and 10 columns for adjustment factors. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns for Sat/Lane, Adjustment, Lanes, and Final Sat. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #23 Sunset Bl & Whitney Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.098  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for volume and 10 columns for adjustment factors. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns for Sat/Lane, Adjustment, Lanes, and Final Sat. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 26-1

-----  
 City of Rocklin General Plan Update  
 2030 No Project Conditions  
 PM Peak Hour LOS (Published Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #101 Blue Oaks Bl & Lonetree  
 \*\*\*\*\*  
 Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.958  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      180                      Level Of Service:                      E  
 \*\*\*\*\*  
 Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
 Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
 -----  
 Control:                      Protected                      Protected                      Protected                      Protected  
 Rights:                      Include                      Ignore                      Ignore                      Include  
 Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
 Lanes:                      2 0 2 0 1                      1 0 2 0 1                      2 0 2 0 1                      1 0 2 0 1  
 -----  
 Volume Module:  
 Base Vol:                      646 385 95                      45 753 948                      808 597 499                      130 428 60  
 Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 Initial Bse:                      646 385 95                      45 753 948                      808 597 499                      130 428 60  
 User Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
 PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
 PHF Volume:                      646 385 95                      45 753 0                      808 597 0                      130 428 60  
 Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Reduced Vol:                      646 385 95                      45 753 0                      808 597 0                      130 428 60  
 PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
 MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
 FinalVolume:                      646 385 95                      45 753 0                      808 597 0                      130 428 60  
 -----  
 Saturation Flow Module:  
 Sat/Lane:                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375  
 Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 Lanes:                      2.00 2.00 1.00                      1.00 2.00 1.00                      2.00 2.00 1.00                      1.00 2.00 1.00  
 Final Sat.:                      2750 2750 1375                      1375 2750 1375                      2750 2750 1375                      1375 2750 1375  
 -----  
 Capacity Analysis Module:  
 Vol/Sat:                      0.23 0.14 0.07                      0.03 0.27 0.00                      0.29 0.22 0.00                      0.09 0.16 0.04  
 Crit Volume:                      323                      376                      404                      214  
 Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
 \*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 27-1

-----  
 City of Rocklin General Plan Update  
 2030 No Project Conditions  
 PM Peak Hour LOS (Published Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #102 Blue Oaks Bl & Market Place  
 \*\*\*\*\*  
 Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.317  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      33                      Level Of Service:                      A  
 \*\*\*\*\*  
 Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
 Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
 -----  
 Control:                      Split Phase                      Split Phase                      Protected                      Protected  
 Rights:                      Include                      Include                      Include                      Include  
 Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
 Lanes:                      0 1 0 0 1                      0 1 0 0 1                      1 0 1 1 0                      1 0 1 1 0  
 -----  
 Volume Module:  
 Base Vol:                      8 0 1                      15 1 10                      17 817 4                      2 553 11  
 Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 Initial Bse:                      8 0 1                      15 1 10                      17 817 4                      2 553 11  
 User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 PHF Volume:                      8 0 1                      15 1 10                      17 817 4                      2 553 11  
 Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
 Reduced Vol:                      8 0 1                      15 1 10                      17 817 4                      2 553 11  
 PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 FinalVolume:                      8 0 1                      15 1 10                      17 817 4                      2 553 11  
 -----  
 Saturation Flow Module:  
 Sat/Lane:                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375  
 Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
 Lanes:                      1.00 0.00 1.00                      0.94 0.06 1.00                      1.00 1.99 0.01                      1.00 1.96 0.04  
 Final Sat.:                      1375 0 1375                      1289 86 1375                      1375 2737 13                      1375 2696 54  
 -----  
 Capacity Analysis Module:  
 Vol/Sat:                      0.01 0.00 0.00                      0.01 0.01 0.01                      0.01 0.30 0.30                      0.00 0.21 0.21  
 Crit Volume:                      8                      16                      411                      2  
 Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
 \*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #103 Blue Oaks Bl & Van Buren Way  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.368  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #104 Five Star & Destiny Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.204  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 29 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 30-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #105 Lonetree Bl & Adams Dr  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.636  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      63                      Level Of Service:                      B  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Split Phase                      Split Phase  
Rights:                      Include                      Include                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      1 0 1 1 0                      1 0 1 1 0                      0 1 0 0 1                      0 0 1 0 0  
-----  
Volume Module:  
Base Vol:                      38 839                      18                      17 1516                      24                      30 1 36                      15 1 15  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      38 839                      18                      17 1516                      24                      30 1 36                      15 1 15  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      38 839                      18                      17 1516                      24                      30 1 36                      15 1 15  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      38 839                      18                      17 1516                      24                      30 1 36                      15 1 15  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      38 839                      18                      17 1516                      24                      30 1 36                      15 1 15  
-----  
Saturation Flow Module:  
Sat/Lane:                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      1.00 1.96 0.04                      1.00 1.97 0.03                      0.97 0.03 1.00                      0.49 0.03 0.48  
Final Sat.:                      1375 2692                      58                      1375 2707                      43                      1331 44 1375                      665 44 665  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.03 0.31 0.31                      0.01 0.56 0.56                      0.02 0.02 0.03                      0.02 0.02 0.02  
Crit Volume:                      38                      770                      36                      31  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 31-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #106 Lonetree Bl & Atherton Rd  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.469  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      35                      Level Of Service:                      A  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Permitted                      Protected                      Protected  
Rights:                      Include                      Include                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      1 0 2 0 0                      0 0 1 1 0                      1 0 0 0 1                      0 0 0 0 0  
-----  
Volume Module:  
Base Vol:                      34 698                      0                      0 852                      12                      39 0 202                      0 0 0  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      34 698                      0                      0 852                      12                      39 0 202                      0 0 0  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      34 698                      0                      0 852                      12                      39 0 202                      0 0 0  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      34 698                      0                      0 852                      12                      39 0 202                      0 0 0  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      34 698                      0                      0 852                      12                      39 0 202                      0 0 0  
-----  
Saturation Flow Module:  
Sat/Lane:                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      1.00 2.00 0.00                      0.00 1.97 0.03                      1.00 0.00 1.00                      0.00 0.00 0.00  
Final Sat.:                      1425 2850                      0                      0 2810 40                      1425 0 1425                      0 0 0  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.02 0.24 0.00                      0.00 0.30 0.30                      0.03 0.00 0.14                      0.00 0.00 0.00  
Crit Volume:                      34                      432                      202                      0  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #107 Lonetree Bl & Grand Canyon Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.808  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 119 Level Of Service: D

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #108 Lonetree Bl & Redwood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.775  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 101 Level Of Service: C

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.



NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 34-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #109 Lonetree Bl & West Oaks Bl  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.580  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      54                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	1	0	2	0	1	1

-----

Volume Module:

Base Vol:	7	672	254	9	1048	1	1	0	4	263	1	8
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	7	672	254	9	1048	1	1	0	4	263	1	8
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	7	672	254	9	1048	1	1	0	4	263	1	8
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	7	672	254	9	1048	1	1	0	4	263	1	8
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	7	672	254	9	1048	1	1	0	4	263	1	8

-----

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	1.00	1.00	2.00	1.00	1.00	2.00	1.00	1.00	1.00	1.00
Final Sat.:	1375	2750	1375	1375	2750	1375	1375	2750	1375	1375	1375	1375

-----

Capacity Analysis Module:

Vol/Sat:	0.01	0.24	0.18	0.01	0.38	0.00	0.00	0.00	0.00	0.19	0.00	0.01
Crit Volume:	7			524			4	263				
Crit Moves:	****			****			****	****				

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 35-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #110 Park Dr & Blaydon Rd  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.273  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      26                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	0	0	1	0	1	1

-----

Volume Module:

Base Vol:	2	1	3	21	2	53	86	597	11	7	318	21
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	2	1	3	21	2	53	86	597	11	7	318	21
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	2	1	3	21	2	53	86	597	11	7	318	21
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	2	1	3	21	2	53	86	597	11	7	318	21
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	2	1	3	21	2	53	86	597	11	7	318	21

-----

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.33	0.17	0.50	0.27	0.03	0.70	1.00	1.96	0.04	1.00	1.88	0.12
Final Sat.:	475	238	713	394	38	994	1425	2798	52	1425	2673	177

-----

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.05	0.05	0.05	0.06	0.21	0.21	0.00	0.12	0.12
Crit Volume:	2			76			304			7		
Crit Moves:	****			****			****	****	****	****		

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #111 Park Dr & Quarry Way

Cycle (sec): 100 Critical Vol./Cap.(X): 0.545  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 50 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #112 Park Dr & Farrier Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.644  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 52 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.





City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #117 Park Dr & Twin Oaks/ Boardwalk  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.402  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 38 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #118 Park Dr & Safeway  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.727  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 83 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #119 South Whitney & Five Star Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.553  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 51 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #120 Spring Creek Dr & Broken Rail Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.053  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 15 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 46-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #121 Stanford Ranch Rd & Cobblestone Dr  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.326  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      28                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Permitted			Permitted		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	1	0	0	0	1	0	1	0

-----

Volume Module:

Base Vol:	15	659	19	42	490	59	27	5	8	35	11	11
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	15	659	19	42	490	59	27	5	8	35	11	11
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	15	659	19	42	490	59	27	5	8	35	11	11
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	15	659	19	42	490	59	27	5	8	35	11	11
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Volume:	15	659	19	42	490	59	27	5	8	35	11	11

-----

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.94	0.06	1.00	1.79	0.21	0.68	0.12	0.20	0.62	0.19	0.19
Final Sat.:	1425	2770	80	1425	2544	306	962	178	285	875	275	275

-----

Capacity Analysis Module:

Vol/Sat:	0.01	0.24	0.24	0.03	0.19	0.19	0.03	0.03	0.03	0.04	0.04	0.04
Crit Volume:	339			42			27			57		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 47-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #122 Stanford Ranch Rd & Darby Rd  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.655  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      66                      Level Of Service:                      B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	1	0	0	1	0	0	1	0	1	0	1

-----

Volume Module:

Base Vol:	80	2	30	47	8	49	80	1116	235	39	674	69
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	80	2	30	47	8	49	80	1116	235	39	674	69
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	80	2	30	47	8	49	80	1116	235	39	674	69
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	80	2	30	47	8	49	80	1116	235	39	674	69
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Volume:	80	2	30	47	8	49	80	1116	235	39	674	69

-----

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.98	0.02	1.00	0.45	0.08	0.47	1.00	1.65	0.35	1.00	1.81	0.19
Final Sat.:	1341	34	1375	621	106	648	1375	2272	478	1375	2495	255

-----

Capacity Analysis Module:

Vol/Sat:	0.06	0.06	0.02	0.08	0.08	0.08	0.06	0.49	0.49	0.03	0.27	0.27
Crit Volume:	82			104			676			39		
Crit Moves:	****			****			****			****		

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #123 Stanford Ranch Rd & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.709  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 78 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected), Rights (Include), Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #124 Stanford Ranch Rd & Plaza  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.591  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 56 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control (Protected, Split Phase), Rights (Include), Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 3 rows: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*



NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 50-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #125 Stanford Ranch Rd & Stoney Dr  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.405  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      31                      Level Of Service:                      A  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Permitted                      Permitted  
Rights:                      Include                      Include                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      1 0 1 1 0                      1 0 1 1 0                      0 0 1! 0 0                      0 0 1! 0 0  
-----  
Volume Module:  
Base Vol:                      92 671 132                      11 533 14                      17 17 50                      81 12 4  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      92 671 132                      11 533 14                      17 17 50                      81 12 4  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      92 671 132                      11 533 14                      17 17 50                      81 12 4  
Reduced Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      92 671 132                      11 533 14                      17 17 50                      81 12 4  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      92 671 132                      11 533 14                      17 17 50                      81 12 4  
-----  
Saturation Flow Module:  
Sat/Lane:                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      1.00 1.67 0.33                      1.00 1.95 0.05                      0.20 0.20 0.60                      0.84 0.12 0.04  
Final Sat.:                      1425 2382 468                      1425 2777 73                      288 288 848                      1190 176 59  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.06 0.28 0.28                      0.01 0.19 0.19                      0.06 0.06 0.06                      0.07 0.07 0.07  
Crit Volume:                      402 11                                           84 81  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 51-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #126 Stanford Ranch Rd & Victory Ln  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.341  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      35                      Level Of Service:                      A  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Protected                      Protected  
Rights:                      Include                      Include                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      0 0 0 0 0                      1 0 1 0 1                      1 0 3 0 0                      0 0 3 0 1  
-----  
Volume Module:  
Base Vol:                      0 0 0                      76 0 97                      57 1046                      0 0 994 77  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      0 0 0                      76 0 97                      57 1046                      0 0 994 77  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      0 0 0                      76 0 97                      57 1046                      0 0 994 77  
Reduced Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      0 0 0                      76 0 97                      57 1046                      0 0 994 77  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      0 0 0                      76 0 97                      57 1046                      0 0 994 77  
-----  
Saturation Flow Module:  
Sat/Lane:                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      0.00 0.00 0.00                      1.00 1.00 1.00                      1.00 3.00 0.00                      0.00 3.00 1.00  
Final Sat.:                      0 0 0                      1425 1425 1425                      1425 4275 0                      0 4275 1425  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.00 0.00 0.00                      0.05 0.00 0.07                      0.04 0.24 0.00                      0.00 0.23 0.05  
Crit Volume:                      0                      97 57                      97 57                      331  
Crit Moves:                                           \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #127 Stanford Ranch Rd & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.688  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 73 Level Of Service: B

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 0 1	1 0 2 0 1	1 0 3 0 1	1 0 3 0 1

Volume Module:

Base Vol:	22 581 255	187 104 80	289 1018 9	82 539 173
Growth Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Initial Bse:	22 581 255	187 104 80	289 1018 9	82 539 173
User Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Volume:	22 581 255	187 104 80	289 1018 9	82 539 173
Reduct Vol:	0 0 0	0 0 0	0 0 0	0 0 0
Reduced Vol:	22 581 255	187 104 80	289 1018 9	82 539 173
PCE Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
MLF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
FinalVolume:	22 581 255	187 104 80	289 1018 9	82 539 173

Saturation Flow Module:

Sat/Lane:	1375 1375 1375	1375 1375 1375	1375 1375 1375	1375 1375 1375
Adjustment:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Lanes:	1.00 2.00 1.00	1.00 2.00 1.00	1.00 3.00 1.00	1.00 3.00 1.00
Final Sat.:	1375 2750 1375	1375 2750 1375	1375 4125 1375	1375 4125 1375

Capacity Analysis Module:

Vol/Sat:	0.02 0.21 0.19	0.14 0.04 0.06	0.21 0.25 0.01	0.06 0.13 0.13
Crit Volume:	291	187	289	180
Crit Moves:	****	****	****	****

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #128 Sunset Bl & Atherton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.953  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Split Phase	Split Phase	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 1 0 0 1	1 0 0 1 0	1 0 3 0 1	1 0 3 0 1

Volume Module:

Base Vol:	392 104 78	185 18 209	227 1212 68	21 1825 537
Growth Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Initial Bse:	392 104 78	185 18 209	227 1212 68	21 1825 537
User Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Volume:	392 104 78	185 18 209	227 1212 68	21 1825 537
Reduct Vol:	0 0 0	0 0 0	0 0 0	0 0 0
Reduced Vol:	392 104 78	185 18 209	227 1212 68	21 1825 537
PCE Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
MLF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
FinalVolume:	392 104 78	185 18 209	227 1212 68	21 1825 537

Saturation Flow Module:

Sat/Lane:	1375 1375 1375	1375 1375 1375	1375 1375 1375	1375 1375 1375
Adjustment:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Lanes:	1.58 0.42 1.00	1.00 0.08 0.92	1.00 3.00 1.00	1.00 3.00 1.00
Final Sat.:	2173 577 1375	1375 109 1266	1375 4125 1375	1375 4125 1375

Capacity Analysis Module:

Vol/Sat:	0.18 0.18 0.06	0.13 0.17 0.17	0.17 0.17 0.29	0.05 0.02 0.44 0.39
Crit Volume:	248	227	227	608
Crit Moves:	****	****	****	****

\*\*\*\*\*





City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #133 Sunset Bl & Pebble Creek

Cycle (sec): 100 Critical Vol./Cap.(X): 0.720  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 66 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #134 Sunset Bl & Stanford Ranch Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.718  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 81 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #135 Sunset Bl & West Oaks Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 1.112
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #136 W Stanford Ranch Rd & Sunset Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 1.240
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #137 W Stanford Ranch Rd & Wildcat Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.856  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 159 Level Of Service: D

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 0 1	2 0 1 0 2	2 0 2 0 1	1 0 3 0 1

Volume Module:

Base Vol:	14 441 0	603 128 505	601 649 13	1 259 355
Growth Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Initial Bse:	14 441 0	603 128 505	601 649 13	1 259 355
User Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Volume:	14 441 0	603 128 505	601 649 13	1 259 355
Reduced Vol:	0 0 0	0 0 0	0 0 0	0 0 0
Reduced Vol:	14 441 0	603 128 505	601 649 13	1 259 355
PCE Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
MLF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
FinalVolume:	14 441 0	603 128 505	601 649 13	1 259 355

Saturation Flow Module:

Sat/Lane:	1375 1375 1375	1375 1375 1375	1375 1375 1375	1375 1375 1375
Adjustment:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Lanes:	1.00 2.00 1.00	2.00 1.00 2.00	2.00 2.00 1.00	1.00 3.00 1.00
Final Sat.:	1375 2750 1375	2750 1375 2750	2750 2750 1375	1375 4125 1375

Capacity Analysis Module:

Vol/Sat:	0.01 0.16 0.00	0.22 0.09 0.18	0.22 0.24 0.01	0.00 0.06 0.26
Crit Volume:	221	302	301	355
Crit Moves:	****	****	****	****

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #138 Whitney Ranch Pkwy & Bridlewood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.354  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 29 Level Of Service: A

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Permitted	Permitted	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	0 0 1 0 0	0 0 1 0 0	1 0 1 1 0	1 0 1 1 0

Volume Module:

Base Vol:	53 1 25	3 0 7	7 664 91	45 372 14
Growth Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Initial Bse:	53 1 25	3 0 7	7 664 91	45 372 14
User Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
PHF Volume:	53 1 25	3 0 7	7 664 91	45 372 14
Reduced Vol:	0 0 0	0 0 0	0 0 0	0 0 0
Reduced Vol:	53 1 25	3 0 7	7 664 91	45 372 14
PCE Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
MLF Adj:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
FinalVolume:	53 1 25	3 0 7	7 664 91	45 372 14

Saturation Flow Module:

Sat/Lane:	1425 1425 1425	1425 1425 1425	1425 1425 1425	1425 1425 1425
Adjustment:	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00	1.00 1.00 1.00
Lanes:	0.67 0.01 0.32	0.30 0.00 0.70	1.00 1.76 0.24	1.00 1.93 0.07
Final Sat.:	956 18 451	428 0 998	1425 2506 344	1425 2747 103

Capacity Analysis Module:

Vol/Sat:	0.06 0.06 0.06	0.01 0.00 0.01	0.00 0.26 0.26	0.03 0.14 0.14
Crit Volume:	79	3	378	45
Crit Moves:	****	****	****	****

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #139 Whitney Ranch Pkwy & Painted Pony Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.316  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Split Phase	Split Phase	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	0 1 0 0 1	0 0 0 0 1	1 0 1 1 0	1 0 1 1 0

Volume Module:

Base Vol:	66	1	18	0	0	6	1	606	85	16	358	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	66	1	18	0	0	6	1	606	85	16	358	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	66	1	18	0	0	6	1	606	85	16	358	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	66	1	18	0	0	6	1	606	85	16	358	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	66	1	18	0	0	6	1	606	85	16	358	0

Saturation Flow Module:

Sat/Lane:	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375	1375
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.99	0.01	1.00	0.00	0.00	1.00	1.00	1.75	0.25	1.00	2.00	0.00
Final Sat.:	1354	21	1375	0	0	1375	1375	2412	338	1375	2750	0

Capacity Analysis Module:

Vol/Sat:	0.05	0.05	0.01	0.00	0.00	0.00	0.00	0.25	0.25	0.01	0.13	0.00
Crit Volume:	67			6		346		16				
Crit Moves:	****			****		****		****		****		

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #140 Whitney Ranch Pkwy & Spring Creek Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.311  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 27 Level Of Service: A

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Permitted	Permitted	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	0 0 1 0 0	0 0 1 0 0	1 0 1 1 0	1 0 1 1 0

Volume Module:

Base Vol:	13	2	2	4	2	37	43	755	16	1	417	13
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	13	2	2	4	2	37	43	755	16	1	417	13
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	13	2	2	4	2	37	43	755	16	1	417	13
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	13	2	2	4	2	37	43	755	16	1	417	13
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	13	2	2	4	2	37	43	755	16	1	417	13

Saturation Flow Module:

Sat/Lane:	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425	1425
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.76	0.12	0.12	0.09	0.05	0.86	1.00	1.96	0.04	1.00	1.94	0.06
Final Sat.:	1090	168	168	133	66	1226	1425	2791	59	1425	2764	86

Capacity Analysis Module:

Vol/Sat:	0.01	0.01	0.01	0.03	0.03	0.03	0.03	0.27	0.27	0.00	0.15	0.15
Crit Volume:	13			43		386		1				
Crit Moves:	****			****		****		****		****		

\*\*\*\*\*



City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #141 Wildcat Bl & Bridlewood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.617  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 60 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #142 Wildcat Bl & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.717  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 81 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

NP30 Future Geo Fri May 22, 2009 10:42:39 Page 68-1
City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #143 Wildcat Bl & S High School Entrance

Cycle (sec): 100 Critical Vol./Cap.(X): 0.509
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 46 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic flows and 10 rows of volume data including Base Vol, Growth Adj, Initial Bse, etc.

Saturation Flow Module table with 10 columns and 5 rows of saturation flow data including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows of capacity analysis data including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

NP30 Future Geo Fri May 22, 2009 10:42:39 Page 69-1
City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #144 Wildcat Bl & N High School Entrance

Cycle (sec): 100 Critical Vol./Cap.(X): 0.431
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 40 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic flows and 10 rows of volume data including Base Vol, Growth Adj, Initial Bse, etc.

Saturation Flow Module table with 10 columns and 5 rows of saturation flow data including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows of capacity analysis data including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 70-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #145 Wildcat Bl & Ranch View Dr  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.827  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      132                      Level Of Service:                      D

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	0	1	1	0	0

Volume Module:  
Base Vol:                      2 1120                      55                      28 527                      77                      485 31                      6                      46 3 34  
Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Initial Bse:                      2 1120                      55                      28 527                      77                      485 31                      6                      46 3 34  
User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Volume:                      2 1120                      55                      28 527                      77                      485 31                      6                      46 3 34  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      2 1120                      55                      28 527                      77                      485 31                      6                      46 3 34  
PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
FinalVolume:                      2 1120                      55                      28 527                      77                      485 31                      6                      46 3 34

Saturation Flow Module:  
Sat/Lane:                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375  
Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Lanes:                      1.00 1.91                      0.09                      1.00 1.75                      0.25                      1.00 0.84                      0.16                      1.00 0.08                      0.92  
Final Sat.:                      1375 2621                      129                      1375 2399                      351                      1375 1152                      223                      1375 111                      1264

Capacity Analysis Module:  
Vol/Sat:                      0.00 0.43                      0.43                      0.02 0.22                      0.22                      0.35 0.03                      0.03                      0.03 0.03                      0.03  
Crit Volume:                      588                      28                      485  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 71-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #152 Stanford Ranch Rd & Crest Dr  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      1.003  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      180                      Level Of Service:                      F

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	1	0	2	0	0	0	0	0	0

Volume Module:  
Base Vol:                      0 548 292                      602 437                      0                      0 0 0                      141 0 407  
Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Initial Bse:                      0 548 292                      602 437                      0                      0 0 0                      141 0 407  
User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Volume:                      0 548 292                      602 437                      0                      0 0 0                      141 0 407  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      0 548 292                      602 437                      0                      0 0 0                      141 0 407  
PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
FinalVolume:                      0 548 292                      602 437                      0                      0 0 0                      141 0 407

Saturation Flow Module:  
Sat/Lane:                      1425 1425                      1425                      1425 1425                      1425                      1425 1425                      1425                      1425 1425                      1425  
Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Lanes:                      0.00 1.30                      0.70                      1.00 2.00                      0.00                      0.00 0.00                      0.00                      1.00 0.00                      1.00  
Final Sat.:                      0 1859 991                      1425 2850                      0                      0 0 0                      1425 0 1425

Capacity Analysis Module:  
Vol/Sat:                      0.00 0.29                      0.29                      0.42 0.15                      0.00                      0.00 0.00                      0.00                      0.10 0.00                      0.29  
Crit Volume:                      420                      602                      0  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #153 Whitney Blvd & Crest Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.821
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 127 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #154 Park Dr & Crest Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.261
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 31 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 74-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #161 Granite Dr & Dominguez Dr  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.802  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      115                      Level Of Service:                      D  
\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 1 1 0	1 0 1 1 0	1 0 0 1 0	1 0 0 1 0

Volume Module:  
Base Vol:                      110 477                      93                      78 479                      11                      109 270                      268                      202 141                      137  
Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Initial Bse:                      110 477                      93                      78 479                      11                      109 270                      268                      202 141                      137  
User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Volume:                      110 477                      93                      78 479                      11                      109 270                      268                      202 141                      137  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      110 477                      93                      78 479                      11                      109 270                      268                      202 141                      137  
PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
FinalVolume:                      110 477                      93                      78 479                      11                      109 270                      268                      202 141                      137

Saturation Flow Module:  
Sat/Lane:                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375  
Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Lanes:                      1.00 1.67                      0.33                      1.00 1.96                      0.04                      1.00 0.50                      0.50                      1.00 0.51                      0.49  
Final Sat.:                      1375 2301                      449                      1375 2688                      62                      1375 690                      685                      1375 697                      678

Capacity Analysis Module:  
Vol/Sat:                      0.08 0.21                      0.21                      0.06 0.18                      0.18                      0.08 0.39                      0.39                      0.15 0.20                      0.20  
Crit Volume:                      285                      78                      538                      202  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 75-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #162 Sierra College Bl & Dominguez Dr  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.864  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      168                      Level Of Service:                      D  
\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Protected	Protected	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 2 1 0	1 0 2 1 0	2 0 1 1 0	2 0 1 1 0

Volume Module:  
Base Vol:                      191 1855                      91                      66 1241                      121                      162 79                      449                      50 44                      109  
Growth Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Initial Bse:                      191 1855                      91                      66 1241                      121                      162 79                      449                      50 44                      109  
User Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
PHF Volume:                      191 1855                      91                      66 1241                      121                      162 79                      449                      50 44                      109  
Reduc Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Reduced Vol:                      191 1855                      91                      66 1241                      121                      162 79                      449                      50 44                      109  
PCE Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
MLF Adj:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
FinalVolume:                      191 1855                      91                      66 1241                      121                      162 79                      449                      50 44                      109

Saturation Flow Module:  
Sat/Lane:                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375                      1375 1375                      1375  
Adjustment:                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00                      1.00 1.00                      1.00  
Lanes:                      1.00 2.86                      0.14                      1.00 2.73                      0.27                      2.00 1.00                      1.00                      2.00 1.00                      1.00  
Final Sat.:                      1375 3932                      193                      1375 3759                      366                      2750 1375                      1375                      2750 1375                      1375

Capacity Analysis Module:  
Vol/Sat:                      0.14 0.47                      0.47                      0.05 0.33                      0.33                      0.06 0.06                      0.33                      0.02 0.03                      0.08  
Crit Volume:                      649                      66                      449                      25  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #163 Park Dr & Valley View Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.596  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 57 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #164 Nature Trail Wy & Valley View Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.746  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 90 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 78-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #165 Sierra College Bl & Valley View Pkwy  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.646  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      64                      Level Of Service:                      B  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Protected                      Protected  
Rights:                      Include                      Include                      Ignore                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      2 0 2 0 0                      0 0 2 0 1                      2 0 0 0 1                      0 0 0 0 0  
-----  
Volume Module:  
Base Vol:                      245 1408                      0                      0 745 293                      432 0 582                      0 0 0 0  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      245 1408                      0                      0 745 293                      432 0 582                      0 0 0 0  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
PHF Volume:                      245 1408                      0                      0 745 293                      432 0 0                      0 0 0 0  
Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0 0  
Reduced Vol:                      245 1408                      0                      0 745 293                      432 0 0                      0 0 0 0  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00  
FinalVolume:                      245 1408                      0                      0 745 293                      432 0 0                      0 0 0 0  
-----  
Saturation Flow Module:  
Sat/Lane:                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425                      1425 1425 1425  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      2.00 2.00 0.00                      0.00 2.00 1.00                      2.00 0.00 1.00                      0.00 0.00 0.00  
Final Sat.:                      2850 2850                      0                      0 2850 1425                      2850 0 1425                      0 0 0 0  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.09 0.49 0.00                      0.00 0.26 0.21                      0.15 0.00 0.00                      0.00 0.00 0.00  
Crit Volume:                      704                      0                      216                      0  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

NP30 Future Geo                      Fri May 22, 2009 10:42:39                      Page 79-1

-----  
City of Rocklin General Plan Update  
2030 No Project Conditions  
PM Peak Hour LOS (Published Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #166 University Ave & Whitney Ranch Pkwy  
\*\*\*\*\*  
Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.667  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      68                      Level Of Service:                      B  
\*\*\*\*\*  
Approach:                      North Bound                      South Bound                      East Bound                      West Bound  
Movement:                      L - T - R                      L - T - R                      L - T - R                      L - T - R  
-----  
Control:                      Protected                      Protected                      Protected                      Protected  
Rights:                      Include                      Ignore                      Include                      Include  
Min. Green:                      0 0 0                      0 0 0                      0 0 0                      0 0 0  
Y+R:                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0                      4.0 4.0 4.0  
Lanes:                      2 0 2 0 1                      2 0 2 0 1                      2 0 3 0 1                      2 0 3 0 1  
-----  
Volume Module:  
Base Vol:                      320 185 41                      188 64 490                      339 1261 82                      37 1684 85  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      320 185 41                      188 64 490                      339 1261 82                      37 1684 85  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      320 185 41                      188 64 0                      339 1261 82                      37 1684 85  
Reduct Vol:                      0 0 0                      0 0 0                      0 0 0                      0 0 0 0  
Reduced Vol:                      320 185 41                      188 64 0                      339 1261 82                      37 1684 85  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 0.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      320 185 41                      188 64 0                      339 1261 82                      37 1684 85  
-----  
Saturation Flow Module:  
Sat/Lane:                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375                      1375 1375 1375  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      2.00 2.00 1.00                      2.00 2.00 1.00                      2.00 3.00 1.00                      2.00 3.00 1.00  
Final Sat.:                      2750 2750 1375                      2750 2750 1375                      2750 4125 1375                      2750 4125 1375  
-----  
Capacity Analysis Module:  
Vol/Sat:                      0.12 0.07 0.03                      0.07 0.02 0.00                      0.12 0.31 0.06                      0.01 0.41 0.06  
Crit Volume:                      93                      94                      170                      561  
Crit Moves:                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*  
\*\*\*\*\*

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #167 West Oaks Bl & Whitney Ranch Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.675
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 70 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Volume, Crit Moves. Rows for Capacity Analysis Module.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #168 West Oaks Bl & Painted Pony Ln

Cycle (sec): 100 Critical Vol./Cap.(X): 0.307
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 33 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Volume, Crit Moves. Rows for Capacity Analysis Module.



City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #169 Laredo Dr & Whitney Ranch Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.487
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 44 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #170 Rocklin Rd & Civic Centr Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.701
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 76 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #171 Pacific St & Civic Center Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.658  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 67 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), and Rights (Include). Includes data for Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #201 Rocklin Rd & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 1.104  
Loss Time (sec): 6 Average Delay (sec/veh): 66.9  
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), and Rights (Include). Includes data for Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

\*\*\*\*\*

Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*



City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #204 Sierra College Bl & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.626
Loss Time (sec): 9 Average Delay (sec/veh): 28.2
Optimal Cycle: 43 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #206 Sunset & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.704
Loss Time (sec): 6 Average Delay (sec/veh): 12.3
Optimal Cycle: 43 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #207 Sunset & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.727
Loss Time (sec): 6 Average Delay (sec/veh): 14.4
Optimal Cycle: 46 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #208 Whitney Ranch Pkwy & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.961
Loss Time (sec): 6 Average Delay (sec/veh): 32.2
Optimal Cycle: 149 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #209 Whitney Ranch Pkwy & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.833
Loss Time (sec): 6 Average Delay (sec/veh): 16.1
Optimal Cycle: 66 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #210 Blue Oaks Blvd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.585
Loss Time (sec): 6 Average Delay (sec/veh): 27.0
Optimal Cycle: 32 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #211 Blue Oaks Blvd & SR 65 NB Off

Cycle (sec): 100 Critical Vol./Cap.(X): 1.083
Loss Time (sec): 6 Average Delay (sec/veh): 41.5
Optimal Cycle: 180 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #212 Pleasant Grove Blvd & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.775
Loss Time (sec): 6 Average Delay (sec/veh): 19.2
Optimal Cycle: 53 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #213 Pleasant Grove Blvd & SR 65 SB  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.627  
Loss Time (sec): 6 Average Delay (sec/veh): 9.4  
Optimal Cycle: 35 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*

City of Rocklin General Plan Update  
2030 No Project Conditions

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #214 Stanford Ranch Rd & SR 65 NB  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.740  
Loss Time (sec): 6 Average Delay (sec/veh): 14.3  
Optimal Cycle: 47 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*



City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #215 Stanford Ranch Rd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.761
Loss Time (sec): 6 Average Delay (sec/veh): 10.2
Optimal Cycle: 51 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control (Protected, Permitted), Rights (Ignore, Include), and Lane configurations (Y+R, Lanes).

Volume Module table showing Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume for each approach and movement.

Saturation Flow Module table showing Sat/Lane, Adjustment, Lanes, and Final Sat for each approach and movement.

Capacity Analysis Module table showing Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ for each approach and movement.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #301 Sierra College Bl & Brace Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.947
Loss Time (sec): 6 Average Delay (sec/veh): 36.7
Optimal Cycle: 131 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control (Permitted, Protected), Rights (Include, Ignore), and Lane configurations (Y+R, Lanes).

Volume Module table showing Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume for each approach and movement.

Saturation Flow Module table showing Sat/Lane, Adjustment, Lanes, and Final Sat for each approach and movement.

Capacity Analysis Module table showing Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ for each approach and movement.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #302 Sierra College Bl & Taylor Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 1.020
Loss Time (sec): 12 Average Delay (sec/veh): 55.9
Optimal Cycle: 180 Level Of Service: E

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #304 Sierra College Bl & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.882
Loss Time (sec): 12 Average Delay (sec/veh): 35.5
Optimal Cycle: 102 Level Of Service: D

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #305 Taylor Rd & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.568
Loss Time (sec): 12 Average Delay (sec/veh): 30.3
Optimal Cycle: 46 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #306 Taylor Rd & Horseshoe Bar

Cycle (sec): 100 Critical Vol./Cap.(X): 1.095
Loss Time (sec): 9 Average Delay (sec/veh): 80.6
Optimal Cycle: 180 Level Of Service: F

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
With DKS Assumed Future Intersection Geometrics

Level Of Service Computation Report
2000 HCM 4-Way Stop Method (Base Volume Alternative)
Intersection #307 Rocklin Rd & Barton Rd
Cycle (sec): 100 Critical Vol./Cap. (X): 0.811
Loss Time (sec): 0 Average Delay (sec/veh): 23.6
Optimal Cycle: 0 Level Of Service: C
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Stop Sign Stop Sign Stop Sign Stop Sign
Rights: Include Include Include Include
Lanes: 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Volume Module:
Base Vol: 261 112 0 0 104 132 429 0 507 0 0 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 261 112 0 0 104 132 429 0 507 0 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 261 112 0 0 104 132 429 0 507 0 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 261 112 0 0 104 132 429 0 507 0 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 261 112 0 0 104 132 429 0 507 0 0 0 0
Saturation Flow Module:
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.00 0.00 0.00 0.44 0.56 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.: 467 497 0 0 242 308 529 0 641 0 0 0 0
Capacity Analysis Module:
Vol/Sat: 0.56 0.23 xxxx 0.43 0.43 0.81 xxxx 0.79 xxxx xxxx
Crit Moves: \*\*\*\*
Delay/Veh: 19.1 11.7 0.0 0.0 14.1 14.1 32.0 0.0 25.7 0.0 0.0 0.0
Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 19.1 11.7 0.0 0.0 14.1 14.1 32.0 0.0 25.7 0.0 0.0 0.0
LOS by Move: C B \* \* B B D \* D \* \* \*
ApproachDel: 16.9 14.1 28.6 xxxxxx
Delay Adj: 1.00 1.00 1.00 xxxxxx
ApprAdjDel: 16.9 14.1 28.6 xxxxxx
LOS by Appr: C B D \*
AllWayAvgQ: 1.1 0.3 0.0 0.7 0.7 0.7 3.3 0.0 3.1 0.0 0.0 0.0
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
With DKS Assumed Future Intersection Geometrics

Level Of Service Computation Report
2000 HCM Unsignalized Method (Base Volume Alternative)
Intersection #308 Barton Rd & Brace Rd
Average Delay (sec/veh): 61.9 Worst Case Level Of Service: F[257.9]
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Stop Sign Stop Sign Uncontrolled Uncontrolled
Rights: Include Include Include Include
Lanes: 0 0 1 0 0 0 0 0 0 0 1 0 0 1 0 0 0 0
Volume Module:
Base Vol: 205 0 129 0 0 0 0 541 173 181 191 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 205 0 129 0 0 0 0 541 173 181 191 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 205 0 129 0 0 0 0 541 173 181 191 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 205 0 129 0 0 0 0 541 173 181 191 0
Critical Gap Module:
Critical Gp: 6.4 6.5 6.2 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 4.1 xxxxx xxxxx
FollowUpTim: 3.5 4.0 3.3 xxxxxx xxxx xxxxxx xxxxxx xxxxx xxxxxx 2.2 xxxxx xxxxxx
Capacity Module:
Cnflct Vol: 1181 1181 628 xxxx xxxx xxxxxx xxxx xxxx xxxxxx 714 xxxxx xxxxxx
Potent Cap.: 212 192 487 xxxxx xxxx xxxxxx xxxxx xxxx xxxxxx 895 xxxxx xxxxxx
Move Cap.: 175 149 487 xxxxx xxxx xxxxxx xxxxx xxxx xxxxxx 895 xxxxx xxxxxx
Volume/Cap: 1.17 0.00 0.26 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 0.20 xxxxx xxxxx
Level Of Service Module:
2Way95thQ: xxxx xxxx xxxxxx xxxx xxxx xxxxxx xxxx xxxx xxxxxx 0.8 xxxxx xxxxxx
Control Del:xxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx 10.0 xxxxx xxxxxx
LOS by Move: \*
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxx 233 xxxxxx xxxx xxxx xxxxxx xxxx xxxx xxxxxx xxxx xxxxx xxxxxx
SharedQueue:xxxxx 19.2 xxxxxx xxxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx 0.8 xxxxx xxxxxx
Shrd ConDel:xxxxx 258 xxxxxx xxxxx xxxxxx xxxxxx xxxxx xxxxx xxxxxx 10.0 xxxxx xxxxxx
Shared LOS: \* F \*
ApproachDel: 257.9 xxxxxxx xxxxxxx xxxxxxx
ApproachLOS: F \*
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
With DKS Assumed Future Intersection Geometrics

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)
Intersection #309 Horseshoe Bar Rd & I-80 WB Ramp
Cycle (sec): 100 Critical Vol./Cap. (X): 0.713
Loss Time (sec): 0 Average Delay (sec/veh): 26.4
Optimal Cycle: 80 Level Of Service: C
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 1 1 0 1 0 1 0 0 1 1 0 0 1 0
Volume Module:
Base Vol: 291 563 175 47 267 537 82 46 174 70 49 140
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 291 563 175 47 267 537 82 46 174 70 49 140
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 291 563 175 47 267 537 82 46 174 70 49 140
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 291 563 175 47 267 537 82 46 174 70 49 140
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 291 563 175 47 267 537 82 46 174 70 49 140
Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjstment: 0.95 0.92 0.92 0.95 1.00 0.85 0.97 0.97 0.85 0.95 0.89 0.89
Lanes: 1.00 1.53 0.47 1.00 1.00 1.00 0.64 0.36 1.00 1.00 0.26 0.74
Final Sat.: 1805 2655 825 1805 1900 1615 1179 662 1615 1805 438 1251
Capacity Analysis Module:
Vol/Sat: 0.16 0.21 0.21 0.03 0.14 0.33 0.07 0.07 0.11 0.04 0.11 0.11
Crit Moves: \*\*\*\*
Green/Cycle: 0.23 0.62 0.62 0.08 0.47 0.47 0.15 0.15 0.15 0.16 0.16 0.16
Volume/Cap: 0.71 0.34 0.34 0.34 0.30 0.71 0.46 0.46 0.71 0.25 0.71 0.71
Delay/Veh: 41.6 9.4 9.4 45.4 16.8 24.6 39.9 39.9 49.9 37.4 48.9 48.9
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 41.6 9.4 9.4 45.4 16.8 24.6 39.9 39.9 49.9 37.4 48.9 48.9
LOS by Move: D A A D B C D D D D D
HCM2kAvgQ: 10 6 6 2 5 14 4 4 7 2 7 7
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
With DKS Assumed Future Intersection Geometrics

Level Of Service Computation Report
2000 HCM Unsignalized Method (Base Volume Alternative)
Intersection #310 Horseshoe Bar Rd & I-80 EB Ramp
Average Delay (sec/veh): 29.8 Worst Case Level Of Service: F[103.3]
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Uncontrolled Uncontrolled Stop Sign Stop Sign
Rights: Include Include Include Include
Lanes: 0 0 1 0 1 0 1 0 0 0 0 0 0 0 1 0 0 0 1
Volume Module:
Base Vol: 0 653 292 119 450 0 0 0 0 189 0 409
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 653 292 119 450 0 0 0 0 189 0 409
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 0 653 292 119 450 0 0 0 0 189 0 409
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 0 653 292 119 450 0 0 0 0 189 0 409
Critical Gap Module:
Critical Gp:xxxxx xxxx xxxxx 4.1 xxxx xxxxx xxxxx xxxx xxxxx 6.4 xxxx 6.2
FollowUpTim:xxxxx xxxx xxxxx 2.2 xxxx xxxxx xxxxx xxxx xxxxx 3.5 xxxx 3.3
Capacity Module:
Cnflct Vol: xxxx xxxx xxxxx 945 xxxx xxxxx xxxx xxxx xxxxx 1341 xxxx 653
Potent Cap.: xxxx xxxx xxxxx 734 xxxx xxxxx xxxx xxxx xxxxx 170 xxxx 471
Move Cap.: xxxx xxxx xxxxx 734 xxxx xxxxx xxxx xxxx xxxxx 147 xxxx 471
Volume/Cap: xxxx xxxx xxxxx 0.16 xxxx xxxxx xxxx xxxx xxxxx 1.29 xxxx 0.87
Level Of Service Module:
2Way95thQ: xxxx xxxx xxxxx 0.6 xxxx xxxxx xxxx xxxx xxxxx 11.4 xxxx 9.1
Control Del:xxxxx xxxx xxxxx 10.8 xxxx xxxxx xxxxx xxxx xxxxx 228.8 xxxx 45.2
LOS by Move: \* \* \* B \* \* \* \* \* F \* \* \* E
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx
SharedQueue:xxxxx xxxx xxxxx 0.6 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxxx xxxxx
Shrd ConDel:xxxxx xxxx xxxxx 10.8 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxxx xxxxx
Shared LOS: \* \* \* B \* \* \* \* \* \* \* \* \*
ApproachDel: xxxxxx xxxxxx xxxxxx 103.3
ApproachLOS: \* \* \* \* \* F
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #501 E Lincoln Pkwy & Twelve Bridges

Cycle (sec): 100 Critical Vol./Cap.(X): 0.832
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 136 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #1216 Sierra College Blvd & SR 193

Cycle (sec): 100 Critical Vol./Cap.(X): 0.927
Loss Time (sec): 9 Average Delay (sec/veh): 34.8
Optimal Cycle: 119 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #1502 Sierra College & Twelve Bridges

Cycle (sec): 100 Critical Vol./Cap.(X): 0.673
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 70 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update
2030 No Project Conditions
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #1601 Sierra College & English Colony

Cycle (sec): 100 Critical Vol./Cap.(X): 0.885
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 162 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
2030 No Project
Roseville Intersections

Impact Analysis Report
Level Of Service

Table with 4 columns: Intersection, Base (Del/V, LOS Veh, C), Future (Del/V, LOS Veh, C), Change in. Rows include #401 Pleasant Grove & Fairway, #402 Stanford Ranch & Fairway, #403 Stanford Ranch & Five Star, #404 Pleasant Grove & Roseville Pkw, #405 Galleria & Roseville Pkwy, #406 Roseville Parkway & Taylor, #407 Roseville Parkway & N. Sunrise, #408 Sierra College & Secret Ravine.

Rocklin General Plan Update
2030 No Project
Roseville Intersections

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

Intersection #401 Pleasant Grove & Fairway

Cycle (sec): 120 Critical Vol./Cap.(X): 1.031
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: F

Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R

Control: Protected Protected Protected Protected
Rights: Ovl Ovl Ovl Ovl
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 2 0 3 0 1 2 0 3 0 1 2 0 2 0 1 2 0 2 0 1

Volume Module:
Base Vol: 671 1472 601 141 1053 238 277 535 749 789 470 149
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 671 1472 601 141 1053 238 277 535 749 789 470 149
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 671 1472 601 141 1053 238 277 535 749 789 470 149
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 671 1472 601 141 1053 238 277 535 749 789 470 149
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 671 1472 601 141 1053 238 277 535 749 789 470 149

Saturation Flow Module:
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 2.00 2.00 1.00 2.00 2.00 1.00
Final Sat.: 2900 4350 1450 2900 4350 1450 2900 2900 1450 2900 2900 1450

Capacity Analysis Module:
Vol/Sat: 0.23 0.34 0.41 0.05 0.24 0.16 0.10 0.18 0.52 0.27 0.16 0.10
Crit Volume: 0 351 749 394
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*



Rocklin General Plan Update
2030 No Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #402 Stanford Ranch & Fairway

Cycle (sec): 120 Critical Vol./Cap.(X): 0.740
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 88 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

Rocklin General Plan Update
2030 No Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #403 Stanford Ranch & Five Star

Cycle (sec): 120 Critical Vol./Cap.(X): 0.676
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 70 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

NP30 Fri May 22, 2009 10:43:59 Page 6-1

-----  
 Rocklin General Plan Update  
 2030 No Project  
 Roseville Intersections  
 -----

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #404 Pleasant Grove & Roseville Pkwy  
 \*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 1.087  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: F  
 \*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ignore			Ignore			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	3	0	2	0	1	2	0	3	0	1	2	0

Volume Module:  
 Base Vol: 711 937 1095 399 977 44 47 1465 788 841 1809 194  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 711 937 1095 399 977 44 47 1465 788 841 1809 194  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 711 937 0 399 977 0 47 1465 0 841 1809 0  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 711 937 0 399 977 0 47 1465 0 841 1809 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 711 937 0 399 977 0 47 1465 0 841 1809 0

Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 3.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
 Final Sat.: 4350 2900 1450 2900 4350 1450 2900 4350 1450 2900 4350 1450

Capacity Analysis Module:  
 Vol/Sat: 0.16 0.32 0.00 0.14 0.22 0.00 0.02 0.34 0.00 0.29 0.42 0.00  
 Crit Volume: 468 199 488 420  
 Crit Moves: \*\*\*\*

\*\*\*\*\*

NP30 Fri May 22, 2009 10:43:59 Page 7-1

-----  
 Rocklin General Plan Update  
 2030 No Project  
 Roseville Intersections  
 -----

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #405 Galleria & Roseville Pkwy  
 \*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.985  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: E  
 \*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ignore			Ignore			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	3	0	1	3	0	3	0	1	2	0

Volume Module:  
 Base Vol: 591 772 34 1008 843 378 669 1702 875 269 2002 607  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 591 772 34 1008 843 378 669 1702 875 269 2002 607  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 591 772 0 1008 843 0 669 1702 0 269 2002 0  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 591 772 0 1008 843 0 669 1702 0 269 2002 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 591 772 0 1008 843 0 669 1702 0 269 2002 0

Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 3.00 1.00 3.00 3.00 1.00 2.00 4.00 1.00 2.00 4.00 1.00  
 Final Sat.: 2900 4350 1450 4350 4350 1450 2900 5800 1450 2900 5800 1450

Capacity Analysis Module:  
 Vol/Sat: 0.20 0.18 0.00 0.23 0.19 0.00 0.23 0.29 0.00 0.09 0.35 0.00  
 Crit Volume: 257 336 335 500  
 Crit Moves: \*\*\*\*

\*\*\*\*\*

NP30 Fri May 22, 2009 10:43:59 Page 8-1

-----  
 Rocklin General Plan Update  
 2030 No Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #406 Roseville Parkway & Taylor  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 0.822  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 128 Level Of Service: D  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ovl Ovl Ovl Ovl  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 2 0 3 0 1 2 0 3 0 1 2 0 4 0 1 2 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 302 333 185 457 314 166 233 2340 288 418 2208 583  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 302 333 185 457 314 166 233 2340 288 418 2208 583  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 302 333 185 457 314 166 233 2340 288 418 2208 583  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 302 333 185 457 314 166 233 2340 288 418 2208 583  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 302 333 185 457 314 166 233 2340 288 418 2208 583  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 2.00 4.00 1.00 2.00 3.00 1.00  
 Final Sat.: 2900 4350 1450 2900 4350 1450 2900 5800 1450 2900 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.10 0.08 0.13 0.16 0.07 0.11 0.08 0.40 0.20 0.14 0.51 0.40  
 Crit Volume: 111 229 117 736  
 Crit Moves: \*\*\*\* \*\*

NP30 Fri May 22, 2009 10:43:59 Page 9-1

-----  
 Rocklin General Plan Update  
 2030 No Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #407 Roseville Parkway & N. Sunrise  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 1.006  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: F  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ignore Ovl Ignore Ovl  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 2 1 0 0 1 1 0 2 0 1 2 0 3 0 1 2 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 548 156 398 170 268 403 150 2237 706 301 2409 87  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 548 156 398 170 268 403 150 2237 706 301 2409 87  
 User Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Volume: 548 156 0 170 268 403 150 2237 0 301 2409 87  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 548 156 0 170 268 403 150 2237 0 301 2409 87  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 FinalVolume: 548 156 0 170 268 403 150 2237 0 301 2409 87  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.34 0.66 1.00 1.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
 Final Sat.: 3386 964 1450 1450 2900 1450 2900 4350 1450 2900 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.16 0.16 0.00 0.12 0.09 0.28 0.05 0.51 0.00 0.10 0.55 0.06  
 Crit Volume: 235 403 746 151  
 Crit Moves: \*\*\*\* \*\*

NP30 Fri May 22, 2009 10:43:59 Page 10-1
Rocklin General Plan Update
2030 No Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)
Intersection #408 Sierra College & Secret Ravine
Cycle (sec): 120 Critical Vol./Cap.(X): 0.909
Loss Time (sec): 9 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: E
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Protected Protected Permitted Permitted
Rights: Ovl Ovl Ovl Ovl
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 2 0 1 1 0 2 0 1 2 0 0 1 0 0 1 0 0 1
Volume Module:
Base Vol: 209 1483 3 1 1555 367 737 2 179 3 5 3
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 209 1483 3 1 1555 367 737 2 179 3 5 3
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 209 1483 3 1 1555 367 737 2 179 3 5 3
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 209 1483 3 1 1555 367 737 2 179 3 5 3
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 209 1483 3 1 1555 367 737 2 179 3 5 3
Saturation Flow Module:
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 2.00 1.00 1.00 2.00 1.00 2.00 0.01 0.99 0.38 0.62 1.00
Final Sat.: 1500 3000 1500 1500 3000 1500 3000 17 1483 563 938 1500
Capacity Analysis Module:
Vol/Sat: 0.14 0.49 0.00 0.00 0.52 0.24 0.25 0.12 0.12 0.01 0.01 0.00
Crit Volume: 209 778 369 8
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

**INTERSECTION LOS WORKSHEETS  
2030 CUMULATIVE PLUS PROJECT CONDITIONS**

---



City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
# 1 Granite Dr & Rocklin Rd	D	xxxxx 0.859	D	xxxxx 0.859	+ 0.000 V/C
# 2 Granite Dr & Sierra College Bl	B	xxxxx 0.655	B	xxxxx 0.655	+ 0.000 V/C
# 3 Granite Dr & Sierra Meadows	B	xxxxx 0.608	B	xxxxx 0.608	+ 0.000 V/C
# 4 Pacific St & Del Mar/ Domingue	E	xxxxx 0.957	E	xxxxx 0.957	+ 0.000 V/C
# 5 Pacific St & Farron St	F	xxxxx 1.120	F	xxxxx 1.120	+ 0.000 V/C
# 6 Pacific St & Midas Ave	C	xxxxx 0.753	C	xxxxx 0.753	+ 0.000 V/C
# 7 Pacific St & Rocklin Rd	D	xxxxx 0.832	D	xxxxx 0.832	+ 0.000 V/C
# 8 Pacific St & Sierra Meadows	C	xxxxx 0.722	C	xxxxx 0.722	+ 0.000 V/C
# 9 Pacific St & Woodside Dr	B	xxxxx 0.640	B	xxxxx 0.640	+ 0.000 V/C
# 10 Rocklin Rd & Aguilar Rd	B	xxxxx 0.662	B	xxxxx 0.662	+ 0.000 V/C
# 11 Rocklin Rd & El Don Dr	C	xxxxx 0.711	C	xxxxx 0.711	+ 0.000 V/C
# 12 Rocklin Rd & Fire Station No 1	A	xxxxx 0.442	A	xxxxx 0.442	+ 0.000 V/C
# 13 Rocklin Rd & Havenhurst Cir	B	xxxxx 0.674	B	xxxxx 0.674	+ 0.000 V/C
# 14 Rocklin Rd & Sierra College Bl	E	xxxxx 0.935	E	xxxxx 0.935	+ 0.000 V/C
# 15 Rocklin Rd & South Grove St	B	xxxxx 0.684	B	xxxxx 0.684	+ 0.000 V/C
# 16 Sierra College Bl & El Don Dr	B	xxxxx 0.659	B	xxxxx 0.659	+ 0.000 V/C
# 17 Sierra College Bl & Nightwatch	A	xxxxx 0.550	A	xxxxx 0.550	+ 0.000 V/C
# 18 Sierra College Bl & Scarborough	A	xxxxx 0.551	A	xxxxx 0.551	+ 0.000 V/C
# 19 Sierra College Bl & Southside	A	xxxxx 0.547	A	xxxxx 0.547	+ 0.000 V/C
# 20 Sunset Bl & Pacific St	D	xxxxx 0.848	D	xxxxx 0.848	+ 0.000 V/C
# 21 Sunset Bl & Springview Dr	F	xxxxx 1.138	F	xxxxx 1.138	+ 0.000 V/C
# 22 Sunset Bl & Topaz Ave	B	xxxxx 0.652	B	xxxxx 0.652	+ 0.000 V/C
# 23 Sunset Bl & Whitney Bl	F	xxxxx 1.156	F	xxxxx 1.156	+ 0.000 V/C

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS	V/ Veh C	Del/ LOS	V/ Veh C	
#101 Blue Oaks Bl & Lonetree	E	xxxxx 0.914	E	xxxxx 0.914	+ 0.000 V/C
#102 Blue Oaks Bl & Market Place	A	xxxxx 0.298	A	xxxxx 0.298	+ 0.000 V/C
#103 Blue Oaks Bl & Van Buren Way	A	xxxxx 0.347	A	xxxxx 0.347	+ 0.000 V/C
#104 Five Star & Destiny Dr	A	xxxxx 0.193	A	xxxxx 0.193	+ 0.000 V/C
#105 Lonetree Bl & Adams Dr	B	xxxxx 0.606	B	xxxxx 0.606	+ 0.000 V/C
#106 Lonetree Bl & Atherton Rd	A	xxxxx 0.449	A	xxxxx 0.449	+ 0.000 V/C
#107 Lonetree Bl & Grand Canyon Dr	C	xxxxx 0.767	C	xxxxx 0.767	+ 0.000 V/C
#108 Lonetree Bl & Redwood Dr	C	xxxxx 0.737	C	xxxxx 0.737	+ 0.000 V/C
#109 Lonetree Bl & West Oaks Bl	A	xxxxx 0.552	A	xxxxx 0.552	+ 0.000 V/C
#110 Park Dr & Blaydon Rd	A	xxxxx 0.262	A	xxxxx 0.262	+ 0.000 V/C
#111 Park Dr & Quarry Way	A	xxxxx 0.507	A	xxxxx 0.507	+ 0.000 V/C
#112 Park Dr & Farrier Rd	A	xxxxx 0.457	A	xxxxx 0.457	+ 0.000 V/C
#113 Park Dr & King Pine Dr	A	xxxxx 0.489	A	xxxxx 0.489	+ 0.000 V/C
#114 Park Dr & Shelton	A	xxxxx 0.324	A	xxxxx 0.324	+ 0.000 V/C
#115 Park Dr & Victory Lane	A	xxxxx 0.387	A	xxxxx 0.387	+ 0.000 V/C
#116 Park Dr & Wykford Bl	A	xxxxx 0.395	A	xxxxx 0.395	+ 0.000 V/C
#117 Park Dr & Twin Oaks/ Boardwalk	A	xxxxx 0.384	A	xxxxx 0.384	+ 0.000 V/C
#118 Park Dr & Safeway	B	xxxxx 0.676	B	xxxxx 0.676	+ 0.000 V/C
#119 South Whitney & Five Star Bl	A	xxxxx 0.583	A	xxxxx 0.583	+ 0.000 V/C
#120 Spring Creek Dr & Broken Rail	A	xxxxx 0.049	A	xxxxx 0.049	+ 0.000 V/C
#121 Stanford Ranch Rd & Cobbleston	A	xxxxx 0.318	A	xxxxx 0.318	+ 0.000 V/C
#122 Stanford Ranch Rd & Darby Rd	A	xxxxx 0.582	A	xxxxx 0.582	+ 0.000 V/C
#123 Stanford Ranch Rd & Park Dr	B	xxxxx 0.675	B	xxxxx 0.675	+ 0.000 V/C
#124 Stanford Ranch Rd & Plaza	A	xxxxx 0.561	A	xxxxx 0.561	+ 0.000 V/C
#125 Stanford Ranch Rd & Stoney Dr	A	xxxxx 0.393	A	xxxxx 0.393	+ 0.000 V/C

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS	V/ C	Del/ LOS	V/ C	
#126 Stanford Ranch Rd & Victory Ln	A	xxxxx 0.317	A	xxxxx 0.317	+ 0.000 V/C
#127 Stanford Ranch Rd & West Oaks	B	xxxxx 0.647	B	xxxxx 0.647	+ 0.000 V/C
#128 Sunset Bl & Atherton	E	xxxxx 0.910	E	xxxxx 0.910	+ 0.000 V/C
#129 Sunset Bl & Blue Oaks Bl	C	xxxxx 0.791	C	xxxxx 0.791	+ 0.000 V/C
#130 Sunset Bl & Fairway Dr	C	xxxxx 0.743	C	xxxxx 0.743	+ 0.000 V/C
#131 Sunset Bl & Little Rock	A	xxxxx 0.583	A	xxxxx 0.583	+ 0.000 V/C
#132 Sunset Bl & Park Dr	D	xxxxx 0.821	D	xxxxx 0.821	+ 0.000 V/C
#133 Sunset Bl & Pebble Creek	B	xxxxx 0.678	B	xxxxx 0.678	+ 0.000 V/C
#134 Sunset Bl & Stanford Ranch Rd	B	xxxxx 0.699	B	xxxxx 0.699	+ 0.000 V/C
#135 Sunset Bl & West Oaks Bl	F	xxxxx 1.051	F	xxxxx 1.051	+ 0.000 V/C
#136 W Stanford Ranch Rd & Sunset B	F	xxxxx 1.164	F	xxxxx 1.164	+ 0.000 V/C
#137 W Stanford Ranch Rd & Wildcat	C	xxxxx 0.796	C	xxxxx 0.796	+ 0.000 V/C
#138 Whitney Ranch Pkwy & Bridlewoo	A	xxxxx 0.334	A	xxxxx 0.334	+ 0.000 V/C
#139 Whitney Ranch Pkwy & Painted P	A	xxxxx 0.299	A	xxxxx 0.299	+ 0.000 V/C
#140 Whitney Ranch Pkwy & Spring Cr	A	xxxxx 0.294	A	xxxxx 0.294	+ 0.000 V/C
#141 Wildcat Bl & Bridlewood Dr	A	xxxxx 0.586	A	xxxxx 0.586	+ 0.000 V/C
#142 Wildcat Bl & Whitney Ranch Pkw	B	xxxxx 0.671	B	xxxxx 0.671	+ 0.000 V/C
#143 Wildcat Bl & S High School Ent	A	xxxxx 0.485	A	xxxxx 0.485	+ 0.000 V/C
#144 Wildcat Bl & N High School Ent	A	xxxxx 0.411	A	xxxxx 0.411	+ 0.000 V/C
#145 Wildcat Bl & Ranch View Dr	C	xxxxx 0.786	C	xxxxx 0.786	+ 0.000 V/C
#152 Stanford Ranch Rd & Crest Dr	E	xxxxx 0.920	E	xxxxx 0.920	+ 0.000 V/C
#153 Whitney Blvd & Crest Dr	C	xxxxx 0.742	C	xxxxx 0.742	+ 0.000 V/C
#154 Park Dr & Crest Dr	A	xxxxx 0.253	A	xxxxx 0.253	+ 0.000 V/C
#161 Granite Dr & Dominguez Dr	C	xxxxx 0.769	C	xxxxx 0.769	+ 0.000 V/C

Traffix 8.0.0715 (c) 2008 Dowling Assoc. Licensed to DKS ASSOC., SACRAMENTO

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Intersection	Base		Future		Change in
	Del/ LOS	V/ C	Del/ LOS	V/ C	
#162 Sierra College Bl & Dominguez	D	xxxxx 0.808	D	xxxxx 0.808	+ 0.000 V/C
#163 Park Dr & Valley View Pkwy	A	xxxxx 0.570	A	xxxxx 0.570	+ 0.000 V/C
#164 Nature Trail Wy & Valley View	C	xxxxx 0.717	C	xxxxx 0.717	+ 0.000 V/C
#165 Sierra College Bl & Valley Vie	B	xxxxx 0.611	B	xxxxx 0.611	+ 0.000 V/C
#166 University Ave & Whitney Ranch	B	xxxxx 0.644	B	xxxxx 0.644	+ 0.000 V/C
#167 West Oaks Bl & Whitney Ranch P	B	xxxxx 0.641	B	xxxxx 0.641	+ 0.000 V/C
#168 West Oaks Bl & Painted Pony Ln	A	xxxxx 0.291	A	xxxxx 0.291	+ 0.000 V/C
#169 Laredo Dr & Whitney Ranch Pkwy	A	xxxxx 0.462	A	xxxxx 0.462	+ 0.000 V/C
#170 Rocklin Rd & Civic Centr Dr	B	xxxxx 0.676	B	xxxxx 0.676	+ 0.000 V/C
#171 Pacific St & Civic Center Dr	B	xxxxx 0.615	B	xxxxx 0.615	+ 0.000 V/C
#201 Rocklin Rd & I-80 EB	E	65.9 1.097	E	65.9 1.097	+ 0.000 D/V
#202 Rocklin Rd & I-80 WB	E	71.4 1.139	E	71.4 1.139	+ 0.000 D/V
#203 Sierra College Bl & I-80 WB	C	32.9 0.862	C	32.9 0.862	+ 0.000 D/V
#204 Sierra College Bl & I-80 EB	C	28.4 0.624	C	28.4 0.624	+ 0.000 D/V
#206 Sunset & SR 65 SB	B	12.3 0.705	B	12.3 0.705	+ 0.000 D/V
#207 Sunset & SR 65 NB	B	14.5 0.720	B	14.5 0.720	+ 0.000 D/V
#208 Whitney Ranch Pkwy & SR 65 SB	C	32.5 0.965	C	32.5 0.965	+ 0.000 D/V
#209 Whitney Ranch Pkwy & SR 65 NB	B	16.2 0.837	B	16.2 0.837	+ 0.000 D/V
#210 Blue Oaks Blvd & SR 65 SB	C	27.0 0.583	C	27.0 0.583	+ 0.000 D/V
#211 Blue Oaks Blvd & SR 65 NB Off	D	41.3 1.082	D	41.3 1.082	+ 0.000 D/V
#212 Pleasant Grove Blvd & SR 65 NB	B	19.3 0.784	B	19.3 0.784	+ 0.000 D/V
#213 Pleasant Grove Blvd & SR 65 SB	A	9.8 0.633	A	9.8 0.633	+ 0.000 D/V
#214 Stanford Ranch Rd & SR 65 NB	B	14.3 0.745	B	14.3 0.745	+ 0.000 D/V
#215 Stanford Ranch Rd & SR 65 SB	B	10.1 0.762	B	10.1 0.762	+ 0.000 D/V
#301 Sierra College Bl & Brace Rd	D	37.0 0.948	D	37.0 0.948	+ 0.000 D/V

Traffix 8.0.0715 (c) 2008 Dowling Assoc. Licensed to DKS ASSOC., SACRAMENTO



City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Intersection		Base		Future		Change in	
		Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C		
#302 Sierra College Bl & Taylor Rd	E	56.0	1.018	E 56.0	1.018	+ 0.000	D/V
#304 Sierra College Bl & King Rd	C	34.6	0.873	C 34.6	0.873	+ 0.000	D/V
#305 Taylor Rd & King Rd	C	30.3	0.570	C 30.3	0.570	+ 0.000	D/V
#306 Taylor Rd & Horseshoe Bar	F	81.9	1.100	F 81.9	1.100	+ 0.000	D/V
#1216 Sierra College Blvd & SR 193	C	34.9	0.927	C 34.9	0.927	+ 0.000	D/V

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1 Granite Dr & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.859  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 162 Level Of Service: D  
\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Split Phase	Split Phase	Protected	Protected
Rights:	Include	Include	Include	Ignore
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 0 1 0	1 1 0 0 1	1 0 1 1 0	1 0 2 0 1

Volume Module:

Base Vol:	30	17	15	594	19	316	301	1653	10	32	1194	606
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	30	17	15	594	19	316	301	1653	10	32	1194	606
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
PHF Volume:	30	17	15	594	19	316	301	1653	10	32	1194	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	30	17	15	594	19	316	301	1653	10	32	1194	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00
FinalVolume:	30	17	15	594	19	316	301	1653	10	32	1194	0

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	0.53	0.47	1.94	0.06	1.00	1.00	1.99	0.01	1.00	2.00	1.00
Final Sat.:	1450	770	680	2810	90	1450	1450	2883	17	1450	2900	1450

Capacity Analysis Module:

Vol/Sat:	0.02	0.02	0.02	0.21	0.21	0.22	0.21	0.57	0.57	0.02	0.41	0.00
Crit Volume:	32			316	301					597		
Crit Moves:	****			****	****					****		

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #2 Granite Dr & Sierra College Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.655  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 66 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), Rights (Include), Min. Green, Y+R, Lanes.

Volume Module: Table with 12 columns for traffic volumes and 12 rows for various adjustment factors like Base Vol, Growth Adj, etc.

Saturation Flow Module: Table with 12 columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with 12 columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #3 Granite Dr & Sierra Meadows  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.608  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Split Phase, Protected, Include), Rights (Include), Min. Green, Y+R, Lanes.

Volume Module: Table with 12 columns for traffic volumes and 12 rows for various adjustment factors like Base Vol, Growth Adj, etc.

Saturation Flow Module: Table with 12 columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with 12 columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #4 Pacific St & Del Mar/ Dominguez  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.957  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #5 Pacific St & Farron St  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.120  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: F

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*



City of Rocklin General Plan Update

2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #8 Pacific St & Sierra Meadows

Cycle (sec): 100 Critical Vol./Cap.(X): 0.722
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 82 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat..

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #9 Pacific St & Woodside Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.640
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 63 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat..

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Volume, Crit Moves.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 12-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #10 Rocklin Rd & Aguilar Rd  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 0.662  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 67 Level Of Service: B  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 0 1 0 0 0 0 0 1 0 2 1 0 1 0 3 0 0  
-----  
Volume Module:  
Base Vol: 268 0 67 0 0 0 70 1580 342 84 1651 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 268 0 67 0 0 0 70 1580 342 84 1651 0  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 268 0 67 0 0 0 70 1580 342 84 1651 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 268 0 67 0 0 0 70 1580 342 84 1651 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 268 0 67 0 0 0 70 1580 342 84 1651 0  
-----  
Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.00 1.00 0.00 0.00 0.00 1.00 2.47 0.53 1.00 3.00 0.00  
Final Sat.: 1500 0 1500 0 0 0 1500 3699 801 1500 4500 0  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.18 0.00 0.04 0.00 0.00 0.00 0.05 0.43 0.43 0.06 0.37 0.00  
Crit Volume: 268 0 641 84  
Crit Moves: \*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 13-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #11 Rocklin Rd & El Don Dr  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 0.711  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 79 Level Of Service: C  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Split Phase Split Phase Protected Protected  
Rights: Include Ovl Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 0 1 0 0 1 0 0 1 1 0 2 1 0 1 0 2 1 0  
-----  
Volume Module:  
Base Vol: 121 6 15 74 11 539 350 1245 103 24 1083 32  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 121 6 15 74 11 539 350 1245 103 24 1083 32  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 121 6 15 74 11 539 350 1245 103 24 1083 32  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 121 6 15 74 11 539 350 1245 103 24 1083 32  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 121 6 15 74 11 539 350 1245 103 24 1083 32  
-----  
Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.29 0.71 0.87 0.13 1.00 1.00 2.77 0.23 1.00 2.91 0.09  
Final Sat.: 1450 414 1036 1262 188 1450 1450 4018 332 1450 4225 125  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.08 0.01 0.01 0.06 0.06 0.37 0.24 0.31 0.31 0.02 0.26 0.26  
Crit Volume: 121 539 0 372  
Crit Moves: \*\*\*\*

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 14-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #12 Rocklin Rd & Fire Station No 1  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.442  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      41                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	0	0	2	0	0	2

-----

Volume Module:

Base Vol:	0	0	0	0	0	0	0	1413	0	0	1165	0
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	0	0	0	0	0	0	1413	0	0	1165	0
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	0	0	0	0	0	1413	0	0	1165	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	0	0	0	0	0	1413	0	0	1165	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	0	0	0	0	0	0	1413	0	0	1165	0

-----

Saturation Flow Module:

Sat/Lane:	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	1.00	0.00	0.00	1.00	0.00	1.00	2.00	0.00	1.00	2.00	0.00
Final Sat.:	0	1600	0	0	1600	0	1600	3200	0	1600	3200	0

-----

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.44	0.00	0.00	0.36	0.00
Crit Volume:	0			0			707		0			
Crit Moves:							****		****			

\*\*\*\*\*

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 15-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #13 Rocklin Rd & Havenhurst Cir  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.674  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      70                      Level Of Service:                      B

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Include			Include			Include			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	0	1	1	0	2	1	0	2

-----

Volume Module:

Base Vol:	15	0	4	387	1	301	209	1119	27	9	814	271
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	15	0	4	387	1	301	209	1119	27	9	814	271
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	15	0	4	387	1	301	209	1119	27	9	814	271
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	15	0	4	387	1	301	209	1119	27	9	814	271
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	15	0	4	387	1	301	209	1119	27	9	814	271

-----

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.79	0.00	0.21	0.99	0.01	1.00	1.00	2.93	0.07	1.00	2.25	0.75
Final Sat.:	1145	0	305	1446	4	1450	1450	4248	102	1450	3264	1086

-----

Capacity Analysis Module:

Vol/Sat:	0.01	0.00	0.01	0.27	0.27	0.21	0.14	0.26	0.26	0.01	0.25	0.25
Crit Volume:	19			388		209				362		
Crit Moves:	****			****		****				****		

\*\*\*\*\*





City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #16 Sierra College Bl & El Don Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.659  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 67 Level Of Service: B

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #17 Sierra College Bl & Nightwatch  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.550  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 51 Level Of Service: A

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #18 Sierra College Bl & Scarborough

Cycle (sec): 100 Critical Vol./Cap.(X): 0.551  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 51 Level Of Service: A

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Protected, Split Phase, and Include movements.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for all four approaches.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for all four approaches.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Includes data for all four approaches.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #19 Sierra College Bl & Southside Ranch

Cycle (sec): 100 Critical Vol./Cap.(X): 0.547  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 50 Level Of Service: A

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Protected, Split Phase, and Include movements.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for all four approaches.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for all four approaches.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Includes data for all four approaches.



City of Rocklin General Plan Update

2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #22 Sunset Bl & Topaz Ave  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.652  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 53 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Permitted, Protected, and Include rights.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for North, South, East, and West bounds.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for North, South, East, and West bounds.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Includes data for North, South, East, and West bounds.

City of Rocklin General Plan Update

2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #23 Sunset Bl & Whitney Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 1.156  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: F

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Includes data for Protected, Include, and Protected rights.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Includes data for North, South, East, and West bounds.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Includes data for North, South, East, and West bounds.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Includes data for North, South, East, and West bounds.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #101 Blue Oaks Bl & Lonetree

Cycle (sec): 100 Critical Vol./Cap.(X): 0.914  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #102 Blue Oaks Bl & Market Place

Cycle (sec): 100 Critical Vol./Cap.(X): 0.298  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 32 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 28-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #103 Blue Oaks Bl & Van Buren Way  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.347  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      35                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	0	1	0	0	1

Volume Module:  
Base Vol:                      38    687    44                      40    501    9                      14    0    26                      31    0    27  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      38    687    44                      40    501    9                      14    0    26                      31    0    27  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      38    687    44                      40    501    9                      14    0    26                      31    0    27  
Reduc Vol:                      0    0    0                      0    0    0                      0    0    0                      0    0    0  
Reduced Vol:                      38    687    44                      40    501    9                      14    0    26                      31    0    27  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      38    687    44                      40    501    9                      14    0    26                      31    0    27

Saturation Flow Module:  
Sat/Lane:                      1450 1450 1450                      1450 1450 1450                      1450 1450 1450                      1450 1450 1450  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      1.00 1.88 0.12                      1.00 1.96 0.04                      0.35 0.00 0.65                      0.53 0.00 0.47  
Final Sat.:                      1450 2725 175                      1450 2849 51                      508 0 943                      775 0 675

Capacity Analysis Module:  
Vol/Sat:                      0.03 0.25 0.25                      0.03 0.18 0.18                      0.03 0.00 0.03                      0.04 0.00 0.04  
Crit Volume:                      366 40                      40                      40                      58  
Crit Moves:                      \*\*\*\*    \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 29-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

-----  
Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #104 Five Star & Destiny Dr  
\*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      0.193  
Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
Optimal Cycle:                      28                      Level Of Service:                      A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Split Phase			Split Phase		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	0	1	0	1	0

Volume Module:  
Base Vol:                      1    93    2                      80 122 13                      13 0 3                      2 1 137  
Growth Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Initial Bse:                      1    93    2                      80 122 13                      13 0 3                      2 1 137  
User Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
PHF Volume:                      1    93    2                      80 122 13                      13 0 3                      2 1 137  
Reduc Vol:                      0    0    0                      0    0    0                      0    0    0                      0    0    0  
Reduced Vol:                      1    93    2                      80 122 13                      13 0 3                      2 1 137  
PCE Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
MLF Adj:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
FinalVolume:                      1    93    2                      80 122 13                      13 0 3                      2 1 137

Saturation Flow Module:  
Sat/Lane:                      1450 1450 1450                      1450 1450 1450                      1450 1450 1450                      1450 1450 1450  
Adjustment:                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00                      1.00 1.00 1.00  
Lanes:                      1.00 1.96 0.04                      1.00 1.81 0.19                      0.81 0.00 0.19                      0.67 0.33 1.00  
Final Sat.:                      1450 2839 61                      1450 2621 279                      1178 0 272                      967 483 1450

Capacity Analysis Module:  
Vol/Sat:                      0.00 0.03 0.03                      0.06 0.05 0.05                      0.01 0.00 0.01                      0.00 0.00 0.09  
Crit Volume:                      48 80                      80                      16                      137  
Crit Moves:                      \*\*\*\*    \*\*\*\*                      \*\*\*\*                      \*\*\*\*                      \*\*\*\*

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #105 Lonetree Bl & Adams Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.606  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #106 Lonetree Bl & Atherton Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.449  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #107 Lonetree Bl & Grand Canyon Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.767  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 98 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 4 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 4 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 4 rows (Vol/Sat, Crit Volume, Crit Moves).

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #108 Lonetree Bl & Redwood Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.737  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 87 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns (North, South, East, West) and 4 rows (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume).

Saturation Flow Module: Table with 4 columns (North, South, East, West) and 4 rows (Sat/Lane, Adjustment, Lanes, Final Sat.).

Capacity Analysis Module: Table with 4 columns (North, South, East, West) and 4 rows (Vol/Sat, Crit Volume, Crit Moves).



City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #109 Lonetree Bl & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.552  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 51 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #110 Park Dr & Blaydon Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.262  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 25 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns for different approaches and movements. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #111 Park Dr & Quarry Way

Cycle (sec): 100 Critical Vol./Cap.(X): 0.507  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 46 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic movements and 10 rows of volume and adjustment factors.

Saturation Flow Module table with 10 columns representing different traffic movements and 10 rows of saturation flow and adjustment factors.

Capacity Analysis Module table with 10 columns representing different traffic movements and 10 rows of capacity and critical volume factors.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

Intersection #112 Park Dr & Farrier Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.457  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic movements and 10 rows of volume and adjustment factors.

Saturation Flow Module table with 10 columns representing different traffic movements and 10 rows of saturation flow and adjustment factors.

Capacity Analysis Module table with 10 columns representing different traffic movements and 10 rows of capacity and critical volume factors.

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #113 Park Dr & King Pine Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.489  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 36 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
Control: Protected Protected Permitted Permitted  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 1 1 0 1 0 1 1 0 1 0 1 0 0 1

Volume Module:  
Base Vol: 24 1308 25 27 1032 7 7 1 9 31 0 15  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 24 1308 25 27 1032 7 7 1 9 31 0 15  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 24 1308 25 27 1032 7 7 1 9 31 0 15  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 24 1308 25 27 1032 7 7 1 9 31 0 15  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 24 1308 25 27 1032 7 7 1 9 31 0 15

Saturation Flow Module:  
Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 1.96 0.04 1.00 1.99 0.01 0.88 0.12 1.00 1.00 0.00 1.00  
Final Sat.: 1500 2944 56 1500 2980 20 1313 188 1500 1500 0 1500

Capacity Analysis Module:  
Vol/Sat: 0.02 0.44 0.44 0.02 0.35 0.35 0.01 0.01 0.01 0.02 0.00 0.01  
Crit Volume: 667 27 9 31  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #114 Park Dr & Shelton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.324  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 34 Level Of Service: A

Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
Control: Protected Protected Protected Protected  
Rights: Include Include Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 1 0 2 1 0 1 0 2 1 0 1 0 0 1 0 1 0 1

Volume Module:  
Base Vol: 116 1024 64 6 567 3 8 0 67 34 4 1  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 116 1024 64 6 567 3 8 0 67 34 4 1  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 116 1024 64 6 567 3 8 0 67 34 4 1  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 116 1024 64 6 567 3 8 0 67 34 4 1  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 116 1024 64 6 567 3 8 0 67 34 4 1

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 2.82 0.18 1.00 2.98 0.02 1.00 0.00 1.00 1.00 1.00 1.00  
Final Sat.: 1450 4094 256 1450 4327 23 1450 0 1450 1450 1450 1450

Capacity Analysis Module:  
Vol/Sat: 0.08 0.25 0.25 0.00 0.13 0.13 0.01 0.00 0.05 0.02 0.00 0.00  
Crit Volume: 363 6 67 34  
Crit Moves: \*\*\*\* \*\*

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #115 Park Dr & Victory Lane  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.387  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #116 Park Dr & Wykford Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.395  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 38 Level Of Service: A

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MFL Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #117 Park Dr & Twin Oaks/ Boardwalk  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.384  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 37 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #118 Park Dr & Safeway  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.676  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 70 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 44-1

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #119 South Whitney & Five Star Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.583  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 55 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	0	1	0	0	1	1	0	1

Volume Module:

Base Vol:	6	243	35	338	177	11	55	16	5	40	23	313
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	6	243	35	338	177	11	55	16	5	40	23	313
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	6	243	35	338	177	11	55	16	5	40	23	313
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	6	243	35	338	177	11	55	16	5	40	23	313
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	6	243	35	338	177	11	55	16	5	40	23	313

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.75	0.25	1.00	1.88	0.12	1.00	0.76	0.24	1.00	1.00	1.00
Final Sat.:	1450	2535	365	1450	2730	170	1450	1105	345	1450	1450	1450

Capacity Analysis Module:

Vol/Sat:	0.00	0.10	0.10	0.23	0.06	0.06	0.04	0.01	0.01	0.03	0.02	0.22
Crit Volume:			139	338		55						313
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 45-1

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #120 Spring Creek Dr & Broken Rail Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.049  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 15 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Permitted			Permitted			Permitted			Permitted		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	1	0	1	0	0	0	1	0	0	1

Volume Module:

Base Vol:	0	49	9	2	36	0	5	0	10	4	0	4
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	49	9	2	36	0	5	0	10	4	0	4
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	49	9	2	36	0	5	0	10	4	0	4
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	49	9	2	36	0	5	0	10	4	0	4
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	49	9	2	36	0	5	0	10	4	0	4

Saturation Flow Module:

Sat/Lane:	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	0.84	0.16	0.05	0.95	0.00	0.33	0.00	0.67	0.50	0.00	0.50
Final Sat.:	0	1352	248	84	1516	0	533	0	1067	800	0	800

Capacity Analysis Module:

Vol/Sat:	0.00	0.04	0.04	0.02	0.02	0.00	0.01	0.00	0.01	0.01	0.00	0.01
Crit Volume:			58	2			15		4			
Crit Moves:	****	****	****	****	****	****	****	****	****	****	****	****

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 46-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #121 Stanford Ranch Rd & Cobblestone Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.318
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 27 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 47-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #122 Stanford Ranch Rd & Darby Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.582
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 55 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #123 Stanford Ranch Rd & Park Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.675  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 70 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #124 Stanford Ranch Rd & Plaza  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.561  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 52 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.



GP30 Future Geo Fri May 22, 2009 10:53:36 Page 50-1

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #125 Stanford Ranch Rd & Stoney Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.393  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Permitted			Permitted		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	1	1	0	0	0	1	0	0	1

Volume Module:

Base Vol:	92	694	133	11	532	15	17	17	50	81	12	4
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	92	694	133	11	532	15	17	17	50	81	12	4
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	92	694	133	11	532	15	17	17	50	81	12	4
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	92	694	133	11	532	15	17	17	50	81	12	4
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	92	694	133	11	532	15	17	17	50	81	12	4

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.68	0.32	1.00	1.95	0.05	0.20	0.20	0.60	0.84	0.12	0.04
Final Sat.:	1500	2518	482	1500	2918	82	304	304	893	1253	186	62

Capacity Analysis Module:

Vol/Sat:	0.06	0.28	0.28	0.01	0.18	0.18	0.06	0.06	0.06	0.06	0.06	0.06
Crit Volume:	414			11			84	81				
Crit Moves:	****			****			****	****				

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 51-1

City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #126 Stanford Ranch Rd & Victory Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.317  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	0	0	0	0	0	0	1	0	1	1	0	3

Volume Module:

Base Vol:	0	0	0	77	0	96	57	1032	0	0	966	77
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	0	0	0	77	0	96	57	1032	0	0	966	77
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	0	0	0	77	0	96	57	1032	0	0	966	77
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	0	0	0	77	0	96	57	1032	0	0	966	77
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	0	0	77	0	96	57	1032	0	0	966	77

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	0.00	0.00	0.00	1.00	1.00	1.00	1.00	3.00	0.00	0.00	3.00	1.00
Final Sat.:	0	0	0	1500	1500	1500	1500	4500	0	0	4500	1500

Capacity Analysis Module:

Vol/Sat:	0.00	0.00	0.00	0.05	0.00	0.06	0.04	0.23	0.00	0.00	0.21	0.05
Crit Volume:	0			96	57					322		
Crit Moves:				****	****					****		

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #127 Stanford Ranch Rd & West Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.647  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 65 Level Of Service: B

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns and 12 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 12 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 12 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #128 Sunset Bl & Atherton  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.910  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 12 columns and 12 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 12 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 12 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #129 Sunset Bl & Blue Oaks Bl  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.791  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 109 Level Of Service: C

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Split Phase			Split Phase			Protected			Protected		
Rights:	Ovl			Include			Ignore			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	1	0	0	1	0	1	0	3	0	1	1

Volume Module:	North Bound			South Bound			East Bound			West Bound		
Base Vol:	303	36	338	29	20	4	27	1653	377	398	1720	58
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	303	36	338	29	20	4	27	1653	377	398	1720	58
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
PHF Volume:	303	36	338	29	20	4	27	1653	0	398	1720	58
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	303	36	338	29	20	4	27	1653	0	398	1720	58
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	1.00
Final Volume:	303	36	338	29	20	4	27	1653	0	398	1720	58

Saturation Flow Module:	North Bound			South Bound			East Bound			West Bound		
Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.79	0.21	1.00	1.00	0.83	0.17	1.00	3.00	1.00	1.00	3.00	1.00
Final Sat.:	2592	308	1450	1450	1208	242	1450	4350	1450	1450	4350	1450

Capacity Analysis Module:	North Bound			South Bound			East Bound			West Bound		
Vol/Sat:	0.12	0.12	0.23	0.02	0.02	0.02	0.02	0.38	0.00	0.27	0.40	0.04
Crit Volume:	170			29			551		398			
Crit Moves:	****			****			****		****			

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #130 Sunset Bl & Fairway Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.743  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 72 Level Of Service: C

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Permitted			Protected			Protected		
Rights:	Include			Include			Include			Include		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	1	0	0	1	0	0	1	1	0	1

Volume Module:	North Bound			South Bound			East Bound			West Bound		
Base Vol:	139	32	237	13	19	29	63	1463	106	183	1669	13
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	139	32	237	13	19	29	63	1463	106	183	1669	13
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	139	32	237	13	19	29	63	1463	106	183	1669	13
Reduced Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	139	32	237	13	19	29	63	1463	106	183	1669	13
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Final Volume:	139	32	237	13	19	29	63	1463	106	183	1669	13

Saturation Flow Module:	North Bound			South Bound			East Bound			West Bound		
Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	1.00	1.00	0.21	0.31	0.48	1.00	2.00	1.00	1.00	1.98	0.02
Final Sat.:	1500	1500	1500	320	467	713	1500	3000	1500	1500	2977	23

Capacity Analysis Module:	North Bound			South Bound			East Bound			West Bound		
Vol/Sat:	0.09	0.02	0.16	0.04	0.04	0.04	0.04	0.49	0.07	0.12	0.56	0.56
Crit Volume:	139			61			732		183			
Crit Moves:	****			****			****		****			



City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #133 Sunset Bl & Pebble Creek  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.678  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 58 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows include movement details and lane configurations.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Rows show volume and adjustment factors.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows show saturation flow and lane adjustments.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Rows show capacity analysis results.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #134 Sunset Bl & Stanford Ranch Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.699  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 76 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows include movement details and lane configurations.

Volume Module table with columns: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume. Rows show volume and adjustment factors.

Saturation Flow Module table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows show saturation flow and lane adjustments.

Capacity Analysis Module table with columns: Vol/Sat, Crit Volume, Crit Moves. Rows show capacity analysis results.

\*\*\*\*\*

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 60-1  
 -----  
 City of Rocklin General Plan Update  
 2030 Plus Project  
 PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
 Intersection #135 Sunset Bl & West Oaks Bl  
 \*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      1.051  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      180                      Level Of Service:                      F

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	1	0	3	0	1	1

Volume Module:

Base Vol:	47	226	230	760	153	123	68	1025	6	193	1290	564
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	47	226	230	760	153	123	68	1025	6	193	1290	564
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00
PHF Volume:	47	226	230	760	153	123	68	1025	0	193	1290	0
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	47	226	230	760	153	123	68	1025	0	193	1290	0
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	1.00	1.00	0.00
FinalVolume:	47	226	230	760	153	123	68	1025	0	193	1290	0

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	1.00	1.00	2.00	1.00	1.00	3.00	1.00	1.00	3.00	1.00
Final Sat.:	1450	2900	1450	1450	2900	1450	1450	4350	1450	1450	4350	1450

Capacity Analysis Module:

Vol/Sat:	0.03	0.08	0.16	0.52	0.05	0.08	0.05	0.24	0.00	0.13	0.30	0.00
Crit Volume:	230			760			342			193		
Crit Moves:	****			****			****			****		

GP30 Future Geo                      Fri May 22, 2009 10:53:36                      Page 61-1  
 -----  
 City of Rocklin General Plan Update  
 2030 Plus Project  
 PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
 Intersection #136 W Stanford Ranch Rd & Sunset Bl  
 \*\*\*\*\*

Cycle (sec):                      100                      Critical Vol./Cap.(X):                      1.164  
 Loss Time (sec):                      0                      Average Delay (sec/veh):                      xxxxxx  
 Optimal Cycle:                      180                      Level Of Service:                      F

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Include			Include			Ignore			Ignore		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	3	0	1	1	2	0	2	1	0	1

Volume Module:

Base Vol:	105	1141	154	412	516	377	790	493	122	229	517	311
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	105	1141	154	412	516	377	790	493	122	229	517	311
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	105	1141	154	412	516	377	790	493	122	229	517	311
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	105	1141	154	412	516	377	790	493	122	229	517	311
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	105	1141	154	412	516	377	790	493	122	229	517	311

Saturation Flow Module:

Sat/Lane:	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450	1450
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	2.00	3.00	1.00	2.00	2.00	1.00	1.00	2.00	1.00	2.00	2.00	1.00
Final Sat.:	2900	4350	1450	2900	2900	1450	1450	2900	1450	2900	2900	1450

Capacity Analysis Module:

Vol/Sat:	0.04	0.26	0.11	0.14	0.18	0.26	0.54	0.17	0.08	0.08	0.18	0.21
Crit Volume:	380			206			790			311		
Crit Moves:	****			****			****			****		

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 62-1  
 -----  
 City of Rocklin General Plan Update  
 2030 Plus Project  
 PM Peak Hour LOS (Modified Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #137 W Stanford Ranch Rd & Wildcat Bl  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.796  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 112 Level Of Service: C  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 1 0 2 0 1 2 0 1 0 2 2 0 2 0 1 1 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 14 442 0 568 129 510 609 614 13 1 247 345  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 14 442 0 568 129 510 609 614 13 1 247 345  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 14 442 0 568 129 510 609 614 13 1 247 345  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 14 442 0 568 129 510 609 614 13 1 247 345  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 14 442 0 568 129 510 609 614 13 1 247 345  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 1.00 2.00 1.00 2.00 1.00 2.00 2.00 1.00 1.00 3.00 1.00  
 Final Sat.: 1450 2900 1450 2900 1450 2900 2900 1450 1450 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.01 0.15 0.00 0.20 0.09 0.18 0.21 0.21 0.01 0.00 0.06 0.24  
 Crit Volume: 221 284 305 345  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 63-1  
 -----  
 City of Rocklin General Plan Update  
 2030 Plus Project  
 PM Peak Hour LOS (Modified Circular 212 Capacities)  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #138 Whitney Ranch Pkwy & Bridlewood Dr  
 \*\*\*\*\*  
 Cycle (sec): 100 Critical Vol./Cap.(X): 0.334  
 Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 28 Level Of Service: A  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Permitted Permitted Protected Protected  
 Rights: Include Include Include Include  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 0 0 1! 0 0 0 0 1! 0 0 1 0 1 1 0 1 0 1 1 0  
 -----  
 Volume Module:  
 Base Vol: 53 1 25 3 0 7 7 660 91 44 375 14  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 53 1 25 3 0 7 7 660 91 44 375 14  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 53 1 25 3 0 7 7 660 91 44 375 14  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 53 1 25 3 0 7 7 660 91 44 375 14  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 53 1 25 3 0 7 7 660 91 44 375 14  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500 1500  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 0.67 0.01 0.32 0.30 0.00 0.70 1.00 1.76 0.24 1.00 1.93 0.07  
 Final Sat.: 1006 19 475 450 0 1050 1500 2636 364 1500 2892 108  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.05 0.05 0.05 0.01 0.00 0.01 0.00 0.25 0.25 0.03 0.13 0.13  
 Crit Volume: 79 3 376 44  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #139 Whitney Ranch Pkwy & Painted Pony Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.299  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 33 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #140 Whitney Ranch Pkwy & Spring Creek Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.294  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 26 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns and 10 rows including Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with 10 columns and 4 rows including Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns and 4 rows including Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*





City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #143 Wildcat Bl & S High School Entrance  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.485  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 44 Level Of Service: A

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #144 Wildcat Bl & N High School Entrance  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.411  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 39 Level Of Service: A

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Table with columns for Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Table with columns for Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #145 Wildcat Bl & Ranch View Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.786  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 107 Level Of Service: C

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #152 Stanford Ranch Rd & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.920  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module: Table with 4 columns: North Bound, South Bound, East Bound, West Bound. Rows include Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #153 Whitney Blvd & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.742  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 88 Level Of Service: C

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #154 Park Dr & Crest Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.253  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 31 Level Of Service: A

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, FinalVolume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Volume, Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #161 Granite Dr & Dominguez Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.769  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 99 Level Of Service: C

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 12 columns for volume and growth factors across different approaches and movements.

Saturation Flow Module: Table with 12 columns for saturation flow factors across different approaches and movements.

Capacity Analysis Module: Table with 12 columns for capacity analysis factors across different approaches and movements.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #162 Sierra College Bl & Dominguez Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.808  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 119 Level Of Service: D

Table with 4 columns: Approach, North Bound, South Bound, East Bound, West Bound. Rows include Movement, Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module: Table with 12 columns for volume and growth factors across different approaches and movements.

Saturation Flow Module: Table with 12 columns for saturation flow factors across different approaches and movements.

Capacity Analysis Module: Table with 12 columns for capacity analysis factors across different approaches and movements.

\*\*\*\*\*



GP30 Future Geo Fri May 22, 2009 10:53:36 Page 78-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #165 Sierra College Bl & Valley View Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.611
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 59 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Vol/Sat, Crit Volume, Crit Moves.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 79-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #166 University Ave & Whitney Ranch Pkwy

Cycle (sec): 100 Critical Vol./Cap.(X): 0.644
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 64 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #167 West Oaks Bl & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.641  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 63 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #168 West Oaks Bl & Painted Pony Ln  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.291  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 32 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*



City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #169 Laredo Dr & Whitney Ranch Pkwy  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.462  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 42 Level Of Service: A

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Vol/Sat, Crit Volume, Crit Moves.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #170 Rocklin Rd & Civic Centr Dr  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.676  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 70 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L-T-R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and 4 rows: Vol/Sat, Crit Volume, Crit Moves.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 84-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #171 Pacific St & Civic Center Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.615
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 59 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 85-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #201 Rocklin Rd & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 1.097
Loss Time (sec): 6 Average Delay (sec/veh): 65.9
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

\*\*\*\*\*

Note: Queue reported is the number of cars per lane.

\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 86-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #202 Rocklin Rd & I-80 WB

Cycle (sec): 100 Critical Vol./Cap.(X): 1.139
Loss Time (sec): 6 Average Delay (sec/veh): 71.4
Optimal Cycle: 180 Level Of Service: E

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Saturation Flow Module, Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 87-1
City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)

Intersection #203 Sierra College Bl & I-80 WB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.862
Loss Time (sec): 9 Average Delay (sec/veh): 32.9
Optimal Cycle: 86 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Saturation Flow Module, Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #204 Sierra College Bl & I-80 EB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.624  
Loss Time (sec): 9 Average Delay (sec/veh): 28.4  
Optimal Cycle: 43 Level Of Service: C

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), Rights, Min. Green, Y+R, Lanes.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #206 Sunset & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.705  
Loss Time (sec): 6 Average Delay (sec/veh): 12.3  
Optimal Cycle: 43 Level Of Service: B

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include, Ignore), Rights, Min. Green, Y+R, Lanes.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #207 Sunset & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.720  
Loss Time (sec): 6 Average Delay (sec/veh): 14.5  
Optimal Cycle: 45 Level Of Service: B

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), Rights, Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #208 Whitney Ranch Pkwy & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.965  
Loss Time (sec): 6 Average Delay (sec/veh): 32.5  
Optimal Cycle: 154 Level Of Service: C

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Include), Rights, Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #209 Whitney Ranch Pkwy & SR 65 NB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.837  
Loss Time (sec): 6 Average Delay (sec/veh): 16.2  
Optimal Cycle: 67 Level Of Service: B

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Ignored), Rights (Include, Ignore), Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update  
2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

Intersection #210 Blue Oaks Blvd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.583  
Loss Time (sec): 6 Average Delay (sec/veh): 27.0  
Optimal Cycle: 32 Level Of Service: C

Table with columns: Approach (North Bound, South Bound, East Bound, West Bound), Movement (L-T-R), Control (Protected, Ignored), Rights (Ovl, Ignore), Min. Green, Y+R, Lanes.

Volume Module: Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Saturation Flow Module: Sat/Lane, Adjustment, Lanes, Final Sat.

Capacity Analysis Module: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 94-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #211 Blue Oaks Blvd & SR 65 NB Off  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 1.082  
Loss Time (sec): 6 Average Delay (sec/veh): 41.3  
Optimal Cycle: 180 Level Of Service: D  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Protected Protected Protected Protected  
Rights: Ignore Ignore Include Include  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 2 0 0 0 1 0 0 0 0 0 0 0 2 0 1 0 1 1 0 1  
-----  
Volume Module:  
Base Vol: 122 0 427 0 0 0 0 1534 477 166 1838 0  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 122 0 427 0 0 0 0 1534 477 166 1838 0  
User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 122 0 0 0 0 0 0 1534 477 166 1838 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 122 0 0 0 0 0 0 1534 477 166 1838 0  
PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 122 0 0 0 0 0 0 1534 477 166 1838 0  
-----  
Saturation Flow Module:  
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
Adjustment: 0.92 1.00 1.00 1.00 1.00 1.00 0.95 0.85 0.95 0.95 1.00  
Lanes: 2.00 0.00 1.00 0.00 0.00 0.00 0.00 2.00 1.00 0.17 1.83 1.00  
Final Sat.: 3502 0 1900 0 0 0 0 3610 1615 298 3298 1900  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.03 0.00 0.00 0.00 0.00 0.00 0.00 0.42 0.30 0.56 0.56 0.00  
Crit Moves: \*\*\*\*  
Green/Cycle: 0.03 0.00 0.00 0.00 0.00 0.00 0.00 0.39 0.39 0.52 0.91 0.00  
Volume/Cap: 1.08 0.00 0.00 0.00 0.00 0.00 0.00 1.08 0.75 1.08 0.61 0.00  
Delay/Veh: 156.9 0.0 0.0 0.0 0.0 0.0 0.0 79.8 31.2 71.2 1.3 0.0  
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
AdjDel/Veh: 156.9 0.0 0.0 0.0 0.0 0.0 0.0 79.8 31.2 71.2 1.3 0.0  
LOS by Move: F A A A A A A E C E A A  
HCM2kAvgQ: 5 0 0 0 0 0 0 37 14 47 8 0  
\*\*\*\*\*  
Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*

GP30 Future Geo Fri May 22, 2009 10:53:36 Page 95-1

-----  
City of Rocklin General Plan Update  
2030 Plus Project  
PM Peak Hour LOS (Modified Circular 212 Capacities)  
-----  
Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)  
\*\*\*\*\*  
Intersection #212 Pleasant Grove Blvd & SR 65 NB  
\*\*\*\*\*  
Cycle (sec): 100 Critical Vol./Cap.(X): 0.784  
Loss Time (sec): 6 Average Delay (sec/veh): 19.3  
Optimal Cycle: 55 Level Of Service: B  
\*\*\*\*\*  
Approach: North Bound South Bound East Bound West Bound  
Movement: L - T - R L - T - R L - T - R L - T - R  
-----  
Control: Permitted Permitted Protected Protected  
Rights: Ovl Include Ignore Ignore  
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
Lanes: 3 0 0 0 2 0 0 0 0 0 0 0 3 0 1 0 0 4 0 1  
-----  
Volume Module:  
Base Vol: 591 0 771 0 0 0 0 2049 602 0 2418 213  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 591 0 771 0 0 0 0 2049 602 0 2418 213  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
PHF Volume: 591 0 771 0 0 0 0 2049 0 0 2418 0  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 591 0 771 0 0 0 0 2049 0 0 2418 0  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 0.00  
FinalVolume: 591 0 771 0 0 0 0 2049 0 0 2418 0  
-----  
Saturation Flow Module:  
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900  
Adjustment: 0.49 1.00 0.75 1.00 1.00 1.00 1.00 0.91 1.00 1.00 0.91 1.00  
Lanes: 3.00 0.00 2.00 0.00 0.00 0.00 0.00 3.00 1.00 0.00 3.00 1.00  
Final Sat.: 2803 0 2842 0 0 0 0 5187 1900 0 5187 1900  
-----  
Capacity Analysis Module:  
Vol/Sat: 0.21 0.00 0.27 0.00 0.00 0.00 0.00 0.40 0.00 0.00 0.47 0.00  
Crit Moves: \*\*\*\*  
Green/Cycle: 0.35 0.00 0.35 0.00 0.00 0.00 0.00 0.59 0.00 0.00 0.59 0.00  
Volume/Cap: 0.61 0.00 0.78 0.00 0.00 0.00 0.00 0.66 0.00 0.00 0.78 0.00  
Delay/Veh: 28.3 0.0 33.6 0.0 0.0 0.0 0.0 14.2 0.0 0.0 16.8 0.0  
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
AdjDel/Veh: 28.3 0.0 33.6 0.0 0.0 0.0 0.0 14.2 0.0 0.0 16.8 0.0  
LOS by Move: C A C A A A A B A A B A  
HCM2kAvgQ: 6 0 14 0 0 0 0 16 0 0 22 0  
\*\*\*\*\*  
Note: Queue reported is the number of cars per lane.  
\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #213 Pleasant Grove Blvd & SR 65 SB  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.633  
Loss Time (sec): 6 Average Delay (sec/veh): 9.8  
Optimal Cycle: 36 Level Of Service: A

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West bounds.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report  
2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #214 Stanford Ranch Rd & SR 65 NB  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.745  
Loss Time (sec): 6 Average Delay (sec/veh): 14.3  
Optimal Cycle: 48 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North, South, East, West bounds.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.



City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #215 Stanford Ranch Rd & SR 65 SB

Cycle (sec): 100 Critical Vol./Cap.(X): 0.762
Loss Time (sec): 6 Average Delay (sec/veh): 10.1
Optimal Cycle: 51 Level Of Service: B

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #301 Sierra College Bl & Brace Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.948
Loss Time (sec): 6 Average Delay (sec/veh): 37.0
Optimal Cycle: 132 Level Of Service: D

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #302 Sierra College Bl & Taylor Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 1.018
Loss Time (sec): 12 Average Delay (sec/veh): 56.0
Optimal Cycle: 180 Level Of Service: E

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #304 Sierra College Bl & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.873
Loss Time (sec): 12 Average Delay (sec/veh): 34.6
Optimal Cycle: 99 Level Of Service: C

Table with columns: Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes. Rows for North Bound, South Bound, East Bound, West Bound.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Sat/Lane, Adjustment, Lanes, Final Sat. Rows for Saturation Flow Module.

Table with columns: Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #305 Taylor Rd & King Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.570
Loss Time (sec): 12 Average Delay (sec/veh): 30.3
Optimal Cycle: 46 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 10 columns for Volume Module. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 10 columns for Saturation Flow Module. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 10 columns for Capacity Analysis Module. Rows include Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

Intersection #306 Taylor Rd & Horseshoe Bar

Cycle (sec): 100 Critical Vol./Cap.(X): 1.100
Loss Time (sec): 9 Average Delay (sec/veh): 81.9
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 10 columns for Volume Module. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 10 columns for Saturation Flow Module. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 10 columns for Capacity Analysis Module. Rows include Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM 4-Way Stop Method (Base Volume Alternative)
Intersection #307 Rocklin Rd & Barton Rd
Cycle (sec): 100 Critical Vol./Cap. (X): 0.789
Loss Time (sec): 0 Average Delay (sec/veh): 22.5
Optimal Cycle: 0 Level Of Service: C
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Stop Sign Stop Sign Stop Sign Stop Sign
Rights: Include Include Include Include
Lanes: 0 0 1! 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Volume Module:
Base Vol: 249 114 0 0 102 122 421 0 508 0 0 0 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 249 114 0 0 102 122 421 0 508 0 0 0 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 249 114 0 0 102 122 421 0 508 0 0 0 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 249 114 0 0 102 122 421 0 508 0 0 0 0
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 249 114 0 0 102 122 421 0 508 0 0 0 0
Saturation Flow Module:
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Lanes: 1.00 1.00 0.00 0.00 0.46 0.54 1.00 0.00 1.00 0.00 0.00 0.00
Final Sat.: 469 499 0 0 251 301 534 0 648 0 0 0 0
Capacity Analysis Module:
Vol/Sat: 0.53 0.23 xxxx xxxx 0.41 0.41 0.79 xxxx 0.78 xxxx xxxx xxxx
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*
Delay/Veh: 18.1 11.7 0.0 0.0 13.6 13.6 29.7 0.0 24.9 0.0 0.0 0.0
Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 18.1 11.7 0.0 0.0 13.6 13.6 29.7 0.0 24.9 0.0 0.0 0.0
LOS by Move: C B \* \* B B D \* C \* \* \*
ApproachDel: 16.1 13.6 27.1 xxxxxx
Delay Adj: 1.00 1.00 1.00 xxxxxx
ApprAdjDel: 16.1 13.6 27.1 xxxxxx
LOS by Appr: C B D \*
AllWayAvgQ: 1.0 0.3 0.0 0.6 0.6 0.6 3.0 0.0 3.0 0.0 0.0 0.0
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM Unsignalized Method (Base Volume Alternative)
Intersection #308 Barton Rd & Brace Rd
Average Delay (sec/veh): 65.7 Worst Case Level Of Service: F[271.3]
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Stop Sign Stop Sign Uncontrolled Uncontrolled
Rights: Include Include Include Include
Lanes: 0 0 1! 0 0 0 0 0 0 0 0 1 0 0 1 0 0 0 0
Volume Module:
Base Vol: 214 0 122 0 0 0 0 541 171 182 186 0
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 214 0 122 0 0 0 0 541 171 182 186 0
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 214 0 122 0 0 0 0 541 171 182 186 0
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 214 0 122 0 0 0 0 541 171 182 186 0
Critical Gap Module:
Critical Gp: 6.4 6.5 6.2 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 4.1 xxxxx xxxxx
FollowUpTim: 3.5 4.0 3.3 xxxxxx xxxx xxxxxx xxxxxx xxxxx xxxxxx 2.2 xxxxx xxxxxx
Capacity Module:
Cnflct Vol: 1177 1177 627 xxxx xxxx xxxxxx xxxx xxxx xxxxxx 712 xxxxx xxxxxx
Potent Cap.: 213 193 487 xxxxx xxxx xxxxxx xxxxx xxxx xxxxxx 897 xxxxx xxxxxx
Move Cap.: 176 149 487 xxxxx xxxx xxxxxx xxxxx xxxx xxxxxx 897 xxxxx xxxxxx
Volume/Cap: 1.21 0.00 0.25 xxxxx xxxx xxxxx xxxxx xxxx xxxxx 0.20 xxxxx xxxxx
Level Of Service Module:
2Way95thQ: xxxxx xxxx xxxxxx xxxx xxxx xxxxxx xxxx xxxx xxxxxx 0.8 xxxxx xxxxxx
Control Del: xxxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx 10.0 xxxxx xxxxxx
LOS by Move: \*
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxxx 229 xxxxxx xxxx xxxx xxxxxx xxxxx xxxx xxxxxx xxxxx xxxx xxxxxx
SharedQueue: xxxxxx 19.7 xxxxxx xxxxxx xxxx xxxxxx xxxxxx xxxx xxxxxx 0.8 xxxxx xxxxxx
Shrd ConDel: xxxxxx 271 xxxxxx xxxxxx xxxxxx xxxxxx xxxxxx xxxxxx 10.0 xxxxx xxxxxx
Shared LOS: \* F \*
ApproachDel: 271.3 xxxxxxx xxxxxxx xxxxxxx
ApproachLOS: F \*
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM Operations Method (Base Volume Alternative)
Intersection #309 Horseshoe Bar Rd & I-80 WB Ramp
Cycle (sec): 100 Critical Vol./Cap. (X): 0.713
Loss Time (sec): 0 Average Delay (sec/veh): 26.4
Optimal Cycle: 80 Level Of Service: C
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Protected Protected Split Phase Split Phase
Rights: Include Include Include Include
Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0
Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0
Lanes: 1 0 1 1 0 1 0 1 0 0 1 1 0 0 1 0
Volume Module:
Base Vol: 293 568 175 47 268 536 81 46 173 70 49 140
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 293 568 175 47 268 536 81 46 173 70 49 140
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 293 568 175 47 268 536 81 46 173 70 49 140
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
Reduced Vol: 293 568 175 47 268 536 81 46 173 70 49 140
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
FinalVolume: 293 568 175 47 268 536 81 46 173 70 49 140
Saturation Flow Module:
Sat/Lane: 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900 1900
Adjstment: 0.95 0.92 0.92 0.95 1.00 0.85 0.97 0.97 0.85 0.95 0.89 0.89
Lanes: 1.00 1.53 0.47 1.00 1.00 1.00 0.64 0.36 1.00 1.00 0.26 0.74
Final Sat.: 1805 2663 821 1805 1900 1615 1174 667 1615 1805 438 1251
Capacity Analysis Module:
Vol/Sat: 0.16 0.21 0.21 0.03 0.14 0.33 0.07 0.07 0.11 0.04 0.11 0.11
Crit Moves: \*\*\*\*
Green/Cycle: 0.23 0.62 0.62 0.08 0.47 0.47 0.15 0.15 0.15 0.16 0.16 0.16
Volume/Cap: 0.71 0.35 0.35 0.35 0.30 0.71 0.46 0.46 0.71 0.25 0.71 0.71
Delay/Veh: 41.4 9.4 9.4 45.4 16.8 24.6 40.0 40.0 50.0 37.4 48.9 48.9
User DelAdj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
AdjDel/Veh: 41.4 9.4 9.4 45.4 16.8 24.6 40.0 40.0 50.0 37.4 48.9 48.9
LOS by Move: D A A D B C D D D D
HCM2kAvgQ: 10 6 6 2 5 14 4 4 7 2 7 7
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS

Level Of Service Computation Report
2000 HCM Unsignalized Method (Base Volume Alternative)
Intersection #310 Horseshoe Bar Rd & I-80 EB Ramp
Average Delay (sec/veh): 31.6 Worst Case Level Of Service: F[107.3]
Approach: North Bound South Bound East Bound West Bound
Movement: L - T - R L - T - R L - T - R L - T - R
Control: Uncontrolled Uncontrolled Stop Sign Stop Sign
Rights: Include Include Include Include
Lanes: 0 0 1 0 1 0 1 0 0 0 0 0 0 0 1 0 0 0 1
Volume Module:
Base Vol: 0 647 301 120 449 0 0 0 0 193 0 423
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
Initial Bse: 0 647 301 120 449 0 0 0 0 193 0 423
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
PHF Volume: 0 647 301 120 449 0 0 0 0 193 0 423
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0
FinalVolume: 0 647 301 120 449 0 0 0 0 193 0 423
Critical Gap Module:
Critical Gp:xxxxx xxxx xxxxx 4.1 xxxx xxxxx xxxxx xxxx xxxxx 6.4 xxxx 6.2
FollowUpTim:xxxxx xxxx xxxxx 2.2 xxxx xxxxx xxxxx xxxx xxxxx 3.5 xxxx 3.3
Capacity Module:
Cnflct Vol: xxxx xxxx xxxxx 948 xxxx xxxxx xxxx xxxx xxxxx 1336 xxxx 647
Potent Cap.: xxxx xxxx xxxxx 732 xxxx xxxxx xxxx xxxx xxxxx 171 xxxx 475
Move Cap.: xxxx xxxx xxxxx 732 xxxx xxxxx xxxx xxxx xxxxx 148 xxxx 475
Volume/Cap: xxxx xxxx xxxxx 0.16 xxxx xxxx xxxxx xxxx xxxxx 1.31 xxxx 0.89
Level Of Service Module:
2Way95thQ: xxxx xxxx xxxxx 0.6 xxxx xxxxx xxxx xxxx xxxxx 11.8 xxxx 9.8
Control Del:xxxxx xxxx xxxxx 10.9 xxxx xxxxx xxxxx xxxx xxxxx 236.1 xxxx 48.5
LOS by Move: \* \* \* B \* \* \* F \* \* \*
Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT LT - LTR - RT
Shared Cap.: xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx xxxx xxxx xxxxx
SharedQueue:xxxxx xxxx xxxxx 0.6 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx
Shrd ConDel:xxxxx xxxx xxxxx 10.9 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx xxxxx
Shared LOS: \* \* \* B \* \* \* \* \* \*
ApproachDel: xxxxxx xxxxxx xxxxxx 107.3
ApproachLOS: \* \* \* F
Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Modified Circular 212 Capacities)

Level Of Service Computation Report

2000 HCM Operations Method (Base Volume Alternative)

\*\*\*\*\*
Intersection #1216 Sierra College Blvd & SR 193
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.927
Loss Time (sec): 9 Average Delay (sec/veh): 34.9
Optimal Cycle: 119 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different volume categories and 10 rows of adjustment factors.

Saturation Flow Module table with 10 columns for Sat/Lane and Adjustment, and 10 rows of values.

Capacity Analysis Module table with 10 columns for Vol/Sat, Crit Moves, Green/Cycle, Volume/Cap, Delay/Veh, User DelAdj, AdjDel/Veh, LOS by Move, and HCM2kAvgQ.

Note: Queue reported is the number of cars per lane.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Published Circular 212 Capacities)

Impact Analysis Report
Level Of Service

Table with 5 columns: Intersection, Base (Del/LOS, V/C), Future (Del/LOS, V/C), Change in, and V/C. Rows include #501 E Lincoln Pkwy & Twelve Bridge, #1502 Sierra College & Twelve Bridge, and #1601 Sierra College & English Colon.

City of Rocklin General Plan Update
2030 Plus Project
PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Level of Service Computation Report for Intersection #501 E Lincoln Pkwy & Twelve Bridges. Includes data for Cycle (sec), Loss Time, Optimal Cycle, Approach, Movement, Control, Rights, Min. Green, Y+R, Lanes, Volume Module, Saturation Flow Module, and Capacity Analysis Module.

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1502 Sierra College & Twelve Bridges  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.672  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 69 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*

City of Rocklin General Plan Update

2030 Plus Project

PM Peak Hour LOS (Published Circular 212 Capacities)

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1601 Sierra College & English Colony  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.884  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 160 Level Of Service: D

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

\*\*\*\*\*



Rocklin General Plan Update
2030 Plus Project
Roseville Intersections

Impact Analysis Report
Level Of Service

Table with 5 columns: Intersection, Base (Del/V, LOS Veh, C), Future (Del/V, LOS Veh, C), Change in, and V/C. Rows include intersections like #401 Pleasant Grove & Fairway, #402 Stanford Ranch & Fairway, etc.

Rocklin General Plan Update
2030 Plus Project
Roseville Intersections

Level Of Service Computation Report

Circular 212 Planning Method (Base Volume Alternative)

Intersection #401 Pleasant Grove & Fairway

Cycle (sec): 120 Critical Vol./Cap.(X): 1.043
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: F

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control Rights, Min. Green, Y+R, and Lanes.

Table with 4 columns: Volume Module (Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume) and 4 columns of values.

Table with 4 columns: Sat/Lane, Adjustment, Lanes, and Final Sat. Values for each approach.

Table with 4 columns: Capacity Analysis Module (Vol/Sat, Crit Volume, Crit Moves) and 4 columns of values.

\*\*\*\*\*

GP30 Fri May 22, 2009 11:04:33 Page 4-1
Rocklin General Plan Update
2030 Plus Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #402 Stanford Ranch & Fairway

Cycle (sec): 120 Critical Vol./Cap.(X): 0.742
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 88 Level Of Service: C

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Saturation Flow Module, Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Volume, Crit Moves.

GP30 Fri May 22, 2009 11:04:33 Page 5-1
Rocklin General Plan Update
2030 Plus Project
Roseville Intersections

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #403 Stanford Ranch & Five Star

Cycle (sec): 120 Critical Vol./Cap.(X): 0.681
Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 72 Level Of Service: B

Table with columns: Approach, North Bound, South Bound, East Bound, West Bound, Movement, Control, Rights, Min. Green, Y+R, Lanes.

Table with columns: Volume Module, Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, Final Volume.

Table with columns: Saturation Flow Module, Sat/Lane, Adjustment, Lanes, Final Sat.

Table with columns: Capacity Analysis Module, Vol/Sat, Crit Volume, Crit Moves.

GP30 Fri May 22, 2009 11:04:33 Page 6-1

-----  
 Rocklin General Plan Update  
 2030 Plus Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #404 Pleasant Grove & Roseville Pkwy  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 1.088  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: F  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ignore Ignore Ignore Ignore  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 3 0 2 0 1 2 0 3 0 1 2 0 3 0 1  
 -----  
 Volume Module:  
 Base Vol: 710 939 1097 399 983 44 44 1459 783 844 1820 193  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 710 939 1097 399 983 44 44 1459 783 844 1820 193  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 710 939 0 399 983 0 44 1459 0 844 1820 0  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 710 939 0 399 983 0 44 1459 0 844 1820 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 710 939 0 399 983 0 44 1459 0 844 1820 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 3.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
 Final Sat.: 4350 2900 1450 2900 4350 1450 2900 4350 1450 2900 4350 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.16 0.32 0.00 0.14 0.23 0.00 0.02 0.34 0.00 0.29 0.42 0.00  
 Crit Volume: 470 199 486 422  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

GP30 Fri May 22, 2009 11:04:33 Page 7-1

-----  
 Rocklin General Plan Update  
 2030 Plus Project  
 Roseville Intersections  
 -----  
 Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #405 Galleria & Roseville Pkwy  
 \*\*\*\*\*  
 Cycle (sec): 120 Critical Vol./Cap.(X): 0.984  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: E  
 \*\*\*\*\*  
 Approach: North Bound South Bound East Bound West Bound  
 Movement: L - T - R L - T - R L - T - R L - T - R  
 -----  
 Control: Protected Protected Protected Protected  
 Rights: Ignore Ignore Ignore Ignore  
 Min. Green: 0 0 0 0 0 0 0 0 0 0 0 0  
 Y+R: 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0 4.0  
 Lanes: 2 0 3 0 1 3 0 3 0 1 2 0 4 0 1  
 -----  
 Volume Module:  
 Base Vol: 599 752 33 1025 838 375 674 1701 874 270 1991 626  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 599 752 33 1025 838 375 674 1701 874 270 1991 626  
 User Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 PHF Volume: 599 752 0 1025 838 0 674 1701 0 270 1991 0  
 Reduced Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 599 752 0 1025 838 0 674 1701 0 270 1991 0  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00 1.00 1.00 0.00  
 FinalVolume: 599 752 0 1025 838 0 674 1701 0 270 1991 0  
 -----  
 Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 3.00 1.00 3.00 3.00 1.00 2.00 4.00 1.00 2.00 4.00 1.00  
 Final Sat.: 2900 4350 1450 4350 4350 1450 2900 5800 1450 2900 5800 1450  
 -----  
 Capacity Analysis Module:  
 Vol/Sat: 0.21 0.17 0.00 0.24 0.19 0.00 0.23 0.29 0.00 0.09 0.34 0.00  
 Crit Volume: 251 342 337 498  
 Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*  
 \*\*\*\*\*

GP30 Fri May 22, 2009 11:04:33 Page 8-1

-----  
 Rocklin General Plan Update  
 2030 Plus Project  
 Roseville Intersections  
 -----

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #406 Roseville Parkway & Taylor  
 \*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.826  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 131 Level Of Service: D  
 \*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ovl			Ovl			Ovl			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	0	3	0	1	2	0	3	0	1	2	0

Volume Module:  
 Base Vol: 304 344 184 469 315 165 225 2339 312 419 2209 584  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 304 344 184 469 315 165 225 2339 312 419 2209 584  
 User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 PHF Volume: 304 344 184 469 315 165 225 2339 312 419 2209 584  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 304 344 184 469 315 165 225 2339 312 419 2209 584  
 PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 FinalVolume: 304 344 184 469 315 165 225 2339 312 419 2209 584

Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.00 3.00 1.00 2.00 3.00 1.00 2.00 4.00 1.00 2.00 3.00 1.00  
 Final Sat.: 2900 4350 1450 2900 4350 1450 2900 5800 1450 2900 4350 1450

Capacity Analysis Module:  
 Vol/Sat: 0.10 0.08 0.13 0.16 0.07 0.11 0.08 0.40 0.22 0.14 0.51 0.40  
 Crit Volume: 115 235 113 736  
 Crit Moves: \*\*\*\*

\*\*\*\*\*

GP30 Fri May 22, 2009 11:04:33 Page 9-1

-----  
 Rocklin General Plan Update  
 2030 Plus Project  
 Roseville Intersections  
 -----

Level Of Service Computation Report  
 Circular 212 Planning Method (Base Volume Alternative)  
 \*\*\*\*\*  
 Intersection #407 Roseville Parkway & N. Sunrise  
 \*\*\*\*\*

Cycle (sec): 120 Critical Vol./Cap.(X): 0.997  
 Loss Time (sec): 12 Average Delay (sec/veh): xxxxxx  
 Optimal Cycle: 180 Level Of Service: E  
 \*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Protected			Protected		
Rights:	Ignore			Ovl			Ignore			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	2	1	0	0	1	1	0	2	0	1	2	0

Volume Module:  
 Base Vol: 555 157 406 159 287 394 149 2203 753 309 2416 88  
 Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Initial Bse: 555 157 406 159 287 394 149 2203 753 309 2416 88  
 User Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 PHF Volume: 555 157 0 159 287 394 149 2203 0 309 2416 88  
 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
 Reduced Vol: 555 157 0 159 287 394 149 2203 0 309 2416 88  
 PCE Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 MLF Adj: 1.00 1.00 0.00 1.00 1.00 1.00 1.00 1.00 0.00 1.00 1.00 1.00  
 FinalVolume: 555 157 0 159 287 394 149 2203 0 309 2416 88

Saturation Flow Module:  
 Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
 Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
 Lanes: 2.34 0.66 1.00 1.00 2.00 1.00 2.00 3.00 1.00 2.00 3.00 1.00  
 Final Sat.: 3391 959 1450 1450 2900 1450 2900 4350 1450 2900 4350 1450

Capacity Analysis Module:  
 Vol/Sat: 0.16 0.16 0.00 0.11 0.10 0.27 0.05 0.51 0.00 0.11 0.56 0.06  
 Crit Volume: 237 394 734 155  
 Crit Moves: \*\*\*\*

\*\*\*\*\*

GP30                      Fri May 22, 2009 11:04:33                      Page 10-1

-----

Rocklin General Plan Update  
2030 Plus Project  
Roseville Intersections

-----

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #408 Sierra College & Secret Ravine  
\*\*\*\*\*

Cycle (sec):            120                      Critical Vol./Cap.(X):            0.924  
Loss Time (sec):        9                        Average Delay (sec/veh):        xxxxxx  
Optimal Cycle:          180                      Level Of Service:                E

\*\*\*\*\*

Approach:	North Bound			South Bound			East Bound			West Bound		
Movement:	L	T	R	L	T	R	L	T	R	L	T	R
Control:	Protected			Protected			Permitted			Permitted		
Rights:	Ovl			Ovl			Ovl			Ovl		
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Y+R:	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
Lanes:	1	0	2	0	1	1	2	0	0	1	0	1

-----

Volume Module:

Base Vol:	208	1498	3	1	1577	370	762	2	177	3	5	3
Growth Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Initial Bse:	208	1498	3	1	1577	370	762	2	177	3	5	3
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	208	1498	3	1	1577	370	762	2	177	3	5	3
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	208	1498	3	1	1577	370	762	2	177	3	5	3
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	208	1498	3	1	1577	370	762	2	177	3	5	3

-----

Saturation Flow Module:

Sat/Lane:	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Adjustment:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:	1.00	2.00	1.00	1.00	2.00	1.00	2.00	0.01	0.99	0.38	0.62	1.00
Final Sat.:	1500	3000	1500	1500	3000	1500	3000	17	1483	563	938	1500

-----

Capacity Analysis Module:

Vol/Sat:	0.14	0.50	0.00	0.00	0.53	0.25	0.25	0.12	0.12	0.01	0.01	0.00
Crit Volume:	208			788			381			8		
Crit Moves:	****			****			****			****		

\*\*\*\*\*



**INTERSECTION LOS WORKSHEETS  
2030 CUMULATIVE PLUS PROJECT CONDITIONS  
POTENTIAL MITIGATION MEASURES**

---





Rocklin General Plan Update  
Cumulative With Buildout of Proposed General Plan  
With Identified Intersection Mitigations

Impact Analysis Report  
Level Of Service

Intersection	Base		Future		Change in
	Del/ LOS Veh	V/ C	Del/ LOS Veh	V/ C	
# 1 Granite Dr & Rocklin Rd	C xxxxx	0.762	C xxxxx	0.762	+ 0.000 V/C
# 4 Pacific St & Del Mar/ Domingue	C xxxxx	0.711	C xxxxx	0.711	+ 0.000 V/C
# 5 Pacific St & Farron St	C xxxxx	0.724	C xxxxx	0.724	+ 0.000 V/C
# 7 Pacific St & Rocklin Rd	C xxxxx	0.707	C xxxxx	0.707	+ 0.000 V/C
# 14 Rocklin Rd & Sierra College Bl	B xxxxx	0.698	B xxxxx	0.698	+ 0.000 V/C
# 20 Sunset Bl & Pacific St	C xxxxx	0.751	C xxxxx	0.751	+ 0.000 V/C
# 21 Sunset Bl & Springview Dr	E xxxxx	0.910	E xxxxx	0.910	+ 0.000 V/C
# 23 Sunset Bl & Whitney Bl	C xxxxx	0.712	C xxxxx	0.712	+ 0.000 V/C
#101 Blue Oaks Bl & Lonetree	C xxxxx	0.777	C xxxxx	0.777	+ 0.000 V/C
#128 Sunset Bl & Atherton	C xxxxx	0.768	C xxxxx	0.768	+ 0.000 V/C
#132 Sunset Bl & Park Dr	C xxxxx	0.736	C xxxxx	0.736	+ 0.000 V/C
#135 Sunset Bl & West Oaks Bl	C xxxxx	0.709	C xxxxx	0.709	+ 0.000 V/C
#136 W Stanford Ranch Rd & Sunset B	C xxxxx	0.796	C xxxxx	0.796	+ 0.000 V/C
#152 Stanford Ranch Rd & Crest Dr	C xxxxx	0.776	C xxxxx	0.776	+ 0.000 V/C
#162 Sierra College Bl & Dominguez	B xxxxx	0.617	B xxxxx	0.617	+ 0.000 V/C

Rocklin General Plan Update  
Cumulative With Buildout of Proposed General Plan  
With Identified Intersection Mitigations

Level Of Service Computation Report  
Circular 212 Planning Method (Base Volume Alternative)

\*\*\*\*\*  
Intersection #1 Granite Dr & Rocklin Rd  
\*\*\*\*\*

Cycle (sec): 100 Critical Vol./Cap.(X): 0.762  
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx  
Optimal Cycle: 96 Level Of Service: C

\*\*\*\*\*

Approach:	North Bound	South Bound	East Bound	West Bound
Movement:	L - T - R	L - T - R	L - T - R	L - T - R
Control:	Split Phase	Split Phase	Protected	Protected
Rights:	Include	Include	Include	Include
Min. Green:	0 0 0	0 0 0	0 0 0	0 0 0
Y+R:	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0	4.0 4.0 4.0
Lanes:	1 0 0 1 0	1 1 0 0 1	2 0 2 1 0	1 0 2 1 0

Volume Module:  
Base Vol: 30 17 15 594 19 316 301 1653 10 32 1194 606  
Growth Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Initial Bse: 30 17 15 594 19 316 301 1653 10 32 1194 606  
User Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
PHF Volume: 30 17 15 594 19 316 301 1653 10 32 1194 606  
Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0  
Reduced Vol: 30 17 15 594 19 316 301 1653 10 32 1194 606  
PCE Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
MLF Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
FinalVolume: 30 17 15 594 19 316 301 1653 10 32 1194 606

Saturation Flow Module:  
Sat/Lane: 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450 1450  
Adjustment: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00  
Lanes: 1.00 0.53 0.47 1.94 0.06 1.00 2.00 2.98 0.02 1.00 2.00 1.00  
Final Sat.: 1450 770 680 2810 90 1450 2900 4324 26 1450 2900 1450

Capacity Analysis Module:  
Vol/Sat: 0.02 0.02 0.02 0.21 0.21 0.22 0.10 0.38 0.38 0.02 0.41 0.42  
Crit Volume: 32 316 151 606  
Crit Moves: \*\*\*\* \*\*\*\* \*\*\*\* \*\*\*\*

\*\*\*\*\*

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #4 Pacific St & Del Mar/ Dominguez

Cycle (sec): 100 Critical Vol./Cap.(X): 0.711
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 79 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #5 Pacific St & Farron St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.724
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 83 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #7 Pacific St & Rocklin Rd

Cycle (sec): 100 Critical Vol./Cap.(X): 0.707
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 78 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #14 Rocklin Rd & Sierra College Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.698
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 75 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduced Vol, and Final Volume across four approaches.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat. across four approaches.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves across four approaches.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #20 Sunset Bl & Pacific St

Cycle (sec): 100 Critical Vol./Cap.(X): 0.751
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 92 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #21 Sunset Bl & Springview Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.910
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 180 Level Of Service: E

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #23 Sunset Bl & Whitney Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.712
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 79 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic volumes and 10 rows of adjustment factors.

Saturation Flow Module table with 10 columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #101 Blue Oaks Bl & Lonetree

Cycle (sec): 100 Critical Vol./Cap.(X): 0.777
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 102 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with 10 columns representing different traffic volumes and 10 rows of adjustment factors.

Saturation Flow Module table with 10 columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with 10 columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #128 Sunset Bl & Atherton

Cycle (sec): 100 Critical Vol./Cap.(X): 0.768
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 98 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 10 columns for Volume Module. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 10 columns for Saturation Flow Module. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 10 columns for Capacity Analysis Module. Rows include Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #132 Sunset Bl & Park Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.736
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 86 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Table with 10 columns for Volume Module. Rows include Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Table with 10 columns for Saturation Flow Module. Rows include Sat/Lane, Adjustment, Lanes, and Final Sat.

Table with 10 columns for Capacity Analysis Module. Rows include Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #135 Sunset Bl & West Oaks Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.709
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 78 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #136 W Stanford Ranch Rd & Sunset Bl

Cycle (sec): 100 Critical Vol./Cap.(X): 0.796
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 112 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #152 Stanford Ranch Rd & Crest Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.776
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 102 Level Of Service: C

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.

Rocklin General Plan Update
Cumulative With Buildout of Proposed General Plan
With Identified Intersection Mitigations

Level Of Service Computation Report
Circular 212 Planning Method (Base Volume Alternative)

Intersection #162 Sierra College Bl & Dominguez Dr

Cycle (sec): 100 Critical Vol./Cap.(X): 0.617
Loss Time (sec): 0 Average Delay (sec/veh): xxxxxx
Optimal Cycle: 60 Level Of Service: B

Table with 4 columns: Approach (North Bound, South Bound, East Bound, West Bound) and Movement (L, T, R). Rows include Control, Rights, Min. Green, Y+R, and Lanes.

Volume Module table with columns for Base Vol, Growth Adj, Initial Bse, User Adj, PHF Adj, PHF Volume, Reduct Vol, Reduced Vol, PCE Adj, MLF Adj, and Final Volume.

Saturation Flow Module table with columns for Sat/Lane, Adjustment, Lanes, and Final Sat.

Capacity Analysis Module table with columns for Vol/Sat, Crit Volume, and Crit Moves.